

6491X Conduit Cable

pro-POWER



Construction

Conductor: Stranded Plain Annealed Copper
Insulation: PVC

Application

Fixed Wiring Cables have been designed for use in Domestic, Industrial Power and Lighting Applications

Technical Data

Voltage: 450/750V (designed suitable for 600/1,000V Volt Systems)
Operating Temperature Range: 20°C to +70°C*

Relevant Standards

BS6004/75, Cenelec Code H07V-R

Core Identification

Standard Colours Available: Red, Black, Blue, Yellow and Green/Yellow

*Insulation is not Recommended for PVC below 0°C as the Compound may become Brittle

Sizes and Dimensions

Conductor Size (mm ²)	Conductor Stranding	Nominal O.D. (mm)	Approx Weight (Kg/Km)
1.5	7/0.53	3	21
2.5	7/0.67	3.7	34
4	7/0.85	4.2	51
6	7/1.04	4.8	71
10	7/1.35	6.1	120
16	7/1.7	7.1	180
25	7/2.14	8.9	285
35	19/1.53	10.1	380
50	19/1.78	11.8	510
70	19/2.14	13.6	715
95	19/2.52	15.9	990
120	37/2.03	17.5	1,230
150	37/2.25	19.4	1,510
185	37/2.52	21.7	1,900
240	61/2.25	24.5	2,490
300	61/2.52	27.5	3,050
400	61/2.85	30.9	3,900
500	61/3.2	34.5	4,800
630	127/2.52	38.4	6,210

www.element14.com
www.farnell.com
www.newark.com
www.cpc.co.uk

pro-POWER

6491X Conduit Cable

pro-POWER

Part Number Table

Description	Part Number
Wire, 6491X, Black, 15mm, 100m	6491X-1.50MMBLK100M
Wire, 6491X, Blue, 15mm, 100m	6491X-1.50MMBLU100M
Wire, 6491X, Brown, 15mm, 100m	6491X-1.50MMBRN100M
Wire, 6491X, Green/Yellow, 15m, 100m	6491X-1.50MMG/Y100M
Wire, 6491X, Grey, 15m, 100m	6491X-1.50MMGRY100M

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com
www.farnell.com
www.newark.com
www.cpc.co.uk

pro-POWER

X-ON Electronics

Authorized Distributor

Click to view similar products for [Pro Power manufacturer](#).

Other Similar products are found below :

[0301CV100W](#) [04JSBLACK](#) [06JSBLACK](#) [08450046010](#) [08450056010](#) [08450066010](#)
[08450166010](#) [08450236010](#) [08450256010](#) [08JSBLACK](#) [10026B](#) [10026BK](#) [10026G](#)
[10026R](#) [10026TB](#) [10026TBK](#) [10026TG](#) [10026TR](#) [10026TW](#) [10026W](#) [10030B](#)
[10030BK](#) [10030G](#) [10030O](#) [10030R](#)