

## SNP6010C2



**Article Number:** 190-00196

**Snapper Hose Clamps, 2.259"/2.582" Min/Max Diameter, POM, White, 100/pkg**



Download drawing



Download spec sheet

### Base Data

**Local Order Number** SNP6010C2

**Type** SNP60

**Color** White (WH)

**Features and Benefits**

- Designed for quick, ratcheted installation and can be released and reused.
- Polyacetal material resists chemicals, corrosion and UV rays making it suitable for extreme environments.

**Product Description** HellermannTyton snapper hose clamps are designed to provide a quick, ratcheted closure reducing installation time. The design also allows the clamp to be easily removed and re-applied when necessary. Snappers are made of high performing materials providing stability in a variety of diverse environments. Available in 32 standard sizes.

**Short Description** Snapper Hose Clamps, 2.259"/2.582" Min/Max Diameter, POM, White, 100/pkg

### Product Dimensions

**Fixation Method** Plug-in mounting

**Variant** Closed

**Width W2 (Imperial)** 0.291 "

**Width W2 (Metric)** 7.39 mm

**Bundle Diameter Min. (Imperial)** 2.28 "

**Bundle Diameter Min. (Metric)** 58.0 mm

**Bundle Diameter Max. (Imperial)** 2.52 "

**Bundle Diameter Max. (Metric)** 64 mm

**Diameter Min. (Imperial)** 2.259 "

**Diameter Min. (Metric)** 57.38 mm

**Diameter Max. (Imperial)** 2.582 "

**Diameter Max. (Metric)** 65.58 mm

**Wall Thickness WT (Imperial)** 0.067 "

**Wall Thickness WT (Metric)** 1.7 mm

### Logistics and Packaging

**Quantity Per** bag

**Package Quantity (Metric)** 100

**Carton Quantity** 500

### Material and Specifications

**Material** Polyacetal (POM)

**Material Shortcut** POM

**Flammability** UL94 HB

**Operating Temperature** -40°F to +185°F (-40°C to +85°C)

**ROHS Compliant** Yes

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Wire Identification](#) category:*

*Click to view products by [Hellermann](#) manufacturer:*

Other Similar products are found below :

[CU6337-000](#) [CU6342-000](#) [FCA-410-12](#) [11631010](#) [1-1768037-1](#) [1-1768037-2](#) [1-1768050-0](#) [PXLK-VI](#) [Q62184-1](#) [A64304-000](#) [QMT221](#)  
[HK032WE1NF038B](#) [1330-0519-10](#) [1395199-1](#) [1395200-1](#) [1395202-1](#) [DMVF050WE-300S6](#) [D-SCE-1K-2.4-50-4-CS7834](#) [1538738-1](#)  
[E90935-000](#) [EC1238-000](#) [EC1465-000](#) [EC1855-000](#) [EC1859-000](#) [EC1863-000](#) [EC5415-000](#) [EC7277-000](#) [EC7352-000](#) [EC7603-000](#)  
[EC7707-000](#) [EC7735-000](#) [EC7768-000](#) [EC7828-000](#) [EC7854-000](#) [EC7952-000](#) [EC8128-000](#) [1768037-8](#) [1768041-7](#) [NC-127191-10-9](#)  
[HS048WE2NF038B](#) [C03232-000](#) [HTCM-SCE-14-4H-9](#) [HTMS-3/16-9](#) [HT-SCE-1/4-2.0-4](#) [HT-SCE-3/16-2.0-4](#) [HTTMS-1/2-1.50-9](#) [HTTMS-](#)  
[CM-1/2-4H-9](#) [HX-SCE-19.0-50-9](#) [HX-SCE-6.4-50-4](#) [C25254-000](#)