

Tinned Annealed Copper Wires **pro-POWER**



Description:

Insulated wires to defence standard 61 - 21 part 6 types 1, 2 and 3 also comply for corresponding standings and types, with the requirements of BS4808 classes 1, 2 and 3. Because the requirements set by the ministry of defence in defence standard 61 - 12 part 6 are more rigorous than the requirements in BS4808, the converse is not necessarily true
The maximum recommended operating temperature for these wires is 85°C. Defence standard current ratings quoted below will give a 15°C temperature rise at an ambient temperature of 70°C for single wires freely ventilated. Commercial ratings are suggested for use at 25°C ambient

Equipment wire with 10/0.1 mm conductors is a standing size not specifically listed in DEF.STAN.61 - 12 part 6. Because of its suitability for in conformance with specifications for similar size wires included in the specification

Temperature rating 7/0.2 type 2 wire

The temperature range of the above product is -15 to 85°C, the upper temperature is the temperature at the conductor due to a combination of ambient and temperature rise due to current flow. The lower temperature is for the product in static mode

Specification Table

Area	Conductor	Number and Size of Wire	Maximum Working Voltage (KV r.m.s)	Nominal Current Rating (A)	Insulation	Nominal Overall Diameter	Insulation Thickness	Ambient Temperature (°C)	Resistance at 20°C (Ω/KM)
7/0.2 (0.22 mm ²) type 2	Tinned annealed copper wire	7 × 0.2	1	1.4	PVC	1.2	0.3	1.4 A at 70°C 2 A at 25°C	88

Dimensions : Millimetres

Part Number Table

Description	Part Number
Wire, Black, 7/0.2 mm, 100 m	MC6A-7/0.2T2-BK-100
Wire, Brown, 7/0.2 mm, 100 m	MC6A-7/0.2T2-BN-100
Wire, Red, 7/0.2 mm, 100 m	MC6A-7/0.2T2-RD-100
Wire, Orange, 7/0.2 mm, 100 m	MC6A-7/0.2T2-OE-100
Wire, Yellow, 7/0.2 mm, 100 m	MC6A-7/0.2T2-YW-100
Wire, Green, 7/0.2 mm, 100 m	MC6A-7/0.2T2-GN-100
Wire, Blue, 7/0.2 mm, 100 m	MC6A-7/0.2T2-BE-100
Wire, Violet, 7/0.2 mm, 100 m	MC6A-7/0.2T2-VT-100
Wire, Grey, 7/0.2 mm, 100 m	MC6A-7/0.2T2-GY-100
Wire, White, 7/0.2 mm, 100 m	MC6A-7/0.2T2-WE-100
Wire, Pink, 7/0.2 mm, 100 m	MC6A-7/0.2T2-PK-100M

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2011.

X-ON Electronics

Authorized Distributor

Click to view similar products for [Pro Power manufacturer](#).

Other Similar products are found below :

[0301CV100W](#) [04JSBLACK](#) [06JSBLACK](#) [08450046010](#) [08450056010](#) [08450066010](#)
[08450166010](#) [08450236010](#) [08450256010](#) [08JSBLACK](#) [10026B](#) [10026BK](#) [10026G](#)
[10026R](#) [10026TB](#) [10026TBK](#) [10026TG](#) [10026TR](#) [10026TW](#) [10026W](#) [10030B](#)
[10030BK](#) [10030G](#) [10030O](#) [10030R](#)