



**RoHS
Compliant**



Description

Solid Tinned Annealed Copper Wire, PVC Insulation
Reference Standard: DEF 61-12 (Part 6) Type 2 BS4808 Part 2

Application

Intended for the internal wiring of electronic and other equipment

Construction

Conductor

Material : Solid Tinned Annealed Copper Wire
Stranding : Solid (1/0.6mm)
Wire Gauge : 23 AWG
CSA : 0.283mm²

Insulation

Material : PVC
Nominal O.D : 1.2mm
Colour : See table below

Electrical Properties

Max. DC resistance : 63.5Ω/km@20°C
Voltage Rating : 150V
Spark Test : 3,000V AC
Packaging : 100M reels and Per M

Physical Properties

Min. Bend Radius : 12mm
Operating Temperature : -15°C to 90°C

Part Number Table

Description	Part Number
Equipment Wire, Black, 1/0.6mm, 100M	MC6A-1/0.6T2-BK-100
Equipment Wire, Brown, 1/0.6mm, 100M	MC6A-1/0.6T2-BR-100
Equipment Wire, Red, 1/0.6mm, 100M	MC6A-1/0.6T2-RD-100
Equipment Wire, Orange, 1/0.6mm, 100M	MC6A-1/0.6T2-OE-100
Equipment Wire, Yellow, 1/0.6mm, 100M	MC6A-1/0.6T2-YW-100
Equipment Wire, Green, 1/0.6mm, 100M	MC6A-1/0.6T2-GN-100
Equipment Wire, Blue, 1/0.6mm, 100M	MC6A-1/0.6T2-BE-100
Equipment Wire, Violet, 1/0.6mm, 100M	MC6A-1/0.6T2-VT-100
Equipment Wire, Grey, 1/0.6mm, 100M	MC6A-1/0.6T2-GY-100
Equipment Wire, White, 1/0.6mm, 100M	MC6A-1/0.6T2-WE-100
Equipment Wire, Pink, 1/0.6mm, 100M	MC6A-1/0.6T2-PK-100

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

X-ON Electronics

Authorized Distributor

Click to view similar products for [Pro Power manufacturer](#).

Other Similar products are found below :

[0301CV100W](#) [04JSBLACK](#) [06JSBLACK](#) [08450046010](#) [08450056010](#) [08450066010](#)
[08450166010](#) [08450236010](#) [08450256010](#) [08JSBLACK](#) [10026B](#) [10026BK](#) [10026G](#)
[10026R](#) [10026TB](#) [10026TBK](#) [10026TG](#) [10026TR](#) [10026TW](#) [10026W](#) [10030B](#)
[10030BK](#) [10030G](#) [10030O](#) [10030R](#)