

### Application


- Horizontal and building backbone cable.
- Support current and future **Category 5 enhanced** applications, such as:  
10 Base-T, 100 Base-T, 1000 Base-T (*Gigabit Ethernet*), FDDI, ATM

### Standards

General standards: **ISO/IEC 11801, EN 50173, TSB 36, TIA/EIA 568-A-5 (enhanced)**  
Future standards like: JTC1 SC25 WG3 N568 and prEN 50288-3-1

### Construction & Dimensions

- Construction: Unshielded 4 twisted pairs
- Conductor: solid bare copper
- Conductor diameter: AWG 24 (0,51 mm)
- Conductor insulation material: Polyethylene (PE)
- Diameter over insulation: 0,90 mm ± 0.05 mm
- Jacket material: FRNC (Flame retardant)
- Outer diameter: 4,70 mm ± 0.30 mm



#### Colour code

Pair 1	White-Blue/Blue
Pair 2	White-Orange/Orange
Pair 3	White-Green/Green
Pair 4	White-Brown/Brown

### Electrical characteristics (at 20 °C)

#### Attenuation

Frequency	1	4	10	16	20	31.25	62.5	100	MHz
Spec. (Max.) <sup>1)</sup>	2.1	4.3	6.6	8.2	9.2	11.8	17.1	22.0	dB/100m
Typical	2.0	4.0	6.3	8.0	9.0	11.3	16.2	20.7	dB/100m

#### NEXT (Near end crosstalk)

Frequency	1	4	10	16	20	31.25	62.5	100	MHz
Spec. (Min.) <sup>1)</sup>	65.3	56.3	50.3	47.3	45.8	42.9	38.4	35.3	dB
Typical	73	64	58	55	54	51	47	44	dB

#### Power sum NEXT

Frequency	1	4	10	16	20	31.25	62.5	100	MHz
Spec. (Min.) <sup>1)</sup>	62.3	53.3	47.3	44.3	42.8	39.9	35.4	32.3	dB/100m
Typical	71	62	56	53	52	49	45	42	dB/100m

#### Power sum ELFEXT

Frequency	1	4	10	16	20	31.25	62.5	100	MHz
Spec. (Min.) <sup>2)</sup>	60.8	48.7	40.8	36.7	34.7	30.9	24.8	20.8	dB/100m
Typical	71	59	51	46	43	39	33	28	dB/100m

#### ACR

Frequency	1	4	10	16	20	31.25	62.5	100	MHz
Spec. (Min.) <sup>1)</sup>	63	52	44	39	37	31	22	14	dB/100m
Typical	71	61	52	48	45	40	31	24	dB/100m

#### Power sum ACR

Frequency	1	4	10	16	20	31.25	62.5	100	MHz
Spec. (Min.) <sup>1)</sup>	60	49	41	36	34	28	19	11	dB/100m
Typical	69	59	50	46	43	38	29	22	dB/100m

<sup>1)</sup>: Specification values according to cable requirements of ISO/IEC 11801 category 5 enhanced

<sup>2)</sup>: Specification values according to cable requirements of ANSI/TIA/EIA-568-A-5 (enhanced)



**Electrical characteristics (at 20 °C)**

Nominal mutual capacitance at 1 kHz	50 nF/km
Maximum conductor DCR	93.5 Ohm/km
NVP - Nominal Velocity of Propagation	0.68 c
SKEW – Propagation delay difference (100 MHz)	Typical ≤ 10 ns/100m
Impedance 1-100 MHz	100 ± 15 Ohm

**General and environmental characteristics**

Temperature range - operation	-20°C - +60°C
Temperature range - installation	+0°C - +50°C
Minimum bending radius - operation	19 mm
Minimum bending radius - installation	38 mm
Maximum pulling tension	80 N
Flame retardancy	IEC 332-1
Energy of flame	250 kJ/m
Weight (approx.)	28 kg/km
Maximum operating voltage	48 V rms
Maximum continuous current per conductor (25°C)	1.4 A

**Ordering information**

**MARKING**

Text on the cable jacket      Inkjet printing

**BELDEN 1583ENH UTP CAT5E 4PR AWG24 LSNH ISO/IEC 11801 EN50173  
VERIFIED 100 OHM**

Meter marking:                      Yes  
Production date marking:        Yes

**JACKET COLOUR**

Colour	RAL code	Belden colour code
Grey	RAL 7032	2807
Blue	RAL 5015	3072

**PACKAGING (PUT UP)**

Belden code	Delivery length	Weight	Remark
46376 xxxx 178	305 m	8,5 kg	Unreel box
46376 xxxx 028	305 m	8,5 kg	Non returnable reel
46376 xxxx 011	500 m	14,0 kg	Non returnable reel
46376 xxxx 240	1000 m	28,0 kg	Non returnable reel

xxxx: Belden colour code

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [belden manufacturer](#):*

Other Similar products are found below :

[HIPWP2LA](#) [49905A 060S2](#) [8916-BRN-100](#) [8916-GRN/YEL-500](#) [8916-YEL-500](#) [8918-GRY-1000](#) [8919-DK-BLU-100](#) [5T00UP 008500](#)  
[7810A-BLK-500](#) [7860NBH](#) [7934A-BLK-1000](#) [7937A-BLK-1000](#) [8019-100](#) [8058](#) [8080](#) [8108-060-1000](#) [8125-CHR-100](#) [8132-CHR-1000](#)  
[8133-CHR-1000](#) [8155-CHR-1000](#) [8162-060-1000](#) [8162-CHR-1000](#) [8164-CHR-100](#) [8164-CHR-1000](#) [8185-CHR-100](#) [8205-CHR-1000](#) [8221-](#)  
[BLK-1000](#) [8233-010-1000](#) [8233-BLK-1000](#) [8237-BLK-500](#) [8238-BLK-500](#) [8241A-BLK-1000](#) [8241F-RED-MATTE-1000](#) [8263-BLK-](#)  
[U1000](#) [8279-BLK-1000](#) [8281-003-1000](#) [8281 010500](#) [83000 002100](#) [83002 0101000](#) [83003-006-500](#) [83007 0081000](#) [83008 0091000](#)  
[83010-RED-100](#) [83029 0021000](#) [8302-CHR-500](#) [8303 060500](#) [8307-CHR-100](#) [8310-060-1000](#) [8310-CHR-1000](#) [83347E 009100](#)