



SPECIFICATIONS 规格:

- CURRENT RATING 电流额定值: 1.0 AMP
- INSULATION RESISTANCE 绝缘电阻值: 1000MΩ Min.
- DIELECTRIC WITHSTANDING 耐电压: 300V AC
- CONTACT RESISTANCE 接触电阻值: 20mΩ Max.
- OPERATING TEMPERATURE 工作温度: -40°C TO +105°C
- CONTACT MATERIAL 端子物料: COPPER ALLOY
- INSULATOR MATERIAL 绝缘体物料: POLYESTER 聚酯, LCP, UL 94 V-0
- SOLDERING PROCESS 可焊性: LCP -
- IR REFLOW 回流焊: 260°C for 10 sec.
- WAVE 波峰焊: 250°C for 5-10 sec
- MANUAL SOLDER 人工焊接: 350°C for 3-5 sec

MATES WITH 配套之母座 (SUBJECT TO PIN LENGTH 在端子长度适合的条件下):

BD095

BD025

BD030

BD035

BD038

BD040

By	REV	DATE
LYH	A	28/12/07
PN	B	27/04/09
AE	C	27/07/09
CM	D	19/10/11
AJO	E	25/06/12
AJO	F	13/12/12



Tolerances	Dimensions in mm
(Except as noted)	X ±0.30
	X ±0.20
	XX ±0.15
	XXX ±0.10

Part Number:-	Date:-
BD060	28 DEC 07

Scale	NTS	F	Revision	Material	See Note	LYH	E & OE

GCT

CONTACTS	A	B
6	2.54	4.16
8	3.81	5.43
10	5.08	6.70
12	6.35	7.97
14	7.62	9.24
16	8.89	10.51
18	10.16	11.78
20	11.43	13.05
22	12.70	14.32
24	13.97	15.59
26	15.24	16.86
28	16.51	18.13
30	17.78	19.40
32	19.05	20.67
34	20.32	21.94
36	21.59	23.21
38	22.86	24.48
40	24.13	25.75
42	25.40	27.02
44	26.67	28.29
46	27.94	29.56
48	29.21	30.83
50	30.48	32.10
52	31.75	33.37
54	33.02	34.64
56	34.29	35.91
58	35.56	37.18
60	36.83	38.45
62	38.10	39.72
64	39.37	40.99
66	40.64	42.26
68	41.91	43.53
70	43.18	44.80
72	44.45	46.07
74	45.72	47.34
76	46.99	48.61
78	48.26	49.88
80	49.53	51.15
82	50.80	52.42
84	52.07	53.69
86	53.34	54.96
88	54.61	56.23
90	55.88	57.50
92	57.15	58.77
94	58.42	60.04
96	59.69	61.31
98	60.96	62.58
100	62.23	63.85

Ordering Grnd
 BD060-XX-X-X-0230-L-X
 REQUEST SAMPLES AND QUOTATION

- No. of Contacts = 00
- 06 to 100
- 100 Contacts = 00
- Contact Plating
- A = Gold Flash All Over (Standard)
- B = Selective Gold Flash Contact Area/
- Tin On Tail
- C = Tin All Over
- G = 10µ" Gold Contact Area/Tin On Tail
- I = 30µ" Gold Contact Area/Tin On Tail
- P = 3.40mm
- Insulator
- Height "H"
- N = 4.40mm (Standard)
- 0230 = 2.30mm
- L = LCP
- F = Tube with Film
- E = Tube with Cap
- D = Tube (Standard)
- Packing Options

For 06 and 08 contacts option G only.

THIS DRAWING IS CONFIDENTIAL AND MUST NOT BE COPIED OR DISCLOSED WITHOUT WRITTEN CONSENT

www.globalconnectortech.com

Sheet No. 1/1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [FFC & FPC Connectors](#) category:

Click to view products by [GCT](#) manufacturer:

Other Similar products are found below :

[HFW11R-1STE1H1LF](#) [FH29B-100S-0.2SHW\(99\)](#) [FA5S008HP1](#) [FH29B-120S-0.2SHW\(99\)](#) [FH29B-80S-0.2SHW\(99\)](#) [FHS-16](#) [FPH-2022G](#)
[52610-1075](#) [52610-1275](#) [52610-1934](#) [XF3M\(1\)-1415-1B-R100](#) [501864-3091-TR225](#) [0525594033](#) [086210010340800](#) [086222026001800](#)
[52271-2869-CUT-TAPE](#) [62674-201121DLF](#) [62684-36210E9ALF](#) [52610-1675](#) [52746-1671-TR250](#) [10051922-2810EHLF](#) [6-520415-9](#)
[BD021-09A-A1-0350-0200-0550-LD](#) [SFV6R-1STE9HLF](#) [XF3M-2915-1B-R100](#) [1658549-1](#) [62674-221121ALF](#) [46214008010800](#)
[046298003000883](#) [151660622](#) [842-816-2630-035](#) [AYF530665TA](#) [AYF351525](#) [046296011930846+](#) [AYF352325A](#) [046254020000800+](#)
[FH19C-13S-0.5SH\(99\)](#) [FH39J-51S-0.3SHW\(99\)](#) [AYF355125A](#) [AYF530365TA](#) [FH29B-44S-0.2SHW\(99\)](#) [SFW5R-2STAE9LF](#) [AYF351125A](#)
[AYF350725A](#) [62684-502100AHLF](#) [FH39-61S-0.3SHW\(99\)](#) [AYF414035A](#) [10064555-172520HLF](#) [AYF212335A](#) [504754-2500](#)