

Printview: Male header (for PCBs); Straight solder pin 1 x 1 mm; 8-pole; pin spacing 3.81 mm / 0.15 in; 100% protected against mismating; with closed end; Vertical PCB mounting - Item No.: 734-238

WAGO® online catalog / eShop

Male header (for PCBs); Straight solder pin 1 x 1 mm; 8-pole; pin spacing 3.81 mm / 0.15 in; 100% protected against mismating; with closed end; Vertical PCB mounting

Item No.: 734-238



Male header (for PCBs); Straight solder pin 1 x 1 mm; 8-pole; pin spacing 3.81 mm / 0.15 in; 100% protected against mismating; with closed end; Vertical PCB mounting

Marking

RoHS ✓
Compliant

Business data

Supplier	WAGO
Item no.	734-238
GTIN / EAN	4044918847933
Content	1
Order amount	100
Customer item number	

Notes

1 x 1mm pin cross section allows nominal current up to 10A100% protected against mismating Coding option available

Technical data

Miscellaneous

No. of poles	8
Pin spacing	3.81 mm / 0.15 in %
Color	orange
Ratings according to 1	IEC/EN 60664-1
Overtoltage category EN 1	III
Pollution degree (1)	2
Rated voltage EN (1) [V]	160 [V]

Printview: Male header (for PCBs); Straight solder pin 1 x 1 mm; 8-pole; pin spacing 3.81 mm / 0.15 in; 100% protected against mismatching; with closed end; Vertical PCB mounting - Item No.: 734-238


Technical data	
<i>Rated surge voltage (1) [kV]</i>	<i>2.5 [kV]</i>
<i>Nominal current [A]</i>	<i>10 [A]</i>
<i>Overvoltage category EN 2</i>	<i>II</i>
<i>Degree of pollution (2)</i>	<i>2</i>
<i>Rated voltage EN (2) [V]</i>	<i>320 [V]</i>
<i>Rated surge voltage (2) [kV]</i>	<i>2.5 [kV]</i>
<i>Nominal current (2) [A]</i>	<i>10 [A]</i>
<i>Overvoltage category EN 3</i>	<i>III</i>
<i>Degree of pollution (3)</i>	<i>3</i>
<i>Rated voltage EN (3) [V]</i>	<i>160 [V]</i>
<i>Rated surge voltage (3) [kV]</i>	<i>2.5 [kV]</i>
<i>Nominal current (3) [A]</i>	<i>10 [A]</i>
<i>Solder pin length [mm]</i>	<i>4.5 [mm]</i>
<i>Solder pin width A [mm]</i>	<i>1 [mm]</i>
<i>Solder pin width B [mm]</i>	<i>1 [mm]</i>
<i>Drilled hole diameter (tolerance) [mm]</i>	<i>1.4(+ 0.1) [mm]</i>
<i>Material group</i>	<i>I</i>
<i>Insulating material</i>	<i>Polyamide 66 (PA 66)</i>
<i>Flammability rating per UL 94</i>	<i>V0</i>
<i>Limit temperature range</i>	<i>-60 C ... 100 C</i>
<i>Contact material</i>	<i>Electrolytic copper (Ecu)</i>
<i>Contact plating</i>	<i>tin-plated</i>
<i>Fire load [MJ]</i>	<i>0.034 [MJ]</i>
<i>Weight [g]</i>	<i>1.93 [g]</i>
<i>Width</i>	<i>32.57 mm / 1.282 in</i>
<i>Height</i>	<i>14.8 mm / 0.583 in</i>
<i>Height from the surface</i>	<i>10.3 mm / 0.406 in</i>
<i>Length</i>	<i>8.5 mm / 0.335 in</i>

Printview: Male header (for PCBs); Straight solder pin 1 x 1 mm; 8-pole; pin spacing 3.81 mm / 0.15 in;
100% protected against mismatching; with closed end; Vertical PCB mounting - Item No.: 734-238

Images & drawings



Printview: Male header (for PCBs); Straight solder pin 1 x 1 mm; 8-pole; pin spacing 3.81 mm / 0.15 in;
100% protected against mismatching; with closed end; Vertical PCB mounting - Item No.: 734-238



Address

WAGO Kontakttechnik GmbH & Co. KG

Hansastr. 27

32423 Minden

Telefon: 0571/887-0

Fax: 0571/887-169

<http://www.wago.com>

© WAGO Kontakttechnik GmbH & Co. KG

Technische Änderungen und Irrtümer vorbehalten.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Pluggable Terminal Blocks](#) category:

Click to view products by [Wago](#) manufacturer:

Other Similar products are found below :

[57.404.7553](#) [57.504.0053.7](#) [57.510.0053](#) [57.910.6153](#) [01.112.1453](#) [CTB932VE/6](#) [MC 1.5/ 6-ST-3.5 GY AU](#) [ET02015000J0G](#) [734-104](#) [734-302](#) [734-304](#) [8-141-P](#) [FKCT 2.5/ 3-ST KMGY](#) [860505](#) [860508](#) [860516](#) [860810](#) [861908](#) [GBPACX-12](#) [93.731.4953.0](#) [PV05-5,08-K](#) [PVP02-5,00](#) [PVP04-3,50](#) [PVS02-5,00](#) [1-1986160-3](#) [H-10](#) [1546228-5](#) [ELFH09150](#) [ELFH16150](#) [ELFP03110](#) [ELFT06250](#) [ELFT07250](#) [ELVF09400](#) [ELVP03100](#) [ELXH03100](#) [ELXH071G0E](#) [ELXP041G0](#) [ELXT046G0](#) [1700101](#) [1700410](#) [1700425](#) [1703176](#) [1703243](#) [1705229](#) [1710175](#) [1714537](#) [1717806](#) [1719600](#) [1728941](#) [1729386](#)