

(1,27 mm) .050"

FTS SERIES

# MICRO LOW PROFILE TERMINAL STRIPS

## SPECIFICATIONS

For complete specifications and recommended PCB layouts see [www.samtec.com?FTS](http://www.samtec.com?FTS)

### HI-TEMP

**Insulator Material:**  
Black Liquid Crystal Polymer  
**Terminal Material:**  
Phosphor Bronze  
**Operating Temp Range:**  
-55°C to +125°C  
**Plating:**  
Sn or Au over 50µ" (1,27 µm) Ni  
**RoHS Compliant:**  
Yes  
**Lead-Free Solderable:**  
Yes  
**SMT Lead Coplanarity:**  
.004" (0,10 mm) max


## RECOGNITIONS

For complete scope of recognitions see [www.samtec.com/quality](http://www.samtec.com/quality)



Mates with:  
FFSD, CLP, FLE

## OPTIONS



Mates with  
socket strips  
or IDC cable

Surface  
mount or  
through-hole

Micro pitch  
.050" x .050"  
(1,27 mm x 1,27 mm)

Low profile  
(1,27 mm) .050"

Shrouded and  
alignment pin  
options available

Impedance matched for  
high speed applications

## ALSO AVAILABLE (MOQ Required)

- Alignment pin
- Contact Samtec.

FTS	1	NO. PINS PER ROW	LEAD STYLE	PLATING OPTION	ROW OPTION	OTHER OPTION							
		02 thru 50 (except -S & -SA option = 05 thru 46)	<p><b>-01</b> = .120" (3,05 mm) Post (Mates with FFSD)</p> <p><b>-02</b> = .075" (1,91 mm) Post (Mates with FLE)</p> <p><b>-03</b> = .065" (1,65 mm) Post (Mates with CLP)</p>	<p><b>-F</b> = Gold flash on post, Matte Tin on tail</p> <p><b>-L</b> = 10µ" (0,25 µm) Gold on post, Matte Tin on tail</p>	<p><b>-D</b> = Double Through-hole</p> <p><b>-DV</b> = Double Vertical SMT</p> <p><b>-S</b> = Single Through-hole</p> <p><b>-SV</b> = Single Vertical SMT</p>	<p>(-D &amp; -DV only)</p> <p><b>-SA</b> = End Shroud with Alignment Pin (05 thru 46 positions. Style -02 &amp; -03 only)</p> <p><b>-S</b> = End Shroud (05 thru 46 positions. Style -02 &amp; -03 only)</p> <p><b>-P</b> = Pick &amp; Place Pad (04 positions minimum)</p> <p><b>-TR</b> = Tape &amp; Reel (-DV only) (Required callout for positions 2 thru 4)</p>							
			<table border="1"> <thead> <tr> <th>LEAD STYLE</th> <th>A</th> </tr> </thead> <tbody> <tr> <td>-01</td> <td>(3,05) .120</td> </tr> <tr> <td>-02</td> <td>(1,91) .075</td> </tr> <tr> <td>-03</td> <td>(1,65) .065</td> </tr> </tbody> </table>	LEAD STYLE	A	-01	(3,05) .120	-02	(1,91) .075	-03	(1,65) .065		
LEAD STYLE	A												
-01	(3,05) .120												
-02	(1,91) .075												
-03	(1,65) .065												

**Note:** Some lengths, styles and options are non-standard, non-returnable.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [FFC & FPC Connectors](#) category:*

*Click to view products by [Samtec](#) manufacturer:*

Other Similar products are found below :

[HFW11R-1STE1H1LF](#) [FH29B-100S-0.2SHW\(99\)](#) [FA5S008HP1](#) [FH29B-120S-0.2SHW\(99\)](#) [FH29B-80S-0.2SHW\(99\)](#) [FHS-16](#) [FPH-2022G](#)  
[52610-1075](#) [52610-1275](#) [52610-1934](#) [XF3M\(1\)-1415-1B-R100](#) [501864-3091-TR225](#) [0525594033](#) [086210010340800](#) [086222026001800](#)  
[52271-2869-CUT-TAPE](#) [62674-201121DLF](#) [62684-36210E9ALF](#) [52610-1675](#) [52746-1671-TR250](#) [10051922-2810EHLF](#) [6-520415-9](#)  
[BD021-09A-A1-0350-0200-0550-LD](#) [SFV6R-1STE9HLF](#) [XF3M-2915-1B-R100](#) [1658549-1](#) [62674-221121ALF](#) [46214008010800](#)  
[046298003000883](#) [151660622](#) [842-816-2630-035](#) [AYF530665TA](#) [AYF351525](#) [046296011930846+](#) [AYF352325A](#) [046254020000800+](#)  
[FH19C-13S-0.5SH\(99\)](#) [FH39J-51S-0.3SHW\(99\)](#) [AYF355125A](#) [AYF530365TA](#) [FH29B-44S-0.2SHW\(99\)](#) [SFW5R-2STAE9LF](#) [AYF351125A](#)  
[AYF350725A](#) [62684-502100AHLF](#) [FH39-61S-0.3SHW\(99\)](#) [AYF414035A](#) [10064555-172520HLF](#) [AYF212335A](#) [504754-2500](#)