



Sierra Wireless® MC Series Embedded Modules

SWITCH NETWORKS ANYTIME

The MC74xx module variants allow device manufacturers to store up to three different firmware variants on-board, while the MC73xx has the same functionality via host download, simplifying logistics and supply chain management.



High-speed connectivity in a mini-card form factor

Sierra Wireless® AirPrime® MC Series supports the latest 4G and 3G networks in North America, Europe, and Asia. Optimized for low power consumption, the MC Series is ideal for today's mobile computing, networking, and industrial IoT applications.

DEPLOY ON THE WORLD'S FASTEST LTE NETWORKS

The MC Series supports 3G and 4G global networks, including LTE Advanced, with automatic fallback to 3G and 2G networks depending on the module variant.

ENABLE LOCATION BASED SERVICES

GNSS tracking lets you locate, monitor, and deploy location-based applications and services with module variants supporting GPS, GLONASS, Beidou, and Galileo satellite systems.

INCORPORATE CLOUD CONNECTED SOLUTIONS

Update firmware, manage applications, and utilize product data over-the-air with AirVantage® cloud connectivity (some module variants require a Linux SDK).

| MODEL | AIR INTERFACE | PEAK D/L RATE | PEAK U/L RATE |
|-------------------|--|--|--|
| MC7455 | LTE-FDD, LTE-TDD HSPA+ | 300 Mbps | 50 Mbps |
| MC7430 | LTE-FDD, LTE-TDD HSPA+, TD-SCDMA | 300 Mbps | 50 Mbps |
| MC73xx | LTE,HSPA+,GSM/GPRS/ EDGE, EV-DO Rev A, 1xRTT (MC7354/50) | 100 Mbps | 50 Mbps |
| MC8705 | HSPA+,GSM/GPRS/EDGE | 21.1 Mbps | 5.76 Mbps |
| MC9090 /MC809x | HSPA+,GSM/GPRS/EDGE, EVDO (MC9090) | HSPA+ 14.4Mbps EVDO 3.1Mbps (MC9090) | HSPA+ 5.76Mbps EVDO 1.8Mbps (MC9090) |

Sierra Wireless MC SERIES EMBEDDED MODULES

| | MC9090 | MC8705 | MC8704 | MC8092 | MC8090 |
|-----------------------------------|---|------------------------------------|------------------------------------|-----------------------------------|-----------------------------------|
| TARGET REGION | Global | Global | Global | EMEA | Global |
| 3G WCDMA | | | | | |
| Frequency Bands | 800, 850, 1900, 2100 | 850, 900, 1900, 2100 | 850, 900, 1900, 2100 | 900, 2100 | 850, 1900, 2100 |
| 2G CDMA 1XRTT/EV-DO REV A | | | | | |
| Frequency Bands | BCO, BC1 | | | | |
| 2G EDGE/GSM/GPRS | | | | | |
| Frequency Bands | Quad-band | Quad-band | Quad-Band | Quad-band | Quad-Band |
| APPROVALS | | | | | |
| Regulatory | FCC, IC, PTCRB, NCC | CE, FCC, IC, NCC, PTCRB, GCF-CC | CE, FCC, IC, NCC, PTCRB, GCF-CC | CE, GCF-CC, JRF/JPA | FCC, IC, PTCRB, JRF/JPA |
| Carrier | AT&T, Verizon, Sprint, Aeris, Rogers | AT&T, Bell, Telus, Rogers | Telstra | | AT&T, docomo |
| CPU PERFORMANCES: IO VOLTAGE | 1.8V | | 1.8V | 1.8V | 1.8 V |
| INTERFACES | | | | | |
| UART | 1 X 8-wire | | | 1 X 4-wire | 1 X 4-wire |
| USB | USB 2.0 High Speed | USB 2.0 High Speed | USB 2.0 High Speed | USB 2.0 High Speed | USB 2.0 High Speed |
| Main Radio Disable | Р | Р | Р | Р | Р |
| Vref | 1.8V | 1.8V | 1.8V | 1.8V | 1.8V |
| GPIO | 4 | | 5 | 4 | 4 |
| Flash LED output | 1 | 1 | 1 | 1 | 1 |
| Audio | PCM/I2S | | 125 | PCM/I2S | PCM/I2S |
| SIM interface: 1.8 or 3V | 1 | 1 | 1 | 1 | 1 |
| ANTENNA | | | | | |
| Connectors | Main, Aux, GNSS | Main, Aux/GNSS | Main, Aux/GNSS | Main, Aux, GNSS | Main, Aux, GNSS |
| Diversity | ✓ | ✓ | ✓ | ✓ | ✓ |
| LOCATION SOLUTION | | | | | |
| Satellite Systems | GPS | GPS | GPS | GPS | GPS |
| Modes | Standalone, SUPL 1.0, XTRA 1.0 | Standalone, SUPL 1.0, XTRA 1.0 | Standalone, SUPL 1.0, XTRA 1.0 | Standalone, SUPL 1.0, XTRA 1.0 | Standalone, SUPL 1.0, XTRA 1.0 |
| CONTROL OPTIONS | | | | | |
| APIs, AT Commands | ✓ | ✓ | ✓ | \checkmark | \checkmark |
| DRIVERS | | | | | |
| Windows® Mobile 6.5 and CE 6.0 | ' | ✓ | ✓ | ✓ | ✓ |
| Android and Linux | ✓ | ✓ | ✓ | ✓ | ✓ |
| DEVICE DIMENSIONS | 51 x 30 x 4.5 mm | 51 x 30 x 4.5 mm | 51 x 30 x 4.5 mm | 51 x 30 x 4.5 mm | 51 x 30 x 4.5 mm |
| TEMPERATURE RANGE | | | | | |
| Industrial Grade | -40°C to +85°C | -25°C to +75°C | -25°C to +75°C | -40°C to +85°C | -40°C to +85°C |



Sierra Wireless MC SERIES EMBEDDED MODULES

| | MC7455 | MC7430 | MC7354 | MC7350 | MC7330 | MC7304 |
|---------------------------------------|---|--|---|-----------------------------------|-----------------------------------|-----------------------------------|
| TARGET REGION | Americas/EMEA | APAC | Americas | USA | Japan | EMEA/Australia |
| 4G LTE Frequency Bands | B1-B5, B7, B12, B13, B20, B25, B26, B29, | B1, B3, B5, B7, B8, B18, B19, B21, B28, | B2, B4, B5, B13, B17, B25 | B4, B13, B25 | B1, B19, B21 | B1, B3, B7, B8, B20 |
| 0.0111001111 | B30, B41 | B38-B41 | | | | |
| 3G WCDMA | D4 D2 D2 D4 D5 D0 | D4 D5 D6 D0 D0 D40 | D4 D3 D4 D5 D0 | D4 D2 D4 D5 D0 | D4 D5 D6 D40 | D4 D2 D5 D0 |
| Frequency Bands 3G TD-SCDMA | B1, B2, B3, B4, B5, B8 | B1, B5, B6, B8, B9, B19 | 81, 82, 84, 85, 88 | B1, B2, B4, B5, B8 | B1, B5, B6, B19 | B1, B2, B5, B8 |
| Frequency Bands | | B39 | | | | |
| 2G CDMA 1XRTT/EV-DO REV A | | 555 | | | | |
| Frequency Bands | | | BC0, BC1, BC10 | BC0, BC1, BC10 | | |
| 2G EDGE/GSM/GPRS | | | BC0, BC 1, BC 10 | BC0, BC 1, BC 10 | | |
| Frequency Bands | | | Quad-band | | | |
| APPROVALS | | | *************************************** | | | |
| Regulatory | FCC, IC, CE, NCC, GCF, PTCRB | JRF/JPA, NCC, CE, GCF | FCC, PTCRB, NCC | FCC, NCC | JRF/JPA, NCC | CE, GCF, NCC, FCC |
| Carrier | AT&T, Verizon, Sprint, Vodafone | docomo, Telstra, Planned: KDDI, Softbank | AT&T, Verizon, Sprint | Verizon, Sprint | docomo | Telstra, Vodafone |
| CPU PERFORMANCES: IO VOLTAGE | 1.8 V | 1.8V | 1.8V | 1.8V | 1.8V | 1.8 V |
| INTERFACES | | | | | | |
| USB | USB 3.0, USB 2.0 High Speed | USB 3.0, USB 2.0 High Speed | USB 2.0 High Speed | USB 2.0 High Speed | USB 2.0 High Speed | USB 2.0 High Speed |
| Main Radio Disable | Р | Р | Р | Р | Р | Р |
| Vref | 1.8V | 1.8V | 1.8V | 1.8V | 1.8V | 1.8V |
| GPIO | 4 | 4 | 4 | 4 | 4 | 4 |
| Flash LED output | 1 | 1 | 1 | 1 | 1 | 1 |
| Audio | PCM/12S | PCM/I2S | PCM/I2S | PCM/I2S | PCM/I2S | PCM/I2S |
| SIM interface: 1.8 or 3V | 1 | 2 | 1 | 1 | 1 | 1 |
| ANTENNA | | Maria Conce conce | | | | |
| Connectors | Main, Aux/GNSS, GNSS | Main, Aux/GNSS, GNSS ✓ | | Main, Aux, GNSS ✓ | Main, Aux, GNSS ✓ | Main, Aux, GNSS √ |
| Diversity MIMO | ✓ | ✓ | ✓ ✓ | ✓ | ✓ | ✓ |
| GNSS Bias | | ∨ | v | ∨ | ∨ | v |
| LOCATION SOLUTION | · | • | • | • | • | • |
| Satellite Systems | GPS, Glonass, Beidou, Galileo | GPS, Glonass, Beidou, Galileo | GPS, Glonass | GPS, Glonass | GPS, Glonass | GPS, Glonass |
| Modes | Standalone, SUPL 2.0, XTRA 3.0 | Standalone, SUPL 2.0, XTRA 3.0 | Standalone, SUPL 2.0, XTRA 2.0 | Standalone, SUPL 2.0, XTRA 2.0 | Standalone, SUPL 2.0, XTRA 2.0 | Standalone, SUPL 2.0, XTRA 2.0 |
| CONTROL OPTIONS | Ĺ | | | | | |
| APIs, AT Commands DRIVERS | ✓ | √ | √ | √ | √ | √ |
| Windows® 7, 8.1 and 10 | ✓ | ✓ | ✓ | ✓ | \checkmark | ✓ |
| Windows® Mobile 6.5 and CE 6.0 | | | ✓ | ✓ | ✓ | ✓ |
| Android and Linux | ✓ | √ | √ | ✓ | ✓ | √ |
| DEVICE DIMENSIONS | 51 x 30 x 2.7 mm | 51 x 30 x 2.7 mm | 50 x 30 x 2.7 mm | 50 x 30 x 2.7 mm | 50 x 30 x 2.7 mm | 50 x 30 x 2.7 mm |
| TEMPERATURE RANGE Industrial Grade | -40°C to +85°C | -40°C to +85°C | -40°C to +85°C | -40°C to +85°C | -40°C to +85°C | -40°C to +85°C |

About Sierra Wireless

Sierra Wireless is building the Internet of Things with intelligent wireless solutions that empower organizations to innovate in the connected world. We offer the industry's most comprehensive portfolio of 2G, 3G, and 4G embedded modules and gateways, seamlessly integrated with our secure cloud and connectivity services. OEMs and enterprises worldwide trust our innovative solutions to get their connected products and services to market faster.

For more information, visit www.sierrawireless.com.



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for sierra manufacturer:

Other Similar products are found below:

Q52-DK XA1110-EVK FX30 DPY102223/5 BX3105 DEV KIT-6001182 XA1100-EVK XM1100-EVK MANGOH-GREEN-STARTER-KIT BX3100 DEV KIT-6001146 XA1110 DEV KIT-6001184 MANGOH-GREEN-BOARD-ONLY HL SNAP-IN TOOL WP8548_1103552 HL6528RD-2.8V 1103167 MC7430 WP7502 HL6528RD-G 1103166 WP SNAP-IN COVER WP8548 HL6528RD WP7504 HL6528_1102464 HL6528RD-2.8V HL7588-ATT WP SNAP-IN BASE