

Products

- О <u>Ву Туре</u> .
 - Connectors • Electromechanical Components
 - . Electronic Modules
 - Fiber Optics
 - Filters
 - Identification & Labeling Passive Components
 - Power Sources
 - . RF & Microwave Products
 - Tooling Products
 - Touch Screen Displays •
 - Tubing, Molded and Harnessing Products Wire, Cable and Cable Assemblies
 - List all product ty pes...
- O By Industry
 - Aerospace & Defense Products

 - <u>Appliance</u>
 <u>Autom otive</u>
 - Communications <u>Computer & Consumer Electronics</u>
 - Industrial & Comm ercial
 - Instrumentation & Medical
- O By Brand
- O <u>A to Z</u> O <u>Product News</u>

Documentation

- O Find Documents & Drawings
- 0 0 Find CAD Models
- SPICE/Electrical Models
- NAFTA Certificate of Origin 0 O White Papers

<u>Resources</u>

- 0 RoHS Compliance & Alternates
- 0 0 Cross Reference Products
- Compare Multiple Products Check Distributor Inventory 0
- O Find Authorized Distributors

• My Account

O Sign In O Register

<u>Customer Support</u>

- Support
 RoHS Support Center
 Glossary of Terms
 eBulletin Newsletter

1571296-2 Product Details

Live Product Chat US Only

Pushbutton Switches

1

Always EU RoHS/ELV Compliant (Statement of Compliance)

- Product Highlights:
- Switch Mechanical
- ٠ Tactile Single Pole - Single Throw Configuration (Pole-Throw) .
- Contact Rating = 50mA Process Sealed
- View all Features | Find Sim ilar Products

Documentation & Additional Information

Product Drawings:

• <u>SWITCH ASSEMBLY, TACTILE, 6mm SEALED, SMT</u> (PDF, English)

Catalog Pages/Data Sheets:

1571296-2

Active

- ALCOSWITCH PRODUCTS (PDF, English)
- Products for Mobile Equipment (PDF, English)

Product Specifications:

None Available

Application Specifications:

None Available

Instruction Sheets:

None Available

CAD Files:

None Available

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Type = Switch Mechanical
- Tactile = Y es
- Configuration (Pole-Throw) = Single Pole Single Throw
- Mount Angle = Vertical
- Term ination Type = Printed Circuit
- Actuator Style = Round
- Leg Style = Gullwing
- Comm ent = (On) indicates mom entary position

Electrical Characteristics:

• Contact Rating = 50mA

Body Related Features:

- Mount Style = Surface Mount
- Actuator Length (mm [in]) = 0.90 [0.035]
- Actuator Profile = Extended
- Actuator Color = Black
- Case Material = Thermoplastic (LCP)
- Actuator Material = Thermoplastic

Contact Related Features:

- Contact Plating = Silver
- Contact Material = Stainless Steel

Housing Related Features:

• Process Sealed = Yes Low Profile = No

Provide Website Feedback| Contact Customer Support Home | Customer Support | Suppliers | Site Map | Privacy Policy | Browser Support 2008 Ty co Electronics Corporation All Rights Reserved

◆ Previous 1 ... [11] 12 13 14 15 ... 20 Next ◆ Quick Links

- Check Pricing & Availability
- . Search for Tooling ٠ Product Feature Selector
 - Compare Products
 - Contact Us About This Product

Additional Information: Product Line Information

Related Products: Tooling

List all Docum ents

Configuration Related Features:

- Operating Function = Off [On]
- Ganged = No
- ESD Grounding Terminal = With
- Actuator Force (g [oz]) = 160.00 [5.648]
- Number of Actuators = Single
- Illum inated = No
- Dust Proof = Yes
- Support Bracket = W ithout
- Snap Action = Without
- Tactile Feel = With
- Switch Height (mm [in]) = 3.30 [0.129]

Industry Standards:

- <u>RoHS/ELV Compliance</u> = RoHS compliant, ELV com pliant
- Lead Free Solder Processes = Reflow solder capable to 245C, Reflow solder capable to 260C
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

• Temperature Rating = Standard

Packaging Related Features:

• Packaging Method = Tape & Reel

Other:

• Brand = Alcoswitch

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Tactile Switches category:

Click to view products by TE Connectivity manufacturer:

Other Similar products are found below :

KMR633NG LFG5GTH920015GTH92022426426-201-11343MJ1226MJTP1109BMJTP1138EAUTRMJTP1230BLMJTPSHWGS6.90F300QP1-1977223-01-1977120-4ADTSA62NVADTSA62RVADTSA63KVADTSA644NVADTSM24NVTRADTSMW66NVADTSMW67RVATM533VTR1571300-3B3F-3123B3F-6055AB3F-B32-01-KIT1977177-81977266-12-1977223-42-1977223-7ADTS644KVADTSA61RVADTSA62KVADTSA63NVADTSA63RVADTSA65NVADTSM21NSVTRADTSM25RVTRADTSM31RVTRADTSM32NVTRADTSM61YVTRADTSM63SVTRADTSM644KVTRADTSMW64RVADTSMW69NVFSMRA4JHA04GS4.70F300QPD38999/20JJ37SATL1105BTL1105JATH447K2QATM534VTR