# **Digital Storage Oscilloscope**





#### **Features**

- · Analog channels and 2GSPS real-time sampling rate
- Dual time base function; unrivaled waveform detail observation and analysis capabilities
- 3½ digital multimeter
- Supports plug-and-play USB storage devices and capable of communicating with a computer
- USB drive system software upgrade
- Built-in FFT and Multiple waveform mathematics functions (including add, subtract, multiply and divide)
- · Edge, Video, Pulse, Slop and Alternate trigger functions

### **Specifications**

Channels : 4

 $\begin{array}{lll} \mbox{Bandwidth} & : 300\mbox{MHz} \\ \mbox{Sample Rate} & : 2\mbox{GSPS} \\ \mbox{Rise Time} & : \le 1.2\mbox{ns} \\ \mbox{Memory Depth} & : 24\mbox{kpts} \\ \end{array}$ 

Vertical Sensitivity : 2mV/div to 5V/div Timebase Range : 1ns/div to 50s/div

Storage : Setup, Wave, Bitmap, CSV

Trigger Modes : Edge, Pulse, Video, Slope, Alternate

Interface : USB Device, USB Host, Multimeter Interface

### **Multimeter Specifications**

	Range	Best Accuracy
DC Voltage (V)	400mV, 4V, 40V, 400V	±(1% + 5)
AC Voltage (V)	4V, 40V, 400V	±(1.2% + 5)
DC Current (A)	4mA, 40mA, 400mA, 4A	±(1% + 5), 4A : ±(1.5% + 5)
Resistance (Ω)	400Ω, 4kΩ, 40kΩ, 400kΩ, 4ΜΩ, 40ΜΩ	±(1.5% + 5)
Display Count	4,000	
Auto Range	$\sqrt{}$	

www.element14.com www.farnell.com www.newark.com www.cpc.co.uk www.mcmelectronics.com



# **Digital Storage Oscilloscope**



#### **General Characteristic**

Power : 100 - 240V AC, 45 - 440Hz

Display : 5.7 Inches 64K Colour TFT LCD, 320 × 240

Product Colour : White and Grey

Product Net Weight : 3.8 kg

Product Size : 330mm × 165mm × 165mm

Standard Accessories : Probe×4 (1×,10× switchable), Current-to-Voltage Convertor Module, Test Leads, Power Cord, USB Cable, PC Software CD

Safety Rating : CAT II 300V

#### **Part Number Table**

Description	Part Number
Oscilloscope, 4CH, 300MHz, 2GSPS	72-7630

Important Notice: This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Tenma is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com www.farnell.com www.newark.com www.cpc.co.uk www.mcmelectronics.com



## **X-ON Electronics**

**Authorized Distributor** 

Click to view similar products for Benchtop Oscilloscopes category.

Click to view products by Tenma manufacturer.

Other Similar products are found below:

FLUKEBP120MH FLUKEBP190 PICOSCOPE2205AMSO PICOSCOPE3203DMSO
PICOSCOPE5244B PK007019 PK007026 PK4001 GDS2072A GDS2074E PP0081
PP0111 MS250 DXC200 MSO5102D MSODLS18 HMO1212 PICOSCOPE2206B
PICOSCOPE2206BMSO PICOSCOPE2207BMSO PICOSCOPE3403D
PICOSCOPE3404DMSO PICOSCOPE4824 PICOSCOPE5444B PK007013