DIN Rail Terminal Blocks

MIK3

5 mm - 600 Volts AC/DC


Specifications:

- Insulating Material, Nylon- 6/6, Gray
- Wire Range #12-#22 AWG 20 Amps
- UL Recognized File No. XCFR2.E62806
- CSA Certified File No. LR700930 25 Amps
- VDE 26 Amps
- (€
- RoHS Compliant



Catalog #	Description
MIK3	Center Section
MN35-2	DIN Rail symmetrical 35 X 7.5 mm slotted 2 m long, steel zinc-plated
MVB2-2	Jumper 2-position
MVB2-12	Jumper 12-position
MVL2-2	Connecting straps for linking together two adjacent 12-pole jumpers
MIW2	Insulating end sections for covering and insulating the last terminal in an assembly
MIW4	Insulating partition walls for visual/electrical separation of terminal groups
MKAW2	Safety cover with warning label for line terminals which cannot be disconnected
MSK35	End bracket used on both ends of the assembly to hold blocks in place

Wire strip length 1/4"



Dimensions:

H = 36 mm (1.417") W = 42 mm (1.653") T = 5 mm (.197")

For electronic drawings or 2D/3D CAD data, submit request at www.marathonsp.com/drawings.html



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for marathon manufacturer:

Other Similar products are found below:

104 599-GP-2004-10 600-2004-3-SP 600-GP-20 600TS-10 601-GP-2102-02 601-GP-3/4ST-12 601-GPYSY-03 602-GPYSY-22 603-2302-04 603-JJ-04 603-JJ-07 604-JJ-06 605-GP-03SLB 605-JJ-02 651-XPR-13 670-3/4ST-9 670A-GP-3000-18 670A-GP-3000-25 670A-GP-3000-27 670A-GP-3/4ST-10 670-GP-19 CW205-01C 671-RZ-25 672-GPY-05 672-RZ-24 699-GP-2102-08 699-GP-2120-12 6F30A3S 6H38-TSKK-C 6R30A3SP F600A1B F600A3B F60A1B 799-6-KT28 799-7-KT28 FPB33588 8TBJ02 R30A1B RF400A3B 1321970 1322970CH 1320972 1331955 1332270 1332554CH 1333280CH 1333575CH 1353701 1353701CH