

# Series 801 Mighty Mouse Double-Start ACME Thread Metal Protective Cover 667-217 and 667-218 Ordering Information



#### **Protect Connectors From Damage**

Machined aluminum covers have rubber gaskets for a watertight fit.

#### **Stainless Steel Fittings and Rings**

Choose small diameter eye fittings for panel attachment. Larger rings fit under the jam nut or over cable jackets. Split rings can be installed on fully assembled cables.

### **Polyurethane-Coated SST Wire Rope**

offers high strength, excellent abrasion resistance and good flexibility. Or, choose Fluoropolymer jacket for high temperature exposure.

**Braided Nylon Rope** provides excellent flexibility and good abrasion resistance, and can be ordered with slip knot fittings for easy installation on any size cable.



Table II: Attachment Code									
Omit for attachment types <b>N</b> (No Attachment)									
and <b>SK</b> (Slip Knot)									
Small Ring	01 –	.126 (3.20) I.D.							
	02 -	.145 (3.68) I.D.							
	04 -	.188 (4.78) I.D.							
± .010 I.D. tolerance	06 -	.197 (5.00) I.D.							
	32 –	.265 (.37) I.D.							
		.315 (8.00) I.D.							
		.385 (9.78) I.D.							
	15 –	.445 (11.30) I.D.							
(( ))	ı	.510 (12.95) I.D.							
	16 –	.570 (14.48) I.D.							
	17 –	(,							
	18 –	.695 (17.65) I.D.							
$(\bigcirc)$	27 –	( )							
	19 –	(==:::)							
	26 –								
		1.070 (27.17) I.D.							
Large Ring	21 –								
± .015	22 -								
I.D. tolerance	23 –	( ,							
i.b. tolerance	30 -	1.380 (35.05) I.D.							
		.432 (11.00) I.D.							
(( ))	52 -								
	54 –								
	56 -	.757 (19.20) I.D.							
	58 -	,,							
Щ	60 -								
		1.137 (28.90) I.D.							
Split Ring	68 –	1.357 (34.50) I.D.							
Split Mily									

	How To Order					
Sample Part Number	667-217	-M	-G	9	04	-6
Series (See Table I)	<b>667-217</b> = Plug Cover <b>667-218</b> = Receptacle Cover					
Material and Finish	C = Aluminum / Black Anodize (Non-Conductive) RoHS Compl M = Aluminum / Electroless Nic RoHS Compliant MT = Aluminum / Nickel-PTFE f Compliant NF = Aluminum / Cadmium wit Olive Drab Chromate ZNU = Aluminum / Zinc-Nickel Black Chromate					
	Z1 = Stainless Steel / Passivated Compliant					
Attachment Type	-D = Bead Chain, CRES, Passivate -F = Wire Rope, Nylon Jacket					
	-G = Nylon Rope					
	-H = SST Wire Rope, Fluoropolymer Jacket					
	-N = No Attachment					
	-R = Wire Rope, PVC Jacket					
	-S = SST Sash Chain					
	-SK = Nylon Rope With Slip Knot					
	-T = SST Wire Rope, No Jacket					
	-U = SST Wire Rope, Polyurethane Jacket					
	"SST" = Stainless Steel					
Shell Size	5, 6, 7,8, 9, 10, 11, 13, 16, 17, 19, 21					
Attachment Code (See Table II)	Small Ring = 01 thru 06 Split Ring = 50 thru 68 Solid Ring = 14 thru 33					
Attachment Length (inches	Omit for attachment Type N (No Attachment) Example "-6" equals six inch length					

Dimensions in Inches (millimeters) are subject to change without notice.

© 2014 Glenair, Inc. Series 80 Mighty Mouse U.S. CAGE Code 06324 Rev. 05.25.17 Printed in U.S.A.

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular MIL Spec Tools, Hardware & Accessories category:

Click to view products by Glenair manufacturer:

Other Similar products are found below:

809-199-3 001104 300 04 600-006-16 600-079-06 M10-101982-143 M10-101982-163 M10-101983-183 M10-150912-083 M10-454396-008 602GB18808 M225201-06 M24758-20E21 M2887610-BC M2887615-CD M38999/9-19B 62GB-812-10 630A007NF083A 630B007M051A 630BJ003NF032H 637-149NF04B M39029/29-215 650FS002NF16 M81969-14-02 660-008NF14S7-01 660-009M22H8-03 660-013NF19U6-210 660-015M10S6-17 660-015NF10S5-01 660-015NF14R3.5-01 660-023NF19H6-19 660-024N09S5-104 660-024NF11S12-01 660-024NF11S3-01 660-050XM17F4-01 660-068NF25R6-30G 660-070M23S8-04 660-073MTCH9-20 M83723/60-116RC M83723/61-18W M83723/61-218R M83723/61-224W 667-224NF16 M85049/118S22A M85049/126S11N M85049130-07M M85049140-09BC M85049/41-16A W/B 687-697NF-1 M85049/75-14-1 M8504980-8