




©Premier Farnell  
Copying of image is prohibited

**PCB TERMINAL STRIP 2 SOLDER PINS / POLE 4 POLE PIN SPACING 2.54 MM / 0.1 IN**

|                                     |                            |
|-------------------------------------|----------------------------|
| Product group                       | 4 (Printed Circuit)        |
| Weight                              | 1.466 g                    |
| Color                               | orange                     |
| No. of connection Points            | 4                          |
| No. of potentials                   | 4                          |
| pole count                          | 4                          |
| Height                              | 11.7 mm                    |
| Height                              | 0.461 in                   |
| Width                               | 12.46 mm                   |
| Width                               | 0.491 in                   |
| Depth                               | 12.1 mm                    |
| Depth                               | 0.476 in                   |
| Pin spacing from                    | 2.54 mm                    |
| Pin spacing from                    | 0.1 in                     |
| Pollution degree                    | 2                          |
| Measured voltage EN                 | 160 V                      |
| Measured shock voltage              | 2.5 kV                     |
| Current intensity EN                | 6 A                        |
| Pollution degree                    | 2                          |
| Measured voltage EN                 | 320 V                      |
| Measured shock voltage              | 2.5 kV                     |
| Current intensity EN                | 6 A                        |
| Connection method                   | CAGE CLAMP® CONNECTION     |
| Cross section [mm <sup>2</sup> ]    | 0.08 - 0.5 mm <sup>2</sup> |
| Wiring method                       | solid                      |
| Cross section [mm <sup>2</sup> ]    | 0.08 - 0.5 mm <sup>2</sup> |
| Cross section to [mm <sup>2</sup> ] | 0.25 mm <sup>2</sup>       |
| Cross section to [mm <sup>2</sup> ] | 0.25 mm <sup>2</sup>       |
| Cross section [AWG]                 | 28 - 20 AWG                |
| Strip length from                   | 5 mm                       |

|                 |      |
|-----------------|------|
| Strip length to | 6 mm |
| Material group  | I    |

| <u>general accessory</u>  |                                |   |        |
|---|--------------------------------|---|--------|
|  | <a href="#"><u>233-331</u></a> | OPERATING TOOL INSULATED  | yellow |
|  | <a href="#"><u>233-332</u></a> | OPERATING TOOL FOR 233 AND 733 SERIES<br>CONTAINS INSULATING MATERIAL | white  |
|  | <a href="#"><u>233-335</u></a> | OPERATING TOOL FOR 233 AND 733 SERIES                                 | green  |

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [wago manufacturer](#):*

Other Similar products are found below :

[750-460](#) [231-118/026-000](#) [231-303/026-000](#) [231-620/019-000](#) [257-403](#) [280-438](#) [280-831](#) [284-624](#) [210-111](#) [231-303/037-000](#) [231-446/001-000\\_NR](#) [232-216/026-000](#) [234-510](#) [264-726](#) [280-339](#) [0283-0671](#) [830-800/000-305](#) [750-512](#) [750-455](#) [51251782](#) [286-312](#) [713-1428/107-000](#) [731-138/048-000](#) [750-459](#) [750-517](#) [793-3505](#) [826-172](#) [859-304](#) [280-335](#) [231-535/001-000](#) [2604-1106](#) [2604-1504](#) [2606-1103/020-000](#) [2624-1103](#) [2626-3103/020-000](#) [821-104](#) [713-1107](#) [852-1411](#) [2106-1307](#) [2116-5307](#) [832-1205](#) [832-3604](#) [2009-110](#) [281-512/281-501](#) [286-336](#) [750-421](#) [750-838](#) [753-559](#) [750-1505](#) [787-732](#)