

This document was generated on 04/22/2015

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 71436-1464

Status: **Active**

PMC Mezzanine 1.00mm Pitch Connector **Overview:**

1.00mm Pitch Mezzanine IEEE 1386 Plug, Surface Mount, Dual Row, Vertical **Description:**

Stacking, 64 Circuits, 7.35mm Unmated Height, with PCB Locator Pegs, with Robotic

Placement Metal Cap, Embossed Tape on Reel Packaging

Documents:

3D Model Product Specification PS-71436-9999 (PDF) RoHS Certificate of Compliance (PDF) Drawing (PDF)

Agency Certification

CSA LR19980 UL E29179

General

Product Family PCB Headers Series 71436

Application Board-to-Board, Signal

Overview PMC Mezzanine 1.00mm Pitch Connector

Product Name Mezzanine **UPC** 800753784673

Physical

Breakaway No Circuits (Loaded) 64 Circuits (maximum) 64 Color - Resin Natural Flammability 94V-0 **Glow-Wire Compliant** No Lock to Mating Part None

Mated Height 11.00mm, 14.00mm, 9.00mm

Material - Metal Phosphor Bronze

Material - Plating Mating Gold Material - Plating Termination Tin

Material - Resin High Temperature Thermoplastic

Net Weight 1.360/q Number of Rows 2 Orientation Vertical **PCB** Locator Yes **PCB** Retention None PCB Thickness - Recommended 1.00mm

Packaging Type **Embossed Tape on Reel**

Pitch - Mating Interface 1.00mm Plating min - Mating 0.762µm Plating min - Termination 1.905µm Polarized to Mating Part No


Robotic Placement Pick and Place Cap

Shrouded Fully Stackable No

Temperature Range - Operating -55°C to +85°C Termination Interface: Style Surface Mount

Electrical

Current - Maximum per Contact 1.0A Voltage - Maximum 100V



EU RoHS ELV and RoHS Compliant **REACH SVHC Contains SVHC: No Low-Halogen Status** Low-Halogen



Need more information on product environmental compliance?

Email productcompliance@molex.com For a multiple part number RoHS Certificate of Compliance, click here

Please visit the Contact Us section for any non-product compliance questions.

Search Parts in this Series

71436Series

Mates With

71439 1.00mm Pitch Mezzanine IEEE 1386 Receptacle. Be sure to match like stack heights

Solder Process Data

Duration at Max. Process Temperature (seconds) 15

Lead-free Process Capability SMC & Wave Capable (TH only)

Max. Cycles at Max. Process Temperature 1
Process Temperature max. C 260

Material Info

Reference - Drawing Numbers

Product Specification PS-71436-9999
Sales Drawing SDA-71436-1***

This document was generated on 04/22/2015

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Headers & Wire Housings category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

95000-104TRLF 10135584-644402LF DF62W-EP2022PCA 95000-106TRLF DF62W-2022SCA DF62W-EP2022PC 2203348 DF62W-2022SC 1084018 1029039 1084017 802-10-012-10-002000 1112640 1112639 891-007-9SS-BST1T 000-34000 0008550134 0009482033 0009507031 57102-F02-18ULF 57102-S06-03LF 57202-S52-04LF PCN6-15S-2.5E 0039019024 58102-G61-06LF 582553-1 0009485154 0009508121 0022285053 0050291907 018731A LY20-4P-DT1-P1E-BR 02.125.8002.8 60101931 60598-1 (Cut Strip) M1625-3R/100 61062-3 61082-181009 CSU011177004 636-1427 638009-1 641938-9 641991-4 644168-1 644827-2 647662-1 65039-019ELF 65692-001LF 65781-018 65781-047