

This document was generated on 02/03/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

-			
	<u>0713492008</u>		
Status: Active			
=	C-Grid® Products		
		ader, Surface Mount, Dual Row, Vertical, Shrouded, 20	
(Circuits, Tin (Sn) Plating, w	ith Press-fit Plastic Pegs	
Decumenter			
Documents: 3D Model		Product Specification PS-71349-001 (PDF)	
Drawing (PDF)		RoHS Certificate of Compliance (PDF)	
			_
Agency Certification			Series image - Reference only
UL		E29179	
General			<u>EU ELV</u>
Product Family		PCB Headers	EU RoHS China RoHS
Series		71349	ELV and RoHS
Application		Signal, Wire-to-Board	Compliant
Overview		C-Grid® Products	REACH SVHC
Product Name		C-Grid®	Not Reviewed
UPC		800753784536	Halogen-Free
Dhusiaal			Status
Physical Brookeway		No	Not Reviewed
Breakaway Circuits (Loaded)		20	Need more information on product
Circuits (maximum)		20	environmental compliance?
Color - Resin		Black	Empil productoompliance@molov.com
Durability (mating cycles	(max)	25	Email <u>productcompliance@molex.com</u> Please visit the <u>Contact Us</u> section for any
First Mate / Last Break		No	non-product compliance questions.
Flammability		94V-0	non-product compliance questions.
Glow-Wire Compliant		No	
Guide to Mating Part		No	
Keying to Mating Part		None	Search Parts in this Series
Lock to Mating Part		Yes	<u>71349</u> Series
Material - Metal		Brass, Phosphor Bronze	<u>11040</u> 00103
Material - Plating Mating		Tin	
Material - Plating Termir	nation	Tin	
Material - Resin		High Temperature Thermoplastic	
Number of Rows		2	
Orientation		Vertical	
PCB Locator		Yes	
PCB Retention		Yes	
Packaging Type Pitch - Mating Interface		Tube 2.54mm	
Pitch - Mating Interface Pitch - Termination Inter	face	2.54mm	
Plating min - Mating		3.810µm	
Plating min - Terminatio	n	3.810µm	
Polarized to Mating Part		Yes	
Shrouded		Fully	
Stackable		No	
Temperature Range - O	perating	-40°C to +105°C	
Termination Interface: S		Surface Mount	
Electrical			
Current - Maximum per	Contact	3.0A	
Voltage - Maximum	/	250V	
Solder Process Data			
	s Temperature (seconds)	30	

Lead-free Process Capability Max. Cycles at Max. Process Temperature Process Temperature max. C Reflow Capable (SMT only) 3 245

Material Info

Reference - Drawing Numbers Product Specification Sales Drawing

PS-71349-001 SDA-71349-****

This document was generated on 02/03/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Headers & Wire Housings category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

95000-104TRLF 10135584-644402LF DF62W-EP2022PCA 95000-106TRLF DF62W-2022SCA DF62W-EP2022PC 2203348 DF62W-2022SC 1084018 1029039 1084017 802-10-012-10-002000 1112640 1112639 891-007-9SS-BST1T 000-34000 0008550134 0009482033 0009507031 57102-F02-18ULF 57102-S06-03LF 57202-S52-04LF PCN6-15S-2.5E 0039019024 58102-G61-06LF 582553-1 0009485154 0009508121 0022285053 0050291907 018731A LY20-4P-DT1-P1E-BR 02.125.8002.8 60101931 60598-1 (Cut Strip) M1625-3R/100 61062-3 61082-181009 CSU011177004 636-1427 638009-1 641938-9 641991-4 644168-1 644827-2 647662-1 65039-019ELF 65692-001LF 65781-018 65781-047