

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	08/31/06	D. PARHAM
B	ECN2694: CABLE WAS BEIGE. ADDED ROHS NOTE.	01/11/07	D. PARHAM
C	ECN2917: UPDATED PICTORIALY. UPDATED NOTE FORMAT AND CONTENT.	07/18/07	D. PARHAM
D	ECN#3219: ADDED 1, 20, 30, 40, 60, 75, 80 & 90 FT LENGTHS	03/07/08	D. PARHAM



2X RJ45 PLUG

WIRING MAP		
"P1"	COLOR	"P2"
1	WHT / ORN	3
2	ORN	6
3	WHT / BLU	1
6	BLU	2

PART NUMBER	LENGTH		PART NUMBER	LENGTH	
	FEET	METERS		FEET	METERS
TRD450CR-1	1	0.31	TRD450CR-30	30	9.14
TRD450CR-2	2	0.61	TRD450CR-40	40	12.19
TRD450CR-3	3	0.91	TRD450CR-50	50	15.24
TRD450CR-5	5	1.52	TRD450CR-60	60	18.29
TRD450CR-7	7	2.13	TRD450CR-75	75	22.86
TRD450CR-10	10	3.05	TRD450CR-80	80	24.38
TRD450CR-15	15	4.57	TRD450CR-90	90	27.43
TRD450CR-20	20	6.1	TRD450CR-100	100	30.48
TRD450CR-25	25	7.62			

NOTES:

MATERIAL:

PLUG HOUSING: POLYCARBONATE, CLEAR, UL94V-0
 CONTACTS: PHOSPHOR BRONZE
 CABLE JACKET: PVC, GRAY

FINISH:

CONTACTS: 50 μINCHES GOLD IN CONTACT AREA
 OVER 100 μINCHES NICKEL PLATE OVERALL.

CABLE CHARACTERISTICS:

UNSHIELDED TWO TWISTED PAIR MODULAR CABLE
 24 AWG STRANDED COPPER

MISCELLANEOUS:

PLUG CONFORMS TO TIA-1096
 OPERATING TEMPERATURE RANGE: -20°C TO +60°C
 CABLES TO BE TESTED FOR CONTINUITY
 CABLES TO BE INDIVIDUALLY PACKAGED IN A POLYBAG

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES (mm) OVERALL CABLE LENGTH TOLERANCE: $\leq 12 (305) = +1 (25) / -0$ $> 12 (305) - 60 (1524) = +2 (51) / -0$ $> 60 (1524) - 120 (3048) = +4 (102) / -0$ $> 120 (3048) - 300 (7620) = +6 (152) / -0$ $> 300 (7620) = +5\% / -0\%$ ALL OTHER DIMENSIONAL TOLERANCES: .X = .3 .XX = .15 PROJECTION 	APPROVALS DRAWN BY D. PARHAM CHECKED BY C. McCORMICK APPROVED BY J. KIEZULAS	DATE 08/29/2006 08/29/2006 08/31/2006	 45 BEECHWOOD DRIVE NORTH ANDOVER, MA 01845
	CATEGORY MODULAR		PRODUCT DESCRIPTION RJ45/RJ45 UTP CAT5E XOVER CABLE
	CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY		
	COLOR VARIATIONS MAY OCCUR	SIZE A	FSCM NO. 43321

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [l-com manufacturer](#):

Other Similar products are found below :

[FOA-550A](#) [SDRA15AG](#) [UMC-201](#) [CSMN50MF-5](#) [CSMNB15MF-15](#) [TRD815RA2BL-5](#) [CA3N050](#) [CA3A-90DA-1M](#) [U3A00003-03M](#)
[CTLF3VGAMM-20](#) [HDCAMM-3](#) [U3A00014-03M](#) [ECF-SK-25](#) [CSMT15MF-10](#) [CSMT15MM-15](#) [CSMT15MM-25](#) [CSPL15MF-50](#)
[CSPL25MF-25](#) [CSPL9MF-10](#) [CSPL9MF-5](#) [CSPL25MF-5](#) [CSPL25MF-2.5](#) [AL-IPEPS](#) [NB201611-10F-1](#) [TDG1026KC5-MNL](#) [NB121005-](#)
[10F](#) [TRD855SRA6DBL-05M](#) [TRD855SRA6DBL-10M](#) [TRD855SRA7DBL-1M](#) [TRD855SRA7DBL-10M](#) [PR175SCDLCQ24](#) [TRG508-T4T-](#)
[3M](#) [TRA5261-15F](#) [TRA5261S-1F](#) [TRA6261-1F](#) [TRA6261-10F](#) [USBBFT](#) [DGB25M](#) [CASATAL-18](#) [CSM25MM-10](#) [CSM37MF-10](#)
[CSUSB-100](#) [CA3A-90RA-1M](#) [CA3A-90RMICB-1M](#) [U2A00003-3M](#) [U3A00003-05M](#) [U2A00008-12I](#) [U3A00056-03M](#) [U3A00007-075M](#)
[U3A00007-1M](#)