

LED Lamp, On/Off Switch or Movement Sensor

Lamp LED 025



- Wide voltage range
- Integrated power unit
- Daisy chain
- Long-lived and maintenance-free by LED technology
- Magnet or screw fixing
- On/off switch or movement sensor

The lamp series LED 025 is suitable for all types of panels and enclosures, especially where space is at a premium. The lamps have a very long service life thanks to the use of LED technology. They are available with powerful

non-slip rubberized magnets allowing them to be quickly positioned in any steel enclosure. Alternatively they can be fixed mechanically. The power output allows up to 10 lamps to be connected to each other (daisy chain). Both the power input and output connectors snap lock into their sockets. With the integrated power unit and the plugs the lamp can quickly be connected.

Technical Details

>> Download PDF

| Danner and an artists | | | | | | |
|----------------------------------|---|--|--|--|--|--|
| Power consumption | max. 5W | | | | | |
| Luminosity | 290Lm at 120° (870Lm at 360° or equivalent 75W light bulb) | | | | | |
| Lamp type | LED, angle of radiation 120° | | | | | |
| | light color: daylight, color temperature: 6,500K | | | | | |
| Service life | 60,000h at +20°C (+68°F) | | | | | |
| Connection | 2-pole connector with snap lock | | | | | |
| | AC: max. 2.5A / 240VAC, color: white | | | | | |
| | DC: max. 2.5A / 60VDC, color: blue | | | | | |
| Mounting | magnet fixing or screw fixing (M5), torque 2Nm max., | | | | | |
| | 250mm centers | | | | | |
| Casing | plastic, transparent | | | | | |
| Dimensions | see drawings | | | | | |
| Operating/Storage temperature | -30 to +60°C (-22 to +140°F) / -40 to +85°C (-40 to +185°F) | | | | | |
| Operating/Storage humidty | max. 90% RH (non-condensing) | | | | | |
| Protection type/Protection class | IP20 / II (double insulated) | | | | | |
| Approvals | UL File No. E234324, VDE | | | | | |

Important note: Connectors and cables for electrical connection are not included in the delivery. These parts can be ordered separately (see Accessories, next page). Sets, consisting of lamp and accessories, are available on request.

To top

| Art. No. Magnet fixing | Art. No. Screw fixing | Operating voltage | Switch | Weight (approx.) |
|------------------------------|-----------------------|---|----------------------------------|---------------------|
| 02540.0-00 | 02540.0-01 | 100-240VAC, 50/60Hz (min. 90VAC, max. 265VAC) | on/off light switch | 0.2kg |
| 02540.1-00 | 02540.1-01 | 24-48VDC (min. 20VDC, max. 60VDC) | on/off light switch | 0.2kg |
| 02541.0-00 02541.0-01 | | 100-240VAC, 50/60Hz (min. 90VAC, max. 265VAC) | PIR movement sensor ¹ | 0.2kg |
| 02541.1-00 | 02541.1-01 | 124-48VDC (MIN. 20VDC. MAX. 60VDC.) | PIR movement sensor ¹ | 0.2kg |

¹ approx. 5 min. fixed switch-on duration

Connection cable with female connector and open end

| No. | Model | rtenam | Voltage type | Color | Use for | Approvals ² |
|--------|--|--------|-----------------|--------------------------------|----------------|------------------------|
| 244356 | connection cable 2 x 1.5mm^2 with female connector | 2.0m | AC | connector: white; cable: white | power input | VDE |
| 244337 | connection cable 2 x AWG 16 with female connector | 2.0m | AC | connector: white; cable: white | power input | VDE + UL |
| 244360 | connection cable 2 x 1.5mm² with female connector | 2.0m | DC | connector: blue; cable: white | power input | VDE |
| 244361 | connection cable 2 x AWG 16 with female connector | 2.0m | DC | connector: blue; cable: white | power input | VDE + UL |

² applies only to the individual components (cable and connectors)

To top

Extension cable with 2 connectors for daisy chain connection

| No. | Model | Length | Voltage type | Color | Use for | Approvals ² |
|--------|--|--------|-----------------|---------------------------------|----------------|------------------------|
| | extension cable 2 x 1.5mm² with 2 connectors | 1.0m | AC | connectors: white; cable: white | daisy chain | VDE |
| | extension cable 2 x AWG 16 with 2 connectors | 1.0m | AC | connectors: white; cable: white | daisy chain | VDE + UL |
| | extension cable 2 x 1.5mm² with 2 connectors | 1.0m | DC | connectors: blue; cable: white | daisy chain | VDE |
| 244363 | extension cable 2 x AWG 16 with 2 connectors | 1.0m | DC | connectors: blue; cable: white | daisy chain | VDE + UL |


² applies only to the individual components (cable and connectors)

To top

Female / Male connectors

| Art. No. | Model | Voltage type | Color | Use for | Approvals |
|----------|------------------|--------------|-------|--------------|-----------|
| 264057 | female connector | AC | white | power input | VDE + UL |
| 264058 | male connector | AC | white | power output | VDE + UL |
| 264059 | female connector | DC | blue | power input | VDE + UL |
| 264060 | male connector | DC | blue | power output | VDE + UL |

Technical Drawing



To top

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for stego manufacturer:

Other Similar products are found below:

| 01870.0-30 | 01872.0-30 | 01873.0-30 | 01874.0-30 | 11884.0-30 | 14003.0-00 | 01805.0-00 | 01925.0-00 | 11870.0-00 | 11873.0-00 | 02541.1-03-0003 |
|------------|-------------|------------|------------|------------|------------|------------|------------|------------|------------|-------------------|
| 03082.0-01 | 03082.0-00 | 03084.0-00 | 01131.2-01 | 02031.0-00 | 02032.0-00 | 02035.0-10 | 02540.0-03 | 01131.9-00 | 08605.0-00 | 03114.0-00 |
| 01871.1-30 | 01925.1-01 | 12101.0-30 | 01163.0-01 | 01163.0-03 | 01164.0-00 | 01170.0-01 | 01170.9-01 | 08601.0-00 | 01882.0-00 | 14006.0-00 |
| 14008.0-00 | 01802.0-00 | 02820.0-06 | 02701.0-00 | 04640.0-00 | 06020.0-00 | 11802.0-00 | 02540.0-00 | 03202.9-00 | 244358 013 | 131.2-00 01610.0- |
| 01 01231.1 | -00 28410.0 | -00 244356 | 01185.1-00 | 02034.0-00 | | | | | | |