



## Description:

The Conclamp System is designed to combine the functions of cable entry and secure clamping and allows the additional facility of incorporating a terminal block.

The Conclamp creates a safe entry for cable when used in conjunction with a hole bush or cable gland, preventing damage caused by movement against sharp edges. Once within the unit the cable is held securely using the Conclamp's integral cable clamp. Finally the cable can be terminated into the terminal block.

## Features:

- Consists of an insulated M20 cable entry bush, clamping facilities and a 3-way terminal block
- For IP66 protection replace the cable bush with M20 thread Nylon cable glands
- High cable retention

## Specifications:

Cable Diameter Max	: 13.5mm
Thread Size - Metric	: M20
Cable Gland Material	: Polyamide 6.6
Material Properties	: Halogen Free
Gland Colour	: Black
Behind Panel Depth	: 59mm
Box Quantity	: 5
Cable Diameter Max	: 13.5mm
Connector Type	: Cable Clamp (Gland)
Current Rating	: 10A
External Length / Height	: 30.5mm
External Width	: 28mm
Material	: Nylon
Mounting Hole Dia	: 20mm
Operating Temperature	: -40°C to 110°C
Voltage Rating	: 380V AC

## Part Number Table

Description	Part Number
Conclamp	690/47/4003T(NL)

**Important Notice** : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

# X-ON Electronics

Authorized Distributor

*Click to view similar products for [Pro Power manufacturer](#).*

Other Similar products are found below :

[0301CV100W](#) [04JSBLACK](#) [06JSBLACK](#) [08450046010](#) [08450056010](#) [08450066010](#)  
[08450166010](#) [08450236010](#) [08450256010](#) [08JSBLACK](#) [10026B](#) [10026BK](#) [10026G](#)  
[10026R](#) [10026TB](#) [10026TBK](#) [10026TG](#) [10026TR](#) [10026TW](#) [10026W](#) [10030B](#)  
[10030BK](#) [10030G](#) [10030O](#) [10030R](#)