

#### General ordering data

Order No.	1024100000
Part designation	WDU 2.5/TC TYP K
Version	Special terminal, special connections, 2.5 mm <sup>2</sup> , Screw connection, Wemid, dark beige, TS 35
EAN	4008190140472
Qty.	50 pc(s).

#### PT OKIECEEx/ATEX rating data

EU-type examination certificate	SIRA02ATEX3153U
Download, German	
Download English	SIRA02ATEX3153U_e.pdf
IECEEx Certificate of Conformity	IECEXSIR05.0039U
Download	IECEXSIR05.0039U_e.pdf
ATEX voltage	55 V
ATEX current	1 A
ATEX conductor cross-section	2.5 mm <sup>2</sup>
IECEEx voltage	55 V
IECEEx conductor cross-section	2.5 mm <sup>2</sup>
Voltage when using cross-connections	CrossConnectionGuide.pdf
Operating temperature range	For operating temperature range see EC Design Test Certificate / IEC Ex-Certificate of Conformity
Marking EN 60079-7	Ex e II
Marking ATEX Directive 94/9/EC	Ex II 2 G D

#### 2 clampable conductors (H05V/H07V) with equal cross-section (rated connection)

Solid, min.	0.5 mm <sup>2</sup>
Solid, max.	1.5 mm <sup>2</sup>
Flexible, min.	0.5 mm <sup>2</sup>
Flexible, max.	1.5 mm <sup>2</sup>
Flexible with ferrule, min. (DIN 46228 pt 1)	0.5 mm <sup>2</sup>
Flexible with ferrule, max. (DIN 46228 pt 1)	1.5 mm <sup>2</sup>

**Additional technical data**

Colour of insulating material	dark beige
Connection direction	on side
End plate required	Yes
Explosion-tested version "Ex e"	No
Installation advice	TS 35
Insulating material	Wemid
Levels cross-connected internally	No
No. of identical terminals	1
No. of levels	1
No. of terminal strips per level	2
Open sides	right
Operating temperature range	- 50 °C, + 120 °C
Product family	W-Series
Type of connection	Screwed
Type of mounting	Snap-on
UL 94 flammability rating of insulation material	V-0
Version	Thermocouple

**Conductors for clamping (additional connection)**

Type of connection	Screw connection
--------------------	------------------

**Conductors for clamping (rated connection)**

Clamping range, min.	0.13 mm <sup>2</sup>
Clamping range, max.	2.5 mm <sup>2</sup>
Type of connection	Screw connection
2nd type of connection	screwed
Connection direction	on side
No. of connections	2
Stripping length	10 mm
Clamping screw	M 2.5
Blade size	0.6 x 3.5 mm
Tightening torque range	0.4...0.6 Nm
Torque level with DMS electric screwdriver	1
Gauge to IEC 60947-1	A2
Solid, min.	0.5 mm <sup>2</sup>
Solid, max.	2.5 mm <sup>2</sup>
Stranded, min.	1.5 mm <sup>2</sup>
Stranded, max.	2.5 mm <sup>2</sup>
Flexible, min.	0.5 mm <sup>2</sup>
Flexible, max.	2.5 mm <sup>2</sup>
Flexible with ferrule, min. (DIN 46228/1)	0.5 mm <sup>2</sup>
Flexible with ferrule, max. (DIN 46228/1)	2.5 mm <sup>2</sup>
Flexible, min., ferrule with plastic collar (DIN 46228 pt 4)	0.5 mm <sup>2</sup>
Flexible, max., ferrule with plastic collar (DIN 46228 pt 4)	2.5 mm <sup>2</sup>
Twin wire-end ferrule, min.	0.5 mm <sup>2</sup>
Twin wire end ferrule, max.	1.5 mm <sup>2</sup>
AWG conductor size, min.	AWG 26
AWG conductor size, max.	AWG 12

#### Conductors for clamping (rated connection)

AWG conductor size, min.	0.13 mm <sup>2</sup>
AWG conductor size, max.	3.31 mm <sup>2</sup>

#### Dimensions

Width	10.2 mm
Height of lowest version	50.5 mm
Length	60 mm
Weight	16.88 g
TS 35 offset	32 mm

#### Disconnect terminals

Torque level with DMS electric screwdriver	1
--------------------------------------------	---

#### Rating data


Rated cross-section	2.5 mm <sup>2</sup>
Standards	IEC 60947-7-1 / IEC 60584
Pollution severity	3

#### Thermal voltage terminals

Type of thermo-elements	NiCr/Ni
-------------------------	---------

#### Approvals

Approvals institutes



#### Downloads

STEP	1024100000_15283_WDU_2.5-TC_STP.stp
------	-------------------------------------

#### Classifications

ETIM 2.0	EC000904
ETIM 3.0	EC000904
eClass 4.1	27-14-11-31
eClass 5.0	27-14-11-31
eClass 5.1	27-14-11-31

#### Similar products

Order No.	Part designation	Version
1033700000	WDU 2.5/TC TYP B	Special terminal, special connections, 2.5 mm <sup>2</sup> , Screw connection, Wemid, dark beige, TS 35
1033300000	WDU 2.5/TC TYP E	Special terminal, special connections, 2.5 mm <sup>2</sup> , Screw connection, Wemid, dark beige, TS 35
1024300000	WDU 2.5/TC TYP J	Special terminal, special connections, 2.5 mm <sup>2</sup> , Screw connection, Wemid, dark beige, TS 35
1041500000	WDU 2.5/TC TYP N	Special terminal, special connections, 2.5 mm <sup>2</sup> , Screw connection, Wemid, dark beige, TS 35

1024400000	WDU 2.5/TC TYP SR	Special terminal, special connections, 2.5 mm <sup>2</sup> , Screw connection, Wemid, dark beige, TS 35
1024200000	WDU 2.5/TC TYP T	Special terminal, special connections, 2.5 mm <sup>2</sup> , Screw connection, Wemid, dark beige, TS 35

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [DIN Rail Terminal Blocks](#) category:*

*Click to view products by [Weidmuller](#) manufacturer:*

Other Similar products are found below :

[1045932](#) [00110420202](#) [00110430402](#) [5724.2/L](#) [592808-3](#) [CTS25U/BL](#) [CTS2.5U-N/Y](#) [91.010](#) [91.040](#) [DP25-GY-ND](#) [15288](#) [90.070](#) [90.905](#)  
[91.001](#) [91.020](#) [91.201](#) [91.340](#) [2713793](#) [2757571](#) [280-331](#) [283-317](#) [283-607](#) [2909044](#) [2909798](#) [29-2052](#) [SRT2-OD08CL-1](#)  
[CDL4U\(E\)MOV](#) [2757801](#) [2794660](#) [284-317](#) [2890975](#) [2907033](#) [3048496](#) [CTS2.5U-N/O](#) [5542152](#) [5602077](#) [0709880](#) [5520682](#) [5605444](#)  
[5607102](#) [EPUSC](#) [SRT2-OD16P](#) [2901288](#) [591620-2](#) [1-591651-1](#) [NRA37-1/2](#) [592814-1](#) [592814-3](#) [SRT2-ID16P](#) [NRA37-12](#)