



Varnished Cambric Tapes 2510 and 2520

Data Sheet

Notice: New straight weave cambric!
Please review the Scotch® Varnished Cambric Tapes 2510 and 2520 Data Sheet carefully to ensure this product meets your application requirements.

Product Description

Scotch® Varnished Cambric Tapes are made from straight-cut woven cotton cambric fabric. The fabric is oil primed and coated with a high-grade yellow electrical insulating varnish. Varnished cambric tapes are flexible, electrically insulating and moisture resistant with a smooth finish. 2510 tape is yellow, non-adhesive coated and 7 mils thick. 2520 tape is yellow with a pressure-sensitive adhesive and 8 mils thick. They are designed to perform continuously in temperatures up to 105°C (220°F) with excellent resistance to abrasion, puncture and cut-through. The adhesive on 2520 tape holds the tape in position after application.

- Excellent dielectric strength.
- Electrical properties are stable up to 105°C.
- High puncture and cut-through resistance.
- Varnish cambric tapes are rated for Class A (105°C).
- Non-corrosive adhesive on 2520 tape. Adhesive holds film in position until the jacket is applied.

Applications

For insulating joints requiring rapid and clean re-entry such as motor lead and service drop connections, heavy split-bolts in raceways and bus bar insulating. Use in areas where mechanical protection and puncture resistance is critical.

Note: *Scotch Varnished Cambric Tapes 2510 and 2520 should not be used as primary insulation for splicing and terminating PILC Cable.*

Contact your 3M Electrical Markets Division Representative for product recommendation for splicing and terminating PILC Cable.

Typical Data/Physical and Electrical Properties

	2510	2520
Color	Yellow	Yellow
Surface Finish	Dry	Dry with adhesive
Thickness (ASTM-D-374)	7 mils	8 mils
Tensile Strength (ASTM-D-295)	50 lbs./in.	50 lbs./in.
Adhesion to Steel (ASTM-D1000)	-	13 oz./in.
Adhesion to Backing (ASTM-D1000)	-	8 oz./in.
Dielectric Strength (ASTM-D-295)	800 V/mil	800 V/mil
Thermal Stability	Class A	Class A
Solvent Resistance	Excellent	Excellent
Oil Resistance	Excellent	Excellent

Note: *These are typical values and should not be used for specification purposes.*

Product Specification

Scotch Varnished Cambric Tapes shall be based on straight-cut woven cotton cambric fabric. It shall be coated to a specified thickness, with high grade yellow electrical insulating varnish producing a visibly smooth surface.

The surface shall be free from peeling, blisters, contamination and other imperfections. Finished product thickness shall be controlled to plus or minus 1 mil. Tapes must unwind freely (except adhesive – backed) with no binding between tape layers.

Yellow, dry-finish varnished cambric tape shall be wax-dipped to preserve electrical properties.

Installation Techniques

Apply Scotch® Varnished Cambric Tape 2510 and 2520 in half-lapped layers with sufficient tension to conform to the connection surface. Apply a minimum of two half-lapped layers for mechanical protection.

Jacket all varnished cambric applications with Scotch rubber and vinyl splicing tapes to provide a contamination and moisture seal.

Shelf Life

Scotch Varnished Cambric Tapes 2510 and 2520 have a 5-year shelf life (from date of manufacture) when stored under the following recommended storage conditions. Store behind present stock in a clean dry place at a temperature of 70°F and 40% to 50% relative humidity. Proper stock rotation is recommended.

Availability

Scotch Varnished Cambric Tapes 2510 and 2520 are available from your local 3M authorized distributor in the following standard roll sizes:

2510	2520
3/4" x 60 feet	3/4" x 60 feet
3/4" x 36 yards	3/4" x 36 yards
1" x 36 yards	1" x 36 yards
1 1/2" x 36 yards	1 1/2" x 36 yards
2" x 36 yards	2" x 36 yards
36" x 25 yards	

3M and Scotch are trademarks of 3M Company.

Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

Warranty; Limited Remedy; Limited Liability. This product will be free from defects in material and manufacture for a period of one (1) year from the date of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, **3M will not be liable for any loss or damage arising from this 3M product, whether direct, indirect, special, incidental or consequential regardless of the legal theory asserted.**

3M

Electrical Markets Division

6801 River Place Blvd.
Austin, TX 78726-9000
www.3M.com/electrical



Printed on 50% recycled paper
with 10% post-consumer

Litho in USA
© 3M 2004 78-8124-4831-0-C

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [3m manufacturer](#):

Other Similar products are found below :

[SC401U](#) [98-0003-3071-6](#) [80-0012-6467-2](#) [00-054007-70220-7](#) [00-054007-34717-0](#) [5952-3/4"x15yds](#) [021200-40230](#) [6840-2X50-GRAY](#)
[6A11-A0121-007.0-0](#) [701-W](#) [7993MP-2CIRCLE-100](#) [FDV14-187C](#) [FE-5100-5126-4](#) [FE-5100-5273-4](#) [FE-5100-5492-0](#) [8124/14](#) [812510-100](#)
[8125/17](#) [813216](#) [8204-3LFM](#) [8425-8](#) [MNG14BCX](#) [FP301-1-6"-Clear](#) [FV14-6C](#) [920102-01-25-R](#) [927739-40](#) [929835-01-28-RK](#)
[929974-01-40-R](#) [951240-2520-AR-PR](#) [960X/980X](#) [98-0003-3075-7](#) [HF365/16SF](#) [HF36564-100](#) [HF625/26-30](#) [1/2-5-4492W](#) [1/2-5-5430](#) [1/2-](#)
[5-850S](#) [1/2-5-3431](#) [12X12-6-4056B](#) [12X12-6-433](#) [12X12-6-4930](#) [1311](#) [13-500-NB](#) [14526-EZ5B-300-02C](#) [1-4-4658F](#) [14520-EZAB-300-](#)
[0EC](#) [DSTK9013-3420](#) [DSTK9015-3402](#) [14T26-SZLB-200-0LC](#) [14T50-SZWB-100-0NC](#)