


Electronic housing - BC 107,6 UT HBUS KMGY - 2202951

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Key Commercial Data

Packing unit	1
GTIN	 4 055626 282114
Custom tariff number	85472000

Technical data

General

Housing material	Polycarbonate
------------------	---------------

Ambient conditions

Ambient temperature (operation)	-40 °C ... 105 °C (depending on power dissipation)
---------------------------------	--

Dimensions

Length	89.7 mm
--------	---------

Technical data

Flammability rating according to UL 94	V0
--	----

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Classifications

eCl@ss

eCl@ss 8.0	27182702
eCl@ss 9.0	27182702

Electronic housing - BC 107,6 UT HBUS KMGY - 2202951

Classifications

ETIM

ETIM 5.0	EC001031
----------	----------

Approvals

Approvals



Approvals

UL Recognized / EAC

Ex Approvals

Approvals submitted

Approval details



Accessories

Accessories

Fiber optics

Component housing - HS LC-V-D3/ R2XC1-5,08 - 2202311



Fiber optics Can be used for the BC housing range (housing must be processed), Color: transparent

Component housing - HS LC-V-D3/ R3XC1-5,08 - 2202312



Fiber optics Can be used for the BC housing range (housing must be processed), Color: transparent

Electronic housing - BC 107,6 UT HBUS KMGY - 2202951

Accessories

Necessary add-on products

Components of electronic housing - BC 107,6 OT U11 KMGY - 2896076



Installation component housing, Upper part, Cross connection: Component housing, Color: light gray, Width: 107.6 mm, Constructional height: 62.2 mm

Upper part of housing - BC 107,6 OT U22 KMGY - 2896089



Installation component housing, Upper part, Color: light gray, Width: 107.6 mm, Constructional height: 62.2 mm

Electronic housing - RPI-BC 107,6 DEV-KIT KMGY P10 - 2202875



DIN rail housing for Raspberry Pi computers (suitable for Raspberry Pi A+, B+, B2, B3); set consisting of upper part and PCB holder; housing according to DIN 43880

Additional products

DIN rail bus connectors - HBUS 107,6-16P-1S BK - 2896306



Plug component, Nominal current: 3 A, Number of positions: 16, Pitch: 2.54 mm, Color: jet black

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [phoenix contact manufacturer](#):

Other Similar products are found below :

[1203259](#) [3240366](#) [1893300](#) [2800744](#) [2867076](#) [3006564](#) [2800741](#) [5146480](#) [1582539](#) [1623633](#) [1507793](#) [3025587](#) [3069708](#) [1582223](#)
[1431461](#) [1586976](#) [0311647](#) [1460160](#) [1771338](#) [3048387](#) [2814605](#) [0309086](#) [1513716](#) [3035684](#) [5451417](#) [0202219](#) [1647747](#) [1730667](#)
[1709267](#) [5449018](#) [0311634](#) [1730696](#) [3034057](#) [0311579](#) [1730683](#) [0719032](#) [5449843](#) [3240098](#) [0311566](#) [0201391](#) [CRIMPFOX 16 S](#)
[CRIMPSET 25](#) [7001438](#) [ETD-BL-1T-F-300S](#) [MCR-1CLP-I-I-00](#) [MCR-4CLP-I-I-00](#) [MCR-DAC 8-I- 4-BUS](#) [FL EPA WMS](#) [FLK 50/EZ-DR/](#)
[400/KONFEK/S](#) [FLS PB M12 DO 8 M12-2A](#)