# Product data sheet Characteristics

## 150SV43A XFMR DRY 1PH .15KVA 120X240V-12/24V

### Main

Commercial Status	Commercialised
Product or component type	Buck and Boost Transformer
Box number	3A
NEMA degree of protection	NEMA 3R
Insulation temperature	221 °F (105 °C)
Primary voltage	120 x 240 V
Rated power in VA	0.15 kVA
Secondary voltage	12/24 V
Temperature rise	55 °C

#### Ordering and shipping details

Category	16265 - BUCK & BOOST	
Discount Schedule	PE2	
GTIN	00785901876090	
Nbr. of units in pkg.	1	
Package weight(Lbs)	7.80	
Product availability	Stock - Normally stocked in distribution facility	
Returnability	Υ	
Country of origin	MX	

#### Contractual warranty

Period	18 months	

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for schneider manufacturer:

Other Similar products are found below:

LU9M1 7D 7S 7XA1 FNQR2 8501RS44V24 8501RSD14P14V51 8501XO20V03Y414 9001KXRK 9001SKR9P35RH25 9001SKT35L31 9003K2C003GA 9007AA1 9007BA1 9007C54D 9007C62A2 9007CA11 9007FA3 9007HA4 9007HA6 9007KA1 9007KB11 9007MS01S0206 9007MS02S0300 9012GAR4 9012GAW2 9012GBW1 9012GDW5E3 9012GFW1 9012GNG1 9012GNG3 9012GNG6 9013FHG39J69 9013GHG2J30 9050JCK2F30V14 GV2ME04 GV2ME10 GV2ME14 GV2ME20 GV2ME32 GV2P08 GV2P10 GV2P16 GV2P20 GV2P21 GV2RT07 GV2RT21 GVAN11 GVAN20 GZ1E02