



### Main

|                           |  |
|---------------------------|--|
| Commercial Status         | Commercialised   |
| Range of product          | Acti 9   |
| Product name              | Disbo iC60   |
| Product or component type | Circuit breaker  |
| Device short name         | IC60H  |
| Poles description         | 3P   |
| Number of protected poles | 3  |
| [In] rated current        | 40 A   |
| Network type              | AC   |
| Trip unit technology      | Thermal-magnetic   |
| Curve code                | C  |
| Breaking capacity         | 10000 A Icn conforming to EN/IEC 60898-1 - 415 V AC 50/60 Hz<br>20 kA Icu conforming to EN/IEC 60947-2 - 100...133 V DC<br>10 kA Icu conforming to EN/IEC 60947-2 - 440 V AC 50/60 Hz<br>15 kA Icu conforming to EN/IEC 60947-2 - 380...415 V AC 50/60 Hz<br>30 kA Icu conforming to EN/IEC 60947-2 - 220...240 V AC 50/60 Hz<br>42 kA Icu conforming to EN/IEC 60947-2 - 12...133 V AC 50/60 Hz |
| Utilisation category      | Category A conforming to EN/IEC 60947-2  |

### Complementary

|  |  |
|--|--|
| Network frequency                      | 50/60 Hz   |
| [Ue] rated operational voltage         | 440 V AC 50/60 Hz  |
| Magnetic tripping limit                | 8 x In +/- 20 %  |
| [Ics] rated service breaking capacity  | 10000 A 100 % x Icu conforming to EN/IEC 60898-1 - 415 V AC 50/60 Hz<br>20 kA 100 % x Icu conforming to EN/IEC 60947-2 - 100...133 V DC<br>5 kA 50 % x Icu conforming to EN/IEC 60947-2 - 440 V AC 50/60 Hz<br>7.5 kA 50 % x Icu conforming to EN/IEC 60947-2 - 380...415 V AC 50/60 Hz<br>15 kA 50 % x Icu conforming to EN/IEC 60947-2 - 220...240 V AC 50/60 Hz<br>21 kA 50 % x Icu conforming to EN/IEC 60947-2 - 12...133 V AC 50/60 Hz |
| Limitation class                       | 3 conforming to EN/IEC 60947-2   |
| [Ui] rated insulation voltage          | 500 V AC 50/60 Hz conforming to EN/IEC 60947-2   |
| [Uimp] rated impulse withstand voltage | 6 kV conforming to EN/IEC 60947-2  |
| Contact position indicator             | Yes  |
| Control type                           | Toggle   |
| Local signalling                       | Trip indicator   |
| Mounting mode                          | Clip-on  |
| Mounting support                       | Rail   |
| 9 mm pitches                           | 6  |
| Height                                 | 85 mm  |
| Width                                  | 54 mm  |
| Depth                                  | 78.5 mm  |
| Product weight                         | 0.375 kg   |
| Colour                                 | White  |
| Mechanical durability                  | 20000 cycles   |
| Electrical durability                  | 10000 cycles   |

|                          |   |
|--------------------------|---|
| Provision for padlocking | Padlockable   |
| Connections - terminals  | Single terminal, top or bottom flexible wire(s) 1...25 mm <sup>2</sup> max<br>Single terminal, top or bottom rigid wire(s) 1...35 mm <sup>2</sup> max |
| Wire stripping length    | 14 mm top or bottom   |
| Tightening torque        | 3.5 N.m top or bottom   |
| Earth-leakage protection | Separate block  |

## Environment

|                                       |                                  |
|---------------------------------------|----------------------------------|
| Standards                             | EN/IEC 60947-2<br>EN/IEC 60898-1 |
| IP degree of protection               | IP20 conforming to IEC 60529     |
| Pollution degree                      | 3 conforming to EN/IEC 60947-2   |
| Tropicalisation                       | 2 conforming to IEC 60068-1      |
| Relative humidity                     | 95 % ( 55 °C )                   |
| Ambient air temperature for operation | -35...70 °C                      |
| Ambient air temperature for storage   | -40...85 °C                      |

## Offer Sustainability

|                          |   |
|--------------------------|---|
| Sustainable offer status | Not Green Premium product   |
| RoHS                     | Compliant - since 1310 - <a href="#">Schneider Electric declaration of conformity</a> |
| REACH                    | Reference not containing SVHC above the threshold                                     |

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Circuit Breakers](#) category:*

*Click to view products by [Schneider](#) manufacturer:*

Other Similar products are found below :

[M39019/04-249S](#) [M39019/04-313S](#) [M55629/1-001](#) [M55629/1-016](#) [M55629/1-018](#) [M55629/1-021](#) [M55629/1-033](#) [M55629/1-036](#) [M55629/1-046](#) [M55629/1-048](#) [M55629/1-058](#) [M55629/1-060](#) [M55629/1-067](#) [M55629/1-070](#) [M55629/1-079](#) [M55629/1-084](#) [M55629/1-085](#) [M55629/1-101](#) [M55629/1-108](#) [M55629/1-109](#) [M55629/11-102](#) [M55629/1-120](#) [M55629/12-045](#) [M55629/12-046](#) [M55629/1-243](#) [M55629/1-330](#) [M55629/1-331](#) [M55629/1-351](#) [M55629/1-366](#) [M55629/1-387](#) [M55629/1-388](#) [M55629/1-401](#) [M55629/1-430](#) [M55629/1-450](#) [M55629/1-453](#) [M55629/2-022](#) [M55629/2-037](#) [M55629/2-082](#) [M55629/2-099](#) [M55629/2-101](#) [M55629/2-102](#) [M55629/2-115](#) [M55629/2-116](#) [M55629/2-183](#) [M55629/21-HM-HM](#) [M55629/21-NS-NS](#) [M55629/21-SK-UK](#) [M55629/22-NR-NR-NR](#) [M55629/22-RS-RS-RS](#) [M55629/22-TM-TM-TM](#)