

FCC-68 Data Cables

Telecommunication Cable




Features:

- 4, 6 and 8-core line cordage with 7 / 0.15 mm (26 AWG) - flat cable
- Western electric and FCC-68 style plugs application
- Plain copper conductors insulated in colour coded PVC and sheathed overall in PVC
- Normal colour coding to plug pin number.
- Nominal overall diameter of conductor : 0.45 mm
- Nominal overall diameter of conductor with insulation : 1 mm (maximum)

Outer Sheath Colours

GC5040 - Grey
GC5041 - Black
GC5042 - White




Dimensions : Millimetres

Lay Up : 4 cores laid side by side (Black, Red, Green and Yellow)

Outer Sheath Colours

GC5043 - Grey
GC5044 - Black
GC5045 - White




Dimensions : Millimetres

Lay Up : 6 cores laid side by side (White, Black, Red, Green, Yellow and Blue)

Maximum Conductor Resistance at 20°C : 166 Ω / Km
Minimum IR at 20°C : 700 MΩ

Outer Sheath Colours

GC5046 - Grey
GC5047 - Black



Dimensions : Millimetres

Lay Up : 8 cores laid side by side (Blue, Orange, Black, Red, Green, Yellow, Brown and Grey)
Maximum Conductor Resistance at 20°C : 166 Ω / Km
Minimum IR at 20°C : 700 MΩ

FCC-68 Data Cables



Telecommunication Cable

Specification Table

Number of Core	Reel Length (m)	Part Number
4	100	GC5040
		GC5041
		GC5042
6		GC5043
GC5044		
GC5045		
8		GC5046
GC5047		

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com
www.farnell.com
www.newark.com
www.cpc.co.uk



X-ON Electronics

Authorized Distributor

Click to view similar products for [Pro Power manufacturer](#).

Other Similar products are found below :

[0301CV100W](#) [04JSBLACK](#) [06JSBLACK](#) [08450046010](#) [08450056010](#) [08450066010](#)
[08450166010](#) [08450236010](#) [08450256010](#) [08JSBLACK](#) [10026B](#) [10026BK](#) [10026G](#)
[10026R](#) [10026TB](#) [10026TBK](#) [10026TG](#) [10026TR](#) [10026TW](#) [10026W](#) [10030B](#)
[10030BK](#) [10030G](#) [10030O](#) [10030R](#)