




POWER

Industry Standard Dimensions



Specifications

Classification: Alkaline

Chemical System: Zinc-Manganese Dioxide (Zn/MnO ₂)

No added mercury or cadmium

Designation: ANSI-15A, IEC-LR6

Nominal Voltage: 1.5 volts

Nominal IR: 150 to 300 milliohms (fresh)
Operating Temp: -18°C to 55°C (0°F to 130°F)


Typical Weight: 22.7 grams (0.8 oz.)

Typical Volume: 8.1 cubic centimeters (0.5 cubic inch)

Jacket:Plastic LabelTerminal:Flat Contact


Milliamp-Hours Capacity

Continuous discharge to 0.8 volts at 21°C



Constant Current Performance

Typical Characteristics (21°C)







ENERGIZER ALKALINE POWER




Industry Standard Tests (21°C)









Pack Quantity : 24

Manufacturers Part Number: E300173100

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for energizer manufacturer:

Other Similar products are found below:

1215F2X3 E11A B2 LR43 186 AC13 AC675 3LR12 603298 625302 625304 638006 639830 S9025 7638900426687 7638900414660
E92 MAX E91 MAX HARD CASE RECHARGEABLE HARD CASE PRO MULTI USE HCHD311 S9029 639826 603386 HARD CASE
PROFF 4AA HARDCASE PRO HEADLIGHT 639618 RCLINM2WR S8865 S8707 S8100 7638900424478 7638900313130 626177
E300116200 639838 HARDCASE PRO WORK LIGHT 603305 E300280600 METAL LED 6AA S8864 HDD32E MS2AALED
ENERGIZER® 2-IN-1 LANTERN HANDHELD E300124200 E300171700 ENFFL81E E300112600 633474 HDA32E 7638900421422
HARD CASE PRO PIVOT