






















# Modular Terminal Blocks with Fixing Flange or Snap-in Mounting Foot 1.5 mm<sup>2</sup> / AWG 16, Series 260










<b>Test plug modules</b> see page 10.28	<b>0.08 – 1.5 mm<sup>2</sup></b> <b>400 V/6 kV/3 ①</b> <b>18 A</b>	<b>AWG 28 – 16</b> <b>300 V, 10 A ②</b> <b>300 V, 15 A ③</b>	<b>2 x 0.08 – 1.5 mm<sup>2</sup></b> <b>400 V/6 kV/3 ①</b> <b>18 A</b>	<b>2 x AWG 28 – 16</b> <b>300 V, 10 A ②</b> <b>300 V, 15 A ③</b>
	<b>Terminal block width 5 mm / 0.197 in</b>  <b>8 – 9 mm / 0.33 in</b>		<b>Terminal block width 8 mm / 0.315 in</b>  <b>8 – 9 mm / 0.33 in</b>	
*        		*        		



① 400 V = rated voltage  
 6 kV = rated surge voltage  
 3 = pollution degree  
 (see also section 15)

Description	Color	Item No.	Pack.-unit pcs	Color	Item No.	Pack.-unit pcs
 <b>Terminal blocks with fixing flange,</b> for screw fixing or similar methods, fixing hole diameter 3.2 mm (with mounting adapter 209-123 also for DIN 35 rail)	<b>2-conductor terminal blocks</b>			<b>4-conductor terminal blocks</b>		
	grey	<b>260-301</b>	300 (6 x 50)	grey	<b>260-331</b>	300 (6 x 50)
	light grey	<b>260-303</b>	300 (6 x 50)	light grey	<b>260-333</b>	300 (6 x 50)
	blue	<b>260-304</b>	300 (6 x 50)	blue	<b>260-334</b>	300 (6 x 50)
	orange	<b>260-306</b>	300 (6 x 50)	orange	<b>260-336</b>	300 (6 x 50)
 <b>Terminal blocks with snap-in mounting foot,</b> for plate thickness 0.6 – 1.2 mm, fixing hole diameter 3.5 mm (fits aluminum rail 210-154 or with mounting adapter 209-120 for DIN 35 rail)	<b>2-conductor terminal blocks</b>			<b>4-conductor terminal blocks</b>		
	grey	<b>260-311</b>	300 (6 x 50)	grey	<b>260-341</b>	300 (6 x 50)
	light grey	<b>260-313</b>	300 (6 x 50)	light grey	<b>260-343</b>	300 (6 x 50)
	blue	<b>260-314</b>	300 (6 x 50)	blue	<b>260-344</b>	300 (6 x 50)
	orange	<b>260-316</b>	300 (6 x 50)	orange	<b>260-346</b>	300 (6 x 50)
 <b>End terminal block ③,</b> without fixing foot, for terminal strips with snap-in mounting feet (see dimensioned drawings on page 10.19)	<b>2-conductor terminal blocks</b>			<b>4-conductor terminal blocks</b>		
	grey	<b>260-321</b>	300 (6 x 50)	grey	<b>260-351</b>	300 (6 x 50)
	light grey	<b>260-323</b>	300 (6 x 50)	light grey	<b>260-353</b>	300 (6 x 50)
	blue	<b>260-324</b>	300 (6 x 50)	blue	<b>260-354</b>	300 (6 x 50)
	orange	<b>260-326</b>	300 (6 x 50)	orange	<b>260-356</b>	300 (6 x 50)
	green-yellow	<b>260-327</b>	300 (6 x 50)	green-yellow	<b>260-357</b>	300 (6 x 50)

## Accessories for modular terminal blocks and terminal strips (Marking accessories see section 14)

	<b>End plate with fixing flange</b>	grey	<b>260-361</b>	100 (2 x 50)	grey	<b>260-361</b>	100 (2 x 50)
	<b>End plate with snap-in mounting foot</b>	grey	<b>260-371</b>	100 (2 x 50)	grey	<b>260-371</b>	100 (2 x 50)
	<b>Comb type jumper bar,</b> insulated, 2-way	I <sub>N</sub> 10 A grey	<b>260-402</b>	25	I <sub>N</sub> 10 A grey	<b>260-402</b>	25
	<b>Operating tool,</b> insulated, for connecting the comb type jumper bar	2-way	<b>209-132</b>	1	2-way	<b>209-132</b>	1
	<b>Aluminum carrier rail,</b> 1000 x 18 x 7 mm 3'3" x 0.709 x 0.276 in		<b>210-154</b>	1		<b>210-154</b>	1
	<b>Plastic end stop,</b> with WSB marking facility, for aluminum rail 210-154	6 mm / 0.236 in wide grey	<b>209-122</b>	25	6 mm / 0.236 in wide grey	<b>209-122</b>	25
	<b>Mounting adapter,</b> for terminal blocks with snap-in mounting foot, for DIN 35 rail	6 mm / 0.236 in wide grey	<b>209-120</b>	25	6 mm / 0.236 in wide grey	<b>209-120</b>	25
	<b>Mounting adapter with screw,</b> for terminal blocks with fixing flange, for DIN 35 rail	6 mm / 0.236 in wide grey	<b>209-123</b>	25	6 mm / 0.236 in wide grey	<b>209-123</b>	25
	Mounting adapter for DIN 35 rail, can be used as <b>end stop</b>	6.5 mm / 0.256 in wide grey	<b>209-137</b>	25	6.5 mm / 0.256 in wide grey	<b>209-137</b>	25

\* For further approvals with corresponding ratings see section 15.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [wago manufacturer](#):*

Other Similar products are found below :

[750-460](#) [231-118/026-000](#) [231-303/026-000](#) [231-620/019-000](#) [257-403](#) [280-438](#) [280-831](#) [284-624](#) [210-111](#) [231-303/037-000](#) [231-446/001-000\\_NR](#) [232-216/026-000](#) [234-510](#) [264-726](#) [280-339](#) [0283-0671](#) [830-800/000-305](#) [750-512](#) [750-455](#) [51251782](#) [286-312](#) [713-1428/107-000](#) [731-138/048-000](#) [750-459](#) [750-517](#) [793-3505](#) [826-172](#) [859-304](#) [280-335](#) [231-535/001-000](#) [2604-1106](#) [2604-1504](#) [2606-1103/020-000](#) [2624-1103](#) [2626-3103/020-000](#) [821-104](#) [713-1107](#) [852-1411](#) [2106-1307](#) [2116-5307](#) [832-1205](#) [832-3604](#) [2009-110](#) [281-512/281-501](#) [286-336](#) [750-421](#) [750-838](#) [753-559](#) [750-1505](#) [787-732](#)