RS-232 ⇔ RS-485 Interface Converter

Multidrop up to 32 devices over 1200 metres






ASeries A450

Applications


■ The A450 interface converter may be used to connect any RS-232 device onto an RS-485 multidrop bus



 Use two A450 converters to connect RS-232 devices over a long distance



Use an A450 converter as an interface to an RS-485
2-wire bus



Monitor mode is a special 'bus snooping' setting that allows an installer or designer to look at what is happening on both pairs of a 4-wire RS-485 bus.

Features

- Multidrop up to 32 drivers and 32 receivers at distances over 1200 metres
- Supports both 4-wire and 2-wire operation
- Transient Protection on RS-485 lines
- Transmits data at up to 115Kbps
- Non-powered RS-485 operation over distances up to 100 metres
- Switchable DCE/DTE selection for RS-232 port
- Switchable termination resistors for RS-485 port
- Screw terminal connector on RS-485 port
- LED indicators for data activity
- Monitor mode allows problem diagnosis on the RS-422/485 bus
- CE and C-Tick Approved
- Very LOW COST Very BIG FEATURES

Specifications - ASeries A450

RS-232 Port: Asynchronous RS-232

DB-25 female connector Switch Selectable DCE/DTE Transfer up to 64Kbps

RS-485 Port: Screw Terminal Block - 5 position

Switchable 120 Ω termination

Protection: Transient Voltage Supression Diodes

RS-485 - Transmit Data Lines - Receive Data Lines

LED Indicators: Receive Data RS-232

Receive Data RS-485

Power Supply: 9V (200mA) DC

Reverse Polarity Protection

Non-powered up to 100 metres (point-to-point

only)

Dimensions: 84m x 58mm x 23mm

Weight: 160 grams

All Specifications subject to change without notice





X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for alfatron manufacturer:

Other Similar products are found below:

<u>A420</u> <u>A440</u>