

SIMATIC S7-200,
PC/PPI CABLE MM MULTIMASTER,
FOR CONNECTING S7-200 TO SERIAL PORT OF PC,
SUPPORTS FREEPORT AND GSM MODEMS

Cables	
belongs to product	SIMATIC S7-200
Interfaces	
Point-to-point	
Transmission rate (PPI), max.	187.5 kbit/s ; 9.6 / 19.3 / 187.5 kbit/s; setting: DIP switch; RS232 not required
Protocols	
PPI	Yes ; 10/11 bit
ASCII	Yes ; Freeport
Interrupts/diagnostics/status information	
Diagnostics indication LED	
Description	Tx (green): RS-232-transmit indication; Rx (Grün): RS-232-receive indication; PPI (Green): RS-485-transmit indication
Galvanic isolation	
Galvanic isolation	1
Software requirement	
Software required	STEP 7 Micro/WIN V3.2 SP4 or higher
Weight	
Weight, approx.	300 g
Status	Mar 11, 2013

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [USB Cables / IEEE 1394 Cables](#) category:

Click to view products by [Siemens](#) manufacturer:

Other Similar products are found below :

[68768-0173](#) [FNY-W6003-01](#) [88764-0800](#) [13805532](#) [148700-1](#) [17-200621](#) [17-250051P](#) [954](#) [AC102012-2](#) [IP-USB1\(C10\)S-RW](#)
[CABLE/RTP/USB/DT](#) [0847290003](#) [10115240-12200LF](#) [RS232-GTD](#) [USBFTVX2SA2N03A](#) [USBFTV2SA2N03A](#) [1689404-1](#) [FTP-](#)
[629Y401](#) [FTP-628Y402](#) [943301-001](#) [FNY-W6022](#) [FNY-W6003-03](#) [1310-1015-05](#) [1310-1018-04](#) [1310-1019-04](#) [0887283402](#) [UA-](#)
[30AMFM-SL7B02](#) [UA-30AMFM-SL7B01](#) [UA-30AFM-LD7B03](#) [UA-30AMFM-SL7B03](#) [USBAPSCC7202A](#) [UES-1001A160](#) [UES-](#)
[1003A160](#) [USBFTVX7SA2N20A](#) [USBFTVX2SA2N20A](#) [USBFTV2PEMSA2N10A](#) [FTP-629Y602](#) [USBCAMCM100](#) [USB A/F*2 to 2.54](#)
[2*5P-SH L=400mm](#) [EP-CBUSB10P2FLT](#) [1310-1033-01](#) [1310-1037-04](#) [ASR-USB](#) [68784-0075](#) [17-241361](#) [17-230471](#) [217B-BC02](#) [USB-29](#)
[19800-010500-200-RS](#) [USB+MINI DIN 6P WITH BKT](#)