

## Heat conductive foam and gel foils

### Gel thermal conducting foil

- highly heat-conductive silocon foil
- smooth, elastic and compressible
- equals uneven surfaces very well (Gap-Filler)



art. no.	material thickness [mm]	$R_{th}$ [ $^{\circ}\text{C in}^2/\text{W}$ ]	UL 94
<b>GEL 05</b>	$0.5 \pm 0.1$	0.57	V-0
<b>GEL 10</b>	$1.0 \pm 0.2$	1.02	V-0
<b>GEL 15</b>	$1.5 \pm 0.2$	1.45	V-0
<b>GEL 20</b>	$2.0 \pm 0.3$	1.71	V-0
<b>GEL 25</b>	$2.5 \pm 0.3$	2.11	V-0
<b>GEL 30</b>	$3.0 \pm 0.3$	2.34	V-0
<b>GEL 35</b>	$3.5 \pm 0.3$	2.59	V-0
<b>GEL 40</b>	$4.0 \pm 0.4$	2.79	V-0
<b>GEL 45</b>	$4.5 \pm 0.4$	3.03	V-0
<b>GEL 50</b>	$5.0 \pm 0.5$	3.30	V-0
<b>GEL G05</b>	$0.5 \pm 0.1$	0.67	V-1
<b>GEL G1</b>	$1.0 \pm 0.2$	1.11	V-1
<b>GEL G15</b>	$1.5 \pm 0.2$	1.66	V-1
<b>GEL G2</b>	$2.0 \pm 0.3$	1.92	V-1
<b>GEL G25</b>	$2.5 \pm 0.3$	2.40	V-1
<b>GEL G3</b>	$3.0 \pm 0.3$	2.68	V-0
<b>GEL G35</b>	$3.5 \pm 0.3$	2.75	V-0
<b>GEL G4</b>	$4.0 \pm 0.4$	2.92	V-0
<b>GEL G45</b>	$4.5 \pm 0.4$	3.19	V-0
<b>GEL G5</b>	$5.0 \pm 0.5$	3.37	V-0

**version:**

**art. no. GEL ...** standard

**art. no. GEL G ...** GF reinforced, adherent layer on one side

**delivery form:**

plates, usable plain 300 X 200 mm, covered with protection film on booth sides, cuttings on customer's requirements

**Technical data**

	<b>GEL</b>	<b>GEL G</b>
<b>thermal conductivity</b>	1.5	1.5
<b>volume resistance</b>	$> 1 \times 10^6 \text{ M}\Omega/\text{m}$	$> 1 \times 10^6 \text{ M}\Omega/\text{m}$
<b>hardness range</b>	< 49 Shore 00	< 49 Shore 00
<b>temperature range</b>	-60 °C ... + 200 °C	-60 °C ... + 200 °C
<b>extensibility</b>	100 %	60 %
<b>dielectric constant</b>	5.8 [50 Hz] / 5.6 [1 KHz] / 5.5 [1 MHz]	5.8 [50 Hz] / 5.6 [1 KHz] / 5.5 [1 MHz]
<b>breakdown voltage</b>	14 kV/mm (AC)	8 kV/mm (AC)
<b>tightness</b>	2.6 g/cm <sup>3</sup>	2.6 g/cm <sup>3</sup>
<b>dielectric loss factor</b>	0.048 [50 Hz] / 0.015 [1 KHz] / 0.003 [1 MHz]	0.048 [50 Hz] / 0.015 [1 KHz] / 0.003 [1 MHz]

**E 7**

Thermal conductive glue  
Thermal conductive paste  
Thermal conduct. foil WLFT 404/405  
SMD-heatsinks

→ E 15  
→ E 13  
→ E 5  
→ B 38 - 40

Heatsinks for PGA  
Profiles for PCB mounting  
Mounting for TO 3 angle  
Profiles for lock-in fixing spring

→ B 10 - 15  
→ A 89 - 110  
→ A 122  
→ A 85 - 88

# X-ON Electronics

Largest Supplier of Electrical and Electronic Components

***Click to view similar products for [fisher](#) manufacturer:***

Other Similar products are found below :

[FR 105 52 220 ME](#) [FR 120 42 200 ME](#) [GEL 28 30](#) [GEL 45 10](#) [GEL 45 50](#) [GEL 60 10](#) [AKG 33 20 80 ME](#) [ICKSR40X30](#) [LA 17 150 230](#) [LA 21 150 230](#) [LA 21 150 24](#) [LA 27 K 100 12](#) [LA 27 K 100 24](#) [LA 27 K 150 12](#) [LA 27 K 50 24](#) [SK4615AL](#) [SK 47 250 SA](#) [SK56920AL](#) [SK57225SA](#) [SK57720AL](#) [SK58420AL](#) [SK58437.5SA](#) [SK 622 1000 AL](#) [SK 622 1000 SA](#) [SK 622 100 AL](#) [SK 623 100 SA](#) [SK 626 1000 SA](#) [SK 626 50 SA](#) [SK 627 1000 AL](#) [SK 627 200 AL](#) [SK 627 200 SA](#) [SK 627 50 SA](#) [SK 632 100 AL](#) [SK 633 25 AL](#) [SK 636 100 AL](#) [SK LED R 65 SA](#) [SK LED R 80 SA](#) [AKG 69 24 100 SA](#) [FR 80 42 160 ME](#) [GE K 80 42 100 SA](#) [GEL 10](#) [GEL 45 30](#) [GEL 60 25](#) [GEL F 15 10](#) [TUF 120 42 220 ME](#) [TUF 55 16 200 SA](#) [LA 27 K 50 12](#) [LA 27 K 75 12](#) [LA 27 K 75 24](#) [WAG 200 SA](#)