

DX-350 Series

Fluid Dispenser/Controller



Advanced, Value-driven, User Friendly and Productivity-focused Dispenser/controller

The DX-350/355 Series dispenses low, medium and high-viscosity fluids accurately and consistently. The DX-350/355 Series is immediately usable anywhere in the world with its accompanying tools, accessories and universal power supply.

The modern-style enclosure has a small footprint and conserves workspace through exterior design that allows multiple units to be stacked and fastened on top of each other. A highly responsive air pressure and vacuum management system, coupled with a digital timing circuit and digital pressure/vacuum read out provides repeatable fluid dispensing.



Key Features

- Universal power supply with snap-on plug for worldwide use
- User programmable manual purge and automatic dispense cycle settings (program and time)
- 10 programmable memories for storing and recalling most frequently used dispensing cycle timing
- “Teach Mode” for determining the dispensing time required when dispensing output is unknown
- Digital timing from 0.008-60.000 seconds
- +/- 0.001% Timing repeat tolerances
- Digital pressure and vacuum read out
- Adjustable vacuum-driven “suck back” to control material “tailing” and waste
- Stable to conserve work space when multiple DX-350/355 units are used together.

Part Number	Description
DX-350 Dispenser/Controller	0-100 psi (0-6.9 bar)
DX-355 Dispenser	0-15 psi (0-1.03 bar)

Designed For User Convenience

- Footprint is 30% smaller than the closest, similar shaped, competitor product
- Weight is 59% lighter than the closest, similar shaped, competitor product
- Tactile-responsive user programming buttons
- Large, clearly marked air pressure and vacuum control knobs
- Digital Pressure and Vacuum display with dual units
- High visibility, 20 x 4 LCD display panel with back lighting
- Accessories included: Universal power adapter, Foot Switch, Syringe Stand, 10-cc Receiver Head, air hose with fittings, hose holder and sample needles

Specifications

- Dimensions: 6”W x 6.5”L x 7.0”H
152mm x 165mm x 178mm
- Weight: 2.6 lb (1.2kg)
- Cycle Rate: 1200 cycle/minute
- Timing Range: 0.008-60.000 seconds
- Timing Tolerances: +/- 0.001%
- Input Voltage: 100-240 VAC
- Input Frequency: 50-60 Hz.
- Cycle Mode: TIMED, INTERRUPT, TEACH, PURGE
- Meets or exceeds: CE, TUV-GS, and NRTL
- Warranty: 1 year

Note: Specifications and technical details subject to change without notice

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Soldering Irons](#) category:

Click to view products by [Metcal](#) manufacturer:

Other Similar products are found below :

[0052918099](#) [918100-TE](#) [PTTC-802](#) [SFV-DRK30AR](#) [SMTC-0167](#) [SMTC-1121](#) [SMTC-1169-PK](#) [SMTC-588](#) [SMTC-8170](#) [AC-CK1](#) [AC-CK2](#) [SSC-625A](#) [SSC-626A](#) [SSC-726A](#) [SSC-774A](#) [FG-BVX](#) [STV-CH24A](#) [PHT-753077](#) [PTK7-B](#) [RTW3MS](#) [SCP-CH25](#) [SMTC-101](#) [SMTC-113](#) [SMTC-160-PK](#) [SMTC-1BL250](#) [SSC-645A](#) [SSC-671A](#) [SSC-713A](#) [SSC-742A](#) [SSC-745A](#) [SSC-746A](#) [SSC-770A](#) [SSC-772A](#) [STTC-120](#) [STTC-513](#) [STTC-545](#) [STTC-547](#) [TATC-609](#) [T0054487399](#) [T0054474199](#) [T0054442699](#) [T0054440899](#) [SMTC-004](#) [T0054441099](#) [T0054440699](#) [T0054440499](#) [PTTC-801B](#) [RPS-1](#) [SMTC-0124](#) [SMTC-006](#)