
Push Pin






All ABL's BGA heatsinks are supplied with thermal tape

	Width	Length	Height	Pad Size	Anodised Finish	Pin Length	°C/W	°C/W
Model	[mm]	[mm]	[mm]	[mm]		[mm]	Natural	Forced 2M/s
BGA-PP-010	40.8	40.8	15.0	20x20	Natural	14.0	11.00	5.50
BGA-PP-015	49	49	10.0	30x30	Natural	14.0	10.50	4.20
BGA-PP-020	49	49	15.0	30x30	Natural	14.0	9.00	4.00
BGA-PP-025	49	49	15.0	30x30	Natural	16.4	9.00	4.00
*BGA-PP-030	49	49	35.0	30x30	Natural	14.0	7.00	3.80
BGA-PP-035	49	49	20.0	30x30	Black	16.4	7.00	3.70
BGA-PP-040	49	49	35.0	30x30	Black	14.0	6.50	3.50

Thermally Conductive Aluminium Foil



Colour	-	White		
Backing Type / Thickness	Mm	Aluminium Foil / 0.10		
Adhesive Type / Thickness	Mm	Arylic 0.075 (on clear liner side)		
Total Thickness	mm	0,27		
Adhesion	Kg/25mm	1,5		
Thermal Conductivity	W/m-K	0,95		
Thermal Resistance	°C-in ² /W	0,2		
Holding Power@23°C	Hour	>72		
Holding Power @ 130°C	Hour	>2		

All ABL's BGA heatsinks are supplied with thermal tape.

With excellent thermal conductivity, cushioning and gap filling properties, the pad is an ideal thermal interface material specifically designed for heat sink attachment to MPU, chip set and other plastic encapsulated components.

It consists of an aluminium foil backing coated, on both sides, with a very high temperature resistance acrylic adhesive. Due to its high heat performance and adhesive properties this tape can also be use to attach components to a vertical heatsink and to metal enclosure surfaces.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for abl heatsinks manufacturer:

Other Similar products are found below:

350AB2000B 173AB2000B 325AB1000B 150AB2000B BGA-PP-025 BGA-STD-050 350AB1500B BGA-STD-020 325AB1500B 205AB1000B BGA-STD-115 205AB1500B LS300 350AB1000B 345AB1000B 520AB0750MB(T03) LS305 205AB0500B PPL0500B BGA-STD-010 515AB0750MB(T03) PPN0750B PPL1000B PPN0500B BGA-STD-015