

Combined machine taps HSS, ground

Thread: metric DIN ISO 13 Flanks: relief-ground Tolerance: ISO 2 / 6 H

Surface: bright Shank: 1/4" hexagon


Right-hand cutting

1.6

The combined machine tap is suitable for sheet metal working with right/left handed rotation cordless drilling machines. For tapping drill hole and through thread in unalloyed or low-alloyed steels up to 600 N/mm² strength, malleable cast iron and non-ferrous metals. The thread is cut in one operation, without any tool changing. The tool incorporates a twist drill before the thread-tapping part. The machine tap consists of heavy-duty high-speed steel.

In one working stroke:

- ✓ Hole drilling
- √ Thread cutting (tapping)
- ✓ Thread deburring
- ✓ Thread cleaning



Packing unit: Individual plastic pack

- 4	'/ / / /	. / ///	. ////	/////		. / / / / / /	. // ///// /	// // // ///	. #/ / / // // /.
	Nominal thread size	Pitch mm	L 1 mm	S 1 mm	L2 mm	D 1 mm	D 2 mm	Article no.	Price each €
4	M 3	0,50	36,0	5,0	6,0	2,5	7,2	270 014	, / // // //
4	M 4	0,70	39,0	6,0	8,0	3,3	7,2	270 015	/ / //////
	M 5	0,80	41,0	7,0	9,0	4,2	7,2	270 016	
/	M 6	1,00	44,0	/ 8,0	11,0	5,0	//7,2	270 017	
	M 8	1,25	51,0	11,0	14,0	6,8	8,8	270 018	
1	M 10	1,50	59,0	15,0	15,0	8,5//	11,0	270 019	////////
	Hexago	n magnetio	270 013						

Combined machine taps HSS-TiN, ground

Thread: metric DIN ISO 13
Flanks: relief-ground
Tolerance: ISO 2 / 6 H

Surface: titanium-nitride coated

Shank: 1/4" hexagon

Right-hand cutting


The combined machine tap is suitable for sheet metal working with right/left handed rotation cordless drilling machines. For tapping drill hole and through thread in unalloyed or low-alloyed steels up to 1000 N/mm² strength, malleable cast iron and non-ferrous metals. The thread is cut in one operation, without any tool changing. The tool incorporates a twist drill before the thread-tapping part. The machine tap consists of heavy-duty high-speed steel.

In one working stroke:

- ✓ Hole drilling
- √ Thread cutting (tapping)
- ✓ Thread deburring
- √ Thread cleaning

Packing unit: Individual plastic pack

Nominal thread size	Pitch mm	L 1 mm	S 1 mm	L 2 mm	D 1 mm	D 2 mm	Article no.	Price each €
M 3	0,50	36,0	5,0	6,0	2,5	7,2	270 014 T	VI 3-1-111
M 4/	0,70	39,0	6,0	8,0	3,3	7,2	270 015 T	/ /// /
M 5	0,80	41,0	7,0	9,0	4,2	7,2	270 016 T	
M 6	1,00	44,0	8,0	11,0	5,0	/ 7,2/	270 017 T	
M 8	1,25	51,0	11,0	14,0	6,8	8,8	270 018 T	
M 10	1,50	59,0	15,0	15,0	8,5	11,0	270 019 T	
Hexago	n magnetio	270 013						



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Fixed Terminal Blocks category:

Click to view products by Ruko manufacturer:

Other Similar products are found below:

00175550202 MBE-1512 MBE-1520 MBE-154 MBE-156 MBES-1510 MBES-153 MBES-156 MH-2512 MHE-132 MHE-133 MHE-163 MI-254 (35) MI-272 8739 880507 880508 MPT-275 1546551-6 ELM023100 ELM10110G ELVD12100 BA311TU BA411SU MV-152 MV-253/NCNOC MV-254-D MV-255 MV-462 MV-472 MV-493 MVE-252 MVE-253 MVE-258 MVE-273 MVEB-153 1700096 1702246 1705142 1712417 1713020 1713088 1776118-2 1790852 1-796689-8 1-796692-6 1800001 1800114 1823215 1838462