



Specifications:

- Contact rating:** 3A, 250V AC / 6A, 125V AC
 4A, 30V DC / 5A, 12V DC
 6A, 6V DC
- Contact resistance:** 10mOhm max.
- Insulation resistance:** 1 000MOhm min. at 500V DC
- Dielectric strength:** 1 500V, 50Hz for duration of 1 minute
- Operating temperature:** -45°C to +140°C
- Mechanical life:** min. 300 000 cycles
- Contacts:** coin silver (common contact copper alloy, silver plated)
 also available gold plated
- Terminals:** solder tags, copper alloy, silver plated
- Mounting:** bushing M6x0.75, with locking plate, key 9mm, tightening torque 49Ncm max.
- Soldering conditions:** hand-soldering: max.: 60W, 3sec., 420°C
 auto-soldering: max.: 5sec., 270°C
- Material:** Case: diallyl phthalate, meets UL94V-0, black
 Lever: chromium plated, metal parts: nickel plated

"x"	Switch function
D	on - on



Tolerances:	Date	Name
		07/08
Modifications	Date	Name

MTL 306 x

knitter-switch

30 15 28

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Toggle Switches](#) category:

Click to view products by [Knitter-Switch](#) manufacturer:

Other Similar products are found below :

[A19HV](#) [8A1-C-222](#) [60012L](#) [6006L](#) [6663](#) [7101MD9V30GE](#) [7101SPDV30BE](#) [7103SDV30BE](#) [7105D](#) [7108P3YAV2BE](#) [71YY50282](#)
[7201MD9AVBE](#) [7301K38](#) [7306K36](#) [7310K36](#) [7314K36](#) [7506K4](#) [7592K6](#) [7691K14](#) [7700K1](#) [8396K108](#) [8824K14](#) [8828K13](#) [G2VX](#) [G3VX](#)
[PS83-121G](#) [A101MD9AB04](#) [A101SD9AB04](#) [A101SDCQ04](#) [A103SD9AQ04](#) [A107TZB04](#) [A123P32YZQ](#) [A123S1YZG](#) [A127S1YCQ](#) [1-](#)
[1825192-0](#) [A131S1YZQ](#) [A201SCWZB04](#) [A207SYCB04](#) [A208J61ZQ0004](#) [A221K12KAG](#) [A221S1YZQ](#) [A221T1TCQ](#) [A232K12KZQ](#)
[A232M1YCQ](#) [A323S1CWZQ](#) [A423S1CWZG-M8](#) [A423S1YZQ](#) [12149A-3V](#) [12156AX408](#) [12147AGKX679](#)