

Criteria: Search = 42L2101

| Part Number       | Suffix | Brand   | Stock Model | $\mu$ F Single | $\mu$ F Dual | Voltage Rating | Case Diameter | Case Style | Case Height | Product Type             | Required Operating Life | Operating Temperature |
|-------------------|--------|---------|-------------|----------------|--------------|----------------|---------------|------------|-------------|--------------------------|-------------------------|-----------------------|
| 23M242F200CD1H1   |        | Genteq  | Special     | 2400           |              | 200            | 1.75          | Round      | 3.125       | Electrolytic             | 2000                    | -40°C to 85°C         |
| 27L533BX          | BX     | Genteq  | Standard    | 30             | 10           | 370            | 1.75          | Oval       | 3.88        | Oil-Filled (UL Approved) | 60000                   | -40°C to 70°C         |
| 42L3333           |        | Genteq  | Stock       | 0.033          |              | 2000           | 0.49          | Round      | 1.22        | Dry-Axial Leaded         | 100000                  | -40°C to 85°C         |
| 97F9069           |        | Genteq  | Special     | 25             |              | 370            | 1.75          | Oval       | 3.88        | Oil-Filled (UL Approved) | 60000                   | -40°C to 70°C         |
| 27L667            |        | Genteq  | Standard    | 42             | 22           | 400            | 2             | Oval       | 3.88        | Oil-Filled (UL Approved) | 60000                   | -40°C to 90°C         |
| 23J811F400DF1H1   |        | Genteq  | Special     | 810            |              | 400            | 2             | Round      | 4.125       | Electrolytic             | 2000                    | -40°C to 105°C        |
| 97F8249           |        | Genteq  | Standard    | 10             |              | 600            | 1.5           | Oval       | 3.88        | Oil-Filled (UL Approved) | 60000                   | -40°C to 70°C         |
| PB200Y050C370CA   |        | PROLINE | Standard    | 20             | 5            | 370            | 1.75          | Oval       | 2.88        | Oil-Filled (UL Approved) | 10000                   | -40°C to 70°C         |
| 97F9086           |        | Genteq  | Special     | 30             |              | 440            | 1.75          | Oval       | 4.75        | Oil-Filled (UL Approved) | 60000                   | -40°C to 70°C         |
| 97F5205           |        | Genteq  | Special     | 35             |              | 440            | 2.5           | Round      | 3.12        | Oil-Filled (UL Approved) | 60000                   | -40°C to 70°C         |
| 97F5050           |        | Genteq  | Standard    | 15             |              | 370            | 1.75          | Round      | 2.88        | Oil-Filled (UL Approved) | 60000                   | -40°C to 70°C         |
| 97F7903           |        | Genteq  | Standard    | 2              |              | 440            | 1.25          | Oval       | 2.12        | Oil-Filled (UL Approved) | 60000                   | -40°C to 70°C         |
| 23F513F050DI1H1   |        | Genteq  | Special     | 51000          |              | 50             | 2             | Round      | 5.625       | Electrolytic             | 1000                    | -55°C to 105°C        |
| 23F163F080DF1H1   |        | Genteq  | Special     | 16000          |              | 80             | 2             | Round      | 4.125       | Electrolytic             | 1000                    | -55°C to 105°C        |
| 97F9898           |        | Genteq  | Standard    | 60             | 7.5          | 440            | 2.5           | Round      | 4.75        | Oil-Filled (UL Approved) | 60000                   | -40°C to 70°C         |
| 97F9623BX         | BX     | Genteq  | Standard    | 50             |              | 370            | 2             | Round      | 3.88        | Oil-Filled (UL Approved) | 60000                   | -40°C to 70°C         |
| 27L55BX           | BX     | Genteq  | Standard    | 35             | 20           | 280            | 2             | Oval       | 3.88        | Oil-Filled (UL Approved) | 60000                   | -40°C to 90°C         |
| 97F6809           |        | Genteq  | Special     | 14             |              | 280            | 1.5           | Oval       | 2.62        | Oil-Filled (UL Approved) | 60000                   | -40°C to 90°C         |
| 23C362F150B1H1    |        | Genteq  | Special     | 3600           |              | 150            | 1.375         | Round      | 5.625       | Electrolytic             | 1000                    | -45°C to 95°C         |
| 23F123F150F1H1    |        | Genteq  | Special     | 12000          |              | 150            | 3             | Round      | 5.625       | Electrolytic             | 1000                    | -55°C to 105°C        |
| 23D303F007BD1H1   |        | Genteq  | Special     | 30000          |              | 7.5            | 1.375         | Round      | 3.125       | Electrolytic             | 1000                    | -55°C to 85°C         |
| 25L6252           |        | Genteq  | Standard    | 7              | 3            | 400            | 1.75          | Oval       | 2.12        | Oil-Filled (UL Approved) | 60000                   | -40°C to 90°C         |
| 97F9751           |        | Genteq  | Special     | 20             | 4            | 370            | 1.75          | Oval       | 2.88        | Oil-Filled (UL Approved) | 60000                   | -40°C to 70°C         |
| PB650E000T440EA   |        | PROLINE | Standard    | 65             |              | 440            | 2.5           | Round      | 4.75        | Oil-Filled (UL Approved) | 10000                   | -40°C to 70°C         |
| 23A312F150CD1H1   |        | Genteq  | Special     | 3100           |              | 150            | 1.75          | Round      | 3.125       | Electrolytic             | 1000                    | -40°C to 85°C         |
| 97F6674BR         | BR     | Genteq  | Special     | 12             |              | 480            | 1.5           | Oval       | 3.88        | Oil-Filled (UL Approved) | 60000                   | -40°C to 90°C         |
| 97F9119BX         | BX     | Genteq  | Special     | 30             |              | 440            | 2             | Oval       | 2.88        | Oil-Filled (UL Approved) | 60000                   | -40°C to 70°C         |
| 23M482F250EE1H1   |        | Genteq  | Special     | 4800           |              | 250            | 2.5           | Round      | 3.625       | Electrolytic             | 2000                    | -40°C to 85°C         |
| PB500Y050C370EABX | BX     | PROLINE | Standard    | 50             | 5            | 370            | 1.75          | Oval       | 4.75        | Oil-Filled (UL Approved) | 10000                   | -40°C to 70°C         |
| 23A573F050ED1H1   |        | Genteq  | Special     | 57000          |              | 50             | 2.5           | Round      | 3.125       | Electrolytic             | 1000                    | -40°C to 85°C         |
| 23M801F350CC1H1   |        | Genteq  | Special     | 800            |              | 350            | 1.75          | Round      | 2.625       | Electrolytic             | 2000                    | -40°C to 85°C         |
| 23D253F035CG1H1   |        | Genteq  | Special     | 25000          |              | 35             | 1.75          | Round      | 4.625       | Electrolytic             | 1000                    | -55°C to 85°C         |
| PB350E000P240DABX | BX     | PROLINE | Standard    | 35             |              | 240            | 1.75          | Round      | 3.88        | Oil-Filled (UL Approved) | 10000                   | -40°C to 70°C         |
| 97F5816BX         | BX     | Genteq  | Special     | 25             | 7.5          | 370            | 2             | Round      | 4.25        | Oil-Filled (UL Approved) | 60000                   | -40°C to 70°C         |
| 97F6960BX         | BX     | Genteq  | Standard    | 8              | 2            | 400            | 1.75          | Oval       | 2.12        | Oil-Filled (UL Approved) | 60000                   | -40°C to 90°C         |
| 97F9989BX         | BX     | Genteq  | Standard    | 55             | 10           | 440            | 2.5           | Round      | 4.75        | Oil-Filled (UL Approved) | 60000                   | -40°C to 70°C         |
| 23J242F250ED1H1   |        | Genteq  | Special     | 2400           |              | 250            | 2.5           | Round      | 3.125       | Electrolytic             | 2000                    | -40°C to 105°C        |
| 23B292F200DG1H1   |        | Genteq  | Special     | 2900           |              | 200            | 2             | Round      | 4.625       | Electrolytic             | 3000                    | -40°C to 85°C         |
| 97F9779           |        | Genteq  | Standard    | 40             | 7.5          | 440            | 2             | Oval       | 4.75        | Oil-Filled (UL Approved) | 60000                   | -40°C to 70°C         |
| 27L573BX          | BX     | Genteq  | Standard    | 40             | 15           | 280            | 1.75          | Oval       | 3.88        | Oil-Filled (UL Approved) | 60000                   | -40°C to 90°C         |
| 23A163F080BH1H1   |        | Genteq  | Special     | 16000          |              | 80             | 1.375         | Round      | 5.125       | Electrolytic             | 1000                    | -40°C to 85°C         |
| 40L6221           |        | Genteq  | Stock       | 2.2            |              | 600            | 0.64          | Oval       | 2.25        | Dry-Axial Leaded         | 100000                  | -55°C to 105°C        |
| 97F9048BX         | BX     | Genteq  | Special     | 20             | 10           | 440            | 1.75          | Oval       | 3.88        | Oil-Filled (UL Approved) | 60000                   | -40°C to 70°C         |
| 97F6660BX         | BX     | Genteq  | Standard    | 12             |              | 400            | 1.75          | Oval       | 2.88        | Oil-Filled (UL Approved) | 60000                   | -40°C to 90°C         |
| 23H571F400BG1H1   |        | Genteq  | Special     | 570            |              | 400            | 1.375         | Round      | 4.625       | Electrolytic             | 2000                    | -40°C to 85°C         |

|                   |    |         |          |        |     |     |       |       |       |                          |        |                |
|-------------------|----|---------|----------|--------|-----|-----|-------|-------|-------|--------------------------|--------|----------------|
| 23F282F200DH1H1   |    | Genteq  | Special  | 2800   |     | 200 | 2     | Round | 5.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F9737BX         | BX | Genteq  | Standard | 35     | 7.5 | 440 | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23B103F075BF1H1   |    | Genteq  | Special  | 10000  |     | 75  | 1.375 | Round | 4.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F9983BX         | BX | Genteq  | Standard | 30     | 10  | 440 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23F402F100BG1H1   |    | Genteq  | Special  | 4000   |     | 100 | 1.375 | Round | 4.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 23B691F200CB1H1   |    | Genteq  | Special  | 690    |     | 200 | 1.75  | Round | 2.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23A123F060BD1H1   |    | Genteq  | Special  | 12000  |     | 60  | 1.375 | Round | 3.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 97F6543BX         | BX | Genteq  | Special  | 28     |     | 280 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23B333F050CH1H1   |    | Genteq  | Special  | 33000  |     | 50  | 1.75  | Round | 5.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23A134F060FH1H1   |    | Genteq  | Special  | 130000 |     | 60  | 3     | Round | 5.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 97F9645           |    | Genteq  | Standard | 45     |     | 440 | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6759BR         | BR | Genteq  | Standard | 24     |     | 330 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23F702F100DE1H1   |    | Genteq  | Special  | 7000   |     | 100 | 2     | Round | 3.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F9613BX         | BX | Genteq  | Standard | 35     |     | 370 | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB200Z050S370CA   |    | PROLINE | Standard | 20     | 5   | 370 | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23A193F100C11H1   |    | Genteq  | Special  | 19000  |     | 100 | 1.75  | Round | 5.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 23F182F100BC1H1   |    | Genteq  | Special  | 1800   |     | 100 | 1.375 | Round | 2.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 27L6013BX         | BX | Genteq  | Special  | 5      |     | 660 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L5180           |    | Genteq  | Standard | 35     | 10  | 440 | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9752BX         | BX | Genteq  | Standard | 25     | 4   | 370 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9968           |    | Genteq  | Standard | 30     | 7.5 | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L7002           |    | Genteq  | Special  | 14     |     | 330 | 1.75  | Oval  | 3.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 100°C |
| 23B273F075DG1H1   |    | Genteq  | Special  | 27000  |     | 75  | 2     | Round | 4.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23B382F100CC1H1   |    | Genteq  | Special  | 3800   |     | 100 | 1.75  | Round | 2.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F5463           |    | Genteq  | Standard | 20     |     | 370 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L400            |    | Genteq  | Standard | 26     | 9   | 300 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F8038           |    | Genteq  | Standard | 30     |     | 240 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23M292F200BI1H1   |    | Genteq  | Special  | 2900   |     | 200 | 1.375 | Round | 5.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 41L7221           |    | Genteq  | Stock    | 2.2    |     | 700 | 0.96  | Round | 1.65  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 23C873F075FI1H1   |    | Genteq  | Special  | 87000  |     | 75  | 3     | Round | 5.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| PB150Y050C440CABX | BX | PROLINE | Standard | 15     | 5   | 440 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23C473F050DF1H1   |    | Genteq  | Special  | 47000  |     | 50  | 2     | Round | 4.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23H371F400CB1H1   |    | Genteq  | Special  | 370    |     | 400 | 1.75  | Round | 2.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23H470F450BH1H1   |    | Genteq  | Special  | 470    |     | 450 | 1.375 | Round | 5.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23J402F300EI1H1   |    | Genteq  | Special  | 4000   |     | 300 | 2.5   | Round | 5.625 | Electrolytic             | 2000   | -40°C to 105°C |
| 27L522BX          | BX | Genteq  | Standard | 80     | 7.5 | 370 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L1027S          | S  | Genteq  | Stock    | 10     |     | 440 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB600Z075T440EABX | BX | PROLINE | Standard | 60     | 7.5 | 440 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| PB075E000P370CABX | BX | PROLINE | Standard | 7.5    |     | 370 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23B312F250EF1H1   |    | Genteq  | Special  | 3100   |     | 250 | 2.5   | Round | 4.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F6764BX         | BX | Genteq  | Standard | 5      |     | 330 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F9248BX         | BX | Genteq  | Special  | 3.75   |     | 370 | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23C902F150EF1H1   |    | Genteq  | Special  | 9000   |     | 150 | 2.5   | Round | 4.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F9266BX         | BX | Genteq  | Standard | 35     |     | 410 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23F602F250FJ1H1   |    | Genteq  | Special  | 6000   |     | 250 | 3     | Round | 5.875 | Electrolytic             | 1000   | -55°C to 105°C |
| PB350E000C440DA   |    | PROLINE | Standard | 35     |     | 440 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F8252           |    | Genteq  | Standard | 18     |     | 600 | 1.5   | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23H781F300DB1H1   |    | Genteq  | Special  | 780    |     | 300 | 2     | Round | 2.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23A523F050CH1H1   |    | Genteq  | Special  | 52000  |     | 50  | 1.75  | Round | 5.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 97F6950RR         | RR | Genteq  | Standard | 12     | 12  | 400 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 25L6252BX         | BX | Genteq  | Standard | 7      | 3   | 400 | 1.75  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |

|                    |    |         |          |       |     |     |       |       |       |                          |        |                |
|--------------------|----|---------|----------|-------|-----|-----|-------|-------|-------|--------------------------|--------|----------------|
| 23H342F400FH1H1    |    | Genteq  | Special  | 3400  |     | 400 | 3     | Round | 5.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| PB250Y075C440DA    |    | PROLINE | Standard | 25    | 7.5 | 440 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23F133F075CE1H1    |    | Genteq  | Special  | 13000 |     | 75  | 1.75  | Round | 3.625 | Electrolytic             | 1000   | -55°C to 105°C |
| PB150Y075C370CAB X | BX | PROLINE | Standard | 15    | 7.5 | 370 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F5706S           | S  | Genteq  | Stock    | 6     |     | 370 | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB400Z100S370DA    |    | PROLINE | Standard | 40    | 10  | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| PB500E000C440EAB X | BX | PROLINE | Standard | 50    |     | 440 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 27L390BX           | BX | Genteq  | Standard | 40    | 10  | 440 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9054            |    | Genteq  | Special  | 30    | 10  | 440 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9048            |    | Genteq  | Special  | 20    | 10  | 440 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23D103F035BE1H1    |    | Genteq  | Special  | 10000 |     | 35  | 1.375 | Round | 3.625 | Electrolytic             | 1000   | -55°C to 85°C  |
| 23A143F080BG1H1    |    | Genteq  | Special  | 14000 |     | 80  | 1.375 | Round | 4.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 23C142F200BF1H1    |    | Genteq  | Special  | 1400  |     | 200 | 1.375 | Round | 4.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23M382F300EE1H1    |    | Genteq  | Special  | 3800  |     | 300 | 2.5   | Round | 3.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 27L651BX           | BX | Genteq  | Standard | 80    | 5   | 370 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9628BX          | BX | Genteq  | Standard | 17.5  |     | 440 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23C122F200BE1H1    |    | Genteq  | Special  | 12100 |     | 200 | 1.375 | Round | 3.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F8042S           | S  | Genteq  | Stock    | 50    |     | 240 | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23F112F200CD1H1    |    | Genteq  | Special  | 1100  |     | 200 | 1.75  | Round | 3.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 23H701F300BD1H1    |    | Genteq  | Special  | 700   |     | 300 | 1.375 | Round | 3.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23B163F075DD1H1    |    | Genteq  | Special  | 16000 |     | 75  | 2     | Round | 3.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23B463F050EE1H1    |    | Genteq  | Special  | 46000 |     | 50  | 2.5   | Round | 3.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23F203F100E1H1     |    | Genteq  | Special  | 20000 |     | 100 | 2.5   | Round | 5.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 23C583F100FJ1H1    |    | Genteq  | Special  | 58000 |     | 100 | 3     | Round | 5.875 | Electrolytic             | 1000   | -45°C to 95°C  |
| PB150E000A370CAB X | BX | PROLINE | Standard | 15    |     | 370 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23M501F400DB1H1    |    | Genteq  | Special  | 500   |     | 400 | 2     | Round | 2.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23F342F200EF1H1    |    | Genteq  | Special  | 3400  |     | 200 | 2.5   | Round | 4.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 23B882F150EG1H1    |    | Genteq  | Special  | 8800  |     | 150 | 2.5   | Round | 4.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F8252BX          | BX | Genteq  | Standard | 18    |     | 600 | 1.5   | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F5001S           | S  | Genteq  | Stock    | 12.5  |     | 440 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23H442F350FH1H1    |    | Genteq  | Special  | 4400  |     | 350 | 3     | Round | 5.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23B711F150BB1H1    |    | Genteq  | Special  | 710   |     | 150 | 1.375 | Round | 2.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23A213F075DD1H1    |    | Genteq  | Special  | 21000 |     | 75  | 2     | Round | 3.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 23B392F150DE1H1    |    | Genteq  | Special  | 3900  |     | 150 | 2     | Round | 3.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| PB350Z050S440EAS   | S  | PROLINE | Stock    | 35    | 5   | 440 | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23C352F250EE1H1    |    | Genteq  | Special  | 3500  |     | 250 | 2.5   | Round | 3.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23M162F200DB1H1    |    | Genteq  | Special  | 1600  |     | 200 | 2     | Round | 2.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 41L7201            |    | Genteq  | Stock    | 2     |     | 700 | 0.93  | Round | 1.65  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 97F5504BX          | BX | Genteq  | Special  | 4     |     | 370 | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23C123F050BD1H1    |    | Genteq  | Special  | 12000 |     | 50  | 1.375 | Round | 3.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23H551F450DD1H1    |    | Genteq  | Special  | 550   |     | 450 | 2     | Round | 3.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F9027BX          | BX | Genteq  | Special  | 45    | 5   | 370 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6836S           | S  | Genteq  | Stock    | 48    |     | 280 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F5503            |    | Genteq  | Standard | 3     |     | 370 | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB250Y075C440DAB X | BX | PROLINE | Standard | 25    | 7.5 | 440 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F6886RR          | RR | Genteq  | Standard | 27    | 8   | 280 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 27L539BX           | BX | Genteq  | Standard | 15    | 11  | 330 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23H162F200CC1H1    |    | Genteq  | Special  | 1600  |     | 200 | 1.75  | Round | 2.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23H152F250CD1H1    |    | Genteq  | Special  | 1500  |     | 250 | 1.75  | Round | 3.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23B522F150ED1H1    |    | Genteq  | Special  | 5200  |     | 150 | 2.5   | Round | 3.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23F163F100EG1H1    |    | Genteq  | Special  | 16000 |     | 100 | 2.5   | Round | 4.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 23H482F200EE1H1    |    | Genteq  | Special  | 4800  |     | 200 | 2.5   | Round | 3.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23J112F250BG1H1    |    | Genteq  | Special  | 1100  |     | 250 | 1.375 | Round | 4.625 | Electrolytic             | 2000   | -40°C to 105°C |
| 23J142F300CF1H1    |    | Genteq  | Special  | 1400  |     | 300 | 1.75  | Round | 4.125 | Electrolytic             | 2000   | -40°C to 105°C |
| 23F403F050DG1H1    |    | Genteq  | Special  | 40000 |     | 50  | 2     | Round | 4.625 | Electrolytic             | 1000   | -55°C to 105°C |

|                   |    |         |          |       |     |     |       |       |       |                          |       |                |
|-------------------|----|---------|----------|-------|-----|-----|-------|-------|-------|--------------------------|-------|----------------|
| PB350E000A370EABX | BX | PROLINE | Standard | 35    |     | 370 | 1.25  | Oval  | 4.75  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| PB125E000A440DA   |    | PROLINE | Standard | 12.5  |     | 440 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23M212F400D1H1    |    | Genteq  | Special  | 2100  |     | 400 | 2     | Round | 5.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 97F5474           |    | Genteq  | Special  | 17.5  | 5   | 370 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F9643BX         | BX | Genteq  | Standard | 40    |     | 440 | 2.5   | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F8294BX         | BX | Genteq  | Standard | 60    |     | 330 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23M212F300CF1H1   |    | Genteq  | Special  | 2100  |     | 300 | 1.75  | Round | 4.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23B721F200BD1H1   |    | Genteq  | Special  | 720   |     | 200 | 1.375 | Round | 3.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| 97F8066S          | S  | Genteq  | Stock    | 35    |     | 370 | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F8061S          | S  | Genteq  | Stock    | 15    |     | 370 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F9265           |    | Genteq  | Standard | 25    |     | 410 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| PB300Z075S440DABX | BX | PROLINE | Standard | 30    | 7.5 | 440 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23J152F350EE1H1   |    | Genteq  | Special  | 1500  |     | 350 | 2.5   | Round | 3.625 | Electrolytic             | 2000  | -40°C to 105°C |
| 97F6761BR         | BR | Genteq  | Standard | 17.5  |     | 330 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F9805           |    | Genteq  | Standard | 45    |     | 440 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23D622F055BE1H1   |    | Genteq  | Special  | 6200  |     | 55  | 1.375 | Round | 3.625 | Electrolytic             | 1000  | -55°C to 85°C  |
| 23B162F200BI1H1   |    | Genteq  | Special  | 1600  |     | 200 | 1.375 | Round | 5.625 | Electrolytic             | 3000  | -40°C to 85°C  |
| 23A673F050DH1H1   |    | Genteq  | Special  | 67000 |     | 50  | 2     | Round | 5.125 | Electrolytic             | 1000  | -40°C to 85°C  |
| 23F402F250EI1H1   |    | Genteq  | Special  | 4000  |     | 250 | 2.5   | Round | 5.625 | Electrolytic             | 1000  | -55°C to 105°C |
| PB150Y075C440CA   |    | PROLINE | Standard | 15    | 7.5 | 440 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| PB125E000P440CAS  | S  | PROLINE | Stock    | 12.5  |     | 440 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| PB100Y100C370BABX | BX | PROLINE | Standard | 10    | 10  | 370 | 1.75  | Oval  | 2.12  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23J262F350FF1H1   |    | Genteq  | Special  | 2600  |     | 350 | 3     | Round | 4.125 | Electrolytic             | 2000  | -40°C to 105°C |
| PB550Z075T370DA   |    | PROLINE | Standard | 55    | 7.5 | 370 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23M501F450BG1H1   |    | Genteq  | Special  | 500   |     | 450 | 1.375 | Round | 4.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23C293F075DG1H1   |    | Genteq  | Special  | 29000 |     | 75  | 2     | Round | 4.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| 23B583F060EG1H1   |    | Genteq  | Special  | 58000 |     | 60  | 2.5   | Round | 4.625 | Electrolytic             | 3000  | -40°C to 85°C  |
| 23F192F200CG1H1   |    | Genteq  | Special  | 1900  |     | 200 | 1.75  | Round | 4.625 | Electrolytic             | 1000  | -55°C to 105°C |
| 23M541F450CD1H1   |    | Genteq  | Special  | 540   |     | 450 | 1.75  | Round | 3.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23J232F300EE1H1   |    | Genteq  | Special  | 2300  |     | 300 | 2.5   | Round | 3.625 | Electrolytic             | 2000  | -40°C to 105°C |
| PB250Z100S440DABX | BX | PROLINE | Standard | 25    | 10  | 440 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23A144F075FL1H1   |    | Genteq  | Special  | 14000 | 0   | 75  | 3     | Round | 8.625 | Electrolytic             | 1000  | -40°C to 85°C  |
| 97F5491BX         | BX | Genteq  | Special  | 30    | 4   | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23B503F075EH1H1   |    | Genteq  | Special  | 50000 |     | 75  | 2.5   | Round | 5.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| 97F9602BX         | BX | Genteq  | Standard | 20    |     | 370 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 27L573            |    | Genteq  | Standard | 40    | 15  | 280 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23C343F100EH1H1   |    | Genteq  | Special  | 34000 |     | 100 | 2.5   | Round | 5.125 | Electrolytic             | 1000  | -45°C to 95°C  |
| 97F6788           |    | Genteq  | Standard | 2.5   |     | 330 | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23A143F050CB1H1   |    | Genteq  | Special  | 14000 |     | 50  | 1.75  | Round | 2.125 | Electrolytic             | 1000  | -40°C to 85°C  |
| 23M322F350FD1H1   |    | Genteq  | Special  | 3200  |     | 350 | 3     | Round | 3.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 97F9613S          | S  | Genteq  | Stock    | 35    |     | 370 | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23F342F250FE1H1   |    | Genteq  | Special  | 3400  |     | 250 | 3     | Round | 3.625 | Electrolytic             | 1000  | -55°C to 105°C |
| 23A323F075CH1H1   |    | Genteq  | Special  | 32000 |     | 75  | 1.75  | Round | 5.125 | Electrolytic             | 1000  | -40°C to 85°C  |
| 23C482F200D1H1    |    | Genteq  | Special  | 4800  |     | 200 | 2     | Round | 5.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| PB040E000P370CABX | BX | PROLINE | Standard | 4     |     | 370 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23A153F060BE1H1   |    | Genteq  | Special  | 15000 |     | 60  | 1.375 | Round | 3.625 | Electrolytic             | 1000  | -40°C to 85°C  |
| 97F8051           |    | Genteq  | Standard | 95    |     | 240 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23H102F400DF1H1   |    | Genteq  | Special  | 1000  |     | 400 | 2     | Round | 4.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 97F6872           |    | Genteq  | Standard | 48    |     | 280 | 2     | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F6510           |    | Genteq  | Special  | 50    |     | 260 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23B352F075BB1H1   |    | Genteq  | Special  | 3500  |     | 75  | 1.375 | Round | 2.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| 23B112F250BH1H1   |    | Genteq  | Special  | 1100  |     | 250 | 1.375 | Round | 5.125 | Electrolytic             | 3000  | -40°C to 85°C  |

|                   |         |          |          |        |     |      |       |       |                          |                          |               |                |
|-------------------|---------|----------|----------|--------|-----|------|-------|-------|--------------------------|--------------------------|---------------|----------------|
| 23F232F100FG1H1   |         | Genteq   | Special  | 23000  |     | 100  | 3     | Round | 4.625                    | Electrolytic             | 1000          | -55°C to 105°C |
| 23H961F250DB1H1   |         | Genteq   | Special  | 960    |     | 250  | 2     | Round | 2.125                    | Electrolytic             | 2000          | -40°C to 85°C  |
| 23A104F080F11H1   |         | Genteq   | Special  | 100000 |     | 80   | 3     | Round | 5.625                    | Electrolytic             | 1000          | -40°C to 85°C  |
| 97F9020           |         | Genteq   | Special  | 25     | 7.5 | 370  | 1.75  | Oval  | 3.88                     | Oil-Filled (UL Approved) | 60000         | -40°C to 70°C  |
| 97F6919BR         | BR      | Genteq   | Standard | 16     |     | 540  | 1.75  | Oval  | 3.88                     | Oil-Filled (UL Approved) | 60000         | -40°C to 90°C  |
| 23B383F050DG1H1   |         | Genteq   | Special  | 38000  |     | 50   | 2     | Round | 4.625                    | Electrolytic             | 3000          | -40°C to 85°C  |
| 97F9644           |         | Genteq   | Standard | 45     |     | 440  | 2     | Oval  | 3.88                     | Oil-Filled (UL Approved) | 60000         | -40°C to 70°C  |
| 27L1022S          | S       | Genteq   | Stock    | 3      |     | 440  | 1.25  | Oval  | 1.56                     | Oil-Filled (UL Approved) | 60000         | -40°C to 70°C  |
| 23B363F080EG1H1   |         | Genteq   | Special  | 36000  |     | 80   | 2.5   | Round | 4.625                    | Electrolytic             | 3000          | -40°C to 85°C  |
| 27L388BX          | BX      | Genteq   | Special  | 60     |     | 440  | 2     | Oval  | 4.25                     | Oil-Filled (UL Approved) | 60000         | -40°C to 70°C  |
| 27L946            |         | Genteq   | Standard | 40     | 5   | 440  | 2.5   | Round | 2.88                     | Oil-Filled (UL Approved) | 60000         | -40°C to 70°C  |
| 27L850BX          | BX      | Genteq   | Standard | 11.5   | 7   | 330  | 1.75  | Oval  | 3.88                     | Oil-Filled (UL Approved) | 60000         | -40°C to 90°C  |
| 23F173F075DE1H1   |         | Genteq   | Special  | 17000  |     | 75   | 2     | Round | 3.625                    | Electrolytic             | 1000          | -55°C to 105°C |
| 97F9993BX         | BX      | Genteq   | Standard | 25     | 7.5 | 440  | 1.75  | Oval  | 3.88                     | Oil-Filled (UL Approved) | 60000         | -40°C to 70°C  |
| 23B811F250BF1H1   |         | Genteq   | Special  | 810    |     | 250  | 1.375 | Round | 4.125                    | Electrolytic             | 3000          | -40°C to 85°C  |
| 23J122F400DI1H1   |         | Genteq   | Special  | 1200   |     | 400  | 2     | Round | 5.625                    | Electrolytic             | 2000          | -40°C to 105°C |
| 97F9337BX         | BX      | Genteq   | Standard | 55     |     | 370  | 2.5   | Round | 3.88                     | Oil-Filled (UL Approved) | 60000         | -40°C to 70°C  |
| 23H371F350BC1H1   |         | Genteq   | Special  | 370    |     | 350  | 1.375 | Round | 2.625                    | Electrolytic             | 2000          | -40°C to 85°C  |
| 23M432F300EF1H1   |         | Genteq   | Special  | 4300   |     | 300  | 2.5   | Round | 4.125                    | Electrolytic             | 2000          | -40°C to 85°C  |
| 27L562            |         | Genteq   | Special  | 45     | 19  | 330  | 1.75  | Oval  | 5.75                     | Oil-Filled (UL Approved) | 60000         | -40°C to 90°C  |
| 97F6694BR         | BR      | Genteq   | Special  | 20     |     | 480  | 1.75  | Oval  | 3.88                     | Oil-Filled (UL Approved) | 60000         | -40°C to 90°C  |
| 97F5461           |         | Genteq   | Special  | 15     |     | 370  | 1.75  | Oval  | 2.62                     | Oil-Filled (UL Approved) | 60000         | -40°C to 70°C  |
| 97F9881           |         | Genteq   | Standard | 35     | 7.5 | 440  | 2     | Round | 4.75                     | Oil-Filled (UL Approved) | 60000         | -40°C to 70°C  |
| 97F9046BX         | BX      | Genteq   | Special  | 15     | 10  | 440  | 1.75  | Oval  | 3.88                     | Oil-Filled (UL Approved) | 60000         | -40°C to 70°C  |
| 23M581F450BH1H1   |         | Genteq   | Special  | 580    |     | 450  | 1.375 | Round | 5.125                    | Electrolytic             | 2000          | -40°C to 85°C  |
| 23A863F075FG1H1   |         | Genteq   | Special  | 86000  |     | 75   | 3     | Round | 4.625                    | Electrolytic             | 1000          | -40°C to 85°C  |
| 97F8068           |         | Genteq   | Standard | 45     |     | 370  | 2     | Round | 4.75                     | Oil-Filled (UL Approved) | 60000         | -40°C to 70°C  |
| 23C583F075FF1H1   |         | Genteq   | Special  | 58000  |     | 75   | 3     | Round | 4.125                    | Electrolytic             | 1000          | -45°C to 95°C  |
| 97F5103BX         | BX      | Genteq   | Special  | 30     |     | 440  | 2     | Round | 3.88                     | Oil-Filled (UL Approved) | 60000         | -40°C to 70°C  |
| 23C783F075FH1H1   |         | Genteq   | Special  | 78000  |     | 75   | 3     | Round | 5.125                    | Electrolytic             | 1000          | -45°C to 95°C  |
| 97F9673           |         | Genteq   | Standard | 20     | 5   | 370  | 1.75  | Oval  | 2.88                     | Oil-Filled (UL Approved) | 60000         | -40°C to 70°C  |
| 23A332F150BH1H1   |         | Genteq   | Special  | 3300   |     | 150  | 1.375 | Round | 5.125                    | Electrolytic             | 1000          | -40°C to 85°C  |
| 97F5814BX         | BX      | Genteq   | Special  | 25     | 5   | 370  | 2     | Round | 4.25                     | Oil-Filled (UL Approved) | 60000         | -40°C to 70°C  |
| 23J582F300F1H1    |         | Genteq   | Special  | 5800   |     | 300  | 3     | Round | 5.625                    | Electrolytic             | 2000          | -40°C to 105°C |
| 23D104F007CH1H1   |         | Genteq   | Special  | 100000 |     | 7.5  | 1.75  | Round | 5.125                    | Electrolytic             | 1000          | -55°C to 85°C  |
| 97F9073BX         | BX      | Genteq   | Special  | 40     |     | 370  | 1.75  | Oval  | 3.88                     | Oil-Filled (UL Approved) | 60000         | -40°C to 70°C  |
| 27L633            |         | Genteq   | Standard | 70     | 5   | 370  | 2.5   | Round | 4.75                     | Oil-Filled (UL Approved) | 60000         | -40°C to 70°C  |
| 97F9838BX         | BX      | Genteq   | Standard | 40     | 5   | 440  | 2     | Round | 4.75                     | Oil-Filled (UL Approved) | 60000         | -40°C to 70°C  |
| 23C203F050BG1H1   |         | Genteq   | Special  | 20000  |     | 50   | 1.375 | Round | 4.625                    | Electrolytic             | 1000          | -45°C to 95°C  |
| 97F9081           |         | Genteq   | Special  | 15     |     | 440  | 1.25  | Oval  | 4.75                     | Oil-Filled (UL Approved) | 60000         | -40°C to 70°C  |
| 23C393F060DF1H1   |         | Genteq   | Special  | 39000  |     | 60   | 2     | Round | 4.125                    | Electrolytic             | 1000          | -45°C to 95°C  |
| 97F9995           |         | Genteq   | Standard | 30     | 7.5 | 440  | 1.75  | Oval  | 3.88                     | Oil-Filled (UL Approved) | 60000         | -40°C to 70°C  |
| 23H252F450FH1H1   |         | Genteq   | Special  | 2500   |     | 450  | 3     | Round | 5.125                    | Electrolytic             | 2000          | -40°C to 85°C  |
| PB450E000P370EA   | PROLINE | Standard | 45       |        | 370 | 1.75 | Round | 4.75  | Oil-Filled (UL Approved) | 10000                    | -40°C to 70°C |                |
| 23F142F200CE1H1   |         | Genteq   | Special  | 1400   |     | 200  | 1.75  | Round | 3.625                    | Electrolytic             | 1000          | -55°C to 105°C |
| 23C144F050F11H1   |         | Genteq   | Special  | 140000 |     | 50   | 3     | Round | 5.625                    | Electrolytic             | 1000          | -45°C to 95°C  |
| 27L1025S          | S       | Genteq   | Stock    | 6      |     | 440  | 1.25  | Oval  | 2.12                     | Oil-Filled (UL Approved) | 60000         | -40°C to 70°C  |
| PB500E000S440FABX | BX      | PROLINE  | Standard | 50     |     | 440  | 2     | Round | 5.75                     | Oil-Filled (UL Approved) | 10000         | -40°C to 70°C  |
| 23A353F075CI1H1   |         | Genteq   | Special  | 35000  |     | 75   | 1.75  | Round | 5.625                    | Electrolytic             | 1000          | -40°C to 85°C  |
| 23A273F075DE1H1   |         | Genteq   | Special  | 27000  |     | 75   | 2     | Round | 3.625                    | Electrolytic             | 1000          | -40°C to 85°C  |

|                   |    |         |          |       |     |     |       |       |       |                          |        |                |
|-------------------|----|---------|----------|-------|-----|-----|-------|-------|-------|--------------------------|--------|----------------|
| 27L1020BX         | BX | Genteq  | Standard | 2     |     | 370 | 1.25  | Oval  | 1.56  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23H222F400FE1H1   |    | Genteq  | Special  | 2200  |     | 400 | 3     | Round | 3.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| PB400Y050C370DABX | BX | PROLINE | Standard | 40    | 5   | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 27L1027BX         | BX | Genteq  | Standard | 10    |     | 440 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23J122F350ED1H1   |    | Genteq  | Special  | 1200  |     | 350 | 2.5   | Round | 3.125 | Electrolytic             | 2000   | -40°C to 105°C |
| 97F6881BR         | BR | Genteq  | Standard | 42    | 14  | 280 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23M992F300F1H1    |    | Genteq  | Special  | 9900  |     | 300 | 3     | Round | 5.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23F733F075FJ1H1   |    | Genteq  | Special  | 73000 |     | 75  | 3     | Round | 5.875 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F9207           |    | Genteq  | Standard | 25    |     | 240 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23C492F150DE1H1   |    | Genteq  | Special  | 4900  |     | 150 | 2     | Round | 3.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23A113F080CC1H1   |    | Genteq  | Special  | 11000 |     | 80  | 1.75  | Round | 2.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 23C213F060CD1H1   |    | Genteq  | Special  | 21000 |     | 60  | 1.75  | Round | 3.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F6882RC         | RC | Genteq  | Standard | 24    | 8   | 280 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 41L7501           |    | Genteq  | Stock    | 5     |     | 700 | 1.2   | Round | 2.17  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 23C883F050EH1H1   |    | Genteq  | Special  | 88000 |     | 50  | 2.5   | Round | 5.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23M592F200DH1H1   |    | Genteq  | Special  | 5900  |     | 200 | 2     | Round | 5.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F9494           |    | Genteq  | Standard | 35    | 7.5 | 440 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23J692F250FH1H1   |    | Genteq  | Special  | 6900  |     | 250 | 3     | Round | 5.125 | Electrolytic             | 2000   | -40°C to 105°C |
| 23C222F250CG1H1   |    | Genteq  | Special  | 2200  |     | 250 | 1.75  | Round | 4.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F8059BX         | BX | Genteq  | Standard | 10    |     | 370 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23H641F200BB1H1   |    | Genteq  | Special  | 640   |     | 200 | 1.375 | Round | 2.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23H122F400DG1H1   |    | Genteq  | Special  | 1200  |     | 400 | 2     | Round | 4.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F8258BX         | BX | Genteq  | Standard | 45    |     | 600 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23C832F080BE1H1   |    | Genteq  | Special  | 8300  |     | 80  | 1.375 | Round | 3.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23C602F250E1H1    |    | Genteq  | Special  | 6000  |     | 250 | 2.5   | Round | 5.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23H291F450DB1H1   |    | Genteq  | Special  | 290   |     | 450 | 2     | Round | 2.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23B612F250FH1H1   |    | Genteq  | Special  | 6100  |     | 250 | 3     | Round | 5.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23B103F150EH1H1   |    | Genteq  | Special  | 10000 |     | 150 | 2.5   | Round | 5.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23D363F016B1H1    |    | Genteq  | Special  | 36000 |     | 16  | 1.375 | Round | 5.625 | Electrolytic             | 1000   | -55°C to 85°C  |
| 23F183F050CD1H1   |    | Genteq  | Special  | 18000 |     | 50  | 1.75  | Round | 3.125 | Electrolytic             | 1000   | -55°C to 105°C |
| PB200Y075C440DA   |    | PROLINE | Standard | 20    | 7.5 | 440 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F5241           |    | Genteq  | Standard | 65    |     | 440 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F8076BX         | BX | Genteq  | Special  | 50    |     | 480 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23M142F450EE1H1   |    | Genteq  | Special  | 1400  |     | 450 | 2.5   | Round | 3.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F9864           |    | Genteq  | Standard | 35    | 7.5 | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23D153F055CG1H1   |    | Genteq  | Special  | 15000 |     | 55  | 1.75  | Round | 4.625 | Electrolytic             | 1000   | -55°C to 85°C  |
| 97F6769           |    | Genteq  | Standard | 16    |     | 330 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23A383F080DH1H1   |    | Genteq  | Special  | 38000 |     | 80  | 2     | Round | 5.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 97F8082BX         | BX | Genteq  | Special  | 30    |     | 480 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23F303F060EE1H1   |    | Genteq  | Special  | 30000 |     | 60  | 2.5   | Round | 3.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 23M801F350BF1H1   |    | Genteq  | Special  | 800   |     | 350 | 1.375 | Round | 4.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| PB600Z050T370DABX | BX | PROLINE | Standard | 60    | 5   | 370 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23C172F150BD1H1   |    | Genteq  | Special  | 1700  |     | 150 | 1.375 | Round | 3.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23D932F055CD1H1   |    | Genteq  | Special  | 9300  |     | 55  | 1.75  | Round | 3.125 | Electrolytic             | 1000   | -55°C to 85°C  |
| 23M601F300BC1H1   |    | Genteq  | Special  | 600   |     | 300 | 1.375 | Round | 2.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 27L443BR          | BR | Genteq  | Standard | 17    | 7   | 400 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 27L53             |    | Genteq  | Standard | 26    | 15  | 400 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| PB450Y075D440EA   |    | PROLINE | Standard | 45    | 7.5 | 440 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23J361F350BD1H1   |    | Genteq  | Special  | 360   |     | 350 | 1.375 | Round | 3.125 | Electrolytic             | 2000   | -40°C to 105°C |
| 23H741F400DD1H1   |    | Genteq  | Special  | 740   |     | 400 | 2     | Round | 3.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23A124F050FF1H1   |    | Genteq  | Special  | 12000 |     | 50  | 3     | Round | 4.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 27L413            |    | Genteq  | Standard | 35    | 16  | 300 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| PB100E000A440CABX | BX | PROLINE | Standard | 10    |     | 440 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23M382F250ED1H1   |    | Genteq  | Special  | 3800  |     | 250 | 2.5   | Round | 3.125 | Electrolytic             | 2000   | -40°C to 85°C  |

|                   |    |         |          |       |     |     |       |       |       |                          |        |                |
|-------------------|----|---------|----------|-------|-----|-----|-------|-------|-------|--------------------------|--------|----------------|
| PB200Y100C440DA   |    | PROLINE | Standard | 20    | 10  | 440 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23J362F300EH1H1   |    | Genteq  | Special  | 3600  |     | 300 | 2.5   | Round | 5.125 | Electrolytic             | 2000   | -40°C to 105°C |
| 97F9998           |    | Genteq  | Standard | 15    | 7.5 | 440 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB400E000S440EABX | BX | PROLINE | Standard | 40    |     | 440 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F9858BX         | BX | Genteq  | Standard | 50    | 7.5 | 370 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23J561F250BC1H1   |    | Genteq  | Special  | 560   |     | 250 | 1.375 | Round | 2.625 | Electrolytic             | 2000   | -40°C to 105°C |
| PB200E000A440EABX | BX | PROLINE | Standard | 20    |     | 440 | 1.25  | Oval  | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23H352F450FL1H1   |    | Genteq  | Special  | 3500  |     | 450 | 3     | Round | 8.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F5043BX         | BX | Genteq  | Special  | 10    |     | 370 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23M442F200DF1H1   |    | Genteq  | Special  | 4400  |     | 200 | 2     | Round | 4.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F5541           |    | Genteq  | Special  | 45    | 7.5 | 370 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6690BX         | BX | Genteq  | Special  | 36    | 12  | 260 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| PB300Y075C370DABX | BX | PROLINE | Standard | 30    | 7.5 | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23H142F300BI1H1   |    | Genteq  | Special  | 1400  |     | 300 | 1.375 | Round | 5.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F9036           |    | Genteq  | Standard | 7.5   |     | 440 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23B541F200BC1H1   |    | Genteq  | Special  | 540   |     | 200 | 1.375 | Round | 2.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23C353F050DD1H1   |    | Genteq  | Special  | 35000 |     | 50  | 2     | Round | 3.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F6883BX         | BX | Genteq  | Standard | 36    | 20  | 280 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23J262F250CI1H1   |    | Genteq  | Special  | 2600  |     | 250 | 1.75  | Round | 5.625 | Electrolytic             | 2000   | -40°C to 105°C |
| 97F9501           |    | Genteq  | Standard | 2.5   |     | 370 | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F8264           |    | Genteq  | Standard | 45    |     | 600 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23F353F050CH1H1   |    | Genteq  | Special  | 35000 |     | 50  | 1.75  | Round | 5.125 | Electrolytic             | 1000   | -55°C to 105°C |
| PB350Z050S370DABX | BX | PROLINE | Standard | 35    | 5   | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23F103F075DC1H1   |    | Genteq  | Special  | 10000 |     | 75  | 2     | Round | 2.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F9681           |    | Genteq  | Standard | 30    | 5   | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6890RR         | RR | Genteq  | Standard | 18    | 10  | 280 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23A252F150BF1H1   |    | Genteq  | Special  | 2500  |     | 150 | 1.375 | Round | 4.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 97F9009           |    | Genteq  | Standard | 50    |     | 370 | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L497BX          | BX | Genteq  | Standard | 80    |     | 370 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23B132F250DD1H1   |    | Genteq  | Special  | 1300  |     | 250 | 2     | Round | 3.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23A103F080DB1H1   |    | Genteq  | Special  | 10000 |     | 80  | 2     | Round | 2.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 97F8020BX         | BX | Genteq  | Special  | 54    |     | 440 | 2.5   | Round | 4.25  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L827BX          | BX | Genteq  | Standard | 18    | 10  | 330 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 40L6151           |    | Genteq  | Stock    | 1.5   |     | 600 | 0.73  | Oval  | 1.5   | Dry-Axial Leaded         | 100000 | -55°C to 105°C |
| 23B273F100FG1H1   |    | Genteq  | Special  | 27000 |     | 100 | 3     | Round | 4.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23B862F100CG1H1   |    | Genteq  | Special  | 8600  |     | 100 | 1.75  | Round | 4.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23C901F200CB1H1   |    | Genteq  | Special  | 900   |     | 200 | 1.75  | Round | 2.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23D143F016BC1H1   |    | Genteq  | Special  | 14000 |     | 16  | 1.375 | Round | 2.625 | Electrolytic             | 1000   | -55°C to 85°C  |
| 97F5818           |    | Genteq  | Special  | 25    | 10  | 370 | 2     | Round | 4.25  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9609BX         | BX | Genteq  | Standard | 30    |     | 370 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23H652F250EI1H1   |    | Genteq  | Special  | 6500  |     | 250 | 2.5   | Round | 5.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23M672F200DI1H1   |    | Genteq  | Special  | 6700  |     | 200 | 2     | Round | 5.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 27L709BX          | BX | Genteq  | Standard | 26    |     | 400 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23A553F080EG1H1   |    | Genteq  | Special  | 55000 |     | 80  | 2.5   | Round | 4.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 27L539            |    | Genteq  | Standard | 15    | 11  | 330 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23M142F250BF1H1   |    | Genteq  | Special  | 1400  |     | 250 | 1.375 | Round | 4.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 27L954            |    | Genteq  | Standard | 60    | 5   | 370 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23H172F400EF1H1   |    | Genteq  | Special  | 1700  |     | 400 | 2.5   | Round | 4.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23F242F200CI1H1   |    | Genteq  | Special  | 2400  |     | 200 | 1.75  | Round | 5.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 23F142F250DE1H1   |    | Genteq  | Special  | 1400  |     | 250 | 2     | Round | 3.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F9593           |    | Genteq  | Standard | 50    | 10  | 440 | 2     | Oval  | 5.25  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23H911F250CB1H1   |    | Genteq  | Special  | 910   |     | 250 | 1.75  | Round | 2.125 | Electrolytic             | 2000   | -40°C to 85°C  |

|                   |    |         |          |       |     |     |       |       |       |                          |       |                |
|-------------------|----|---------|----------|-------|-----|-----|-------|-------|-------|--------------------------|-------|----------------|
| 97F6766RC         | RC | Genteq  | Standard | 7     |     | 330 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| PB100Y100C370BA   |    | PROLINE | Standard | 10    | 10  | 370 | 1.75  | Oval  | 2.12  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23F123F100EE1H1   |    | Genteq  | Special  | 12000 |     | 100 | 2.5   | Round | 3.625 | Electrolytic             | 1000  | -55°C to 105°C |
| 23J412F250EG1H1   |    | Genteq  | Special  | 4100  |     | 250 | 2.5   | Round | 4.625 | Electrolytic             | 2000  | -40°C to 105°C |
| 23A143F150FF1H1   |    | Genteq  | Special  | 14000 |     | 150 | 3     | Round | 4.125 | Electrolytic             | 1000  | -40°C to 85°C  |
| 97F8073BX         | BX | Genteq  | Standard | 70    |     | 370 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23C183F100DG1H1   |    | Genteq  | Special  | 18000 |     | 100 | 2     | Round | 4.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| 23B173F050CD1H1   |    | Genteq  | Special  | 17000 |     | 50  | 1.75  | Round | 3.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| 27L1023S          | S  | Genteq  | Stock    | 4     |     | 440 | 1.25  | Oval  | 1.56  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F6763S          | S  | Genteq  | Stock    | 10    |     | 330 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 27L589            |    | Genteq  | Standard | 10    | 5   | 400 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F9318           |    | Genteq  | Special  | 55    | 5   | 440 | 2     | Oval  | 5.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23C563F100F11H1   |    | Genteq  | Special  | 56000 |     | 100 | 3     | Round | 5.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| 27L877S           | S  | Genteq  | Stock    | 30    | 5   | 370 | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23C733F080FH1H1   |    | Genteq  | Special  | 73000 |     | 80  | 3     | Round | 5.125 | Electrolytic             | 1000  | -45°C to 95°C  |
| 97F6694RC         | RC | Genteq  | Special  | 20    |     | 480 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F5067           |    | Genteq  | Standard | 12.5  |     | 370 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F8057S          | S  | Genteq  | Stock    | 6     |     | 370 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F6766BX         | BX | Genteq  | Standard | 7     |     | 330 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23A163F100DF1H1   |    | Genteq  | Special  | 16000 |     | 100 | 2     | Round | 4.125 | Electrolytic             | 1000  | -40°C to 85°C  |
| 97F9833BX         | BX | Genteq  | Standard | 30    | 5   | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F9006           |    | Genteq  | Standard | 25    |     | 370 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F8067S          | S  | Genteq  | Stock    | 40    |     | 370 | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F8077BX         | BX | Genteq  | Special  | 5     |     | 440 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| PB500Z100S370EA   |    | PROLINE | Standard | 50    | 10  | 370 | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23F172F250CH1H1   |    | Genteq  | Special  | 1700  |     | 250 | 1.75  | Round | 5.125 | Electrolytic             | 1000  | -55°C to 105°C |
| 97F5541BX         | BX | Genteq  | Special  | 45    | 7.5 | 370 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 27L954BX          | BX | Genteq  | Standard | 60    | 5   | 370 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 27L427BX          | BX | Genteq  | Standard | 15    | 10  | 400 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23M133F250FJ1H1   |    | Genteq  | Special  | 13000 |     | 250 | 3     | Round | 5.875 | Electrolytic             | 2000  | -40°C to 85°C  |
| PB040E000A370AABX | BX | PROLINE | Standard | 4     |     | 370 | 1.25  | Oval  | 1.56  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F9265BX         | BX | Genteq  | Standard | 25    |     | 410 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23B692F080BE1H1   |    | Genteq  | Special  | 6900  |     | 80  | 1.375 | Round | 3.625 | Electrolytic             | 3000  | -40°C to 85°C  |
| 23M832F350FL1H1   |    | Genteq  | Special  | 8300  |     | 350 | 3     | Round | 8.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23F112F250CE1H1   |    | Genteq  | Special  | 1100  |     | 250 | 1.75  | Round | 3.625 | Electrolytic             | 1000  | -55°C to 105°C |
| 97F6514BX         | BX | Genteq  | Special  | 20    |     | 170 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23M282F450FG1H1   |    | Genteq  | Special  | 2800  |     | 450 | 3     | Round | 4.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23J711F250BD1H1   |    | Genteq  | Special  | 710   |     | 250 | 1.375 | Round | 3.125 | Electrolytic             | 2000  | -40°C to 105°C |
| PB125E000P440CA   |    | PROLINE | Standard | 12.5  |     | 440 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 27L1052           |    | Genteq  | Standard | 55    |     | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23A583F050CI1H1   |    | Genteq  | Special  | 58000 |     | 50  | 1.75  | Round | 5.625 | Electrolytic             | 1000  | -40°C to 85°C  |
| 23D553F007CD1H1   |    | Genteq  | Special  | 55000 |     | 7.5 | 1.75  | Round | 3.125 | Electrolytic             | 1000  | -55°C to 85°C  |
| 97F6753           |    | Genteq  | Special  | 7     |     | 330 | 1.5   | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23M142F250CC1H1   |    | Genteq  | Special  | 1400  |     | 250 | 1.75  | Round | 2.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23A612F150CH1H1   |    | Genteq  | Special  | 6100  |     | 150 | 1.75  | Round | 5.125 | Electrolytic             | 1000  | -40°C to 85°C  |
| 27L176BX          | BX | Genteq  | Special  | 7.5   |     | 540 | 1.5   | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23A593F075EG1H1   |    | Genteq  | Special  | 59000 |     | 75  | 2.5   | Round | 4.625 | Electrolytic             | 1000  | -40°C to 85°C  |
| 97F9843           |    | Genteq  | Standard | 40    | 5   | 440 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F8060BX         | BX | Genteq  | Standard | 12.5  |     | 370 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F6783           |    | Genteq  | Special  | 25    |     | 330 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |



|                    |    |         |          |        |     |     |       |       |       |                          |        |                |
|--------------------|----|---------|----------|--------|-----|-----|-------|-------|-------|--------------------------|--------|----------------|
| 27L961             |    | Genteq  | Standard | 25     |     | 440 | 1.25  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23H702F200FE1H1    |    | Genteq  | Special  | 7000   |     | 200 | 3     | Round | 3.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| PB500E000S370DA    |    | PROLINE | Standard | 50     |     | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23F143F050CC1H1    |    | Genteq  | Special  | 14000  |     | 50  | 1.75  | Round | 2.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 23A193F100DG1H1    |    | Genteq  | Special  | 19000  |     | 100 | 2     | Round | 4.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| PB350Y075C440EA    |    | PROLINE | Standard | 35     | 7.5 | 440 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 27L7008BX          | BX | Genteq  | Special  | 11     | 6   | 330 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 100°C |
| 97F9828            |    | Genteq  | Standard | 30     | 10  | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 42L1222            |    | Genteq  | Stock    | 0.22   |     | 850 | 0.47  | Round | 1.22  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 23A273F060CE1H1    |    | Genteq  | Special  | 27000  |     | 60  | 1.75  | Round | 3.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 23M512F400FJ1H1    |    | Genteq  | Special  | 5100   |     | 400 | 3     | Round | 5.875 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F8042            |    | Genteq  | Standard | 50     |     | 240 | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F5011BX          | BX | Genteq  | Standard | 10     |     | 440 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB200Y050C370CAB X | BX | PROLINE | Standard | 20     | 5   | 370 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F6854RC          | RC | Genteq  | Standard | 34     |     | 280 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| PB500Z075T440EABX  | BX | PROLINE | Standard | 50     | 7.5 | 440 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F6725            |    | Genteq  | Special  | 29     |     | 330 | 1.75  | Oval  | 3.5   | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| PB350E000C370DAB X | BX | PROLINE | Standard | 35     |     | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23M312F300C1H1     |    | Genteq  | Special  | 3100   |     | 300 | 1.75  | Round | 5.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23A593F050DG1H1    |    | Genteq  | Special  | 59000  |     | 50  | 2     | Round | 4.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 41L6221            |    | Genteq  | Stock    | 2.2    |     | 600 | 0.77  | Round | 1.65  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| PB500Z050T370DABX  | BX | PROLINE | Standard | 50     | 5   | 370 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23H302F300EE1H1    |    | Genteq  | Special  | 3000   |     | 300 | 2.5   | Round | 3.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23M112F450CH1H1    |    | Genteq  | Special  | 1100   |     | 450 | 1.75  | Round | 5.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| PB075E000P440CA    |    | PROLINE | Standard | 7.5    |     | 440 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23A523F100FH1H1    |    | Genteq  | Special  | 52000  |     | 100 | 3     | Round | 5.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 23H222F200BI1H1    |    | Genteq  | Special  | 2200   |     | 200 | 1.375 | Round | 5.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F6521            |    | Genteq  | Standard | 28     |     | 330 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23J142F250DD1H1    |    | Genteq  | Special  | 1400   |     | 250 | 2     | Round | 3.125 | Electrolytic             | 2000   | -40°C to 105°C |
| 27L444BX           | BX | Genteq  | Special  | 37     | 11  | 300 | 1.75  | Oval  | 4.25  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23C902F250FJ1H1    |    | Genteq  | Special  | 9000   |     | 250 | 3     | Round | 5.875 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23A173F075BH1H1    |    | Genteq  | Special  | 17000  |     | 75  | 1.375 | Round | 5.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 23B472F200EG1H1    |    | Genteq  | Special  | 4700   |     | 200 | 2.5   | Round | 4.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F6685BX          | BX | Genteq  | Special  | 15     |     | 480 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F6868BR          | BR | Genteq  | Standard | 26     |     | 280 | 1.5   | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 27L6017            |    | Genteq  | Special  | 10     |     | 660 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F5452            |    | Genteq  | Special  | 30     | 10  | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6733            |    | Genteq  | Special  | 40     |     | 330 | 2     | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F6506BR          | BR | Genteq  | Standard | 14     |     | 330 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23A104F050EG1H1    |    | Genteq  | Special  | 100000 |     | 50  | 2.5   | Round | 4.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| PB500E000C440EA    |    | PROLINE | Standard | 50     |     | 440 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23C313F050CF1H1    |    | Genteq  | Special  | 31000  |     | 50  | 1.75  | Round | 4.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F9084            |    | Genteq  | Standard | 55     |     | 440 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB150Y100C370CAB X | BX | PROLINE | Standard | 15     | 10  | 370 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23B503F060FD1H1    |    | Genteq  | Special  | 50000  |     | 60  | 3     | Round | 3.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23B102F250BG1H1    |    | Genteq  | Special  | 1000   |     | 250 | 1.375 | Round | 4.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23A234F050FL1H1    |    | Genteq  | Special  | 230000 |     | 50  | 3     | Round | 8.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 97F9047BX          | BX | Genteq  | Standard | 20     | 5   | 440 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB400Z075S440EABX  | BX | PROLINE | Standard | 40     | 7.5 | 440 | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23A632F080BC1H1    |    | Genteq  | Special  | 6300   |     | 80  | 1.375 | Round | 2.625 | Electrolytic             | 1000   | -40°C to 85°C  |

|                    |    |         |          |       |     |     |       |       |       |                          |       |                |
|--------------------|----|---------|----------|-------|-----|-----|-------|-------|-------|--------------------------|-------|----------------|
| 97F8247BX          | BX | Genteq  | Standard | 7     |     | 600 | 1.25  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23F183F050DC1H1    |    | Genteq  | Special  | 18000 |     | 50  | 2     | Round | 2.625 | Electrolytic             | 1000  | -55°C to 105°C |
| 97F8065BX          | BX | Genteq  | Standard | 30    |     | 370 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23F472F150EE1H1    |    | Genteq  | Special  | 4700  |     | 150 | 2.5   | Round | 3.625 | Electrolytic             | 1000  | -55°C to 105°C |
| 23F183F075CG1H1    |    | Genteq  | Special  | 18000 |     | 75  | 1.75  | Round | 4.625 | Electrolytic             | 1000  | -55°C to 105°C |
| 27L5200BX          | BX | Genteq  | Standard | 50    | 5   | 440 | 2     | Oval  | 5.25  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23B133F080DD1H1    |    | Genteq  | Special  | 13000 |     | 80  | 2     | Round | 3.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| 97F9059            |    | Genteq  | Special  | 55    | 5   | 440 | 2     | Oval  | 6.25  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F9016BX          | BX | Genteq  | Special  | 20    | 5   | 370 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23B293F050CG1H1    |    | Genteq  | Special  | 29000 |     | 50  | 1.75  | Round | 4.625 | Electrolytic             | 3000  | -40°C to 85°C  |
| 27L1026            |    | Genteq  | Standard | 8     |     | 370 | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F9023            |    | Genteq  | Special  | 35    | 10  | 370 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23H412F300EG1H1    |    | Genteq  | Special  | 4100  |     | 300 | 2.5   | Round | 4.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 97F9641BX          | BX | Genteq  | Standard | 40    |     | 440 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23C532F200FD1H1    |    | Genteq  | Special  | 5300  |     | 200 | 3     | Round | 3.125 | Electrolytic             | 1000  | -45°C to 95°C  |
| 97F9602            |    | Genteq  | Standard | 20    |     | 370 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23B213F060DD1H1    |    | Genteq  | Special  | 21000 |     | 60  | 2     | Round | 3.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| 97F5066            |    | Genteq  | Standard | 10    |     | 370 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23F373F100FL1H1    |    | Genteq  | Special  | 37000 |     | 100 | 3     | Round | 8.625 | Electrolytic             | 1000  | -55°C to 105°C |
| 23C563F080E11H1    |    | Genteq  | Special  | 56000 |     | 80  | 2.5   | Round | 5.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| PB075E000A370BAS   | S  | PROLINE | Stock    | 7.5   |     | 370 | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F9612            |    | Genteq  | Standard | 35    |     | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 27L724BR           | BR | Genteq  | Standard | 24    | 11  | 280 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F9081BX          | BX | Genteq  | Special  | 15    |     | 440 | 1.25  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 27L866BX           | BX | Genteq  | Standard | 70    | 10  | 440 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23M522F200DG1H1    |    | Genteq  | Special  | 5200  |     | 200 | 2     | Round | 4.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 97F9874            |    | Genteq  | Standard | 55    | 7.5 | 440 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F9888BX          | BX | Genteq  | Standard | 35    | 10  | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F8257BX          | BX | Genteq  | Standard | 40    |     | 600 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23F432F075BC1H1    |    | Genteq  | Special  | 4300  |     | 75  | 1.375 | Round | 2.625 | Electrolytic             | 1000  | -55°C to 105°C |
| 27L7004            |    | Genteq  | Special  | 24    |     | 360 | 1.25  | Oval  | 3.12  | Oil-Filled (UL Approved) | 60000 | -40°C to 100°C |
| PB300E000C370CAB X | BX | PROLINE | Standard | 30    |     | 370 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| PB200E000A370DA    |    | PROLINE | Standard | 20    |     | 370 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 27L797BR           | BR | Genteq  | Standard | 15    | 7.5 | 400 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23C323F100FE1H1    |    | Genteq  | Special  | 32000 |     | 100 | 3     | Round | 3.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| 97F6927BR          | BR | Genteq  | Special  | 11.5  | 3   | 400 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F6535BX          | BX | Genteq  | Standard | 24    |     | 400 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F6773BX          | BX | Genteq  | Standard | 22.5  |     | 330 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F9892BX          | BX | Genteq  | Standard | 35    | 7.5 | 440 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23H252F400FF1H1    |    | Genteq  | Special  | 2500  |     | 400 | 3     | Round | 4.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| PB500Y075C370EA    |    | PROLINE | Standard | 50    | 7.5 | 370 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23J272F300FD1H1    |    | Genteq  | Special  | 2700  |     | 300 | 3     | Round | 3.125 | Electrolytic             | 2000  | -40°C to 105°C |
| 23J152F400EG1H1    |    | Genteq  | Special  | 1500  |     | 400 | 2.5   | Round | 4.625 | Electrolytic             | 2000  | -40°C to 105°C |
| 23C223F075CG1H1    |    | Genteq  | Special  | 22000 |     | 75  | 1.75  | Round | 4.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| PB050E000P370CAB X | BX | PROLINE | Standard | 5     |     | 370 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23C881F150BB1H1    |    | Genteq  | Special  | 880   |     | 150 | 1.375 | Round | 2.125 | Electrolytic             | 1000  | -45°C to 95°C  |
| 23M742F300FG1H1    |    | Genteq  | Special  | 7400  |     | 300 | 3     | Round | 4.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 97F6656            |    | Genteq  | Standard | 7.5   |     | 400 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23H502F350F11H1    |    | Genteq  | Special  | 5000  |     | 350 | 3     | Round | 5.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23A353F060DE1H1    |    | Genteq  | Special  | 35000 |     | 60  | 2     | Round | 3.625 | Electrolytic             | 1000  | -40°C to 85°C  |

|                   |    |         |          |       |     |      |       |       |       |                          |        |                |
|-------------------|----|---------|----------|-------|-----|------|-------|-------|-------|--------------------------|--------|----------------|
| PB300E000S440DA   |    | PROLINE | Standard | 30    |     | 440  | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F9834BX         | BX | Genteq  | Standard | 35    | 5   | 370  | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23A463F075DI1H1   |    | Genteq  | Special  | 46000 |     | 75   | 2     | Round | 5.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 23A213F060DC1H1   |    | Genteq  | Special  | 21000 |     | 60   | 2     | Round | 2.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 97F6519BX         | BX | Genteq  | Standard | 16    |     | 330  | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23J152F300CG1H1   |    | Genteq  | Special  | 1500  |     | 300  | 1.75  | Round | 4.625 | Electrolytic             | 2000   | -40°C to 105°C |
| 23C152F250BI1H1   |    | Genteq  | Special  | 1500  |     | 250  | 1.375 | Round | 5.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F9830BX         | BX | Genteq  | Standard | 35    | 10  | 370  | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9831           |    | Genteq  | Standard | 40    | 10  | 370  | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 42L3102           |    | Genteq  | Stock    | 0.1   |     | 2000 | 0.81  | Round | 1.22  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 97F9645BX         | BX | Genteq  | Standard | 45    |     | 440  | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6726           |    | Genteq  | Standard | 30    |     | 330  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 41L4151           |    | Genteq  | Stock    | 1.5   |     | 400  | 0.57  | Round | 1.22  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 23F382F150CI1H1   |    | Genteq  | Special  | 3800  |     | 150  | 1.75  | Round | 5.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 23H122F450DI1H1   |    | Genteq  | Special  | 1200  |     | 450  | 2     | Round | 5.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23H261F450BD1H1   |    | Genteq  | Special  | 260   |     | 450  | 1.375 | Round | 3.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F6929           |    | Genteq  | Standard | 12    |     | 400  | 1.5   | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| PB175E000A370DAS  | S  | PROLINE | Stock    | 17.5  |     | 370  | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23C132F250CD1H1   |    | Genteq  | Special  | 1300  |     | 250  | 1.75  | Round | 3.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 27L1021BX         | BX | Genteq  | Standard | 2     |     | 440  | 1.25  | Oval  | 1.56  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB350E000C240DA   |    | PROLINE | Standard | 35    |     | 240  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F5436BX         | BX | Genteq  | Standard | 6     |     | 440  | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23J142F350DH1H1   |    | Genteq  | Special  | 1400  |     | 350  | 2     | Round | 5.125 | Electrolytic             | 2000   | -40°C to 105°C |
| 23A763F075EI1H1   |    | Genteq  | Special  | 76000 |     | 75   | 2.5   | Round | 5.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| PB550E000S370DA   |    | PROLINE | Standard | 55    |     | 370  | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23D223F028BI1H1   |    | Genteq  | Special  | 22000 |     | 28   | 1.375 | Round | 5.625 | Electrolytic             | 1000   | -55°C to 85°C  |
| 23B114F060FI1H1   |    | Genteq  | Special  | 11000 | 0   | 60   | 3     | Round | 5.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 27L1002           |    | Genteq  | Standard | 20    |     | 370  | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23F322F150DF1H1   |    | Genteq  | Special  | 3200  |     | 150  | 2     | Round | 4.125 | Electrolytic             | 1000   | -55°C to 105°C |
| PB200E000S370CABX | BX | PROLINE | Standard | 20    |     | 370  | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23C173F075DD1H1   |    | Genteq  | Special  | 17000 |     | 75   | 2     | Round | 3.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| PB250Y050C370CABX | BX | PROLINE | Standard | 25    | 5   | 370  | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23F871F250CD1H1   |    | Genteq  | Special  | 870   |     | 250  | 1.75  | Round | 3.125 | Electrolytic             | 1000   | -55°C to 105°C |
| PB200Z050S440CABX | BX | PROLINE | Standard | 20    | 5   | 440  | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23M392F200DE1H1   |    | Genteq  | Special  | 3900  |     | 200  | 2     | Round | 3.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F6698           |    | Genteq  | Standard | 13    |     | 400  | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F6930BX         | BX | Genteq  | Standard | 10    |     | 580  | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 27L797            |    | Genteq  | Standard | 15    | 7.5 | 400  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F5729           |    | Genteq  | Standard | 50    | 5   | 440  | 2     | Oval  | 5.25  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23C802F200EI1H1   |    | Genteq  | Special  | 8000  |     | 200  | 2.5   | Round | 5.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23M992F300FJ1H1   |    | Genteq  | Special  | 9900  |     | 300  | 3     | Round | 5.875 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23F523F060EI1H1   |    | Genteq  | Special  | 52000 |     | 60   | 2.5   | Round | 5.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F6759RC         | RC | Genteq  | Standard | 24    |     | 330  | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F5914           |    | Genteq  | Standard | 32.5  |     | 370  | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9667           |    | Genteq  | Standard | 25    |     | 440  | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23J352F250FD1H1   |    | Genteq  | Special  | 3500  |     | 250  | 3     | Round | 3.125 | Electrolytic             | 2000   | -40°C to 105°C |
| 23C683F075FG1H1   |    | Genteq  | Special  | 68000 |     | 75   | 3     | Round | 4.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23A313F075DF1H1   |    | Genteq  | Special  | 31000 |     | 75   | 2     | Round | 4.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 97F9855BX         | BX | Genteq  | Standard | 40    | 7.5 | 370  | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23A183F080BI1H1   |    | Genteq  | Special  | 18000 |     | 80   | 1.375 | Round | 5.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 97F8077           |    | Genteq  | Special  | 5     |     | 440  | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23M541F350CB1H1   |    | Genteq  | Special  | 540   |     | 350  | 1.75  | Round | 2.125 | Electrolytic             | 2000   | -40°C to 85°C  |

|                   |    |         |          |        |     |     |       |       |       |                          |        |                |
|-------------------|----|---------|----------|--------|-----|-----|-------|-------|-------|--------------------------|--------|----------------|
| 23H581F450CE1H1   |    | Genteq  | Special  | 580    |     | 450 | 1.75  | Round | 3.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23B673F080F1H1    |    | Genteq  | Special  | 67000  |     | 80  | 3     | Round | 5.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23B124F050FJ1H1   |    | Genteq  | Special  | 120000 |     | 50  | 3     | Round | 5.875 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F8293BR         | BR | Genteq  | Standard | 48     |     | 330 | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23H742F250FG1H1   |    | Genteq  | Special  | 7400   |     | 250 | 3     | Round | 4.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23J851F300DC1H1   |    | Genteq  | Special  | 850    |     | 300 | 2     | Round | 2.625 | Electrolytic             | 2000   | -40°C to 105°C |
| 23F563F050EF1H1   |    | Genteq  | Special  | 56000  |     | 50  | 2.5   | Round | 4.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F8063S          | S  | Genteq  | Stock    | 20     |     | 370 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23F223F050BI1H1   |    | Genteq  | Special  | 22000  |     | 50  | 1.375 | Round | 5.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F9041           |    | Genteq  | Standard | 35     |     | 440 | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 41L7101           |    | Genteq  | Stock    | 1      |     | 700 | 0.81  | Round | 1.22  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 23B133F050CC1H1   |    | Genteq  | Special  | 13000  |     | 50  | 1.75  | Round | 2.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F8069S          | S  | Genteq  | Stock    | 50     |     | 370 | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23J541F300BD1H1   |    | Genteq  | Special  | 540    |     | 300 | 1.375 | Round | 3.125 | Electrolytic             | 2000   | -40°C to 105°C |
| 27L5538BX         | BX | Genteq  | Special  | 60     | 10  | 440 | 2     | Oval  | 5.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23A243F100DI1H1   |    | Genteq  | Special  | 24000  |     | 100 | 2     | Round | 5.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 97F5001           |    | Genteq  | Standard | 12.5   |     | 440 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23D123F035CC1H1   |    | Genteq  | Special  | 12000  |     | 35  | 1.75  | Round | 2.625 | Electrolytic             | 1000   | -55°C to 85°C  |
| 97F6885           |    | Genteq  | Standard | 36     | 12  | 280 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| PB550Z050T440EABX | BX | PROLINE | Standard | 55     | 5   | 440 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23C682F250FG1H1   |    | Genteq  | Special  | 6800   |     | 250 | 3     | Round | 4.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23A184F060FL1H1   |    | Genteq  | Special  | 180000 |     | 60  | 3     | Round | 8.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 23H162F400DI1H1   |    | Genteq  | Special  | 1600   |     | 400 | 2     | Round | 5.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23C353F075EE1H1   |    | Genteq  | Special  | 35000  |     | 75  | 2.5   | Round | 3.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23F393F080EI1H1   |    | Genteq  | Special  | 39000  |     | 80  | 2.5   | Round | 5.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F5710BX         | BX | Genteq  | Special  | 10     |     | 370 | 1.25  | Oval  | 2.62  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23C302F150CD1H1   |    | Genteq  | Special  | 3000   |     | 150 | 1.75  | Round | 3.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| PB150E000P370CABX | BX | PROLINE | Standard | 15     |     | 370 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| PB150E000A370CA   |    | PROLINE | Standard | 15     |     | 370 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23C212F200BI1H1   |    | Genteq  | Special  | 2100   |     | 200 | 1.375 | Round | 5.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23B343F060ED1H1   |    | Genteq  | Special  | 34000  |     | 60  | 2.5   | Round | 3.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F6644           |    | Genteq  | Special  | 45     |     | 300 | 1.75  | Oval  | 4.25  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F9631BX         | BX | Genteq  | Standard | 20     |     | 440 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F5706           |    | Genteq  | Standard | 6      |     | 370 | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23D383F016CE1H1   |    | Genteq  | Special  | 38000  |     | 16  | 1.75  | Round | 3.625 | Electrolytic             | 1000   | -55°C to 85°C  |
| PB500Z050S370DABX | BX | PROLINE | Standard | 50     | 5   | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F5339BX         | BX | Genteq  | Standard | 5      |     | 440 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23B124F050FI1H1   |    | Genteq  | Special  | 120000 |     | 50  | 3     | Round | 5.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| PB200Y075C370CA   |    | PROLINE | Standard | 20     | 7.5 | 370 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| PB400Z050T440CA   |    | PROLINE | Standard | 40     | 5   | 440 | 2.5   | Round | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 27L651            |    | Genteq  | Standard | 80     | 5   | 370 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23B253F080DH1H1   |    | Genteq  | Special  | 25000  |     | 80  | 2     | Round | 5.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 27L6016           |    | Genteq  | Special  | 8      |     | 660 | 1.25  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L7009           |    | Genteq  | Special  | 24     |     | 400 | 1.25  | Oval  | 3.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 100°C |
| 97F9012           |    | Genteq  | Standard | 70     |     | 370 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F5251BX         | BX | Genteq  | Standard | 70     |     | 440 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23F103F050BD1H1   |    | Genteq  | Special  | 10000  |     | 50  | 1.375 | Round | 3.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F9017           |    | Genteq  | Special  | 20     | 7.5 | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB350Y050C440EABX | BX | PROLINE | Standard | 35     | 5   | 440 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F8037BX         | BX | Genteq  | Standard | 25     |     | 240 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |

|                  |    |         |          |       |      |     |       |       |       |                          |       |                |
|------------------|----|---------|----------|-------|------|-----|-------|-------|-------|--------------------------|-------|----------------|
| 23F123F060BH1H1  |    | Genteq  | Special  | 12000 |      | 60  | 1.375 | Round | 5.125 | Electrolytic             | 1000  | -55°C to 105°C |
| 27L973           |    | Genteq  | Standard | 15    | 9    | 400 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F5504          |    | Genteq  | Special  | 4     |      | 370 | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F6863BX        | BX | Genteq  | Special  | 22.5  |      | 280 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23F193F060CG1H1  |    | Genteq  | Special  | 19000 |      | 60  | 1.75  | Round | 4.625 | Electrolytic             | 1000  | -55°C to 105°C |
| 23H871F250BD1H1  |    | Genteq  | Special  | 870   |      | 250 | 1.375 | Round | 3.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 97F9732BX        | BX | Genteq  | Standard | 25    | 7.5  | 440 | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F5707          |    | Genteq  | Special  | 7.5   |      | 370 | 1.25  | Oval  | 2.62  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F9015          |    | Genteq  | Special  | 15    | 10   | 370 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23F122F150DB1H1  |    | Genteq  | Special  | 1200  |      | 150 | 2     | Round | 2.125 | Electrolytic             | 1000  | -55°C to 105°C |
| 97F9849BX        | BX | Genteq  | Standard | 40    | 5    | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23M422F350EH1H1  |    | Genteq  | Special  | 4200  |      | 350 | 2.5   | Round | 5.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23C473F075EG1H1  |    | Genteq  | Special  | 47000 |      | 75  | 2.5   | Round | 4.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| 97F9831BX        | BX | Genteq  | Standard | 40    | 10   | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| PB300Y050C440DA  |    | PROLINE | Standard | 30    | 5    | 440 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23M701F400BG1H1  |    | Genteq  | Special  | 700   |      | 400 | 1.375 | Round | 4.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23D243F028CE1H1  |    | Genteq  | Special  | 24000 |      | 28  | 1.75  | Round | 3.625 | Electrolytic             | 1000  | -55°C to 85°C  |
| 97F8082          |    | Genteq  | Special  | 30    |      | 480 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23C501F200BB1H1  |    | Genteq  | Special  | 500   |      | 200 | 1.375 | Round | 2.125 | Electrolytic             | 1000  | -45°C to 95°C  |
| 97F6679BX        | BX | Genteq  | Special  | 24    |      | 480 | 2     | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23F263F080EF1H1  |    | Genteq  | Special  | 26000 |      | 80  | 2.5   | Round | 4.125 | Electrolytic             | 1000  | -55°C to 105°C |
| 23C892F075DB1H1  |    | Genteq  | Special  | 8900  |      | 75  | 2     | Round | 2.125 | Electrolytic             | 1000  | -45°C to 95°C  |
| 23C142F250BH1H1  |    | Genteq  | Special  | 1400  |      | 250 | 1.375 | Round | 5.125 | Electrolytic             | 1000  | -45°C to 95°C  |
| 23J881F200CB1H1  |    | Genteq  | Special  | 880   |      | 200 | 1.75  | Round | 2.125 | Electrolytic             | 2000  | -40°C to 105°C |
| 23A113F060CB1H1  |    | Genteq  | Special  | 11000 |      | 60  | 1.75  | Round | 2.125 | Electrolytic             | 1000  | -40°C to 85°C  |
| 27L200           |    | Genteq  | Special  | 90    |      | 370 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| PB050E000A440BAS | S  | PROLINE | Stock    | 5     |      | 440 | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| PB350E000C440DAS | S  | PROLINE | Stock    | 35    |      | 440 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F9088          |    | Genteq  | Special  | 35    |      | 440 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23A802F080CB1H1  |    | Genteq  | Special  | 8000  |      | 80  | 1.75  | Round | 2.125 | Electrolytic             | 1000  | -40°C to 85°C  |
| 97F5211          |    | Genteq  | Standard | 50    |      | 440 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F9815BX        | BX | Genteq  | Standard | 55    | 5    | 370 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F9780          |    | Genteq  | Standard | 40    | 10   | 440 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23C363F075DI1H1  |    | Genteq  | Special  | 36000 |      | 75  | 2     | Round | 5.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| 23B153F060BG1H1  |    | Genteq  | Special  | 15000 |      | 60  | 1.375 | Round | 4.625 | Electrolytic             | 3000  | -40°C to 85°C  |
| 23F133F100EF1H1  |    | Genteq  | Special  | 13000 |      | 100 | 2.5   | Round | 4.125 | Electrolytic             | 1000  | -55°C to 105°C |
| 97F6861BX        | BX | Genteq  | Standard | 20    |      | 280 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23C183F150FH1H1  |    | Genteq  | Special  | 18000 |      | 150 | 3     | Round | 5.125 | Electrolytic             | 1000  | -45°C to 95°C  |
| 27L541           |    | Genteq  | Standard | 14    | 10.5 | 330 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 27L382           |    | Genteq  | Standard | 8.5   | 3.5  | 280 | 1.75  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| PB175E000A440EA  |    | PROLINE | Standard | 17.5  |      | 440 | 1.25  | Oval  | 4.75  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F9883          |    | Genteq  | Standard | 45    | 7.5  | 440 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23M102F350DC1H1  |    | Genteq  | Special  | 1000  |      | 350 | 2     | Round | 2.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 97F9501BX        | BX | Genteq  | Standard | 2.5   |      | 370 | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F6516          |    | Genteq  | Standard | 22.5  |      | 280 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F9967BX        | BX | Genteq  | Standard | 20    | 10   | 370 | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F9694          |    | Genteq  | Standard | 15    | 5    | 440 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 27L551BX         | BX | Genteq  | Standard | 20    |      | 440 | 1.25  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23H561F300BC1H1  |    | Genteq  | Special  | 560   |      | 300 | 1.375 | Round | 2.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23C263F080ED1H1  |    | Genteq  | Special  | 26000 |      | 80  | 2.5   | Round | 3.125 | Electrolytic             | 1000  | -45°C to 95°C  |
| 23C462F100BD1H1  |    | Genteq  | Special  | 4600  |      | 100 | 1.375 | Round | 3.125 | Electrolytic             | 1000  | -45°C to 95°C  |

|                    |    |         |          |       |     |      |       |       |       |                          |        |                |
|--------------------|----|---------|----------|-------|-----|------|-------|-------|-------|--------------------------|--------|----------------|
| 23H481F350CB1H1    |    | Genteq  | Special  | 480   |     | 350  | 1.75  | Round | 2.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 27L514             |    | Genteq  | Standard | 60    |     | 370  | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 41L2100            |    | Genteq  | Stock    | 10    |     | 250  | 0.79  | Round | 1.65  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 23M302F200CE1H1    |    | Genteq  | Special  | 3000  |     | 200  | 1.75  | Round | 3.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23C172F200DC1H1    |    | Genteq  | Special  | 1700  |     | 200  | 2     | Round | 2.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23H282F300DH1H1    |    | Genteq  | Special  | 2800  |     | 300  | 2     | Round | 5.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| PB050E000P370CA    |    | PROLINE | Standard | 5     |     | 370  | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 42L2101            |    | Genteq  | Stock    | 1     |     | 1200 | 1.32  | Round | 1.65  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 97F9994            |    | Genteq  | Standard | 30    | 5   | 440  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB400Y075C370DAB X | BX | PROLINE | Standard | 40    | 7.5 | 370  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23C372F200ED1H1    |    | Genteq  | Special  | 3700  |     | 200  | 2.5   | Round | 3.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23F722F075DB1H1    |    | Genteq  | Special  | 7200  |     | 75   | 2     | Round | 2.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F9080BX          | BX | Genteq  | Standard | 12.5  |     | 440  | 1.25  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23B113F150FF1H1    |    | Genteq  | Special  | 11000 |     | 150  | 3     | Round | 4.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23B263F075ED1H1    |    | Genteq  | Special  | 26000 |     | 75   | 2.5   | Round | 3.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23M142F300CD1H1    |    | Genteq  | Special  | 1400  |     | 300  | 1.75  | Round | 3.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23C872F060BC1H1    |    | Genteq  | Special  | 8700  |     | 60   | 1.375 | Round | 2.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23F453F080FG1H1    |    | Genteq  | Special  | 45000 |     | 80   | 3     | Round | 4.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F5573            |    | Genteq  | Special  | 10    |     | 370  | 1.75  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23M192F350DF1H1    |    | Genteq  | Special  | 1900  |     | 350  | 2     | Round | 4.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F5222            |    | Genteq  | Special  | 30    |     | 440  | 2.5   | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB075E000P370CA    |    | PROLINE | Standard | 7.5   |     | 370  | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| PB100Y100C440CA    |    | PROLINE | Standard | 10    | 10  | 440  | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F6934            |    | Genteq  | Standard | 26    |     | 540  | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23C622F050BB1H1    |    | Genteq  | Special  | 6200  |     | 50   | 1.375 | Round | 2.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 27L801             |    | Genteq  | Standard | 80    | 7.5 | 440  | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6643RC          | RC | Genteq  | Special  | 30    |     | 370  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23F462F100BH1H1    |    | Genteq  | Special  | 4600  |     | 100  | 1.375 | Round | 5.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F9142            |    | Genteq  | Standard | 17.5  | 7.5 | 440  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23F413F060EG1H1    |    | Genteq  | Special  | 41000 |     | 60   | 2.5   | Round | 4.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 23A103F150EF1H1    |    | Genteq  | Special  | 10000 |     | 150  | 2.5   | Round | 4.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 23A263F100EF1H1    |    | Genteq  | Special  | 26000 |     | 100  | 2.5   | Round | 4.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 23C282F250DG1H1    |    | Genteq  | Special  | 2800  |     | 250  | 2     | Round | 4.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23B343F100FI1H1    |    | Genteq  | Special  | 34000 |     | 100  | 3     | Round | 5.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 27L567S            | S  | Genteq  | Stock    | 15    |     | 370  | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23B183F100EG1H1    |    | Genteq  | Special  | 18000 |     | 100  | 2.5   | Round | 4.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23B172F150DB1H1    |    | Genteq  | Special  | 1700  |     | 150  | 2     | Round | 2.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F9202            |    | Genteq  | Standard | 5     |     | 370  | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6880            |    | Genteq  | Standard | 20    | 12  | 280  | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23F511F150BB1H1    |    | Genteq  | Special  | 510   |     | 150  | 1.375 | Round | 2.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 42L4152            |    | Genteq  | Stock    | 0.15  |     | 3000 | 1.26  | Round | 1.65  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 97F6506BX          | BX | Genteq  | Standard | 14    |     | 330  | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F6951            |    | Genteq  | Standard | 22.5  |     | 540  | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F5115BX          | BX | Genteq  | Special  | 35    |     | 440  | 2     | Round | 4.25  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23A153F080DC1H1    |    | Genteq  | Special  | 15000 |     | 80   | 2     | Round | 2.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 27L6012            |    | Genteq  | Special  | 4     |     | 660  | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6866BX          | BX | Genteq  | Standard | 40    |     | 280  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| PB250Y100C370CA    |    | PROLINE | Standard | 25    | 10  | 370  | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23J122F200CC1H1    |    | Genteq  | Special  | 1200  |     | 200  | 1.75  | Round | 2.625 | Electrolytic             | 2000   | -40°C to 105°C |
| 97F9635            |    | Genteq  | Standard | 30    |     | 440  | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F8041            |    | Genteq  | Standard | 45    |     | 240  | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6515BX          | BX | Genteq  | Standard | 10    |     | 330  | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |

|                   |    |         |          |       |     |     |       |       |       |                          |        |                |
|-------------------|----|---------|----------|-------|-----|-----|-------|-------|-------|--------------------------|--------|----------------|
| PB300E000A370EAS  | S  | PROLINE | Stock    | 30    |     | 370 | 1.25  | Oval  | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23A113F150EG1H1   |    | Genteq  | Special  | 11000 |     | 150 | 2.5   | Round | 4.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 23M142F350CF1H1   |    | Genteq  | Special  | 1400  |     | 350 | 1.75  | Round | 4.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F5266           |    | Genteq  | Special  | 45    |     | 370 | 2.5   | Round | 3.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L571BX          | BX | Genteq  | Standard | 4     |     | 370 | 1.25  | Oval  | 1.56  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L204RR          | RR | Genteq  | Standard | 35    | 10  | 440 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23F123F100D1H1    |    | Genteq  | Special  | 12000 |     | 100 | 2     | Round | 5.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F6522RC         | RC | Genteq  | Standard | 24    |     | 280 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23B912F200FJ1H1   |    | Genteq  | Special  | 9100  |     | 200 | 3     | Round | 5.875 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23H952F250FI1H1   |    | Genteq  | Special  | 9500  |     | 250 | 3     | Round | 5.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F5222BX         | BX | Genteq  | Special  | 30    |     | 440 | 2.5   | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23F842F080DC1H1   |    | Genteq  | Special  | 8400  |     | 80  | 2     | Round | 2.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 27L1052BX         | BX | Genteq  | Standard | 55    |     | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23F732F250FL1H1   |    | Genteq  | Special  | 7300  |     | 250 | 3     | Round | 8.625 | Electrolytic             | 1000   | -55°C to 105°C |
| PB450Z050T440DABX | BX | PROLINE | Standard | 45    | 5   | 440 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F9526           |    | Genteq  | Standard | 15    | 7.5 | 370 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23B222F250DG1H1   |    | Genteq  | Special  | 2200  |     | 250 | 2     | Round | 4.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| PB450Z050S370DA   |    | PROLINE | Standard | 45    | 5   | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23A583F100FI1H1   |    | Genteq  | Special  | 58000 |     | 100 | 3     | Round | 5.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 97F8255           |    | Genteq  | Standard | 30    |     | 600 | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F5209BX         | BX | Genteq  | Standard | 45    |     | 440 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9011BX         | BX | Genteq  | Standard | 65    |     | 370 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23M133F200FG1H1   |    | Genteq  | Special  | 13000 |     | 200 | 3     | Round | 4.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F6686BX         | BX | Genteq  | Special  | 11.5  |     | 480 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| PB300Z100S440DA   |    | PROLINE | Standard | 30    | 10  | 440 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F5209           |    | Genteq  | Standard | 45    |     | 440 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23D253F016BF1H1   |    | Genteq  | Special  | 25000 |     | 16  | 1.375 | Round | 4.125 | Electrolytic             | 1000   | -55°C to 85°C  |
| PB500Y100D370EABX | BX | PROLINE | Standard | 50    | 10  | 370 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23D512F055BD1H1   |    | Genteq  | Special  | 5100  |     | 55  | 1.375 | Round | 3.125 | Electrolytic             | 1000   | -55°C to 85°C  |
| 23C103F075BF1H1   |    | Genteq  | Special  | 10000 |     | 75  | 1.375 | Round | 4.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23C252F200CF1H1   |    | Genteq  | Special  | 2500  |     | 200 | 1.75  | Round | 4.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 41L6100           |    | Genteq  | Stock    | 10    |     | 600 | 1.36  | Round | 2.17  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 23B282F100BD1H1   |    | Genteq  | Special  | 2800  |     | 100 | 1.375 | Round | 3.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F8244BX         | BX | Genteq  | Special  | 4     |     | 600 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23C372F200C11H1   |    | Genteq  | Special  | 3700  |     | 200 | 1.75  | Round | 5.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23C103F100B11H1   |    | Genteq  | Special  | 10000 |     | 100 | 1.375 | Round | 5.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23C213F075DE1H1   |    | Genteq  | Special  | 21000 |     | 75  | 2     | Round | 3.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23A443F075EE1H1   |    | Genteq  | Special  | 44000 |     | 75  | 2.5   | Round | 3.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 23F153F150FL1H1   |    | Genteq  | Special  | 15000 |     | 150 | 3     | Round | 8.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F6679           |    | Genteq  | Special  | 24    |     | 480 | 2     | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23F102F200BG1H1   |    | Genteq  | Special  | 1000  |     | 200 | 1.375 | Round | 4.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 23F243F080D11H1   |    | Genteq  | Special  | 24000 |     | 80  | 2     | Round | 5.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 23J232F350FE1H1   |    | Genteq  | Special  | 2300  |     | 350 | 3     | Round | 3.625 | Electrolytic             | 2000   | -40°C to 105°C |
| 27L1008BX         | BX | Genteq  | Standard | 60    | 10  | 370 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23F593F060FG1H1   |    | Genteq  | Special  | 59000 |     | 60  | 3     | Round | 4.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 27L973BX          | BX | Genteq  | Standard | 15    | 9   | 400 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 27L630            |    | Genteq  | Standard | 19    | 7   | 300 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F9123           |    | Genteq  | Special  | 17.5  |     | 370 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23A393F050CF1H1   |    | Genteq  | Special  | 39000 |     | 50  | 1.75  | Round | 4.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 97F9689           |    | Genteq  | Standard | 40    | 5   | 370 | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB050E000A370AABX | BX | PROLINE | Standard | 5     |     | 370 | 1.25  | Oval  | 1.56  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F6521BX         | BX | Genteq  | Standard | 28    |     | 330 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |

|                   |    |         |          |       |     |     |       |       |       |                          |        |                |
|-------------------|----|---------|----------|-------|-----|-----|-------|-------|-------|--------------------------|--------|----------------|
| 97F5474BX         | BX | Genteq  | Special  | 17.5  | 5   | 370 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9811           |    | Genteq  | Standard | 15    | 7.5 | 370 | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9967           |    | Genteq  | Standard | 20    | 10  | 370 | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F8293BX         | BX | Genteq  | Standard | 48    |     | 330 | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9061           |    | Genteq  | Standard | 55    | 10  | 440 | 2     | Oval  | 6.25  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23A512F150DE1H1   |    | Genteq  | Special  | 5100  |     | 150 | 2     | Round | 3.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 23C113F250FL1H1   |    | Genteq  | Special  | 11000 |     | 250 | 3     | Round | 8.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23B163F080DE1H1   |    | Genteq  | Special  | 16000 |     | 80  | 2     | Round | 3.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 27L868BX          | BX | Genteq  | Special  | 80    | 10  | 440 | 2     | Oval  | 5.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23J122F250BH1H1   |    | Genteq  | Special  | 1200  |     | 250 | 1.375 | Round | 5.125 | Electrolytic             | 2000   | -40°C to 105°C |
| 27L1024           |    | Genteq  | Standard | 5     |     | 440 | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23D363F007BE1H1   |    | Genteq  | Special  | 36000 |     | 7.5 | 1.375 | Round | 3.625 | Electrolytic             | 1000   | -55°C to 85°C  |
| 97F9002           |    | Genteq  | Standard | 10    |     | 370 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9337           |    | Genteq  | Standard | 55    |     | 370 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB350Z050S370DA   |    | PROLINE | Standard | 35    | 5   | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F9804BX         | BX | Genteq  | Standard | 25    |     | 370 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F5052BX         | BX | Genteq  | Special  | 20    |     | 370 | 1.75  | Round | 3.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23C543F075EH1H1   |    | Genteq  | Special  | 54000 |     | 75  | 2.5   | Round | 5.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F7075           |    | Genteq  | Special  | 90    |     | 370 | 2.5   | Round | 5.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB250Y100C440EABX | BX | PROLINE | Standard | 25    | 10  | 440 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F9036BX         | BX | Genteq  | Standard | 7.5   |     | 440 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23B193F060BI1H1   |    | Genteq  | Special  | 19000 |     | 60  | 1.375 | Round | 5.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23B113F150EI1H1   |    | Genteq  | Special  | 11000 |     | 150 | 2.5   | Round | 5.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F9170BX         | BX | Genteq  | Special  | 35    |     | 440 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23A292F150BG1H1   |    | Genteq  | Special  | 2900  |     | 150 | 1.375 | Round | 4.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 27L853BX          | BX | Genteq  | Standard | 24    | 10  | 400 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| PB250Z050S440DAS  | S  | PROLINE | Stock    | 25    | 5   | 440 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23C402F250EF1H1   |    | Genteq  | Special  | 4000  |     | 250 | 2.5   | Round | 4.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F6887BR         | BR | Genteq  | Standard | 38    | 17  | 280 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F8038S          | S  | Genteq  | Stock    | 30    |     | 240 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23B612F150DH1H1   |    | Genteq  | Special  | 6100  |     | 150 | 2     | Round | 5.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23C903F060FF1H1   |    | Genteq  | Special  | 90000 |     | 60  | 3     | Round | 4.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23F243F060CI1H1   |    | Genteq  | Special  | 24000 |     | 60  | 1.75  | Round | 5.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 23D662F035BC1H1   |    | Genteq  | Special  | 6600  |     | 35  | 1.375 | Round | 2.625 | Electrolytic             | 1000   | -55°C to 85°C  |
| 97F9991BX         | BX | Genteq  | Standard | 20    | 7.5 | 370 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 42L1221           |    | Genteq  | Stock    | 2.2   |     | 850 | 1.18  | Round | 1.65  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 97F9842BX         | BX | Genteq  | Standard | 35    | 5   | 440 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23F233F075CI1H1   |    | Genteq  | Special  | 23000 |     | 75  | 1.75  | Round | 5.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F9827           |    | Genteq  | Standard | 25    | 10  | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB700Z075T370EABX | BX | PROLINE | Standard | 70    | 7.5 | 370 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23A153F060DB1H1   |    | Genteq  | Special  | 15000 |     | 60  | 2     | Round | 2.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 23C543F050DG1H1   |    | Genteq  | Special  | 54000 |     | 50  | 2     | Round | 4.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23D732F055CC1H1   |    | Genteq  | Special  | 7300  |     | 55  | 1.75  | Round | 2.625 | Electrolytic             | 1000   | -55°C to 85°C  |
| 97F9838           |    | Genteq  | Standard | 40    | 5   | 440 | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23H891F200BC1H1   |    | Genteq  | Special  | 890   |     | 200 | 1.375 | Round | 2.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 27L6089BX         | BX | Genteq  | Special  | 18    |     | 660 | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6691BX         | BX | Genteq  | Standard | 24    | 4   | 280 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 27L797BX          | BX | Genteq  | Standard | 15    | 7.5 | 400 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 27L7000BR         | BR | Genteq  | Standard | 48    |     | 280 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 100°C |
| 23F122F150BE1H1   |    | Genteq  | Special  | 1200  |     | 150 | 1.375 | Round | 3.625 | Electrolytic             | 1000   | -55°C to 105°C |



|                   |    |         |          |       |     |     |       |       |       |                          |        |                |
|-------------------|----|---------|----------|-------|-----|-----|-------|-------|-------|--------------------------|--------|----------------|
| 97F6517BR         | BR | Genteq  | Standard | 15    |     | 400 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F5459           |    | Genteq  | Standard | 12.5  |     | 370 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23H392F200DG1H1   |    | Genteq  | Special  | 3900  |     | 200 | 2     | Round | 4.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23C442F150CF1H1   |    | Genteq  | Special  | 4400  |     | 150 | 1.75  | Round | 4.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23D453F020CG1H1   |    | Genteq  | Special  | 45000 |     | 20  | 1.75  | Round | 4.625 | Electrolytic             | 1000   | -55°C to 85°C  |
| 97F6883RC         | RC | Genteq  | Standard | 36    | 20  | 280 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| PB450E000C440EA   |    | PROLINE | Standard | 45    |     | 440 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F9030           |    | Genteq  | Special  | 50    | 10  | 370 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23A723F050EE1H1   |    | Genteq  | Special  | 72000 |     | 50  | 2.5   | Round | 3.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| PB600Z100T370EABX | BX | PROLINE | Standard | 60    | 10  | 370 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23C113F150EG1H1   |    | Genteq  | Special  | 11000 |     | 150 | 2.5   | Round | 4.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F6538           |    | Genteq  | Standard | 35    |     | 280 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23F233F080EE1H1   |    | Genteq  | Special  | 23000 |     | 80  | 2.5   | Round | 3.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F9595           |    | Genteq  | Standard | 6     |     | 370 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9816           |    | Genteq  | Standard | 60    | 5   | 370 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F5035           |    | Genteq  | Special  | 5     |     | 440 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L349            |    | Genteq  | Special  | 75    |     | 440 | 2.5   | Round | 5.25  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23H162F450FE1H1   |    | Genteq  | Special  | 1600  |     | 450 | 3     | Round | 3.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23B902F100DF1H1   |    | Genteq  | Special  | 9000  |     | 100 | 2     | Round | 4.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23F932F100ED1H1   |    | Genteq  | Special  | 9300  |     | 100 | 2.5   | Round | 3.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F6778BR         | BR | Genteq  | Standard | 45    |     | 330 | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23H232F200DD1H1   |    | Genteq  | Special  | 2300  |     | 200 | 2     | Round | 3.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23D842F020BB1H1   |    | Genteq  | Special  | 8400  |     | 20  | 1.375 | Round | 2.125 | Electrolytic             | 1000   | -55°C to 85°C  |
| 40L3201           |    | Genteq  | Stock    | 2     |     | 400 | 0.48  | Oval  | 1.25  | Dry-Axial Leaded         | 100000 | -55°C to 105°C |
| 97F8070           |    | Genteq  | Standard | 55    |     | 370 | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23F542F100CE1H1   |    | Genteq  | Special  | 5400  |     | 100 | 1.75  | Round | 3.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 23F102F250BI1H1   |    | Genteq  | Special  | 1000  |     | 250 | 1.375 | Round | 5.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 23C162F150CB1H1   |    | Genteq  | Special  | 1600  |     | 150 | 1.75  | Round | 2.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23B113F080BH1H1   |    | Genteq  | Special  | 11000 |     | 80  | 1.375 | Round | 5.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F5564BX         | BX | Genteq  | Standard | 8     |     | 370 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L114            |    | Genteq  | Standard | 70    | 7.5 | 440 | 2     | Oval  | 6.25  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23D402F055BC1H1   |    | Genteq  | Special  | 4000  |     | 55  | 1.375 | Round | 2.625 | Electrolytic             | 1000   | -55°C to 85°C  |
| 27L390            |    | Genteq  | Standard | 40    | 10  | 440 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23M742F250EH1H1   |    | Genteq  | Special  | 7400  |     | 250 | 2.5   | Round | 5.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F9016           |    | Genteq  | Special  | 20    | 5   | 370 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB350Z050T440CABX | BX | PROLINE | Standard | 35    | 5   | 440 | 2.5   | Round | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| PB350E000P370DABX | BX | PROLINE | Standard | 35    |     | 370 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F8066           |    | Genteq  | Standard | 35    |     | 370 | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23C103F100CE1H1   |    | Genteq  | Special  | 10000 |     | 100 | 1.75  | Round | 3.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F9003           |    | Genteq  | Standard | 12.5  |     | 370 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23H202F350DI1H1   |    | Genteq  | Special  | 2000  |     | 350 | 2     | Round | 5.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F5706BX         | BX | Genteq  | Standard | 6     |     | 370 | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23A463F060ED1H1   |    | Genteq  | Special  | 46000 |     | 60  | 2.5   | Round | 3.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 23A452F150CF1H1   |    | Genteq  | Special  | 4500  |     | 150 | 1.75  | Round | 4.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| PB350E000C240DAS  | S  | PROLINE | Stock    | 35    |     | 240 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| PB100E000P370CA   |    | PROLINE | Standard | 10    |     | 370 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| PB800Z100T370EA   |    | PROLINE | Standard | 80    | 10  | 370 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F8046           |    | Genteq  | Standard | 70    |     | 240 | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23M632F300FF1H1   |    | Genteq  | Special  | 6300  |     | 300 | 3     | Round | 4.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 42L1682           |    | Genteq  | Stock    | 0.68  |     | 850 | 0.81  | Round | 1.22  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 97F9510           |    | Genteq  | Special  | 30    | 3   | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |

|                   |    |         |          |       |     |      |       |       |       |                          |        |                |
|-------------------|----|---------|----------|-------|-----|------|-------|-------|-------|--------------------------|--------|----------------|
| 97F6846BX         | BX | Genteq  | Standard | 29    |     | 280  | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F6681           |    | Genteq  | Special  | 5     |     | 480  | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23H382F400F1H1    |    | Genteq  | Special  | 3800  |     | 400  | 3     | Round | 5.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| PB500E000P370EABX | BX | PROLINE | Standard | 50    |     | 370  | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23C833F050FE1H1   |    | Genteq  | Special  | 83000 |     | 50   | 3     | Round | 3.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23H112F300BG1H1   |    | Genteq  | Special  | 1100  |     | 300  | 1.375 | Round | 4.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| PB700Z050T440GABX | BX | PROLINE | Standard | 70    | 5   | 440  | 2.5   | Round | 5.25  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23F153F075CF1H1   |    | Genteq  | Special  | 15000 |     | 75   | 1.75  | Round | 4.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 42L4223           |    | Genteq  | Stock    | 0.022 |     | 3000 | 0.65  | Round | 1.22  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 97F5927BX         | BX | Genteq  | Standard | 70    | 7.5 | 440  | 2.5   | Round | 5.25  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6788BX         | BX | Genteq  | Standard | 2.5   |     | 330  | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F6886BR         | BR | Genteq  | Standard | 27    | 8   | 280  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F9851BX         | BX | Genteq  | Standard | 45    | 5   | 440  | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L413BX          | BX | Genteq  | Standard | 35    | 16  | 300  | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 27L558BX          | BX | Genteq  | Standard | 25    | 10  | 440  | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23M862F200EG1H1   |    | Genteq  | Special  | 8600  |     | 200  | 2.5   | Round | 4.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23J931F200DB1H1   |    | Genteq  | Special  | 930   |     | 200  | 2     | Round | 2.125 | Electrolytic             | 2000   | -40°C to 105°C |
| 97F9643           |    | Genteq  | Standard | 40    |     | 440  | 2.5   | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23B703F050FE1H1   |    | Genteq  | Special  | 70000 |     | 50   | 3     | Round | 3.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F6918BX         | BX | Genteq  | Special  | 28    |     | 480  | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 27L7003BX         | BX | Genteq  | Standard | 26    |     | 330  | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 100°C |
| 97F9970           |    | Genteq  | Standard | 50    | 5   | 370  | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23H232F400EH1H1   |    | Genteq  | Special  | 2300  |     | 400  | 2.5   | Round | 5.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F9608BX         | BX | Genteq  | Standard | 30    |     | 370  | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F8050BX         | BX | Genteq  | Standard | 90    |     | 240  | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23C322F150BH1H1   |    | Genteq  | Special  | 3200  |     | 150  | 1.375 | Round | 5.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23B771F250CC1H1   |    | Genteq  | Special  | 770   |     | 250  | 1.75  | Round | 2.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F6509BX         | BX | Genteq  | Standard | 38    |     | 280  | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F9073           |    | Genteq  | Special  | 40    |     | 370  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23F293F050DE1H1   |    | Genteq  | Special  | 29000 |     | 50   | 2     | Round | 3.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 23B353F100FJ1H1   |    | Genteq  | Special  | 35000 |     | 100  | 3     | Round | 5.875 | Electrolytic             | 3000   | -40°C to 85°C  |
| PB400E000P370DABX | BX | PROLINE | Standard | 40    |     | 370  | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23A293F050BH1H1   |    | Genteq  | Special  | 29000 |     | 50   | 1.375 | Round | 5.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| PB100E000A440CAS  | S  | PROLINE | Stock    | 10    |     | 440  | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23B472F250EI1H1   |    | Genteq  | Special  | 4700  |     | 250  | 2.5   | Round | 5.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23H852F250FH1H1   |    | Genteq  | Special  | 8500  |     | 250  | 3     | Round | 5.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23A323F080ED1H1   |    | Genteq  | Special  | 32000 |     | 80   | 2.5   | Round | 3.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 27L6023BX         | BX | Genteq  | Special  | 30    |     | 660  | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6948BX         | BX | Genteq  | Standard | 14.5  |     | 580  | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23H352F300FD1H1   |    | Genteq  | Special  | 3500  |     | 300  | 3     | Round | 3.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| PB300E000C440DABX | BX | PROLINE | Standard | 30    |     | 440  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F5913BX         | BX | Genteq  | Standard | 30    |     | 370  | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F5160           |    | Genteq  | Standard | 25    |     | 370  | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6504           |    | Genteq  | Standard | 15    |     | 330  | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 27L567            |    | Genteq  | Standard | 15    |     | 370  | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23F332F100CC1H1   |    | Genteq  | Special  | 3300  |     | 100  | 1.75  | Round | 2.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 42L2682           |    | Genteq  | Stock    | 0.68  |     | 1200 | 1.08  | Round | 1.65  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 97F8062           |    | Genteq  | Standard | 17.5  |     | 370  | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23A223F060CD1H1   |    | Genteq  | Special  | 22000 |     | 60   | 1.75  | Round | 3.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 97F5450           |    | Genteq  | Special  | 30    | 7.5 | 370  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |

|                   |    |         |          |       |     |     |       |       |       |                          |       |                |
|-------------------|----|---------|----------|-------|-----|-----|-------|-------|-------|--------------------------|-------|----------------|
| 97F6505BR         | BR | Genteq  | Standard | 17.5  |     | 330 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23F302F100BE1H1   |    | Genteq  | Special  | 3000  |     | 100 | 1.375 | Round | 3.625 | Electrolytic             | 1000  | -55°C to 105°C |
| 23B142F200BH1H1   |    | Genteq  | Special  | 1400  |     | 200 | 1.375 | Round | 5.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| 97F6769BX         | BX | Genteq  | Standard | 16    |     | 330 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23J222F200CF1H1   |    | Genteq  | Special  | 2200  |     | 200 | 1.75  | Round | 4.125 | Electrolytic             | 2000  | -40°C to 105°C |
| 97F9971BX         | BX | Genteq  | Standard | 50    | 7.5 | 370 | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| PB350Z075S440EA   |    | PROLINE | Standard | 35    | 7.5 | 440 | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F9739           |    | Genteq  | Standard | 40    | 5   | 440 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23H252F250CG1H1   |    | Genteq  | Special  | 2500  |     | 250 | 1.75  | Round | 4.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 97F5160BX         | BX | Genteq  | Standard | 25    |     | 370 | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F8052BX         | BX | Genteq  | Standard | 100   |     | 240 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23B703F080FJ1H1   |    | Genteq  | Special  | 70000 |     | 80  | 3     | Round | 5.875 | Electrolytic             | 3000  | -40°C to 85°C  |
| 23H931F400DE1H1   |    | Genteq  | Special  | 930   |     | 400 | 2     | Round | 3.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 97F5241BX         | BX | Genteq  | Standard | 65    |     | 440 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23J532F250EI1H1   |    | Genteq  | Special  | 5300  |     | 250 | 2.5   | Round | 5.625 | Electrolytic             | 2000  | -40°C to 105°C |
| 97F6862           |    | Genteq  | Standard | 20    |     | 280 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23D183F020BE1H1   |    | Genteq  | Special  | 18000 |     | 20  | 1.375 | Round | 3.625 | Electrolytic             | 1000  | -55°C to 85°C  |
| 23C413F060CH1H1   |    | Genteq  | Special  | 41000 |     | 60  | 1.75  | Round | 5.125 | Electrolytic             | 1000  | -45°C to 95°C  |
| 97F6758RC         | RC | Genteq  | Standard | 15    |     | 330 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| PB600Z075T370EA   |    | PROLINE | Standard | 60    | 7.5 | 370 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| PB300E000S370CABX | BX | PROLINE | Standard | 30    |     | 370 | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| PB250Y050C370CA   |    | PROLINE | Standard | 25    | 5   | 370 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23C253F060BI1H1   |    | Genteq  | Special  | 25000 |     | 60  | 1.375 | Round | 5.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| 97F6538BX         | BX | Genteq  | Standard | 35    |     | 280 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23M392F400FG1H1   |    | Genteq  | Special  | 3900  |     | 400 | 3     | Round | 4.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23C812F100DC1H1   |    | Genteq  | Special  | 8100  |     | 100 | 2     | Round | 2.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| PB300Z050S370CABX | BX | PROLINE | Standard | 30    | 5   | 370 | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23F582F250FI1H1   |    | Genteq  | Special  | 5800  |     | 250 | 3     | Round | 5.625 | Electrolytic             | 1000  | -55°C to 105°C |
| PB250Z050S370CA   |    | PROLINE | Standard | 25    | 5   | 370 | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F6948           |    | Genteq  | Standard | 14.5  |     | 580 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F9381BX         | BX | Genteq  | Standard | 35    |     | 440 | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23C163F100DF1H1   |    | Genteq  | Special  | 16000 |     | 100 | 2     | Round | 4.125 | Electrolytic             | 1000  | -45°C to 95°C  |
| 23B273F060CG1H1   |    | Genteq  | Special  | 27000 |     | 60  | 1.75  | Round | 4.625 | Electrolytic             | 3000  | -40°C to 85°C  |
| 23J312F300EG1H1   |    | Genteq  | Special  | 3100  |     | 300 | 2.5   | Round | 4.625 | Electrolytic             | 2000  | -40°C to 105°C |
| 97F6674RC         | RC | Genteq  | Special  | 12    |     | 480 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23C163F050CC1H1   |    | Genteq  | Special  | 16000 |     | 50  | 1.75  | Round | 2.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| 27L204BR          | BR | Genteq  | Standard | 35    | 10  | 440 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23C102F250BF1H1   |    | Genteq  | Special  | 1000  |     | 250 | 1.375 | Round | 4.125 | Electrolytic             | 1000  | -45°C to 95°C  |
| 23C233F050BH1H1   |    | Genteq  | Special  | 23000 |     | 50  | 1.375 | Round | 5.125 | Electrolytic             | 1000  | -45°C to 95°C  |
| PB500Z050T440HABX | BX | PROLINE | Standard | 50    | 5   | 440 | 2.5   | Round | 4.25  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F5368           |    | Genteq  | Special  | 35    | 5   | 440 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F9088BX         | BX | Genteq  | Special  | 35    |     | 440 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F8248BX         | BX | Genteq  | Standard | 8     |     | 600 | 1.25  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| PB800E000T440GABX | BX | PROLINE | Standard | 80    |     | 440 | 2.5   | Round | 5.75  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F6926BR         | BR | Genteq  | Standard | 26    |     | 400 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F6919BX         | BX | Genteq  | Standard | 16    |     | 540 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23F432F200FE1H1   |    | Genteq  | Special  | 4300  |     | 200 | 3     | Round | 3.625 | Electrolytic             | 1000  | -55°C to 105°C |
| 97F5522BX         | BX | Genteq  | Special  | 6     |     | 370 | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F6641BX         | BX | Genteq  | Special  | 52    |     | 170 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F9975BX         | BX | Genteq  | Standard | 20    | 5   | 440 | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |

|                   |    |         |          |       |     |      |       |       |       |                          |        |                |
|-------------------|----|---------|----------|-------|-----|------|-------|-------|-------|--------------------------|--------|----------------|
| 97F6709           |    | Genteq  | Special  | 14    |     | 330  | 1.5   | Oval  | 3.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 42L2121           |    | Genteq  | Stock    | 1.2   |     | 1200 | 1.14  | Round | 2.17  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 41L7151           |    | Genteq  | Stock    | 1.5   |     | 700  | 0.81  | Round | 1.65  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 97F9975           |    | Genteq  | Standard | 20    | 5   | 440  | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 41L4471           |    | Genteq  | Stock    | 4.7   |     | 400  | 0.83  | Round | 1.65  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 23F972F075BG1H1   |    | Genteq  | Special  | 9700  |     | 75   | 1.375 | Round | 4.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F9796           |    | Genteq  | Standard | 35    | 5   | 370  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 42L3472           |    | Genteq  | Stock    | 0.47  |     | 2000 | 1.32  | Round | 1.65  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 97F9623           |    | Genteq  | Standard | 50    |     | 370  | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6836           |    | Genteq  | Standard | 48    |     | 280  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F6659BX         | BX | Genteq  | Standard | 12    |     | 400  | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23F772F060BE1H1   |    | Genteq  | Special  | 7700  |     | 60   | 1.375 | Round | 3.625 | Electrolytic             | 1000   | -55°C to 105°C |
| PB350E000C370DA   |    | PROLINE | Standard | 35    |     | 370  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| PB550Z100T440EABX | BX | PROLINE | Standard | 55    | 10  | 440  | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23M182F400DH1H1   |    | Genteq  | Special  | 1800  |     | 400  | 2     | Round | 5.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| PB050E000A440BABX | BX | PROLINE | Standard | 5     |     | 440  | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23M142F450DH1H1   |    | Genteq  | Special  | 1400  |     | 450  | 2     | Round | 5.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F9850BX         | BX | Genteq  | Standard | 50    | 5   | 440  | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23C813F080F1H1    |    | Genteq  | Special  | 81000 |     | 80   | 3     | Round | 5.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23H172F200DC1H1   |    | Genteq  | Special  | 1700  |     | 200  | 2     | Round | 2.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| PB075E000A440CAS  | S  | PROLINE | Stock    | 7.5   |     | 440  | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23B743F060E1H1    |    | Genteq  | Special  | 74000 |     | 60   | 2.5   | Round | 5.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23B422F250EH1H1   |    | Genteq  | Special  | 4200  |     | 250  | 2.5   | Round | 5.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23H332F200DF1H1   |    | Genteq  | Special  | 3300  |     | 200  | 2     | Round | 4.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F8069           |    | Genteq  | Standard | 50    |     | 370  | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23F522F100B1H1    |    | Genteq  | Special  | 5200  |     | 100  | 1.375 | Round | 5.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 27L758            |    | Genteq  | Special  | 50    |     | 440  | 2     | Round | 5.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23D453F016CF1H1   |    | Genteq  | Special  | 45000 |     | 16   | 1.75  | Round | 4.125 | Electrolytic             | 1000   | -55°C to 85°C  |
| 97F5502BX         | BX | Genteq  | Standard | 2     |     | 370  | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23C193F075CF1H1   |    | Genteq  | Special  | 19000 |     | 75   | 1.75  | Round | 4.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F6708BX         | BX | Genteq  | Standard | 13    |     | 330  | 1.5   | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F6918RC         | RC | Genteq  | Special  | 28    |     | 480  | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23M163F200F1H1    |    | Genteq  | Special  | 16000 |     | 200  | 3     | Round | 5.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23H102F300BF1H1   |    | Genteq  | Special  | 1000  |     | 300  | 1.375 | Round | 4.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F9606           |    | Genteq  | Standard | 25    |     | 370  | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L880            |    | Genteq  | Standard | 45    | 5   | 370  | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F8242BX         | BX | Genteq  | Special  | 2.5   |     | 600  | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23A313F060CF1H1   |    | Genteq  | Special  | 31000 |     | 60   | 1.75  | Round | 4.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 23B243F075CH1H1   |    | Genteq  | Special  | 24000 |     | 75   | 1.75  | Round | 5.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23J182F200CE1H1   |    | Genteq  | Special  | 1800  |     | 200  | 1.75  | Round | 3.625 | Electrolytic             | 2000   | -40°C to 105°C |
| 23A633F080EH1H1   |    | Genteq  | Special  | 63000 |     | 80   | 2.5   | Round | 5.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 97F8250           |    | Genteq  | Standard | 12    |     | 600  | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23F393F050ED1H1   |    | Genteq  | Special  | 39000 |     | 50   | 2.5   | Round | 3.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 23H102F400CG1H1   |    | Genteq  | Special  | 1000  |     | 400  | 1.75  | Round | 4.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23M301F400BC1H1   |    | Genteq  | Special  | 300   |     | 400  | 1.375 | Round | 2.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23M162F200BE1H1   |    | Genteq  | Special  | 1600  |     | 200  | 1.375 | Round | 3.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23F503F060FF1H1   |    | Genteq  | Special  | 50000 |     | 60   | 3     | Round | 4.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F9982BX         | BX | Genteq  | Standard | 30    | 7.5 | 440  | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9992           |    | Genteq  | Standard | 15    | 7.5 | 440  | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6777BR         | BR | Genteq  | Special  | 35    |     | 330  | 1.5   | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F8047BX         | BX | Genteq  | Standard | 75    |     | 240  | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB060E000A370BAS  | S  | PROLINE | Stock    | 6     |     | 370  | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |

|                   |    |         |          |       |     |     |       |       |       |                          |       |                |
|-------------------|----|---------|----------|-------|-----|-----|-------|-------|-------|--------------------------|-------|----------------|
| 97F6873           |    | Genteq  | Standard | 24    |     | 280 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23F312F200DI1H1   |    | Genteq  | Special  | 3100  |     | 200 | 2     | Round | 5.625 | Electrolytic             | 1000  | -55°C to 105°C |
| 23H392F350FG1H1   |    | Genteq  | Special  | 3900  |     | 350 | 3     | Round | 4.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| PB350Z100T440DABX | BX | PROLINE | Standard | 35    | 10  | 440 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23A104F075FH1H1   |    | Genteq  | Special  | 10000 |     | 75  | 3     | Round | 5.125 | Electrolytic             | 1000  | -40°C to 85°C  |
| 23D183F016CB1H1   |    | Genteq  | Special  | 18000 |     | 16  | 1.75  | Round | 2.125 | Electrolytic             | 1000  | -55°C to 85°C  |
| 97F6621           |    | Genteq  | Standard | 15    |     | 400 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F6759BX         | BX | Genteq  | Standard | 24    |     | 330 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23C163F060CC1H1   |    | Genteq  | Special  | 16000 |     | 60  | 1.75  | Round | 2.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| 23B762F080CC1H1   |    | Genteq  | Special  | 7600  |     | 80  | 1.75  | Round | 2.625 | Electrolytic             | 3000  | -40°C to 85°C  |
| 23C273F060DD1H1   |    | Genteq  | Special  | 27000 |     | 60  | 2     | Round | 3.125 | Electrolytic             | 1000  | -45°C to 95°C  |
| PB450Y050C370DABX | BX | PROLINE | Standard | 45    | 5   | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F8061BX         | BX | Genteq  | Standard | 15    |     | 370 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 27L572S           | S  | Genteq  | Stock    | 12.5  |     | 370 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23H832F200EI1H1   |    | Genteq  | Special  | 8300  |     | 200 | 2.5   | Round | 5.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 97F5051BX         | BX | Genteq  | Standard | 17.5  |     | 370 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F8060S          | S  | Genteq  | Stock    | 12.5  |     | 370 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F9973           |    | Genteq  | Standard | 55    | 7.5 | 370 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 25L261BX          | BX | Genteq  | Standard | 80    | 10  | 370 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23A403F100EI1H1   |    | Genteq  | Special  | 40000 |     | 100 | 2.5   | Round | 5.625 | Electrolytic             | 1000  | -40°C to 85°C  |
| 23H103F200FH1H1   |    | Genteq  | Special  | 10000 |     | 200 | 3     | Round | 5.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23B701F250BE1H1   |    | Genteq  | Special  | 700   |     | 250 | 1.375 | Round | 3.625 | Electrolytic             | 3000  | -40°C to 85°C  |
| 97F6526           |    | Genteq  | Standard | 10    |     | 400 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 27L877            |    | Genteq  | Standard | 30    | 5   | 370 | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23B463F080EI1H1   |    | Genteq  | Special  | 46000 |     | 80  | 2.5   | Round | 5.625 | Electrolytic             | 3000  | -40°C to 85°C  |
| 97F5503BX         | BX | Genteq  | Standard | 3     |     | 370 | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 27L63             |    | Genteq  | Standard | 80    |     | 370 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F8037           |    | Genteq  | Standard | 25    |     | 240 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23A113F100CE1H1   |    | Genteq  | Special  | 11000 |     | 100 | 1.75  | Round | 3.625 | Electrolytic             | 1000  | -40°C to 85°C  |
| 23A114F075FI1H1   |    | Genteq  | Special  | 11000 |     | 75  | 3     | Round | 5.625 | Electrolytic             | 1000  | -40°C to 85°C  |
| 23C762F150DH1H1   |    | Genteq  | Special  | 7600  |     | 150 | 2     | Round | 5.125 | Electrolytic             | 1000  | -45°C to 95°C  |
| 97F5727BX         | BX | Genteq  | Special  | 25    | 15  | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F9617BX         | BX | Genteq  | Standard | 45    |     | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23D213F020CC1H1   |    | Genteq  | Special  | 21000 |     | 20  | 1.75  | Round | 2.625 | Electrolytic             | 1000  | -55°C to 85°C  |
| PB450Y100C370DABX | BX | PROLINE | Standard | 45    | 10  | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F6823S          | S  | Genteq  | Stock    | 28    |     | 280 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F9242           |    | Genteq  | Special  | 20    |     | 440 | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F5283BX         | BX | Genteq  | Special  | 30    |     | 370 | 2.5   | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23J132F400FD1H1   |    | Genteq  | Special  | 1300  |     | 400 | 3     | Round | 3.125 | Electrolytic             | 2000  | -40°C to 105°C |
| 27L945            |    | Genteq  | Standard | 45    |     | 440 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23A173F060BF1H1   |    | Genteq  | Special  | 17000 |     | 60  | 1.375 | Round | 4.125 | Electrolytic             | 1000  | -40°C to 85°C  |
| 23H952F200FG1H1   |    | Genteq  | Special  | 9500  |     | 200 | 3     | Round | 4.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 97F6504BX         | BX | Genteq  | Standard | 15    |     | 330 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 27L572            |    | Genteq  | Standard | 12.5  |     | 370 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23B102F150BC1H1   |    | Genteq  | Special  | 1000  |     | 150 | 1.375 | Round | 2.625 | Electrolytic             | 3000  | -40°C to 85°C  |
| 23B372F200DI1H1   |    | Genteq  | Special  | 3700  |     | 200 | 2     | Round | 5.625 | Electrolytic             | 3000  | -40°C to 85°C  |
| PB500E000P370EA   |    | PROLINE | Standard | 50    |     | 370 | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F6674           |    | Genteq  | Special  | 12    |     | 480 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F6538RC         | RC | Genteq  | Standard | 35    |     | 280 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |

|                   |    |         |          |            |     |     |       |       |       |                          |        |                |
|-------------------|----|---------|----------|------------|-----|-----|-------|-------|-------|--------------------------|--------|----------------|
| 97F9981BX         | BX | Genteq  | Standard | 30         | 5   | 440 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 41L2151           |    | Genteq  | Stock    | 1.5        |     | 250 | 0.39  | Round | 1.22  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 23C462F200EE1H1   |    | Genteq  | Special  | 4600       |     | 200 | 2.5   | Round | 3.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23M431F450BF1H1   |    | Genteq  | Special  | 430        |     | 450 | 1.375 | Round | 4.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23A194F050FJ1H1   |    | Genteq  | Special  | 19000<br>0 |     | 50  | 3     | Round | 5.875 | Electrolytic             | 1000   | -40°C to 85°C  |
| 97F9969           |    | Genteq  | Standard | 45         | 7.5 | 370 | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6682BR         | BR | Genteq  | Special  | 31.5       |     | 420 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 27L1051BX         | BX | Genteq  | Special  | 50         | 5   | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB200E000P440CAS  | S  | PROLINE | Stock    | 20         |     | 440 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23B381F200BB1H1   |    | Genteq  | Special  | 380        |     | 200 | 1.375 | Round | 2.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F9018BX         | BX | Genteq  | Standard | 20         | 10  | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23F782F150FF1H1   |    | Genteq  | Special  | 7800       |     | 150 | 3     | Round | 4.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F9025BX         | BX | Genteq  | Special  | 40         | 7.5 | 370 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23H641F400CD1H1   |    | Genteq  | Special  | 640        |     | 400 | 1.75  | Round | 3.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 42L1151           |    | Genteq  | Stock    | 1.5        |     | 850 | 0.96  | Round | 1.65  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 23C813F060FE1H1   |    | Genteq  | Special  | 81000      |     | 60  | 3     | Round | 3.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F6764           |    | Genteq  | Standard | 5          |     | 330 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23H452F200DH1H1   |    | Genteq  | Special  | 4500       |     | 200 | 2     | Round | 5.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23D323F016CD1H1   |    | Genteq  | Special  | 32000      |     | 16  | 1.75  | Round | 3.125 | Electrolytic             | 1000   | -55°C to 85°C  |
| 97F9849           |    | Genteq  | Standard | 40         | 5   | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB300Z100S370DA   |    | PROLINE | Standard | 30         | 10  | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F8054BX         | BX | Genteq  | Standard | 3          |     | 370 | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23A193F075BI1H1   |    | Genteq  | Special  | 19000      |     | 75  | 1.375 | Round | 5.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 23M112F300CC1H1   |    | Genteq  | Special  | 1100       |     | 300 | 1.75  | Round | 2.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F9982           |    | Genteq  | Standard | 30         | 7.5 | 440 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23J722F200FG1H1   |    | Genteq  | Special  | 7200       |     | 200 | 3     | Round | 4.625 | Electrolytic             | 2000   | -40°C to 105°C |
| 97F6517           |    | Genteq  | Standard | 15         |     | 400 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23B532F150CI1H1   |    | Genteq  | Special  | 5300       |     | 150 | 1.75  | Round | 5.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23C902F200FG1H1   |    | Genteq  | Special  | 9000       |     | 200 | 3     | Round | 4.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F8247           |    | Genteq  | Standard | 7          |     | 600 | 1.25  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23C113F050CB1H1   |    | Genteq  | Special  | 11000      |     | 50  | 1.75  | Round | 2.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23B263F075CI1H1   |    | Genteq  | Special  | 26000      |     | 75  | 1.75  | Round | 5.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F9614           |    | Genteq  | Standard | 40         |     | 370 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L402BX          | BX | Genteq  | Standard | 24         | 8   | 300 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F5520BX         | BX | Genteq  | Special  | 45         | 5   | 370 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23M752F200FD1H1   |    | Genteq  | Special  | 7500       |     | 200 | 3     | Round | 3.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23H102F300CC1H1   |    | Genteq  | Special  | 1000       |     | 300 | 1.75  | Round | 2.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23A592F100BE1H1   |    | Genteq  | Special  | 5900       |     | 100 | 1.375 | Round | 3.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| PB150Z075S440DABX | BX | PROLINE | Standard | 15         | 7.5 | 440 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23B102F250CD1H1   |    | Genteq  | Special  | 1000       |     | 250 | 1.75  | Round | 3.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23C382F075BB1H1   |    | Genteq  | Special  | 3800       |     | 75  | 1.375 | Round | 2.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| PB800Z075T370EABX | BX | PROLINE | Standard | 80         | 7.5 | 370 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 27L880BX          | BX | Genteq  | Standard | 45         | 5   | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB400E000P370DA   |    | PROLINE | Standard | 40         |     | 370 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23J132F200BG1H1   |    | Genteq  | Special  | 1300       |     | 200 | 1.375 | Round | 4.625 | Electrolytic             | 2000   | -40°C to 105°C |
| 23M532F350FG1H1   |    | Genteq  | Special  | 5300       |     | 350 | 3     | Round | 4.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 25L2005           |    | Genteq  | Special  | 35         |     | 370 | 1.25  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L567BX          | BX | Genteq  | Standard | 15         |     | 370 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F8057BX         | BX | Genteq  | Standard | 6          |     | 370 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6692           |    | Genteq  | Special  | 8.5        |     | 480 | 1.5   | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23J661F350BH1H1   |    | Genteq  | Special  | 660        |     | 350 | 1.375 | Round | 5.125 | Electrolytic             | 2000   | -40°C to 105°C |
| 23M292F250DE1H1   |    | Genteq  | Special  | 2900       |     | 250 | 2     | Round | 3.625 | Electrolytic             | 2000   | -40°C to 85°C  |

|                    |    |         |          |       |     |     |       |       |       |                          |        |                |
|--------------------|----|---------|----------|-------|-----|-----|-------|-------|-------|--------------------------|--------|----------------|
| 97F9510BX          | BX | Genteq  | Special  | 30    | 3   | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB200E000P440CA    |    | PROLINE | Standard | 20    |     | 440 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 41L6501            |    | Genteq  | Stock    | 5     |     | 600 | 1.12  | Round | 1.65  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 97F8258            |    | Genteq  | Standard | 45    |     | 600 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB450Y100C370DA    |    | PROLINE | Standard | 45    | 10  | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23H562F200FD1H1    |    | Genteq  | Special  | 5600  |     | 200 | 3     | Round | 3.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23F123F080CF1H1    |    | Genteq  | Special  | 12000 |     | 80  | 1.75  | Round | 4.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 23H512F250EG1H1    |    | Genteq  | Special  | 5100  |     | 250 | 2.5   | Round | 4.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 27L865RR           | RR | Genteq  | Standard | 15    | 6   | 400 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23A473F060C11H1    |    | Genteq  | Special  | 47000 |     | 60  | 1.75  | Round | 5.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 23J292F200ED1H1    |    | Genteq  | Special  | 2900  |     | 200 | 2.5   | Round | 3.125 | Electrolytic             | 2000   | -40°C to 105°C |
| 23M202F450EG1H1    |    | Genteq  | Special  | 2000  |     | 450 | 2.5   | Round | 4.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23J122F200BF1H1    |    | Genteq  | Special  | 1200  |     | 200 | 1.375 | Round | 4.125 | Electrolytic             | 2000   | -40°C to 105°C |
| 97F9617            |    | Genteq  | Standard | 45    |     | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9796BX          | BX | Genteq  | Standard | 35    | 5   | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L114BX           | BX | Genteq  | Standard | 70    | 7.5 | 440 | 2     | Oval  | 6.25  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23A373F060CG1H1    |    | Genteq  | Special  | 37000 |     | 60  | 1.75  | Round | 4.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 27L531BX           | BX | Genteq  | Standard | 16    | 10  | 400 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F8060            |    | Genteq  | Standard | 12.5  |     | 370 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23M291F450CB1H1    |    | Genteq  | Special  | 290   |     | 450 | 1.75  | Round | 2.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23M641F450B11H1    |    | Genteq  | Special  | 640   |     | 450 | 1.375 | Round | 5.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23H632F250FF1H1    |    | Genteq  | Special  | 6300  |     | 250 | 3     | Round | 4.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F9462BX          | BX | Genteq  | Standard | 40    | 10  | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB050E000P440CAB X | BX | PROLINE | Standard | 5     |     | 440 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F8040S           | S  | Genteq  | Stock    | 40    |     | 240 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23J671F350CD1H1    |    | Genteq  | Special  | 670   |     | 350 | 1.75  | Round | 3.125 | Electrolytic             | 2000   | -40°C to 105°C |
| 23C122F200DB1H1    |    | Genteq  | Special  | 1200  |     | 200 | 2     | Round | 2.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23A843F060FE1H1    |    | Genteq  | Special  | 84000 |     | 60  | 3     | Round | 3.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 97F6506RC          | RC | Genteq  | Standard | 14    |     | 330 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| PB400Z050S370DABX  | BX | PROLINE | Standard | 40    | 5   | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| PB300Y100C370DAB X | BX | PROLINE | Standard | 30    | 10  | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 40L3681            |    | Genteq  | Stock    | 6.8   |     | 400 | 0.67  | Oval  | 2.25  | Dry-Axial Leaded         | 100000 | -55°C to 105°C |
| 27L570             |    | Genteq  | Standard | 5     |     | 370 | 1.25  | Oval  | 1.56  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L7004BX          | BX | Genteq  | Special  | 24    |     | 360 | 1.25  | Oval  | 3.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 100°C |
| 97F8084BX          | BX | Genteq  | Standard | 60    |     | 440 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F8058BX          | BX | Genteq  | Standard | 7.5   |     | 370 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L1045BX          | BX | Genteq  | Standard | 60    |     | 370 | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L7001BX          | BX | Genteq  | Standard | 10    |     | 400 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 100°C |
| 97F6867BX          | BX | Genteq  | Standard | 52    |     | 280 | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F5513            |    | Genteq  | Special  | 4     |     | 440 | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9803BX          | BX | Genteq  | Standard | 25    | 5   | 370 | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB550Z100T370DA    |    | PROLINE | Standard | 55    | 10  | 370 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23F772F060DB1H1    |    | Genteq  | Special  | 7700  |     | 60  | 2     | Round | 2.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F9971            |    | Genteq  | Standard | 50    | 7.5 | 370 | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6857            |    | Genteq  | Standard | 8     |     | 280 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F9115BX          | BX | Genteq  | Special  | 45    |     | 370 | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23F153F080CG1H1    |    | Genteq  | Special  | 15000 |     | 80  | 1.75  | Round | 4.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 27L990             |    | Genteq  | Special  | 35    |     | 240 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F8067BX          | BX | Genteq  | Standard | 40    |     | 370 | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |

|                   |    |         |          |       |     |     |       |       |       |                          |        |                |
|-------------------|----|---------|----------|-------|-----|-----|-------|-------|-------|--------------------------|--------|----------------|
| 23F283F060DH1H1   |    | Genteq  | Special  | 28000 |     | 60  | 2     | Round | 5.125 | Electrolytic             | 1000   | -55°C to 105°C |
| PB450Y050C440EA   |    | PROLINE | Standard | 45    | 5   | 440 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F8064BX         | BX | Genteq  | Standard | 25    |     | 370 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB350E000C240DABX | BX | PROLINE | Standard | 35    |     | 240 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23A123F080BF1H1   |    | Genteq  | Special  | 12000 |     | 80  | 1.375 | Round | 4.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 97F5502           |    | Genteq  | Standard | 2     |     | 370 | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L53BX           | BX | Genteq  | Standard | 26    | 15  | 400 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23B912F050CB1H1   |    | Genteq  | Special  | 9100  |     | 50  | 1.75  | Round | 2.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23H102F450DH1H1   |    | Genteq  | Special  | 1000  |     | 450 | 2     | Round | 5.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 41L2501           |    | Genteq  | Stock    | 5     |     | 250 | 0.67  | Round | 1.22  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 97F6950BR         | BR | Genteq  | Standard | 12    | 12  | 400 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23D153F020BD1H1   |    | Genteq  | Special  | 15000 |     | 20  | 1.375 | Round | 3.125 | Electrolytic             | 1000   | -55°C to 85°C  |
| 97F6678           |    | Genteq  | Special  | 4.5   |     | 480 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23M551F400CC1H1   |    | Genteq  | Special  | 550   |     | 400 | 1.75  | Round | 2.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F6858RC         | RC | Genteq  | Standard | 10    |     | 280 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23M132F300DC1H1   |    | Genteq  | Special  | 1300  |     | 300 | 2     | Round | 2.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23A603F100FJ1H1   |    | Genteq  | Special  | 60000 |     | 100 | 3     | Round | 5.875 | Electrolytic             | 1000   | -40°C to 85°C  |
| 97F9264BX         | BX | Genteq  | Standard | 20    |     | 410 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB250Z075S440DA   |    | PROLINE | Standard | 25    | 7.5 | 440 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23B122F250BI1H1   |    | Genteq  | Special  | 1200  |     | 250 | 1.375 | Round | 5.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23B301F250BB1H1   |    | Genteq  | Special  | 300   |     | 250 | 1.375 | Round | 2.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| PB200E000P240CA   |    | PROLINE | Standard | 20    |     | 240 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 41L4150           |    | Genteq  | Stock    | 15    |     | 400 | 1.26  | Round | 2.17  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 97F6531BX         | BX | Genteq  | Standard | 7     |     | 330 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F9612BX         | BX | Genteq  | Standard | 35    |     | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB350Y050C370DABX | BX | PROLINE | Standard | 35    | 5   | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23F562F100DD1H1   |    | Genteq  | Special  | 5600  |     | 100 | 2     | Round | 3.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F6530BR         | BR | Genteq  | Standard | 40    |     | 280 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23D153F028BF1H1   |    | Genteq  | Special  | 15000 |     | 28  | 1.375 | Round | 4.125 | Electrolytic             | 1000   | -55°C to 85°C  |
| 23F682F080BF1H1   |    | Genteq  | Special  | 6800  |     | 80  | 1.375 | Round | 4.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F6533           |    | Genteq  | Standard | 30    |     | 280 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F6758BR         | BR | Genteq  | Standard | 15    |     | 330 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F9024BX         | BX | Genteq  | Special  | 40    | 5   | 370 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23F183F080ED1H1   |    | Genteq  | Special  | 18000 |     | 80  | 2.5   | Round | 3.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 23B114F060FJ1H1   |    | Genteq  | Special  | 11000 |     | 60  | 3     | Round | 5.875 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F8245           |    | Genteq  | Standard | 5     |     | 600 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB800Z100T370EABX | BX | PROLINE | Standard | 80    | 10  | 370 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23F173F050BG1H1   |    | Genteq  | Special  | 17000 |     | 50  | 1.375 | Round | 4.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F9840           |    | Genteq  | Standard | 40    | 5   | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB150Y050C370CA   |    | PROLINE | Standard | 15    | 5   | 370 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23H412F200CI1H1   |    | Genteq  | Special  | 4100  |     | 200 | 1.75  | Round | 5.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23F742F200FI1H1   |    | Genteq  | Special  | 7400  |     | 200 | 3     | Round | 5.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 23C273F080DG1H1   |    | Genteq  | Special  | 27000 |     | 80  | 2     | Round | 4.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23M232F450EH1H1   |    | Genteq  | Special  | 2300  |     | 450 | 2.5   | Round | 5.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| PB500E000T440DA   |    | PROLINE | Standard | 50    |     | 440 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23C453F060ED1H1   |    | Genteq  | Special  | 45000 |     | 60  | 2.5   | Round | 3.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 41L6471           |    | Genteq  | Stock    | 4.7   |     | 600 | 1.08  | Round | 1.65  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| PB350Z100S370DABX | BX | PROLINE | Standard | 35    | 10  | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F6934RC         | RC | Genteq  | Standard | 26    |     | 540 | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F6540BX         | BX | Genteq  | Standard | 45    |     | 280 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F6824           |    | Genteq  | Standard | 28    |     | 280 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |



|                    |    |         |          |       |     |     |       |       |       |                          |       |                |
|--------------------|----|---------|----------|-------|-----|-----|-------|-------|-------|--------------------------|-------|----------------|
| 23D493F007BG1H1    |    | Genteq  | Special  | 49000 |     | 7.5 | 1.375 | Round | 4.625 | Electrolytic             | 1000  | -55°C to 85°C  |
| 97F6755S           | S  | Genteq  | Stock    | 26    |     | 330 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| PB450Z075S370DA    |    | PROLINE | Standard | 45    | 7.5 | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F5300BX          | BX | Genteq  | Standard | 10    |     | 440 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 27L402RC           | RC | Genteq  | Standard | 24    | 8   | 300 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F7075BX          | BX | Genteq  | Special  | 90    |     | 370 | 2.5   | Round | 5.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 27L378BX           | BX | Genteq  | Standard | 45    | 10  | 440 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F6675BX          | BX | Genteq  | Special  | 16    |     | 480 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23A223F150FJ1H1    |    | Genteq  | Special  | 22000 |     | 150 | 3     | Round | 5.875 | Electrolytic             | 1000  | -40°C to 85°C  |
| 23B242F150DC1H1    |    | Genteq  | Special  | 2400  |     | 150 | 2     | Round | 2.625 | Electrolytic             | 3000  | -40°C to 85°C  |
| 23H222F250CF1H1    |    | Genteq  | Special  | 2200  |     | 250 | 1.75  | Round | 4.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| PB250Z050S440DA    |    | PROLINE | Standard | 25    | 5   | 440 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 27L727BX           | BX | Genteq  | Standard | 45    | 19  | 300 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F8051BX          | BX | Genteq  | Standard | 95    |     | 240 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23D193F035CE1H1    |    | Genteq  | Special  | 19000 |     | 35  | 1.75  | Round | 3.625 | Electrolytic             | 1000  | -55°C to 85°C  |
| 23J381F350CB1H1    |    | Genteq  | Special  | 380   |     | 350 | 1.75  | Round | 2.125 | Electrolytic             | 2000  | -40°C to 105°C |
| 97F9011S           | S  | Genteq  | Stock    | 65    |     | 370 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23B302F150CE1H1    |    | Genteq  | Special  | 3000  |     | 150 | 1.75  | Round | 3.625 | Electrolytic             | 3000  | -40°C to 85°C  |
| 23M652F250EG1H1    |    | Genteq  | Special  | 6500  |     | 250 | 2.5   | Round | 4.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 97F9743            |    | Genteq  | Standard | 17.5  |     | 370 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F6890BX          | BX | Genteq  | Standard | 18    | 10  | 280 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23A392F150CE1H1    |    | Genteq  | Special  | 3900  |     | 150 | 1.75  | Round | 3.625 | Electrolytic             | 1000  | -40°C to 85°C  |
| PB700E000T440EABX  | BX | PROLINE | Standard | 70    |     | 440 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F5437            |    | Genteq  | Standard | 3     |     | 440 | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23C172F250DD1H1    |    | Genteq  | Special  | 1700  |     | 250 | 2     | Round | 3.125 | Electrolytic             | 1000  | -45°C to 95°C  |
| 23C763F060EG1H1    |    | Genteq  | Special  | 76000 |     | 60  | 2.5   | Round | 4.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| PB450E000C440EAS   | S  | PROLINE | Stock    | 45    |     | 440 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 27L801BX           | BX | Genteq  | Standard | 80    | 7.5 | 440 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23A173F150FG1H1    |    | Genteq  | Special  | 17000 |     | 150 | 3     | Round | 4.625 | Electrolytic             | 1000  | -40°C to 85°C  |
| 23H152F400EE1H1    |    | Genteq  | Special  | 1500  |     | 400 | 2.5   | Round | 3.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23M152F300BH1H1    |    | Genteq  | Special  | 1500  |     | 300 | 1.375 | Round | 5.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| PB100E000P370CAB X | BX | PROLINE | Standard | 10    |     | 370 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F5401BX          | BX | Genteq  | Special  | 45    | 5   | 440 | 2     | Oval  | 5.25  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23A503F075EF1H1    |    | Genteq  | Special  | 50000 |     | 75  | 2.5   | Round | 4.125 | Electrolytic             | 1000  | -40°C to 85°C  |
| PB450E000S370DAB X | BX | PROLINE | Standard | 45    |     | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23J562F200EH1H1    |    | Genteq  | Special  | 5600  |     | 200 | 2.5   | Round | 5.125 | Electrolytic             | 2000  | -40°C to 105°C |
| 23J541F400BH1H1    |    | Genteq  | Special  | 540   |     | 400 | 1.375 | Round | 5.625 | Electrolytic             | 2000  | -40°C to 105°C |
| 23M242F300CG1H1    |    | Genteq  | Special  | 2400  |     | 300 | 1.75  | Round | 4.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 27L1054            |    | Genteq  | Standard | 20    |     | 440 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F8253            |    | Genteq  | Standard | 20    |     | 600 | 1.5   | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F9804            |    | Genteq  | Standard | 25    |     | 370 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23C662F100BF1H1    |    | Genteq  | Special  | 6600  |     | 100 | 1.375 | Round | 4.125 | Electrolytic             | 1000  | -45°C to 95°C  |
| 97F6526BX          | BX | Genteq  | Standard | 10    |     | 400 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F6824BX          | BX | Genteq  | Standard | 28    |     | 280 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23D623F007B11H1    |    | Genteq  | Special  | 62000 |     | 7.5 | 1.375 | Round | 5.625 | Electrolytic             | 1000  | -55°C to 85°C  |
| 97F6927RC          | RC | Genteq  | Special  | 11.5  | 3   | 400 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23D903F007CG1H1    |    | Genteq  | Special  | 90000 |     | 7.5 | 1.75  | Round | 4.625 | Electrolytic             | 1000  | -55°C to 85°C  |
| 97F6862BX          | BX | Genteq  | Standard | 20    |     | 280 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F6881RC          | RC | Genteq  | Standard | 42    | 14  | 280 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 27L427             |    | Genteq  | Standard | 15    | 10  | 400 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |

|                    |    |         |          |       |     |     |       |       |       |                          |        |                |
|--------------------|----|---------|----------|-------|-----|-----|-------|-------|-------|--------------------------|--------|----------------|
| 97F5276            |    | Genteq  | Standard | 60    |     | 370 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23A383F100FF1H1    |    | Genteq  | Special  | 38000 |     | 100 | 3     | Round | 4.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| PB600E000S370DAB X | BX | PROLINE | Standard | 60    |     | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F6952BX          | BX | Genteq  | Standard | 36    |     | 540 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23B202F250CH1H1    |    | Genteq  | Special  | 2000  |     | 250 | 1.75  | Round | 5.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| PB350Z075S370DA    |    | PROLINE | Standard | 35    | 7.5 | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23D952F055BH1H1    |    | Genteq  | Special  | 9500  |     | 55  | 1.375 | Round | 5.125 | Electrolytic             | 1000   | -55°C to 85°C  |
| PB400E000S440EA    |    | PROLINE | Standard | 40    |     | 440 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| PB800E000T440GA    |    | PROLINE | Standard | 80    |     | 440 | 2.5   | Round | 5.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23B132F200DC1H1    |    | Genteq  | Special  | 1300  |     | 200 | 2     | Round | 2.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F9839            |    | Genteq  | Standard | 55    | 5   | 440 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L6014BX          | BX | Genteq  | Special  | 6     |     | 660 | 1.25  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23A783F060EG1H1    |    | Genteq  | Special  | 78000 |     | 60  | 2.5   | Round | 4.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 97F9965BX          | BX | Genteq  | Standard | 15    | 10  | 370 | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F8241BX          | BX | Genteq  | Special  | 2     |     | 600 | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23F223F060CH1H1    |    | Genteq  | Special  | 22000 |     | 60  | 1.75  | Round | 5.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 23A703F080EI1H1    |    | Genteq  | Special  | 70000 |     | 80  | 2.5   | Round | 5.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 23H142F250BG1H1    |    | Genteq  | Special  | 1400  |     | 250 | 1.375 | Round | 4.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 27L589BX           | BX | Genteq  | Standard | 10    | 5   | 400 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| PB030E000A440AAS   | S  | PROLINE | Stock    | 3     |     | 440 | 1.25  | Oval  | 1.56  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23F192F250CI1H1    |    | Genteq  | Special  | 1900  |     | 250 | 1.75  | Round | 5.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 23B473F075FE1H1    |    | Genteq  | Special  | 47000 |     | 75  | 3     | Round | 3.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F6887            |    | Genteq  | Standard | 38    | 17  | 280 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23F233F050DD1H1    |    | Genteq  | Special  | 23000 |     | 50  | 2     | Round | 3.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 23J342F300FE1H1    |    | Genteq  | Special  | 3400  |     | 300 | 3     | Round | 3.625 | Electrolytic             | 2000   | -40°C to 105°C |
| 97F9829BX          | BX | Genteq  | Standard | 35    | 7.5 | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6805BX          | BX | Genteq  | Standard | 10    |     | 280 | 1.5   | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23J392F350F1H1     |    | Genteq  | Special  | 3900  |     | 350 | 3     | Round | 5.625 | Electrolytic             | 2000   | -40°C to 105°C |
| 23C523F060DH1H1    |    | Genteq  | Special  | 52000 |     | 60  | 2     | Round | 5.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F8045            |    | Genteq  | Standard | 65    |     | 240 | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23D323F035CI1H1    |    | Genteq  | Special  | 32000 |     | 35  | 3     | Round | 8.625 | Electrolytic             | 1000   | -55°C to 85°C  |
| PB100E000P440CAB X | BX | PROLINE | Standard | 10    |     | 440 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| PB450Z050S370DABX  | BX | PROLINE | Standard | 45    | 5   | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F8043BX          | BX | Genteq  | Standard | 55    |     | 240 | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23H172F400FD1H1    |    | Genteq  | Special  | 1700  |     | 400 | 3     | Round | 3.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 40L3100            |    | Genteq  | Stock    | 10    |     | 400 | 0.7   | Oval  | 2.25  | Dry-Axial Leaded         | 100000 | -55°C to 105°C |
| 23C902F080CC1H1    |    | Genteq  | Special  | 9000  |     | 80  | 1.75  | Round | 2.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23J751F350BI1H1    |    | Genteq  | Special  | 750   |     | 350 | 1.375 | Round | 5.625 | Electrolytic             | 2000   | -40°C to 105°C |
| 23M151F450BB1H1    |    | Genteq  | Special  | 150   |     | 450 | 1.375 | Round | 2.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 27L7002BX          | BX | Genteq  | Special  | 14    |     | 330 | 1.75  | Oval  | 3.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 100°C |
| 23F362F250EH1H1    |    | Genteq  | Special  | 3600  |     | 250 | 2.5   | Round | 5.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 25L501             |    | Genteq  | Standard | 40    |     | 440 | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L6015BX          | BX | Genteq  | Special  | 7     |     | 660 | 1.25  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9815            |    | Genteq  | Standard | 55    | 5   | 370 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6884RC          | RC | Genteq  | Standard | 33    | 15  | 280 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23B502F075BC1H1    |    | Genteq  | Special  | 5000  |     | 75  | 1.375 | Round | 2.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23C662F080BD1H1    |    | Genteq  | Special  | 6600  |     | 80  | 1.375 | Round | 3.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23H352F300EF1H1    |    | Genteq  | Special  | 3500  |     | 300 | 2.5   | Round | 4.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23M522F200CI1H1    |    | Genteq  | Special  | 5200  |     | 200 | 1.75  | Round | 5.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23C213F050CD1H1    |    | Genteq  | Special  | 21000 |     | 50  | 1.75  | Round | 3.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F8264BX          | BX | Genteq  | Standard | 45    |     | 600 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23C443F080EG1H1    |    | Genteq  | Special  | 44000 |     | 80  | 2.5   | Round | 4.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23B92F080DB1H1     |    | Genteq  | Special  | 6900  |     | 80  | 2     | Round | 2.125 | Electrolytic             | 3000   | -40°C to 85°C  |

|                   |    |         |          |            |     |     |       |       |       |                          |        |                |
|-------------------|----|---------|----------|------------|-----|-----|-------|-------|-------|--------------------------|--------|----------------|
| 23F393F050C1H1    |    | Genteq  | Special  | 39000      |     | 50  | 1.75  | Round | 5.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F6865           |    | Genteq  | Standard | 35         |     | 280 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23J291F400DB1H1   |    | Genteq  | Special  | 290        |     | 400 | 2     | Round | 2.125 | Electrolytic             | 2000   | -40°C to 105°C |
| 97F6658           |    | Genteq  | Standard | 18         |     | 400 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F9152BX         | BX | Genteq  | Standard | 40         |     | 440 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23B713F050EH1H1   |    | Genteq  | Special  | 71000      |     | 50  | 2.5   | Round | 5.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F6865BR         | BR | Genteq  | Standard | 35         |     | 280 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F6864           |    | Genteq  | Standard | 24         |     | 280 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23C502F250FE1H1   |    | Genteq  | Special  | 5000       |     | 250 | 3     | Round | 3.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23B153F075CE1H1   |    | Genteq  | Special  | 15000      |     | 75  | 1.75  | Round | 3.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23M122F450DG1H1   |    | Genteq  | Special  | 1200       |     | 450 | 2     | Round | 4.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23F302F075BB1H1   |    | Genteq  | Special  | 3000       |     | 75  | 1.375 | Round | 2.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 23F193F080DG1H1   |    | Genteq  | Special  | 19000      |     | 80  | 2     | Round | 4.625 | Electrolytic             | 1000   | -55°C to 105°C |
| PB3502075S370DABX | BX | PROLINE | Standard | 35         | 7.5 | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23C122F150BC1H1   |    | Genteq  | Special  | 1200       |     | 150 | 1.375 | Round | 2.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23B163F100FD1H1   |    | Genteq  | Special  | 16000      |     | 100 | 3     | Round | 3.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| PB040E000P370CA   |    | PROLINE | Standard | 4          |     | 370 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F9632BX         | BX | Genteq  | Standard | 25         |     | 440 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23D433F007CC1H1   |    | Genteq  | Special  | 43000      |     | 7.5 | 1.75  | Round | 2.625 | Electrolytic             | 1000   | -55°C to 85°C  |
| 97F6873BX         | BX | Genteq  | Standard | 24         |     | 280 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F6534           |    | Genteq  | Special  | 28         |     | 170 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F9010BX         | BX | Genteq  | Standard | 55         |     | 370 | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6759S          | S  | Genteq  | Stock    | 24         |     | 330 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23F691F250BF1H1   |    | Genteq  | Special  | 690        |     | 250 | 1.375 | Round | 4.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 23C343F060DE1H1   |    | Genteq  | Special  | 34000      |     | 60  | 2     | Round | 3.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 25L6252BR         | BR | Genteq  | Standard | 7          | 3   | 400 | 1.75  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23H851F300BE1H1   |    | Genteq  | Special  | 850        |     | 300 | 1.375 | Round | 3.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23M502F250DI1H1   |    | Genteq  | Special  | 5000       |     | 250 | 2     | Round | 5.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23F123F050DB1H1   |    | Genteq  | Special  | 12000      |     | 50  | 2     | Round | 2.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 23C134F050FH1H1   |    | Genteq  | Special  | 13000<br>0 |     | 50  | 3     | Round | 5.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23C282F250C1H1    |    | Genteq  | Special  | 2800       |     | 250 | 1.75  | Round | 5.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 27L987BX          | BX | Genteq  | Standard | 3          |     | 370 | 1.25  | Oval  | 1.56  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23B283F080DI1H1   |    | Genteq  | Special  | 28000      |     | 80  | 2     | Round | 5.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| PB2502050S440DABX | BX | PROLINE | Standard | 25         | 5   | 440 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 41L4251           |    | Genteq  | Stock    | 2.5        |     | 400 | 0.73  | Round | 1.22  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 97F9639           |    | Genteq  | Standard | 35         |     | 440 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23M901F450DE1H1   |    | Genteq  | Special  | 900        |     | 450 | 2     | Round | 3.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F6926           |    | Genteq  | Standard | 26         |     | 400 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23B123F075DC1H1   |    | Genteq  | Special  | 12000      |     | 75  | 2     | Round | 2.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 27L6023           |    | Genteq  | Special  | 30         |     | 660 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23J222F200DE1H1   |    | Genteq  | Special  | 2200       |     | 200 | 2     | Round | 3.625 | Electrolytic             | 2000   | -40°C to 105°C |
| 23J252F200DF1H1   |    | Genteq  | Special  | 2500       |     | 200 | 2     | Round | 4.125 | Electrolytic             | 2000   | -40°C to 105°C |
| 41L4201           |    | Genteq  | Stock    | 2          |     | 400 | 0.65  | Round | 1.22  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| PB060E000A370BA   |    | PROLINE | Standard | 6          |     | 370 | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23A543F060DH1H1   |    | Genteq  | Special  | 54000      |     | 60  | 2     | Round | 5.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 25L6252RR         | RR | Genteq  | Standard | 7          | 3   | 400 | 1.75  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| PB6002075T370EABX | BX | PROLINE | Standard | 60         | 7.5 | 370 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F6823           |    | Genteq  | Standard | 28         |     | 280 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F6764RC         | RC | Genteq  | Standard | 5          |     | 330 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 27L827BR          | BR | Genteq  | Standard | 18         | 10  | 330 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23M612F400FL1H1   |    | Genteq  | Special  | 6100       |     | 400 | 3     | Round | 8.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F9018           |    | Genteq  | Standard | 20         | 10  | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |

|                    |    |         |          |       |     |      |       |       |       |                          |        |                |
|--------------------|----|---------|----------|-------|-----|------|-------|-------|-------|--------------------------|--------|----------------|
| 97F6854BR          | BR | Genteq  | Standard | 34    |     | 280  | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F6660            |    | Genteq  | Standard | 12    |     | 400  | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F5513BX          | BX | Genteq  | Special  | 4     |     | 440  | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23B652F150EE1H1    |    | Genteq  | Special  | 6500  |     | 150  | 2.5   | Round | 3.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23M692F250FE1H1    |    | Genteq  | Special  | 6900  |     | 250  | 3     | Round | 3.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 41L7401            |    | Genteq  | Stock    | 4     |     | 700  | 1.3   | Round | 1.65  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 97F6918            |    | Genteq  | Special  | 28    |     | 480  | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23F942F100C1H1     |    | Genteq  | Special  | 9400  |     | 100  | 1.75  | Round | 5.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 40L3472            |    | Genteq  | Stock    | 0.47  |     | 400  | 0.28  | Oval  | 1.25  | Dry-Axial Leaded         | 100000 | -55°C to 105°C |
| 23B402F200EF1H1    |    | Genteq  | Special  | 4000  |     | 200  | 2.5   | Round | 4.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F6872BR          | BR | Genteq  | Standard | 48    |     | 280  | 2     | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23B443F075EG1H1    |    | Genteq  | Special  | 44000 |     | 75   | 2.5   | Round | 4.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 42L4102            |    | Genteq  | Stock    | 0.1   |     | 3000 | 1.04  | Round | 1.65  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 27L630BX           | BX | Genteq  | Standard | 19    | 7   | 300  | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23F222F200CH1H1    |    | Genteq  | Special  | 2200  |     | 200  | 1.75  | Round | 5.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F6853            |    | Genteq  | Special  | 36    | 12  | 280  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F6951BX          | BX | Genteq  | Standard | 22.5  |     | 540  | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23M232F350DG1H1    |    | Genteq  | Special  | 2300  |     | 350  | 2     | Round | 4.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23C212F150DB1H1    |    | Genteq  | Special  | 2100  |     | 150  | 2     | Round | 2.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23M501F250BB1H1    |    | Genteq  | Special  | 500   |     | 250  | 1.375 | Round | 2.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23J481F400CD1H1    |    | Genteq  | Special  | 480   |     | 400  | 1.75  | Round | 3.125 | Electrolytic             | 2000   | -40°C to 105°C |
| 42L1152            |    | Genteq  | Stock    | 0.15  |     | 850  | 0.39  | Round | 1.22  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 23M102F250BD1H1    |    | Genteq  | Special  | 1000  |     | 250  | 1.375 | Round | 3.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F6681BX          | BX | Genteq  | Special  | 5     |     | 480  | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F5388BX          | BX | Genteq  | Standard | 12.5  |     | 440  | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L92              |    | Genteq  | Special  | 80    | 7.5 | 440  | 2     | Oval  | 5.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L695S            | S  | Genteq  | Stock    | 7.5   |     | 440  | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23M123F250F1H1     |    | Genteq  | Special  | 12000 |     | 250  | 3     | Round | 5.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F9621BX          | BX | Genteq  | Standard | 50    |     | 370  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9248            |    | Genteq  | Special  | 3.75  |     | 370  | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6868            |    | Genteq  | Standard | 26    |     | 280  | 1.5   | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| PB350E000S370CA    |    | PROLINE | Standard | 35    |     | 370  | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F9615BX          | BX | Genteq  | Standard | 40    |     | 370  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L862BX           | BX | Genteq  | Standard | 35    | 24  | 400  | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23F852F060CC1H1    |    | Genteq  | Special  | 8500  |     | 60   | 1.75  | Round | 2.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 23C273F050CE1H1    |    | Genteq  | Special  | 27000 |     | 50   | 1.75  | Round | 3.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 27L600             |    | Genteq  | Standard | 39    | 13  | 330  | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23M113F250FH1H1    |    | Genteq  | Special  | 11000 |     | 250  | 3     | Round | 5.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F9635BX          | BX | Genteq  | Standard | 30    |     | 440  | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6661            |    | Genteq  | Standard | 14    |     | 400  | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 27L573BR           | BR | Genteq  | Standard | 40    | 15  | 280  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F9802            |    | Genteq  | Standard | 50    |     | 370  | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F8053S           | S  | Genteq  | Stock    | 120   |     | 240  | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB400Y075C440EAB X | BX | PROLINE | Standard | 40    | 7.5 | 440  | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23J791F300CC1H1    |    | Genteq  | Special  | 790   |     | 300  | 1.75  | Round | 2.625 | Electrolytic             | 2000   | -40°C to 105°C |
| 27L533             |    | Genteq  | Standard | 30    | 10  | 370  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23C263F060CE1H1    |    | Genteq  | Special  | 26000 |     | 60   | 1.75  | Round | 3.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 27L33              |    | Genteq  | Standard | 25    | 5   | 440  | 2.5   | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23M152F450DI1H1    |    | Genteq  | Special  | 1500  |     | 450  | 2     | Round | 5.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F6658BX          | BX | Genteq  | Standard | 18    |     | 400  | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |

|                    |    |         |          |       |     |     |       |       |       |                          |        |                |
|--------------------|----|---------|----------|-------|-----|-----|-------|-------|-------|--------------------------|--------|----------------|
| 97F6919RC          | RC | Genteq  | Standard | 16    |     | 540 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 27L591RR           | RR | Genteq  | Standard | 35    | 15  | 300 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23J921F400ED1H1    |    | Genteq  | Special  | 920   |     | 400 | 2.5   | Round | 3.125 | Electrolytic             | 2000   | -40°C to 105°C |
| 23B223F080DG1H1    |    | Genteq  | Special  | 22000 |     | 80  | 2     | Round | 4.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23M442F300FD1H1    |    | Genteq  | Special  | 4400  |     | 300 | 3     | Round | 3.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F6715            |    | Genteq  | Standard | 19    |     | 330 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F9730            |    | Genteq  | Standard | 25    | 5   | 440 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6603BX          | BX | Genteq  | Special  | 24    |     | 400 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F5051            |    | Genteq  | Standard | 17.5  |     | 370 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6521BR          | BR | Genteq  | Standard | 28    |     | 330 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F9491BX          | BX | Genteq  | Standard | 30    |     | 370 | 1.25  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23A222F150BE1H1    |    | Genteq  | Special  | 2200  |     | 150 | 1.375 | Round | 3.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 23J182F300ED1H1    |    | Genteq  | Special  | 1800  |     | 300 | 2.5   | Round | 3.125 | Electrolytic             | 2000   | -40°C to 105°C |
| PB250E000P370CA    |    | PROLINE | Standard | 25    |     | 370 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23H332F350FF1H1    |    | Genteq  | Special  | 3300  |     | 350 | 3     | Round | 4.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23B172F200DD1H1    |    | Genteq  | Special  | 1700  |     | 200 | 2     | Round | 3.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| PB600Z050T440EABX  | BX | PROLINE | Standard | 60    | 5   | 440 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F9090BX          | BX | Genteq  | Standard | 40    |     | 440 | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23J152F250CE1H1    |    | Genteq  | Special  | 1500  |     | 250 | 1.75  | Round | 3.625 | Electrolytic             | 2000   | -40°C to 105°C |
| 23J102F400DH1H1    |    | Genteq  | Special  | 1000  |     | 400 | 2     | Round | 5.125 | Electrolytic             | 2000   | -40°C to 105°C |
| PB150E000P440CAB X | BX | PROLINE | Standard | 15    |     | 440 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F6868BX          | BX | Genteq  | Standard | 26    |     | 280 | 1.5   | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F9204            |    | Genteq  | Standard | 7.5   |     | 370 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23J342F200DH1H1    |    | Genteq  | Special  | 3400  |     | 200 | 2     | Round | 5.125 | Electrolytic             | 2000   | -40°C to 105°C |
| 23F272F250FD1H1    |    | Genteq  | Special  | 2700  |     | 250 | 3     | Round | 3.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 23M192F200BF1H1    |    | Genteq  | Special  | 1900  |     | 200 | 1.375 | Round | 4.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F5320BX          | BX | Genteq  | Standard | 50    |     | 440 | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L6018            |    | Genteq  | Special  | 12    |     | 660 | 1.5   | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L556BX           | BX | Genteq  | Standard | 70    | 7.5 | 370 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9619BX          | BX | Genteq  | Standard | 45    |     | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F5300            |    | Genteq  | Standard | 10    |     | 440 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F7903BX          | BX | Genteq  | Standard | 2     |     | 440 | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6951RC          | RC | Genteq  | Standard | 22.5  |     | 540 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23B472F150CH1H1    |    | Genteq  | Special  | 4700  |     | 150 | 1.75  | Round | 5.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F8047            |    | Genteq  | Standard | 75    |     | 240 | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9677BX          | BX | Genteq  | Standard | 25    | 7.5 | 370 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23D113F055CE1H1    |    | Genteq  | Special  | 11000 |     | 55  | 1.75  | Round | 3.625 | Electrolytic             | 1000   | -55°C to 85°C  |
| 97F9611BX          | BX | Genteq  | Standard | 35    |     | 370 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23F881F200BF1H1    |    | Genteq  | Special  | 880   |     | 200 | 1.375 | Round | 4.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F6946RC          | RC | Genteq  | Standard | 21    |     | 580 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23C143F200FL1H1    |    | Genteq  | Special  | 14000 |     | 200 | 3     | Round | 8.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F8257            |    | Genteq  | Standard | 40    |     | 600 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23F392F250FF1H1    |    | Genteq  | Special  | 3900  |     | 250 | 3     | Round | 4.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 23M452F250DH1H1    |    | Genteq  | Special  | 4500  |     | 250 | 2     | Round | 5.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23A273F100FD1H1    |    | Genteq  | Special  | 27000 |     | 100 | 3     | Round | 3.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 97F9995BX          | BX | Genteq  | Standard | 30    | 7.5 | 440 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 42L1332            |    | Genteq  | Stock    | 0.33  |     | 850 | 0.57  | Round | 1.22  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| PB175E000A440EABX  | BX | PROLINE | Standard | 17.5  |     | 440 | 1.25  | Oval  | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| PB250Y100C440EA    |    | PROLINE | Standard | 25    | 10  | 440 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F9803            |    | Genteq  | Standard | 25    | 5   | 370 | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |

|                   |    |         |          |        |     |     |       |       |       |                          |        |                |
|-------------------|----|---------|----------|--------|-----|-----|-------|-------|-------|--------------------------|--------|----------------|
| 23J822F200FH1H1   |    | Genteq  | Special  | 8200   |     | 200 | 3     | Round | 5.125 | Electrolytic             | 2000   | -40°C to 105°C |
| 23M152F400ED1H1   |    | Genteq  | Special  | 1500   |     | 400 | 2.5   | Round | 3.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23M102F250CB1H1   |    | Genteq  | Special  | 1000   |     | 250 | 1.75  | Round | 2.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23C114F075FL1H1   |    | Genteq  | Special  | 110000 |     | 75  | 3     | Round | 8.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F9892           |    | Genteq  | Standard | 35     | 7.5 | 440 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9817BX         | BX | Genteq  | Standard | 60     | 7.5 | 370 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23A683F080FF1H1   |    | Genteq  | Special  | 68000  |     | 80  | 3     | Round | 4.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 97F9444           |    | Genteq  | Standard | 15     |     | 370 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9698           |    | Genteq  | Special  | 25     | 4   | 440 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 41L2250           |    | Genteq  | Stock    | 25     |     | 250 | 1.24  | Round | 1.65  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 23F783F060FJ1H1   |    | Genteq  | Special  | 78000  |     | 60  | 3     | Round | 5.875 | Electrolytic             | 1000   | -55°C to 105°C |
| 23B153F150FH1H1   |    | Genteq  | Special  | 15000  |     | 150 | 3     | Round | 5.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| PB800E000T370EABX | BX | PROLINE | Standard | 80     |     | 370 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23F483F050EE1H1   |    | Genteq  | Special  | 48000  |     | 50  | 2.5   | Round | 3.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 23J182F250DE1H1   |    | Genteq  | Special  | 1800   |     | 250 | 2     | Round | 3.625 | Electrolytic             | 2000   | -40°C to 105°C |
| 23B143F050BF1H1   |    | Genteq  | Special  | 14000  |     | 50  | 1.375 | Round | 4.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23H372F250EE1H1   |    | Genteq  | Special  | 3700   |     | 250 | 2.5   | Round | 3.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23F862F080CD1H1   |    | Genteq  | Special  | 8600   |     | 80  | 1.75  | Round | 3.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 23F892F060BF1H1   |    | Genteq  | Special  | 8900   |     | 60  | 1.375 | Round | 4.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 23F842F100CH1H1   |    | Genteq  | Special  | 8400   |     | 100 | 1.75  | Round | 5.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 23J102F250CC1H1   |    | Genteq  | Special  | 1000   |     | 250 | 1.75  | Round | 2.625 | Electrolytic             | 2000   | -40°C to 105°C |
| 97F6763BR         | BR | Genteq  | Standard | 10     |     | 330 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23A912F100BH1H1   |    | Genteq  | Special  | 9100   |     | 100 | 1.375 | Round | 5.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 23D163F035BH1H1   |    | Genteq  | Special  | 16000  |     | 35  | 1.375 | Round | 5.125 | Electrolytic             | 1000   | -55°C to 85°C  |
| PB450Y075D440EABX | BX | PROLINE | Standard | 45     | 7.5 | 440 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23D323F028CG1H1   |    | Genteq  | Special  | 32000  |     | 28  | 1.75  | Round | 4.625 | Electrolytic             | 1000   | -55°C to 85°C  |
| 23M182F300CE1H1   |    | Genteq  | Special  | 1800   |     | 300 | 1.75  | Round | 3.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F9694BX         | BX | Genteq  | Standard | 15     | 5   | 440 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6677BX         | BX | Genteq  | Special  | 4      |     | 480 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F9201BX         | BX | Genteq  | Standard | 4      |     | 370 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23F323F075EF1H1   |    | Genteq  | Special  | 32000  |     | 75  | 2.5   | Round | 4.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 23B313F080FD1H1   |    | Genteq  | Special  | 31000  |     | 80  | 3     | Round | 3.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F8293RC         | RC | Genteq  | Standard | 48     |     | 330 | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9001           |    | Genteq  | Standard | 7.5    |     | 370 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23B134F060FL1H1   |    | Genteq  | Special  | 130000 |     | 60  | 3     | Round | 8.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23F303F100FJ1H1   |    | Genteq  | Special  | 30000  |     | 100 | 3     | Round | 5.875 | Electrolytic             | 1000   | -55°C to 105°C |
| 23B222F200CG1H1   |    | Genteq  | Special  | 2200   |     | 200 | 1.75  | Round | 4.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F5704BX         | BX | Genteq  | Standard | 4      |     | 370 | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23H182F250DD1H1   |    | Genteq  | Special  | 1800   |     | 250 | 2     | Round | 3.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23C632F200EG1H1   |    | Genteq  | Special  | 6300   |     | 200 | 2.5   | Round | 4.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 27L866            |    | Genteq  | Standard | 70     | 10  | 440 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F8090BX         | BX | Genteq  | Standard | 20     |     | 240 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F8249BX         | BX | Genteq  | Standard | 10     |     | 600 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F8067           |    | Genteq  | Standard | 40     |     | 370 | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23C243F075DF1H1   |    | Genteq  | Special  | 24000  |     | 75  | 2     | Round | 4.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 41L4401           |    | Genteq  | Stock    | 4      |     | 400 | 0.77  | Round | 1.22  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 23H152F450EG1H1   |    | Genteq  | Special  | 1500   |     | 450 | 2.5   | Round | 4.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 42L1251           |    | Genteq  | Stock    | 2.5    |     | 850 | 1.24  | Round | 1.65  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 97F5159BX         | BX | Genteq  | Standard | 40     |     | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L569            |    | Genteq  | Special  | 50     | 5   | 440 | 2.5   | Round | 4.25  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F5054BX         | BX | Genteq  | Standard | 30     |     | 370 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9675           |    | Genteq  | Standard | 25     | 5   | 370 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 25L502            |    | Genteq  | Standard | 35     |     | 440 | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |

|                   |    |         |          |        |     |     |       |       |       |                          |       |                |
|-------------------|----|---------|----------|--------|-----|-----|-------|-------|-------|--------------------------|-------|----------------|
| 97F6643           |    | Genteq  | Special  | 30     |     | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F9882BX         | BX | Genteq  | Standard | 40     | 7.5 | 440 | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23M122F450CI1H1   |    | Genteq  | Special  | 1200   |     | 450 | 1.75  | Round | 5.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23F323F075FD1H1   |    | Genteq  | Special  | 32000  |     | 75  | 3     | Round | 3.125 | Electrolytic             | 1000  | -55°C to 105°C |
| 23J182F350EF1H1   |    | Genteq  | Special  | 1800   |     | 350 | 2.5   | Round | 4.125 | Electrolytic             | 2000  | -40°C to 105°C |
| 23J871F400CH1H1   |    | Genteq  | Special  | 870    |     | 400 | 1.75  | Round | 5.125 | Electrolytic             | 2000  | -40°C to 105°C |
| 97F9530           |    | Genteq  | Standard | 2.5    |     | 440 | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F9040           |    | Genteq  | Standard | 25     |     | 440 | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F9848BX         | BX | Genteq  | Standard | 35     | 5   | 440 | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23B123F050BE1H1   |    | Genteq  | Special  | 12000  |     | 50  | 1.375 | Round | 3.625 | Electrolytic             | 3000  | -40°C to 85°C  |
| 23A412F150DD1H1   |    | Genteq  | Special  | 4100   |     | 150 | 2     | Round | 3.125 | Electrolytic             | 1000  | -40°C to 85°C  |
| 23H812F200FF1H1   |    | Genteq  | Special  | 8100   |     | 200 | 3     | Round | 4.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23F113F080DD1H1   |    | Genteq  | Special  | 11000  |     | 80  | 2     | Round | 3.125 | Electrolytic             | 1000  | -55°C to 105°C |
| 27L204            |    | Genteq  | Standard | 35     | 10  | 440 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23B102F200BF1H1   |    | Genteq  | Special  | 1000   |     | 200 | 1.375 | Round | 4.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| 97F9602S          | S  | Genteq  | Stock    | 20     |     | 370 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F6744           |    | Genteq  | Special  | 12.5   |     | 330 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F6885RR         | RR | Genteq  | Standard | 36     | 12  | 280 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F5063           |    | Genteq  | Special  | 17.5   |     | 370 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23A113F075DB1H1   |    | Genteq  | Special  | 11000  |     | 75  | 2     | Round | 2.125 | Electrolytic             | 1000  | -40°C to 85°C  |
| 23C442F100CB1H1   |    | Genteq  | Special  | 4400   |     | 100 | 1.75  | Round | 2.125 | Electrolytic             | 1000  | -45°C to 95°C  |
| 23H781F400CE1H1   |    | Genteq  | Special  | 780    |     | 400 | 1.75  | Round | 3.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23F443F060FE1H1   |    | Genteq  | Special  | 44000  |     | 60  | 3     | Round | 3.625 | Electrolytic             | 1000  | -55°C to 105°C |
| 97F9695BX         | BX | Genteq  | Standard | 20     | 5   | 440 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23H771F450CG1H1   |    | Genteq  | Special  | 770    |     | 450 | 1.75  | Round | 4.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23F943F060FL1H1   |    | Genteq  | Special  | 94000  |     | 60  | 3     | Round | 8.625 | Electrolytic             | 1000  | -55°C to 105°C |
| 23H282F350FE1H1   |    | Genteq  | Special  | 2800   |     | 350 | 3     | Round | 3.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23C483F050DI1H1   |    | Genteq  | Special  | 48000  |     | 50  | 2     | Round | 5.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| 23F142F200DD1H1   |    | Genteq  | Special  | 1400   |     | 200 | 2     | Round | 3.125 | Electrolytic             | 1000  | -55°C to 105°C |
| 97F9619           |    | Genteq  | Standard | 45     |     | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F8072S          | S  | Genteq  | Stock    | 65     |     | 370 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23C133F100DE1H1   |    | Genteq  | Special  | 13000  |     | 100 | 2     | Round | 3.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| 97F9985BX         | BX | Genteq  | Standard | 40     | 10  | 440 | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23B103F080CD1H1   |    | Genteq  | Special  | 70000  |     | 80  | 1.75  | Round | 3.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| 23M362F450FI1H1   |    | Genteq  | Special  | 3600   |     | 450 | 3     | Round | 5.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 97F6680BX         | BX | Genteq  | Special  | 24     |     | 480 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 27L33BX           | BX | Genteq  | Standard | 25     | 5   | 440 | 2.5   | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| PB125E000A440DABX | BX | PROLINE | Standard | 12.5   |     | 440 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23H122F200DB1H1   |    | Genteq  | Special  | 1200   |     | 200 | 2     | Round | 2.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| PB200E000A370DAS  | S  | PROLINE | Stock    | 20     |     | 370 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| PB450Y100C440EA   |    | PROLINE | Standard | 45     | 10  | 440 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23H151F450BB1H1   |    | Genteq  | Special  | 150    |     | 450 | 1.375 | Round | 2.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| PB500E000S440FA   |    | PROLINE | Standard | 50     |     | 440 | 2     | Round | 5.75  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F6763BX         | BX | Genteq  | Standard | 10     |     | 330 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23B144F050FL1H1   |    | Genteq  | Special  | 140000 |     | 50  | 3     | Round | 8.625 | Electrolytic             | 3000  | -40°C to 85°C  |
| 97F6945RC         | RC | Genteq  | Standard | 24     |     | 580 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F6788RC         | RC | Genteq  | Standard | 2.5    |     | 330 | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F9082BX         | BX | Genteq  | Standard | 20     |     | 440 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F9638           |    | Genteq  | Standard | 35     |     | 440 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23J211F400BC1H1   |    | Genteq  | Special  | 210    |     | 400 | 1.375 | Round | 2.625 | Electrolytic             | 2000  | -40°C to 105°C |
| 97F9600           |    | Genteq  | Standard | 17.5   |     | 370 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |

|                    |    |         |          |       |     |      |       |       |       |                          |        |                |
|--------------------|----|---------|----------|-------|-----|------|-------|-------|-------|--------------------------|--------|----------------|
| 27L6095BX          | BX | Genteq  | Special  | 2     |     | 660  | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23C102F200BD1H1    |    | Genteq  | Special  | 1000  |     | 200  | 1.375 | Round | 3.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F6830            |    | Genteq  | Special  | 35    |     | 280  | 1.75  | Oval  | 3.5   | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F6774            |    | Genteq  | Standard | 24    |     | 330  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| PB075E000A440CAB X | BX | PROLINE | Standard | 7.5   |     | 440  | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F9970S           | S  | Genteq  | Stock    | 50    | 5   | 370  | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F8057            |    | Genteq  | Standard | 6     |     | 370  | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 42L3683            |    | Genteq  | Stock    | 0.068 |     | 2000 | 0.67  | Round | 1.22  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 97F9760            |    | Genteq  | Standard | 45    | 7.5 | 440  | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23H232F300CH1H1    |    | Genteq  | Special  | 2300  |     | 300  | 1.75  | Round | 5.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 25L6753BX          | BX | Genteq  | Standard | 35    | 13  | 280  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| PB450Y075C370DA    |    | PROLINE | Standard | 45    | 7.5 | 370  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23J601F300DB1H1    |    | Genteq  | Special  | 600   |     | 300  | 2     | Round | 2.125 | Electrolytic             | 2000   | -40°C to 105°C |
| 97F9052            |    | Genteq  | Special  | 30    | 5   | 440  | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L865             |    | Genteq  | Standard | 15    | 6   | 400  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F6716            |    | Genteq  | Standard | 20    |     | 330  | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 25L6755            |    | Genteq  | Standard | 20    | 8   | 280  | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23M512F200ED1H1    |    | Genteq  | Special  | 5100  |     | 200  | 2.5   | Round | 3.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F5211BX          | BX | Genteq  | Standard | 50    |     | 440  | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23F222F150CE1H1    |    | Genteq  | Special  | 2200  |     | 150  | 1.75  | Round | 3.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F6880BX          | BX | Genteq  | Standard | 20    | 12  | 280  | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F8042BX          | BX | Genteq  | Standard | 50    |     | 240  | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L6018BX          | BX | Genteq  | Special  | 12    |     | 660  | 1.5   | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23B823F075F11H1    |    | Genteq  | Special  | 82000 |     | 75   | 3     | Round | 5.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F6655            |    | Genteq  | Standard | 50    |     | 260  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F9010            |    | Genteq  | Standard | 55    |     | 370  | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23A263F060B11H1    |    | Genteq  | Special  | 26000 |     | 60   | 1.375 | Round | 5.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| PB400Y100C370DAB X | BX | PROLINE | Standard | 40    | 10  | 370  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F6760            |    | Genteq  | Standard | 12    |     | 330  | 1.5   | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23F703F075F11H1    |    | Genteq  | Special  | 70000 |     | 75   | 3     | Round | 5.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 23C363F060CG1H1    |    | Genteq  | Special  | 36000 |     | 60   | 1.75  | Round | 4.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23C103F080BF1H1    |    | Genteq  | Special  | 10000 |     | 80   | 1.375 | Round | 4.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F5001BX          | BX | Genteq  | Standard | 12.5  |     | 440  | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23M412F200CG1H1    |    | Genteq  | Special  | 4100  |     | 200  | 1.75  | Round | 4.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F9020BX          | BX | Genteq  | Special  | 25    | 7.5 | 370  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23A413F080EE1H1    |    | Genteq  | Special  | 41000 |     | 80   | 2.5   | Round | 3.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 97F9266            |    | Genteq  | Standard | 35    |     | 410  | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L6022BX          | BX | Genteq  | Special  | 25    |     | 660  | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6683RC          | RC | Genteq  | Special  | 21    |     | 480  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F9802S           | S  | Genteq  | Stock    | 50    |     | 370  | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23F182F200DE1H1    |    | Genteq  | Special  | 1800  |     | 200  | 2     | Round | 3.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 23C113F060CB1H1    |    | Genteq  | Special  | 11000 |     | 60   | 1.75  | Round | 2.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23B642F100CE1H1    |    | Genteq  | Special  | 6400  |     | 100  | 1.75  | Round | 3.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F6682RC          | RC | Genteq  | Special  | 31.5  |     | 420  | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23B901F200DB1H1    |    | Genteq  | Special  | 900   |     | 200  | 2     | Round | 2.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23M122F350B11H1    |    | Genteq  | Special  | 1200  |     | 350  | 1.375 | Round | 5.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F9856BX          | BX | Genteq  | Standard | 40    | 5   | 440  | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23C192F250CF1H1    |    | Genteq  | Special  | 1900  |     | 250  | 1.75  | Round | 4.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 27L945BX           | BX | Genteq  | Standard | 45    |     | 440  | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23A353F050DD1H1    |    | Genteq  | Special  | 35000 |     | 50   | 2     | Round | 3.125 | Electrolytic             | 1000   | -40°C to 85°C  |



|                   |    |         |          |       |     |     |       |       |       |                          |       |                |
|-------------------|----|---------|----------|-------|-----|-----|-------|-------|-------|--------------------------|-------|----------------|
| 97F6677           |    | Genteq  | Special  | 4     |     | 480 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23D133F028BE1H1   |    | Genteq  | Special  | 13000 |     | 28  | 1.375 | Round | 3.625 | Electrolytic             | 1000  | -55°C to 85°C  |
| 23M501F400BE1H1   |    | Genteq  | Special  | 500   |     | 400 | 1.375 | Round | 3.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| PB500Z100T440EABX | BX | PROLINE | Standard | 50    | 10  | 440 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 25L756BX          | BX | Genteq  | Standard | 60    | 10  | 440 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F6784           |    | Genteq  | Standard | 36    |     | 330 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F6780BX         | BX | Genteq  | Standard | 29    |     | 330 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| PB020E000A440AABX | BX | PROLINE | Standard | 2     |     | 440 | 1.25  | Oval  | 1.56  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23F672F150FE1H1   |    | Genteq  | Special  | 6700  |     | 150 | 3     | Round | 3.625 | Electrolytic             | 1000  | -55°C to 105°C |
| 23A283F075CG1H1   |    | Genteq  | Special  | 28000 |     | 75  | 1.75  | Round | 4.625 | Electrolytic             | 1000  | -40°C to 85°C  |
| 97F6691           |    | Genteq  | Standard | 24    | 4   | 280 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F8251BX         | BX | Genteq  | Standard | 15    |     | 600 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 27L442            |    | Genteq  | Standard | 28    | 7   | 280 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 27L6073BX         | BX | Genteq  | Special  | 15    |     | 660 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F9060           |    | Genteq  | Special  | 55    | 7.5 | 440 | 2     | Oval  | 6.25  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F6890BR         | BR | Genteq  | Standard | 18    | 10  | 280 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| PB075E000A370BABX | BX | PROLINE | Standard | 7.5   |     | 370 | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| PB600Z050T440EA   |    | PROLINE | Standard | 60    | 5   | 440 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23D313F007CB1H1   |    | Genteq  | Special  | 31000 |     | 7.5 | 1.75  | Round | 2.125 | Electrolytic             | 1000  | -55°C to 85°C  |
| PB300Z075S370DABX | BX | PROLINE | Standard | 30    | 7.5 | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F9636           |    | Genteq  | Standard | 30    |     | 440 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23C133F150EH1H1   |    | Genteq  | Special  | 13000 |     | 150 | 2.5   | Round | 5.125 | Electrolytic             | 1000  | -45°C to 95°C  |
| 23B203F150FL1H1   |    | Genteq  | Special  | 20000 |     | 150 | 3     | Round | 8.625 | Electrolytic             | 3000  | -40°C to 85°C  |
| 97F9899BX         | BX | Genteq  | Standard | 35    | 5   | 440 | 2.5   | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| PB300Z100S370DABX | BX | PROLINE | Standard | 30    | 10  | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| PB250E000A440EABX | BX | PROLINE | Standard | 25    |     | 440 | 1.25  | Oval  | 4.75  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 27L6094           |    | Genteq  | Special  | 3     |     | 660 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F6860BX         | BX | Genteq  | Standard | 15    |     | 280 | 1.5   | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| PB550E000D440EA   |    | PROLINE | Standard | 55    |     | 440 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23M162F350DE1H1   |    | Genteq  | Special  | 1600  |     | 350 | 2     | Round | 3.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| PB200Z100S370CA   |    | PROLINE | Standard | 20    | 10  | 370 | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23H312F250DG1H1   |    | Genteq  | Special  | 3100  |     | 250 | 2     | Round | 4.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 97F9026BX         | BX | Genteq  | Special  | 40    | 10  | 370 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23M222F350ED1H1   |    | Genteq  | Special  | 2200  |     | 350 | 2.5   | Round | 3.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 27L476BX          | BX | Genteq  | Standard | 33    | 15  | 330 | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F9593BX         | BX | Genteq  | Standard | 50    | 10  | 440 | 2     | Oval  | 5.25  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| PB030E000P370CABX | BX | PROLINE | Standard | 3     |     | 370 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23J861F250BE1H1   |    | Genteq  | Special  | 860   |     | 250 | 1.375 | Round | 3.625 | Electrolytic             | 2000  | -40°C to 105°C |
| 27L827            |    | Genteq  | Standard | 18    | 10  | 330 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 27L576RR          | RR | Genteq  | Special  | 20    | 8   | 400 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23B113F060DB1H1   |    | Genteq  | Special  | 11000 |     | 60  | 2     | Round | 2.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| 23M832F250E11H1   |    | Genteq  | Special  | 8300  |     | 250 | 2.5   | Round | 5.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23A372F150BI1H1   |    | Genteq  | Special  | 3700  |     | 150 | 1.375 | Round | 5.625 | Electrolytic             | 1000  | -40°C to 85°C  |
| 23M122F200BC1H1   |    | Genteq  | Special  | 1200  |     | 200 | 1.375 | Round | 2.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23C153F050BE1H1   |    | Genteq  | Special  | 15000 |     | 50  | 1.375 | Round | 3.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| 97F6540           |    | Genteq  | Standard | 45    |     | 280 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 27L200BX          | BX | Genteq  | Special  | 90    |     | 370 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F9391           |    | Genteq  | Special  | 80    |     | 370 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |

|                    |    |         |          |       |     |     |       |       |       |                          |       |                |
|--------------------|----|---------|----------|-------|-----|-----|-------|-------|-------|--------------------------|-------|----------------|
| 97F9841            |    | Genteq  | Standard | 45    | 7.5 | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23F883F075FL1H1    |    | Genteq  | Special  | 80000 |     | 75  | 3     | Round | 8.625 | Electrolytic             | 1000  | -55°C to 105°C |
| 97F6861            |    | Genteq  | Standard | 20    |     | 280 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F6776            |    | Genteq  | Standard | 28    |     | 330 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23A902F075BD1H1    |    | Genteq  | Special  | 9000  |     | 75  | 1.375 | Round | 3.125 | Electrolytic             | 1000  | -40°C to 85°C  |
| 97F8059S           | S  | Genteq  | Stock    | 10    |     | 370 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F8008            |    | Genteq  | Special  | 50    |     | 440 | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F9976            |    | Genteq  | Standard | 20    | 7.5 | 440 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23H262F250DF1H1    |    | Genteq  | Special  | 2600  |     | 250 | 2     | Round | 4.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 97F6531            |    | Genteq  | Standard | 7     |     | 330 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| PB200Y075C440DAB X | BX | PROLINE | Standard | 20    | 7.5 | 440 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| PB400E000C440DAS   | S  | PROLINE | Stock    | 40    |     | 440 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23C203F060BG1H1    |    | Genteq  | Special  | 20000 |     | 60  | 1.375 | Round | 4.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| 23F333F080FE1H1    |    | Genteq  | Special  | 33000 |     | 80  | 3     | Round | 3.625 | Electrolytic             | 1000  | -55°C to 105°C |
| PB250E000A370DAB X | BX | PROLINE | Standard | 25    |     | 370 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23J162F300DF1H1    |    | Genteq  | Special  | 1600  |     | 300 | 2     | Round | 4.125 | Electrolytic             | 2000  | -40°C to 105°C |
| 97F8256BX          | BX | Genteq  | Standard | 35    |     | 600 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23C283F075CI1H1    |    | Genteq  | Special  | 28000 |     | 75  | 1.75  | Round | 5.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| PB175E000P370CAB X | BX | PROLINE | Standard | 17.5  |     | 370 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F9810BX          | BX | Genteq  | Standard | 15    | 5   | 370 | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23M173F200FJ1H1    |    | Genteq  | Special  | 17000 |     | 200 | 3     | Round | 5.875 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23H113F250FL1H1    |    | Genteq  | Special  | 11000 |     | 250 | 3     | Round | 8.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 97F9829            |    | Genteq  | Standard | 35    | 7.5 | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23A882F150DI1H1    |    | Genteq  | Special  | 8800  |     | 150 | 2     | Round | 5.625 | Electrolytic             | 1000  | -40°C to 85°C  |
| 97F6850BX          | BX | Genteq  | Standard | 45    |     | 280 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| PB600E000P370EA    |    | PROLINE | Standard | 60    |     | 370 | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F9883BX          | BX | Genteq  | Standard | 45    | 7.5 | 440 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F9526BX          | BX | Genteq  | Standard | 15    | 7.5 | 370 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23F162F150BG1H1    |    | Genteq  | Special  | 1600  |     | 150 | 1.375 | Round | 4.625 | Electrolytic             | 1000  | -55°C to 105°C |
| 23A253F050BG1H1    |    | Genteq  | Special  | 25000 |     | 50  | 1.375 | Round | 4.625 | Electrolytic             | 1000  | -40°C to 85°C  |
| 23F931F250BH1H1    |    | Genteq  | Special  | 930   |     | 250 | 1.375 | Round | 5.125 | Electrolytic             | 1000  | -55°C to 105°C |
| 23H622F350FL1H1    |    | Genteq  | Special  | 6200  |     | 350 | 3     | Round | 8.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 97F8073            |    | Genteq  | Standard | 70    |     | 370 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23D482F035BB1H1    |    | Genteq  | Special  | 4800  |     | 35  | 1.375 | Round | 2.125 | Electrolytic             | 1000  | -55°C to 85°C  |
| 23J172F300CH1H1    |    | Genteq  | Special  | 1700  |     | 300 | 1.75  | Round | 5.125 | Electrolytic             | 2000  | -40°C to 105°C |
| PB500Y100D370EA    |    | PROLINE | Standard | 50    | 10  | 370 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F9675BX          | BX | Genteq  | Standard | 25    | 5   | 370 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| PB400Z100S440EA    |    | PROLINE | Standard | 40    | 10  | 440 | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23M312F400EH1H1    |    | Genteq  | Special  | 3100  |     | 400 | 2.5   | Round | 5.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23B732F100CF1H1    |    | Genteq  | Special  | 7300  |     | 100 | 1.75  | Round | 4.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| 23F332F060BB1H1    |    | Genteq  | Special  | 3300  |     | 60  | 1.375 | Round | 2.125 | Electrolytic             | 1000  | -55°C to 105°C |
| 23B582F200FF1H1    |    | Genteq  | Special  | 5800  |     | 200 | 3     | Round | 4.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| 23A293F080CH1H1    |    | Genteq  | Special  | 29000 |     | 80  | 1.75  | Round | 5.125 | Electrolytic             | 1000  | -40°C to 85°C  |
| 23H302F400FG1H1    |    | Genteq  | Special  | 3000  |     | 400 | 3     | Round | 4.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23M701F350DB1H1    |    | Genteq  | Special  | 700   |     | 350 | 2     | Round | 2.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23B133F075BH1H1    |    | Genteq  | Special  | 13000 |     | 75  | 1.375 | Round | 5.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| 97F6711            |    | Genteq  | Special  | 16    |     | 330 | 1.5   | Oval  | 3.5   | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| PB250E000A370DAS   | S  | PROLINE | Stock    | 25    |     | 370 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F5170            |    | Genteq  | Special  | 20    |     | 370 | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F9251            |    | Genteq  | Standard | 25    | 3.2 | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23M182F300DD1H1    |    | Genteq  | Special  | 1800  |     | 300 | 2     | Round | 3.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23C154F050FJ1H1    |    | Genteq  | Special  | 15000 | 0   | 50  | 3     | Round | 5.875 | Electrolytic             | 1000  | -45°C to 95°C  |

|                    |    |         |          |       |    |      |       |       |       |                          |        |                |
|--------------------|----|---------|----------|-------|----|------|-------|-------|-------|--------------------------|--------|----------------|
| PB150Y100C440DAB X | BX | PROLINE | Standard | 15    | 10 | 440  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| PB500Y100D440GA    |    | PROLINE | Standard | 50    | 10 | 440  | 2     | Oval  | 5.25  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F5052            |    | Genteq  | Special  | 20    |    | 370  | 1.75  | Round | 3.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9625            |    | Genteq  | Standard | 15    |    | 440  | 1.25  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9989            |    | Genteq  | Standard | 55    | 10 | 440  | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6517BX          | BX | Genteq  | Standard | 15    |    | 400  | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23H671F350CC1H1    |    | Genteq  | Special  | 670   |    | 350  | 1.75  | Round | 2.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23H302F250ED1H1    |    | Genteq  | Special  | 3000  |    | 250  | 2.5   | Round | 3.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23J312F350FG1H1    |    | Genteq  | Special  | 3100  |    | 350  | 3     | Round | 4.625 | Electrolytic             | 2000   | -40°C to 105°C |
| PB250E000A440EA    |    | PROLINE | Standard | 25    |    | 440  | 1.25  | Oval  | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F8241            |    | Genteq  | Special  | 2     |    | 600  | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23B902F060BD1H1    |    | Genteq  | Special  | 9000  |    | 60   | 1.375 | Round | 3.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F6760RC          | RC | Genteq  | Standard | 12    |    | 330  | 1.5   | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F6685            |    | Genteq  | Special  | 15    |    | 480  | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23J961F350DE1H1    |    | Genteq  | Special  | 960   |    | 350  | 2     | Round | 3.625 | Electrolytic             | 2000   | -40°C to 105°C |
| 97F9477            |    | Genteq  | Standard | 45    | 10 | 440  | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6621RC          | RC | Genteq  | Standard | 15    |    | 400  | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23J352F250EF1H1    |    | Genteq  | Special  | 3500  |    | 250  | 2.5   | Round | 4.125 | Electrolytic             | 2000   | -40°C to 105°C |
| PB150E000A440EAS   | S  | PROLINE | Stock    | 15    |    | 440  | 1.25  | Oval  | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F9780BX          | BX | Genteq  | Standard | 40    | 10 | 440  | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB250E000P370CAB X | BX | PROLINE | Standard | 25    |    | 370  | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 42L4153            |    | Genteq  | Stock    | 0.015 |    | 3000 | 0.55  | Round | 1.22  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 27L729             |    | Genteq  | Special  | 20    | 4  | 400  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23H511F400CC1H1    |    | Genteq  | Special  | 510   |    | 400  | 1.75  | Round | 2.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23M521F450DC1H1    |    | Genteq  | Special  | 520   |    | 450  | 2     | Round | 2.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23J741F250CB1H1    |    | Genteq  | Special  | 740   |    | 250  | 1.75  | Round | 2.125 | Electrolytic             | 2000   | -40°C to 105°C |
| 23F601F250DB1H1    |    | Genteq  | Special  | 600   |    | 250  | 2     | Round | 2.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F5377            |    | Genteq  | Special  | 35    | 10 | 440  | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23B223F080CI1H1    |    | Genteq  | Special  | 22000 |    | 80   | 1.75  | Round | 5.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F9451            |    | Genteq  | Standard | 20    | 10 | 440  | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6776BX          | BX | Genteq  | Standard | 28    |    | 330  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23B822F100DE1H1    |    | Genteq  | Special  | 8200  |    | 100  | 2     | Round | 3.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F6702            |    | Genteq  | Special  | 7     |    | 330  | 1.25  | Oval  | 2.62  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| PB200Y100C440DAB X | BX | PROLINE | Standard | 20    | 10 | 440  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F8063            |    | Genteq  | Standard | 20    |    | 370  | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L1054BX          | BX | Genteq  | Standard | 20    |    | 440  | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23C672F150DG1H1    |    | Genteq  | Special  | 6700  |    | 150  | 2     | Round | 4.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F9611            |    | Genteq  | Standard | 35    |    | 370  | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9638BX          | BX | Genteq  | Standard | 35    |    | 440  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L6013            |    | Genteq  | Special  | 5     |    | 660  | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L637BX           | BX | Genteq  | Special  | 80    | 5  | 440  | 2     | Oval  | 6.25  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB200Y100C370DAB X | BX | PROLINE | Standard | 20    | 10 | 370  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| PB400Z050S370DA    |    | PROLINE | Standard | 40    | 5  | 370  | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F9814BX          | BX | Genteq  | Standard | 20    | 5  | 370  | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6606BR          | BR | Genteq  | Standard | 10    |    | 400  | 1.5   | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F9023BX          | BX | Genteq  | Special  | 35    | 10 | 370  | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB150Z100S440DA    |    | PROLINE | Standard | 15    | 10 | 440  | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |

|                    |    |         |          |       |     |      |       |       |       |                            |        |                |
|--------------------|----|---------|----------|-------|-----|------|-------|-------|-------|----------------------------|--------|----------------|
| 97F6777            |    | Genteq  | Special  | 35    |     | 330  | 1.5   | Oval  | 4.75  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 27L1053            |    | Genteq  | Standard | 7.5   |     | 440  | 1.75  | Round | 2.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 23H961F350DD1H1    |    | Genteq  | Special  | 960   |     | 350  | 2     | Round | 3.125 | Electrolytic               | 2000   | -40°C to 85°C  |
| 97F5465BX          | BX | Genteq  | Special  | 30    |     | 370  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 23H281F400BC1H1    |    | Genteq  | Special  | 280   |     | 400  | 1.375 | Round | 2.625 | Electrolytic               | 2000   | -40°C to 85°C  |
| 97F6812BR          | BR | Genteq  | Standard | 17.5  |     | 280  | 1.5   | Oval  | 2.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 23F123F050BE1H1    |    | Genteq  | Special  | 12000 |     | 50   | 1.375 | Round | 3.625 | Electrolytic               | 1000   | -55°C to 105°C |
| 23J282F250DH1H1    |    | Genteq  | Special  | 2800  |     | 250  | 2     | Round | 5.125 | Electrolytic               | 2000   | -40°C to 105°C |
| 97F6749            |    | Genteq  | Standard | 13.5  |     | 330  | 1.5   | Oval  | 2.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 97F9119            |    | Genteq  | Special  | 30    |     | 440  | 2     | Oval  | 2.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| PB700Z075T440GABX  | BX | PROLINE | Standard | 70    | 7.5 | 440  | 2.5   | Round | 4.75  | Oil-Filled (UL Approved)   | 10000  | -40°C to 70°C  |
| 27L7000RC          | RC | Genteq  | Standard | 48    |     | 280  | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 100°C |
| 97F9696            |    | Genteq  | Standard | 20    | 7.5 | 440  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 23M162F450FD1H1    |    | Genteq  | Special  | 1600  |     | 450  | 3     | Round | 3.125 | Electrolytic               | 2000   | -40°C to 85°C  |
| 97F9021            |    | Genteq  | Special  | 35    | 5   | 370  | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 97F8062BX          | BX | Genteq  | Standard | 17.5  |     | 370  | 1.75  | Round | 2.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 27L591BR           | BR | Genteq  | Standard | 35    | 15  | 300  | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 23D253F020BG1H1    |    | Genteq  | Special  | 25000 |     | 20   | 1.375 | Round | 4.625 | Electrolytic               | 1000   | -55°C to 85°C  |
| 23C772F250FH1H1    |    | Genteq  | Special  | 7700  |     | 250  | 3     | Round | 5.125 | Electrolytic               | 1000   | -45°C to 95°C  |
| 97F9985            |    | Genteq  | Standard | 40    | 10  | 440  | 2     | Round | 4.75  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 97F6768RC          | RC | Genteq  | Standard | 14    |     | 330  | 1.5   | Oval  | 2.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| PB250Z100S370CABX  | BX | PROLINE | Standard | 25    | 10  | 370  | 2     | Round | 2.88  | Oil-Filled (UL Approved)   | 10000  | -40°C to 70°C  |
| 97F6623BX          | BX | Genteq  | Standard | 24    |     | 400  | 2     | Oval  | 2.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 42L2222            |    | Genteq  | Stock    | 0.22  |     | 1200 | 0.81  | Round | 1.22  | Dry-Axial Leaded           | 100000 | -40°C to 85°C  |
| 23M231F450BC1H1    |    | Genteq  | Special  | 230   |     | 450  | 1.375 | Round | 2.625 | Electrolytic               | 2000   | -40°C to 85°C  |
| 97F6922            |    | Genteq  | Special  | 8     |     | 525  | 1.5   | Oval  | 2.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 23H282F450FI1H1    |    | Genteq  | Special  | 2800  |     | 450  | 3     | Round | 5.625 | Electrolytic               | 2000   | -40°C to 85°C  |
| 23B113F075BG1H1    |    | Genteq  | Special  | 11000 |     | 75   | 1.375 | Round | 4.625 | Electrolytic               | 3000   | -40°C to 85°C  |
| 97F6521RC          | RC | Genteq  | Standard | 28    |     | 330  | 1.75  | Round | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 27L531             |    | Genteq  | Standard | 16    | 10  | 400  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 23F342F150CH1H1    |    | Genteq  | Special  | 3400  |     | 150  | 1.75  | Round | 5.125 | Electrolytic               | 1000   | -55°C to 105°C |
| 27L6089            |    | Genteq  | Special  | 18    |     | 660  | 2     | Oval  | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 97F5608            |    | Genteq  | Special  | 35    | 7.5 | 370  | 2     | Oval  | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 97F6782BX          | BX | Genteq  | Special  | 18.5  |     | 330  | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 23A795F150DH1H1    |    | Genteq  | Special  | 7900  |     | 150  | 2     | Round | 5.125 | Electrolytic               | 1000   | -40°C to 85°C  |
| 23H132F450FD1H1    |    | Genteq  | Special  | 1300  |     | 450  | 3     | Round | 3.125 | Electrolytic               | 2000   | -40°C to 85°C  |
| PB400Y050C370DA    |    | PROLINE | Standard | 40    | 5   | 370  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved)   | 10000  | -40°C to 70°C  |
| 23F132F250CF1H1    |    | Genteq  | Special  | 1300  |     | 250  | 1.75  | Round | 4.125 | Electrolytic               | 1000   | -55°C to 105°C |
| 97F9874S           | S  | Genteq  | Stock    | 55    | 7.5 | 440  | 2.5   | Round | 4.75  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 23B533F050FD1H1    |    | Genteq  | Special  | 53000 |     | 50   | 3     | Round | 3.125 | Electrolytic               | 3000   | -40°C to 85°C  |
| 23F462F250FG1H1    |    | Genteq  | Special  | 4600  |     | 250  | 3     | Round | 4.625 | Electrolytic               | 1000   | -55°C to 105°C |
| 24DB300B370PA      |    | Genteq  | Standard | 30    |     | 370  | 1.75  | Round | 3.189 | Dry (UL Construction Only) | 60000  | -40°C to 70°C  |
| 97F9969BX          | BX | Genteq  | Standard | 45    | 7.5 | 370  | 2     | Round | 4.75  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 97F6749S           | S  | Genteq  | Stock    | 13.5  |     | 330  | 1.5   | Oval  | 2.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 97F5457            |    | Genteq  | Special  | 7.5   |     | 370  | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| PB500Y075C370EAB X | BX | PROLINE | Standard | 50    | 7.5 | 370  | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved)   | 10000  | -40°C to 70°C  |
| 97F6712            |    | Genteq  | Special  | 17.5  |     | 330  | 1.5   | Oval  | 3.5   | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 97F6882            |    | Genteq  | Standard | 24    | 8   | 280  | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |

|                   |    |         |          |       |     |     |       |       |       |                          |       |                |
|-------------------|----|---------|----------|-------|-----|-----|-------|-------|-------|--------------------------|-------|----------------|
| 97F5522           |    | Genteq  | Special  | 6     |     | 370 | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23B233F100FF1H1   |    | Genteq  | Special  | 23000 |     | 100 | 3     | Round | 4.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| PB250E000A370DA   |    | PROLINE | Standard | 25    |     | 370 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F6751           |    | Genteq  | Special  | 9.25  |     | 330 | 1.25  | Oval  | 3.12  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F9760BX         | BX | Genteq  | Standard | 45    | 7.5 | 440 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 27L872BX          | BX | Genteq  | Standard | 60    | 5   | 370 | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F9695           |    | Genteq  | Standard | 20    | 5   | 440 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F5304BX         | BX | Genteq  | Special  | 15    |     | 440 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F6200BX         | BX | Genteq  | Special  | 9.4   |     | 290 | 1.5   | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F9625S          | S  | Genteq  | Stock    | 15    |     | 440 | 1.25  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23C213F100DH1H1   |    | Genteq  | Special  | 21000 |     | 100 | 2     | Round | 5.125 | Electrolytic             | 1000  | -45°C to 95°C  |
| PB500Z075S370EABX | BX | PROLINE | Standard | 50    | 7.5 | 370 | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F9851           |    | Genteq  | Standard | 45    | 5   | 440 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| PB200Z100S370CABX | BX | PROLINE | Standard | 20    | 10  | 370 | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F5377BX         | BX | Genteq  | Special  | 35    | 10  | 440 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23M232F250CE1H1   |    | Genteq  | Special  | 2300  |     | 250 | 1.75  | Round | 3.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23D872F035CB1H1   |    | Genteq  | Special  | 87000 |     | 35  | 1.75  | Round | 2.125 | Electrolytic             | 1000  | -55°C to 85°C  |
| 23C852F150DI1H1   |    | Genteq  | Special  | 8500  |     | 150 | 2     | Round | 5.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| 97F6533BX         | BX | Genteq  | Standard | 30    |     | 280 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F6601RC         | RC | Genteq  | Standard | 10    |     | 400 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F8095BX         | BX | Genteq  | Standard | 30    | 30  | 150 | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 27L576BR          | BR | Genteq  | Special  | 20    | 8   | 400 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 27L442BR          | BR | Genteq  | Standard | 28    | 7   | 280 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F6858BX         | BX | Genteq  | Standard | 10    |     | 280 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| PB600Z050T370DA   |    | PROLINE | Standard | 60    | 5   | 370 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23H192F250CE1H1   |    | Genteq  | Special  | 1900  |     | 250 | 1.75  | Round | 3.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 97F9062BX         | BX | Genteq  | Standard | 60    | 5   | 440 | 2     | Oval  | 6.25  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F9842           |    | Genteq  | Standard | 35    | 5   | 440 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| PB700Z100T370EABX | BX | PROLINE | Standard | 70    | 10  | 370 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23A243F075CF1H1   |    | Genteq  | Special  | 24000 |     | 75  | 1.75  | Round | 4.125 | Electrolytic             | 1000  | -40°C to 85°C  |
| 23C172F200CD1H1   |    | Genteq  | Special  | 1700  |     | 200 | 1.75  | Round | 3.125 | Electrolytic             | 1000  | -45°C to 95°C  |
| 23J262F300EF1H1   |    | Genteq  | Special  | 2600  |     | 300 | 2.5   | Round | 4.125 | Electrolytic             | 2000  | -40°C to 105°C |
| 23B353F060DG1H1   |    | Genteq  | Special  | 35000 |     | 60  | 2     | Round | 4.625 | Electrolytic             | 3000  | -40°C to 85°C  |
| PB400E000C440DA   |    | PROLINE | Standard | 40    |     | 440 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23F192F150BH1H1   |    | Genteq  | Special  | 1900  |     | 150 | 1.375 | Round | 5.125 | Electrolytic             | 1000  | -55°C to 105°C |
| 23H901F450ED1H1   |    | Genteq  | Special  | 900   |     | 450 | 2.5   | Round | 3.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23C862F250FI1H1   |    | Genteq  | Special  | 8600  |     | 250 | 3     | Round | 5.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| 23B104F060FH1H1   |    | Genteq  | Special  | 10000 |     | 60  | 3     | Round | 5.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| 97F5330           |    | Genteq  | Special  | 25    | 4   | 440 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| PB150Y075C370CA   |    | PROLINE | Standard | 15    | 7.5 | 370 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23C772F200FF1H1   |    | Genteq  | Special  | 7700  |     | 200 | 3     | Round | 4.125 | Electrolytic             | 1000  | -45°C to 95°C  |
| 27L1023           |    | Genteq  | Standard | 4     |     | 440 | 1.25  | Oval  | 1.56  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23C643F060EF1H1   |    | Genteq  | Special  | 64000 |     | 60  | 2.5   | Round | 4.125 | Electrolytic             | 1000  | -45°C to 95°C  |
| 23B173F060BH1H1   |    | Genteq  | Special  | 17000 |     | 60  | 1.375 | Round | 5.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| 97F6703BR         | BR | Genteq  | Standard | 8     |     | 330 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| PB150Z100S370CABX | BX | PROLINE | Standard | 15    | 10  | 370 | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F6522BR         | BR | Genteq  | Standard | 24    |     | 280 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 27L400BX          | BX | Genteq  | Standard | 26    | 9   | 300 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |

|                   |    |         |          |       |     |     |       |       |       |                          |       |                |
|-------------------|----|---------|----------|-------|-----|-----|-------|-------|-------|--------------------------|-------|----------------|
| 97F9681BX         | BX | Genteq  | Standard | 30    | 5   | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23F183F100EH1H1   |    | Genteq  | Special  | 18000 |     | 100 | 2.5   | Round | 5.125 | Electrolytic             | 1000  | -55°C to 105°C |
| PB150Z050S370CA   |    | PROLINE | Standard | 15    | 5   | 370 | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 27L6022           |    | Genteq  | Special  | 25    |     | 660 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23F582F200FG1H1   |    | Genteq  | Special  | 5800  |     | 200 | 3     | Round | 4.625 | Electrolytic             | 1000  | -55°C to 105°C |
| 97F6602RC         | RC | Genteq  | Standard | 15    |     | 400 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| PB400Z100S370DABX | BX | PROLINE | Standard | 40    | 10  | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23A123F150FE1H1   |    | Genteq  | Special  | 12000 |     | 150 | 3     | Round | 3.625 | Electrolytic             | 1000  | -40°C to 85°C  |
| 97F9051           |    | Genteq  | Special  | 25    | 10  | 440 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23J132F350DG1H1   |    | Genteq  | Special  | 1300  |     | 350 | 2     | Round | 4.625 | Electrolytic             | 2000  | -40°C to 105°C |
| PB250Z075S370CABX | BX | PROLINE | Standard | 25    | 7.5 | 370 | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 27L558            |    | Genteq  | Standard | 25    | 10  | 440 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23F242F100BD1H1   |    | Genteq  | Special  | 2400  |     | 100 | 1.375 | Round | 3.125 | Electrolytic             | 1000  | -55°C to 105°C |
| PB550E000T370DABX | BX | PROLINE | Standard | 55    |     | 370 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 27L724            |    | Genteq  | Standard | 24    | 11  | 280 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23B313F080EF1H1   |    | Genteq  | Special  | 31000 |     | 80  | 2.5   | Round | 4.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| 23C282F250ED1H1   |    | Genteq  | Special  | 2800  |     | 250 | 2.5   | Round | 3.125 | Electrolytic             | 1000  | -45°C to 95°C  |
| 97F8052S          | S  | Genteq  | Stock    | 100   |     | 240 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23M902F200FE1H1   |    | Genteq  | Special  | 9000  |     | 200 | 3     | Round | 3.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 97F8068BX         | BX | Genteq  | Standard | 45    |     | 370 | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F9997BX         | BX | Genteq  | Standard | 15    | 5   | 440 | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23M402F300DI1H1   |    | Genteq  | Special  | 4000  |     | 300 | 2     | Round | 5.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23J192F300DG1H1   |    | Genteq  | Special  | 1900  |     | 300 | 2     | Round | 4.625 | Electrolytic             | 2000  | -40°C to 105°C |
| 97F9972           |    | Genteq  | Standard | 50    | 10  | 370 | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F6920BX         | BX | Genteq  | Standard | 16    |     | 540 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23C222F200CE1H1   |    | Genteq  | Special  | 2200  |     | 200 | 1.75  | Round | 3.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| PB200Z100S440DABX | BX | PROLINE | Standard | 20    | 10  | 440 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23F633F075FH1H1   |    | Genteq  | Special  | 63000 |     | 75  | 3     | Round | 5.125 | Electrolytic             | 1000  | -55°C to 105°C |
| 97F9667BX         | BX | Genteq  | Standard | 25    |     | 440 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23H691F450DE1H1   |    | Genteq  | Special  | 690   |     | 450 | 2     | Round | 3.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23A733F075FF1H1   |    | Genteq  | Special  | 73000 |     | 75  | 3     | Round | 4.125 | Electrolytic             | 1000  | -40°C to 85°C  |
| 97F9637           |    | Genteq  | Standard | 30    |     | 440 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 27L349BX          | BX | Genteq  | Special  | 75    |     | 440 | 2.5   | Round | 5.25  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23H252F300DG1H1   |    | Genteq  | Special  | 2500  |     | 300 | 2     | Round | 4.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23F322F250EG1H1   |    | Genteq  | Special  | 3200  |     | 250 | 2.5   | Round | 4.625 | Electrolytic             | 1000  | -55°C to 105°C |
| 23F563F050FD1H1   |    | Genteq  | Special  | 56000 |     | 50  | 3     | Round | 3.125 | Electrolytic             | 1000  | -55°C to 105°C |
| 23B223F050CE1H1   |    | Genteq  | Special  | 22000 |     | 50  | 1.75  | Round | 3.625 | Electrolytic             | 3000  | -40°C to 85°C  |
| 23A103F150FD1H1   |    | Genteq  | Special  | 10000 |     | 150 | 3     | Round | 3.125 | Electrolytic             | 1000  | -40°C to 85°C  |
| 23C522F150CG1H1   |    | Genteq  | Special  | 5200  |     | 150 | 1.75  | Round | 4.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| 97F9669           |    | Genteq  | Standard | 40    |     | 440 | 2     | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| PB550E000P370EA   |    | PROLINE | Standard | 55    |     | 370 | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F9735           |    | Genteq  | Standard | 35    | 5   | 440 | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23H122F400ED1H1   |    | Genteq  | Special  | 1200  |     | 400 | 2.5   | Round | 3.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 97F6923           |    | Genteq  | Special  | 32    |     | 540 | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23C163F100CH1H1   |    | Genteq  | Special  | 16000 |     | 100 | 1.75  | Round | 5.125 | Electrolytic             | 1000  | -45°C to 95°C  |
| 97F9966BX         | BX | Genteq  | Standard | 20    | 7.5 | 370 | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23B392F250FE1H1   |    | Genteq  | Special  | 3900  |     | 250 | 3     | Round | 3.625 | Electrolytic             | 3000  | -40°C to 85°C  |
| 97F6766           |    | Genteq  | Standard | 7     |     | 330 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 27L543            |    | Genteq  | Standard | 9.5   | 6.5 | 330 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F6760BR         | BR | Genteq  | Standard | 12    |     | 330 | 1.5   | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 27L1025           |    | Genteq  | Standard | 6     |     | 440 | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |

|                       |    |         |          |            |     |     |       |       |       |                             |        |                |
|-----------------------|----|---------|----------|------------|-----|-----|-------|-------|-------|-----------------------------|--------|----------------|
| 23A114F060FG1H1       |    | Genteq  | Special  | 11000<br>0 |     | 60  | 3     | Round | 4.625 | Electrolytic                | 1000   | -40°C to 85°C  |
| 97F8068S              | S  | Genteq  | Stock    | 45         |     | 370 | 2     | Round | 4.75  | Oil-Filled (UL<br>Approved) | 60000  | -40°C to 70°C  |
| 23B602F200E1H1        |    | Genteq  | Special  | 6000       |     | 200 | 2.5   | Round | 5.625 | Electrolytic                | 3000   | -40°C to 85°C  |
| 97F6763               |    | Genteq  | Standard | 10         |     | 330 | 1.25  | Oval  | 3.88  | Oil-Filled (UL<br>Approved) | 60000  | -40°C to 90°C  |
| PB400Y100C370DA       |    | PROLINE | Standard | 40         | 10  | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL<br>Approved) | 10000  | -40°C to 70°C  |
| 27L1030               |    | Genteq  | Standard | 2.5        |     | 370 | 1.25  | Oval  | 1.56  | Oil-Filled (UL<br>Approved) | 60000  | -40°C to 70°C  |
| 23F382F150DG1H1       |    | Genteq  | Special  | 3800       |     | 150 | 2     | Round | 4.625 | Electrolytic                | 1000   | -55°C to 105°C |
| 23J442F250FE1H1       |    | Genteq  | Special  | 4400       |     | 250 | 3     | Round | 3.625 | Electrolytic                | 2000   | -40°C to 105°C |
| 23F912F080BH1H1       |    | Genteq  | Special  | 9100       |     | 80  | 1.375 | Round | 5.125 | Electrolytic                | 1000   | -55°C to 105°C |
| 97F5465               |    | Genteq  | Special  | 30         |     | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL<br>Approved) | 60000  | -40°C to 70°C  |
| 23B173F080CG1H1       |    | Genteq  | Special  | 17000      |     | 80  | 1.75  | Round | 4.625 | Electrolytic                | 3000   | -40°C to 85°C  |
| 23J182F350FD1H1       |    | Genteq  | Special  | 1800       |     | 350 | 3     | Round | 3.125 | Electrolytic                | 2000   | -40°C to 105°C |
| 23F173F100FE1H1       |    | Genteq  | Special  | 17000      |     | 100 | 3     | Round | 3.625 | Electrolytic                | 1000   | -55°C to 105°C |
| 27L889                |    | Genteq  | Standard | 45         | 5   | 440 | 2     | Round | 4.75  | Oil-Filled (UL<br>Approved) | 60000  | -40°C to 70°C  |
| 97F9639BX             | BX | Genteq  | Standard | 35         |     | 440 | 2     | Round | 3.88  | Oil-Filled (UL<br>Approved) | 60000  | -40°C to 70°C  |
| 27L6082               |    | Genteq  | Special  | 20         |     | 660 | 2     | Oval  | 4.75  | Oil-Filled (UL<br>Approved) | 60000  | -40°C to 70°C  |
| 97F8095               |    | Genteq  | Standard | 30         | 30  | 150 | 2     | Oval  | 3.88  | Oil-Filled (UL<br>Approved) | 60000  | -40°C to 70°C  |
| 23B133F060BF1H1       |    | Genteq  | Special  | 13000      |     | 60  | 1.375 | Round | 4.125 | Electrolytic                | 3000   | -40°C to 85°C  |
| 23J272F200CH1H1       |    | Genteq  | Special  | 2700       |     | 200 | 1.75  | Round | 5.125 | Electrolytic                | 2000   | -40°C to 105°C |
| 23F132F200BI1H1       |    | Genteq  | Special  | 1300       |     | 200 | 1.375 | Round | 5.625 | Electrolytic                | 1000   | -55°C to 105°C |
| 23H831F350BH1H1       |    | Genteq  | Special  | 830        |     | 350 | 1.375 | Round | 5.125 | Electrolytic                | 2000   | -40°C to 85°C  |
| 41L2221               |    | Genteq  | Stock    | 2.2        |     | 250 | 0.45  | Round | 1.22  | Dry-Axial Leaded            | 100000 | -40°C to 85°C  |
| 23C154F060FJ1H1       |    | Genteq  | Special  | 15000<br>0 |     | 60  | 3     | Round | 5.875 | Electrolytic                | 1000   | -45°C to 95°C  |
| 97F6725BX             | BX | Genteq  | Special  | 29         |     | 330 | 1.75  | Oval  | 3.5   | Oil-Filled (UL<br>Approved) | 60000  | -40°C to 90°C  |
| 23F143F060CE1H1       |    | Genteq  | Special  | 14000      |     | 60  | 1.75  | Round | 3.625 | Electrolytic                | 1000   | -55°C to 105°C |
| 23B502F200FE1H1       |    | Genteq  | Special  | 5000       |     | 200 | 3     | Round | 3.625 | Electrolytic                | 3000   | -40°C to 85°C  |
| 23H652F200EG1H1       |    | Genteq  | Special  | 6500       |     | 200 | 2.5   | Round | 4.625 | Electrolytic                | 2000   | -40°C to 85°C  |
| 97F6763RC             | RC | Genteq  | Standard | 10         |     | 330 | 1.25  | Oval  | 3.88  | Oil-Filled (UL<br>Approved) | 60000  | -40°C to 90°C  |
| 23H731F300CB1H1       |    | Genteq  | Special  | 730        |     | 300 | 1.75  | Round | 2.125 | Electrolytic                | 2000   | -40°C to 85°C  |
| 97F9839BX             | BX | Genteq  | Standard | 55         | 5   | 440 | 2.5   | Round | 4.75  | Oil-Filled (UL<br>Approved) | 60000  | -40°C to 70°C  |
| PB700Z050T440GA       |    | PROLINE | Standard | 70         | 5   | 440 | 2.5   | Round | 5.25  | Oil-Filled (UL<br>Approved) | 10000  | -40°C to 70°C  |
| 97F6858BR             | BR | Genteq  | Standard | 10         |     | 280 | 1.25  | Oval  | 2.88  | Oil-Filled (UL<br>Approved) | 60000  | -40°C to 90°C  |
| 97F6621BR             | BR | Genteq  | Standard | 15         |     | 400 | 1.75  | Oval  | 2.88  | Oil-Filled (UL<br>Approved) | 60000  | -40°C to 90°C  |
| 23F252F200DG1H1       |    | Genteq  | Special  | 2500       |     | 200 | 2     | Round | 4.625 | Electrolytic                | 1000   | -55°C to 105°C |
| 23A893F060EH1H1       |    | Genteq  | Special  | 89000      |     | 60  | 2.5   | Round | 5.125 | Electrolytic                | 1000   | -40°C to 85°C  |
| PB030E000A370AABX     | BX | PROLINE | Standard | 3          |     | 370 | 1.25  | Oval  | 1.56  | Oil-Filled (UL<br>Approved) | 10000  | -40°C to 70°C  |
| 27L213                |    | Genteq  | Standard | 7.5        |     | 400 | 1.25  | Oval  | 2.88  | Oil-Filled (UL<br>Approved) | 60000  | -40°C to 70°C  |
| 97F5583BX             | BX | Genteq  | Standard | 2          |     | 440 | 1.25  | Oval  | 2.12  | Oil-Filled (UL<br>Approved) | 60000  | -40°C to 70°C  |
| 23A163F060CC1H1       |    | Genteq  | Special  | 16000      |     | 60  | 1.75  | Round | 2.625 | Electrolytic                | 1000   | -40°C to 85°C  |
| 97F9037BX             | BX | Genteq  | Standard | 15         |     | 440 | 1.75  | Round | 2.88  | Oil-Filled (UL<br>Approved) | 60000  | -40°C to 70°C  |
| 97F6878BX             | BX | Genteq  | Standard | 20         | 15  | 280 | 1.75  | Oval  | 3.88  | Oil-Filled (UL<br>Approved) | 60000  | -40°C to 90°C  |
| PB350E000C440DAB<br>X | BX | PROLINE | Standard | 35         |     | 440 | 1.75  | Oval  | 3.88  | Oil-Filled (UL<br>Approved) | 10000  | -40°C to 70°C  |
| 97F6830BX             | BX | Genteq  | Special  | 35         |     | 280 | 1.75  | Oval  | 3.5   | Oil-Filled (UL<br>Approved) | 60000  | -40°C to 90°C  |
| 97F9864BX             | BX | Genteq  | Standard | 35         | 7.5 | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL<br>Approved) | 60000  | -40°C to 70°C  |
| 97F6518               |    | Genteq  | Standard | 8          |     | 330 | 1.75  | Round | 2.88  | Oil-Filled (UL<br>Approved) | 60000  | -40°C to 90°C  |
| 97F9888               |    | Genteq  | Standard | 35         | 10  | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL<br>Approved) | 60000  | -40°C to 70°C  |
| 23B902F080BG1H1       |    | Genteq  | Special  | 9000       |     | 80  | 1.375 | Round | 4.625 | Electrolytic                | 3000   | -40°C to 85°C  |
| 23A312F150DC1H1       |    | Genteq  | Special  | 3100       |     | 150 | 2     | Round | 2.625 | Electrolytic                | 1000   | -40°C to 85°C  |
| 23J172F400EH1H1       |    | Genteq  | Special  | 1700       |     | 400 | 2.5   | Round | 5.125 | Electrolytic                | 2000   | -40°C to 105°C |
| 27L907BR              | BR | Genteq  | Special  | 55         |     | 240 | 1.75  | Oval  | 3.5   | Oil-Filled (UL<br>Approved) | 60000  | -40°C to 90°C  |

|                   |    |         |          |        |     |      |       |       |       |                          |        |                |
|-------------------|----|---------|----------|--------|-----|------|-------|-------|-------|--------------------------|--------|----------------|
| PB800Z050T440EA   |    | PROLINE | Standard | 80     | 5   | 440  | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F9970BX         | BX | Genteq  | Standard | 50     | 5   | 370  | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F8312           |    | Genteq  | Standard | 90     |     | 370  | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23M203F200FL1H1   |    | Genteq  | Special  | 20000  |     | 200  | 3     | Round | 8.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F5727           |    | Genteq  | Special  | 25     | 15  | 370  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9851S          | S  | Genteq  | Stock    | 45     | 5   | 440  | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB200E000P240CABX | BX | PROLINE | Standard | 20     |     | 240  | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F9884BX         | BX | Genteq  | Standard | 45     |     | 370  | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23A433F050DE1H1   |    | Genteq  | Special  | 43000  |     | 50   | 2     | Round | 3.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 23D113F028CB1H1   |    | Genteq  | Special  | 11000  |     | 28   | 1.75  | Round | 2.125 | Electrolytic             | 1000   | -55°C to 85°C  |
| 23F251F250BB1H1   |    | Genteq  | Special  | 250    |     | 250  | 1.375 | Round | 2.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F5452BX         | BX | Genteq  | Special  | 30     | 10  | 370  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23C232F150CC1H1   |    | Genteq  | Special  | 2300   |     | 150  | 1.75  | Round | 2.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F6670           |    | Genteq  | Special  | 38.5   |     | 370  | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23D173F007BB1H1   |    | Genteq  | Special  | 17000  |     | 7.5  | 1.375 | Round | 2.125 | Electrolytic             | 1000   | -55°C to 85°C  |
| 97F9530BX         | BX | Genteq  | Standard | 2.5    |     | 440  | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23B172F250DE1H1   |    | Genteq  | Special  | 1700   |     | 250  | 2     | Round | 3.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F5035BX         | BX | Genteq  | Special  | 5      |     | 440  | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23C352F080BB1H1   |    | Genteq  | Special  | 3500   |     | 80   | 1.375 | Round | 2.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F6703           |    | Genteq  | Standard | 8      |     | 330  | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23M122F250BE1H1   |    | Genteq  | Special  | 1200   |     | 250  | 1.375 | Round | 3.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F9994BX         | BX | Genteq  | Standard | 30     | 5   | 440  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9044           |    | Genteq  | Special  | 15     | 5   | 440  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23A442F080BB1H1   |    | Genteq  | Special  | 4400   |     | 80   | 1.375 | Round | 2.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 27L7000           |    | Genteq  | Standard | 48     |     | 280  | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 100°C |
| 97F6682           |    | Genteq  | Special  | 31.5   |     | 420  | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 42L4683           |    | Genteq  | Stock    | 0.068  |     | 3000 | 0.87  | Round | 1.65  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 23A333F080CI1H1   |    | Genteq  | Special  | 33000  |     | 80   | 1.75  | Round | 5.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 97F6809BX         | BX | Genteq  | Special  | 14     |     | 280  | 1.5   | Oval  | 2.62  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23M232F200DC1H1   |    | Genteq  | Special  | 2300   |     | 200  | 2     | Round | 2.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23C133F075CD1H1   |    | Genteq  | Special  | 13000  |     | 75   | 1.75  | Round | 3.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F9974           |    | Genteq  | Standard | 55     | 10  | 370  | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L695            |    | Genteq  | Standard | 7.5    |     | 440  | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6726BX         | BX | Genteq  | Standard | 30     |     | 330  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| PB350Z100S370DA   |    | PROLINE | Standard | 35     | 10  | 370  | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23H511F350DB1H1   |    | Genteq  | Special  | 510    |     | 350  | 2     | Round | 2.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F7050BX         | BX | Genteq  | Special  | 120    |     | 240  | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23B192F200CF1H1   |    | Genteq  | Special  | 1900   |     | 200  | 1.75  | Round | 4.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23A184F050F11H1   |    | Genteq  | Special  | 180000 |     | 50   | 3     | Round | 5.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 97F8244           |    | Genteq  | Special  | 4      |     | 600  | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9833           |    | Genteq  | Standard | 30     | 5   | 370  | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23C252F250CH1H1   |    | Genteq  | Special  | 2500   |     | 250  | 1.75  | Round | 5.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F9976BX         | BX | Genteq  | Standard | 20     | 7.5 | 440  | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L1025BX         | BX | Genteq  | Standard | 6      |     | 440  | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9063           |    | Genteq  | Standard | 60     | 7.5 | 440  | 2     | Oval  | 6.25  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23F292F150CG1H1   |    | Genteq  | Special  | 2900   |     | 150  | 1.75  | Round | 4.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 23F462F200EH1H1   |    | Genteq  | Special  | 4600   |     | 200  | 2.5   | Round | 5.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F9640BX         | BX | Genteq  | Standard | 35     |     | 440  | 2.5   | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6514           |    | Genteq  | Special  | 20     |     | 170  | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |



|                   |    |         |          |       |      |      |       |       |       |                          |        |                |
|-------------------|----|---------|----------|-------|------|------|-------|-------|-------|--------------------------|--------|----------------|
| PB500Z050S370DA   |    | PROLINE | Standard | 50    | 5    | 370  | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23M102F350BG1H1   |    | Genteq  | Special  | 1000  |      | 350  | 1.375 | Round | 4.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F9895           |    | Genteq  | Standard | 45    | 5    | 370  | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB200E000P440CABX | BX | PROLINE | Standard | 20    |      | 440  | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F5276S          | S  | Genteq  | Stock    | 60    |      | 370  | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB150Y100C440DA   |    | PROLINE | Standard | 15    | 10   | 440  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 27L541BX          | BX | Genteq  | Standard | 14    | 10.5 | 330  | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23H153F200FL1H1   |    | Genteq  | Special  | 15000 |      | 200  | 3     | Round | 8.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23J122F350CH1H1   |    | Genteq  | Special  | 1200  |      | 350  | 1.75  | Round | 5.125 | Electrolytic             | 2000   | -40°C to 105°C |
| 23M392F250C1H1    |    | Genteq  | Special  | 3900  |      | 250  | 1.75  | Round | 5.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F6530BX         | BX | Genteq  | Standard | 40    |      | 280  | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23H152F300CE1H1   |    | Genteq  | Special  | 1500  |      | 300  | 1.75  | Round | 3.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F6887RR         | RR | Genteq  | Standard | 38    | 17   | 280  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| PB150Z075S440DA   |    | PROLINE | Standard | 15    | 7.5  | 440  | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23J561F400DD1H1   |    | Genteq  | Special  | 560   |      | 400  | 2     | Round | 3.125 | Electrolytic             | 2000   | -40°C to 105°C |
| 23C863F060EH1H1   |    | Genteq  | Special  | 86000 |      | 60   | 2.5   | Round | 5.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23M322F350EF1H1   |    | Genteq  | Special  | 3200  |      | 350  | 2.5   | Round | 4.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23C902F150FD1H1   |    | Genteq  | Special  | 9000  |      | 150  | 3     | Round | 3.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23A283F060DD1H1   |    | Genteq  | Special  | 28000 |      | 60   | 2     | Round | 3.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 97F5482BX         | BX | Genteq  | Special  | 30    | 5    | 370  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23A153F080CD1H1   |    | Genteq  | Special  | 15000 |      | 80   | 1.75  | Round | 3.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 23B802F075BE1H1   |    | Genteq  | Special  | 8000  |      | 75   | 1.375 | Round | 3.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23A503F050DF1H1   |    | Genteq  | Special  | 50000 |      | 50   | 2     | Round | 4.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 23M612F350FH1H1   |    | Genteq  | Special  | 6100  |      | 350  | 3     | Round | 5.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| PB200E000P370CABX | BX | PROLINE | Standard | 20    |      | 370  | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23A103F080BE1H1   |    | Genteq  | Special  | 10000 |      | 80   | 1.375 | Round | 3.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 27L443            |    | Genteq  | Standard | 17    | 7    | 400  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23H542F250FE1H1   |    | Genteq  | Special  | 5400  |      | 250  | 3     | Round | 3.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23F253F060DG1H1   |    | Genteq  | Special  | 25000 |      | 60   | 2     | Round | 4.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 23A513F075FD1H1   |    | Genteq  | Special  | 51000 |      | 75   | 3     | Round | 3.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 97F6622BX         | BX | Genteq  | Standard | 24    |      | 400  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23F162F250DF1H1   |    | Genteq  | Special  | 1600  |      | 250  | 2     | Round | 4.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F6836BX         | BX | Genteq  | Standard | 48    |      | 280  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23A452F100CB1H1   |    | Genteq  | Special  | 4500  |      | 100  | 1.75  | Round | 2.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 97F6927BX         | BX | Genteq  | Special  | 11.5  | 3    | 400  | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| PB175E000A370DABX | BX | PROLINE | Standard | 17.5  |      | 370  | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23F193F050BH1H1   |    | Genteq  | Special  | 19000 |      | 50   | 1.375 | Round | 5.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F9003BX         | BX | Genteq  | Standard | 12.5  |      | 370  | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23B203F100FE1H1   |    | Genteq  | Special  | 20000 |      | 100  | 3     | Round | 3.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23A253F080DE1H1   |    | Genteq  | Special  | 25000 |      | 80   | 2     | Round | 3.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| PB800Z050T440EABX | BX | PROLINE | Standard | 80    | 5    | 440  | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F9015BX         | BX | Genteq  | Special  | 15    | 10   | 370  | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6940RC         | RC | Genteq  | Standard | 35    |      | 580  | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F6883BR         | BR | Genteq  | Standard | 36    | 20   | 280  | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23M122F450ED1H1   |    | Genteq  | Special  | 1200  |      | 450  | 2.5   | Round | 3.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23B192F150BF1H1   |    | Genteq  | Special  | 1900  |      | 150  | 1.375 | Round | 4.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23B672F075BD1H1   |    | Genteq  | Special  | 6700  |      | 75   | 1.375 | Round | 3.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F9974BX         | BX | Genteq  | Standard | 55    | 10   | 370  | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L1003BR         | BR | Genteq  | Standard | 20    |      | 440  | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9008BX         | BX | Genteq  | Standard | 45    |      | 370  | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23F601F250BE1H1   |    | Genteq  | Special  | 600   |      | 250  | 1.375 | Round | 3.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 42L2472           |    | Genteq  | Stock    | 0.47  |      | 1200 | 0.91  | Round | 1.65  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| PB500Y050D440GA   |    | PROLINE | Standard | 50    | 5    | 440  | 2     | Oval  | 5.25  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |

|                   |    |         |          |       |     |     |       |       |       |                          |       |                |
|-------------------|----|---------|----------|-------|-----|-----|-------|-------|-------|--------------------------|-------|----------------|
| PB125E000A370CABX | BX | PROLINE | Standard | 12.5  |     | 370 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23H941F350BI1H1   |    | Genteq  | Special  | 940   |     | 350 | 1.375 | Round | 5.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 97F5023           |    | Genteq  | Standard | 30    |     | 440 | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F9603           |    | Genteq  | Standard | 20    |     | 370 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23F463F060EH1H1   |    | Genteq  | Special  | 46000 |     | 60  | 2.5   | Round | 5.125 | Electrolytic             | 1000  | -55°C to 105°C |
| 27L1026BX         | BX | Genteq  | Standard | 8     |     | 370 | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| PB600Z100T440EABX | BX | PROLINE | Standard | 60    | 10  | 440 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| PB800E000T370EA   |    | PROLINE | Standard | 80    |     | 370 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F9677           |    | Genteq  | Standard | 25    | 7.5 | 370 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23F103F075CD1H1   |    | Genteq  | Special  | 10000 |     | 75  | 1.75  | Round | 3.125 | Electrolytic             | 1000  | -55°C to 105°C |
| PB400E000C370DABX | BX | PROLINE | Standard | 40    |     | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23A183F050DB1H1   |    | Genteq  | Special  | 18000 |     | 50  | 2     | Round | 2.125 | Electrolytic             | 1000  | -40°C to 85°C  |
| 27L6095           |    | Genteq  | Special  | 2     |     | 660 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23J272F350E1H1    |    | Genteq  | Special  | 2700  |     | 350 | 2.5   | Round | 5.625 | Electrolytic             | 2000  | -40°C to 105°C |
| PB700Z050T370EA   |    | PROLINE | Standard | 70    | 5   | 370 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23M371F450DB1H1   |    | Genteq  | Special  | 370   |     | 450 | 2     | Round | 2.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23M252F450E1H1    |    | Genteq  | Special  | 2500  |     | 450 | 2.5   | Round | 5.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23M472F200CH1H1   |    | Genteq  | Special  | 4700  |     | 200 | 1.75  | Round | 5.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23M132F400CG1H1   |    | Genteq  | Special  | 1300  |     | 400 | 1.75  | Round | 4.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23B104F075FL1H1   |    | Genteq  | Special  | 10000 | 0   | 75  | 3     | Round | 8.625 | Electrolytic             | 3000  | -40°C to 85°C  |
| 97F6853BX         | BX | Genteq  | Special  | 36    | 12  | 280 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F5818BX         | BX | Genteq  | Special  | 25    | 10  | 370 | 2     | Round | 4.25  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F9741           |    | Genteq  | Standard | 45    | 5   | 440 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F9758           |    | Genteq  | Standard | 45    | 10  | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23B132F150CB1H1   |    | Genteq  | Special  | 1300  |     | 150 | 1.75  | Round | 2.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| 27L877BX          | BX | Genteq  | Standard | 30    | 5   | 370 | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23J772F250F1H1    |    | Genteq  | Special  | 7700  |     | 250 | 3     | Round | 5.625 | Electrolytic             | 2000  | -40°C to 105°C |
| 97F9836           |    | Genteq  | Special  | 30    | 4   | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23D283F020BH1H1   |    | Genteq  | Special  | 28000 |     | 20  | 1.375 | Round | 5.125 | Electrolytic             | 1000  | -55°C to 85°C  |
| 23B702F050BC1H1   |    | Genteq  | Special  | 7000  |     | 50  | 1.375 | Round | 2.625 | Electrolytic             | 3000  | -40°C to 85°C  |
| 23B273F080EE1H1   |    | Genteq  | Special  | 27000 |     | 80  | 2.5   | Round | 3.625 | Electrolytic             | 3000  | -40°C to 85°C  |
| 27L956            |    | Genteq  | Standard | 10    | 10  | 370 | 1.75  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F9882           |    | Genteq  | Standard | 40    | 7.5 | 440 | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| PB600Z075T440EA   |    | PROLINE | Standard | 60    | 7.5 | 440 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 27L5538           |    | Genteq  | Special  | 60    | 10  | 440 | 2     | Oval  | 5.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23B412F080BC1H1   |    | Genteq  | Special  | 4100  |     | 80  | 1.375 | Round | 2.625 | Electrolytic             | 3000  | -40°C to 85°C  |
| 27L1023BX         | BX | Genteq  | Standard | 4     |     | 440 | 1.25  | Oval  | 1.56  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| PB250Y050C440DA   |    | PROLINE | Standard | 25    | 5   | 440 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F6780           |    | Genteq  | Standard | 29    |     | 330 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F6925BR         | BR | Genteq  | Special  | 48    |     | 300 | 2     | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23M442F400FH1H1   |    | Genteq  | Special  | 4400  |     | 400 | 3     | Round | 5.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23H501F400BF1H1   |    | Genteq  | Special  | 500   |     | 400 | 1.375 | Round | 4.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23J212F250DF1H1   |    | Genteq  | Special  | 2100  |     | 250 | 2     | Round | 4.125 | Electrolytic             | 2000  | -40°C to 105°C |
| PB300E000P370DA   |    | PROLINE | Standard | 30    |     | 370 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23J951F350CF1H1   |    | Genteq  | Special  | 950   |     | 350 | 1.75  | Round | 4.125 | Electrolytic             | 2000  | -40°C to 105°C |
| 23C104F060E1H1    |    | Genteq  | Special  | 10000 | 0   | 60  | 2.5   | Round | 5.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| 23A343F050CE1H1   |    | Genteq  | Special  | 34000 |     | 50  | 1.75  | Round | 3.625 | Electrolytic             | 1000  | -40°C to 85°C  |
| 97F6946BX         | BX | Genteq  | Standard | 21    |     | 580 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23M222F350C1H1    |    | Genteq  | Special  | 2200  |     | 350 | 1.75  | Round | 5.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23F572F075BD1H1   |    | Genteq  | Special  | 5700  |     | 75  | 1.375 | Round | 3.125 | Electrolytic             | 1000  | -55°C to 105°C |
| 23C123F100CF1H1   |    | Genteq  | Special  | 12000 |     | 100 | 1.75  | Round | 4.125 | Electrolytic             | 1000  | -45°C to 95°C  |

|                 |    |         |          |       |     |     |       |       |       |                          |       |                |
|-----------------|----|---------|----------|-------|-----|-----|-------|-------|-------|--------------------------|-------|----------------|
| 97F8072         |    | Genteq  | Standard | 65    |     | 370 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 27L497          |    | Genteq  | Standard | 80    |     | 370 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F8046BX       | BX | Genteq  | Standard | 70    |     | 240 | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23A672F150ED1H1 |    | Genteq  | Special  | 6700  |     | 150 | 2.5   | Round | 3.125 | Electrolytic             | 1000  | -40°C to 85°C  |
| 23J382F200DI1H1 |    | Genteq  | Special  | 3800  |     | 200 | 2     | Round | 5.625 | Electrolytic             | 2000  | -40°C to 105°C |
| PB450Z100S370EA |    | PROLINE | Standard | 45    | 10  | 370 | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23B292F250DI1H1 |    | Genteq  | Special  | 2900  |     | 250 | 2     | Round | 5.625 | Electrolytic             | 3000  | -40°C to 85°C  |
| 97F9626         |    | Genteq  | Standard | 15    |     | 440 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F9595BX       | BX | Genteq  | Standard | 6     |     | 370 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F6871         |    | Genteq  | Standard | 12    |     | 280 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23D393F020CF1H1 |    | Genteq  | Special  | 39000 |     | 20  | 1.75  | Round | 4.125 | Electrolytic             | 1000  | -55°C to 85°C  |
| 27L7007BX       | BX | Genteq  | Special  | 18    | 8   | 330 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 100°C |
| 23H162F200BF1H1 |    | Genteq  | Special  | 1600  |     | 200 | 1.375 | Round | 4.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23A682F100BF1H1 |    | Genteq  | Special  | 6800  |     | 100 | 1.375 | Round | 4.125 | Electrolytic             | 1000  | -40°C to 85°C  |
| 23C123F080DC1H1 |    | Genteq  | Special  | 12000 |     | 80  | 2     | Round | 2.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| 23D663F016CI1H1 |    | Genteq  | Special  | 66000 |     | 16  | 3     | Round | 8.625 | Electrolytic             | 1000  | -55°C to 85°C  |
| 23F361F250BC1H1 |    | Genteq  | Special  | 360   |     | 250 | 1.375 | Round | 2.625 | Electrolytic             | 1000  | -55°C to 105°C |
| 23B332F200DH1H1 |    | Genteq  | Special  | 3300  |     | 200 | 2     | Round | 5.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| PB300Y100C370DA |    | PROLINE | Standard | 30    | 10  | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23A902F060BC1H1 |    | Genteq  | Special  | 9000  |     | 60  | 1.375 | Round | 2.625 | Electrolytic             | 1000  | -40°C to 85°C  |
| 23A613F060DI1H1 |    | Genteq  | Special  | 61000 |     | 60  | 2     | Round | 5.625 | Electrolytic             | 1000  | -40°C to 85°C  |
| 23B282F200CI1H1 |    | Genteq  | Special  | 2800  |     | 200 | 1.75  | Round | 5.625 | Electrolytic             | 3000  | -40°C to 85°C  |
| 97F9841BX       | BX | Genteq  | Standard | 45    | 7.5 | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| PB200Z075S370CA |    | PROLINE | Standard | 20    | 7.5 | 370 | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| PB200E000A440EA |    | PROLINE | Standard | 20    |     | 440 | 1.25  | Oval  | 4.75  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23H172F350CI1H1 |    | Genteq  | Special  | 1700  |     | 350 | 1.75  | Round | 5.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23B452F250FF1H1 |    | Genteq  | Special  | 4500  |     | 250 | 3     | Round | 4.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| 23C703F100FL1H1 |    | Genteq  | Special  | 70000 |     | 100 | 3     | Round | 8.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| 97F9002S        | S  | Genteq  | Stock    | 10    |     | 370 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23A433F080DI1H1 |    | Genteq  | Special  | 43000 |     | 80  | 2     | Round | 5.625 | Electrolytic             | 1000  | -40°C to 85°C  |
| 23B333F075EE1H1 |    | Genteq  | Special  | 33000 |     | 75  | 2.5   | Round | 3.625 | Electrolytic             | 3000  | -40°C to 85°C  |
| 27L850          |    | Genteq  | Standard | 11.5  | 7   | 330 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 27L7003BR       | BR | Genteq  | Standard | 26    |     | 330 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 100°C |
| PB150Z050S440CA |    | PROLINE | Standard | 15    | 5   | 440 | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F5023BX       | BX | Genteq  | Standard | 30    |     | 440 | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F8055BX       | BX | Genteq  | Standard | 4     |     | 370 | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F6956         |    | Genteq  | Standard | 22.5  |     | 540 | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23B901F200BE1H1 |    | Genteq  | Special  | 900   |     | 200 | 1.375 | Round | 3.625 | Electrolytic             | 3000  | -40°C to 85°C  |
| 97F6746RC       | RC | Genteq  | Standard | 12    |     | 330 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| PB030E000P370CA |    | PROLINE | Standard | 3     |     | 370 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23C212F250DE1H1 |    | Genteq  | Special  | 2100  |     | 250 | 2     | Round | 3.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| 23F422F100DC1H1 |    | Genteq  | Special  | 4200  |     | 100 | 2     | Round | 2.625 | Electrolytic             | 1000  | -55°C to 105°C |
| 97F6778         |    | Genteq  | Standard | 45    |     | 330 | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23M142F400DF1H1 |    | Genteq  | Special  | 1400  |     | 400 | 2     | Round | 4.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 97F9437BX       | BX | Genteq  | Standard | 15    | 5   | 370 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 27L570S         | S  | Genteq  | Stock    | 5     |     | 370 | 1.25  | Oval  | 1.56  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 27L442BX        | BX | Genteq  | Standard | 28    | 7   | 280 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 27L907RC        | RC | Genteq  | Special  | 55    |     | 240 | 1.75  | Oval  | 3.5   | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23F103F080BI1H1 |    | Genteq  | Special  | 10000 |     | 80  | 1.375 | Round | 5.625 | Electrolytic             | 1000  | -55°C to 105°C |
| 27L5180BX       | BX | Genteq  | Standard | 35    | 10  | 440 | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23J661F300BE1H1 |    | Genteq  | Special  | 660   |     | 300 | 1.375 | Round | 3.625 | Electrolytic             | 2000  | -40°C to 105°C |

|                   |    |         |          |       |     |     |       |       |       |                          |        |                |
|-------------------|----|---------|----------|-------|-----|-----|-------|-------|-------|--------------------------|--------|----------------|
| 27L967BX          | BX | Genteq  | Standard | 45    | 7.5 | 440 | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23M402F350FE1H1   |    | Genteq  | Special  | 4000  |     | 350 | 3     | Round | 3.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23C242F150BF1H1   |    | Genteq  | Special  | 2400  |     | 150 | 1.375 | Round | 4.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23J182F250CF1H1   |    | Genteq  | Special  | 1800  |     | 250 | 1.75  | Round | 4.125 | Electrolytic             | 2000   | -40°C to 105°C |
| 27L853            |    | Genteq  | Standard | 24    | 10  | 400 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 27L956BX          | BX | Genteq  | Standard | 10    | 10  | 370 | 1.75  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6621BX         | BX | Genteq  | Standard | 15    |     | 400 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F9616BX         | BX | Genteq  | Standard | 40    |     | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23H531F450BI1H1   |    | Genteq  | Special  | 530   |     | 450 | 1.375 | Round | 5.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F9899           |    | Genteq  | Standard | 35    | 5   | 440 | 2.5   | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB250Y050C440DABX | BX | PROLINE | Standard | 25    | 5   | 440 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23B602F100BI1H1   |    | Genteq  | Special  | 6000  |     | 100 | 1.375 | Round | 5.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23B113F100ED1H1   |    | Genteq  | Special  | 11000 |     | 100 | 2.5   | Round | 3.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F6924BX         | BX | Genteq  | Standard | 13    |     | 540 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23D273F020CD1H1   |    | Genteq  | Special  | 27000 |     | 20  | 1.75  | Round | 3.125 | Electrolytic             | 1000   | -55°C to 85°C  |
| PB550E000T440EA   |    | PROLINE | Standard | 55    |     | 440 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23M592F300EH1H1   |    | Genteq  | Special  | 5900  |     | 300 | 2.5   | Round | 5.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23B232F150BG1H1   |    | Genteq  | Special  | 2300  |     | 150 | 1.375 | Round | 4.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23M642F200EE1H1   |    | Genteq  | Special  | 6400  |     | 200 | 2.5   | Round | 3.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23B212F100BC1H1   |    | Genteq  | Special  | 2100  |     | 100 | 1.375 | Round | 2.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F8066BX         | BX | Genteq  | Standard | 35    |     | 370 | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9080           |    | Genteq  | Standard | 12.5  |     | 440 | 1.25  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23J102F200BE1H1   |    | Genteq  | Special  | 1000  |     | 200 | 1.375 | Round | 3.625 | Electrolytic             | 2000   | -40°C to 105°C |
| 23H132F400C11H1   |    | Genteq  | Special  | 1300  |     | 400 | 1.75  | Round | 5.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23J113F200FL1H1   |    | Genteq  | Special  | 11000 |     | 200 | 3     | Round | 8.625 | Electrolytic             | 2000   | -40°C to 105°C |
| PB060E000A370BABX | BX | PROLINE | Standard | 6     |     | 370 | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23D123F035BF1H1   |    | Genteq  | Special  | 12000 |     | 35  | 1.375 | Round | 4.125 | Electrolytic             | 1000   | -55°C to 85°C  |
| 23H741F350BG1H1   |    | Genteq  | Special  | 740   |     | 350 | 1.375 | Round | 4.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 27L55             |    | Genteq  | Standard | 35    | 20  | 280 | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F6673           |    | Genteq  | Special  | 14    |     | 480 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23M431F350BC1H1   |    | Genteq  | Special  | 430   |     | 350 | 1.375 | Round | 2.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23B903F050FG1H1   |    | Genteq  | Special  | 90000 |     | 50  | 3     | Round | 4.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23J222F400FG1H1   |    | Genteq  | Special  | 2200  |     | 400 | 3     | Round | 4.625 | Electrolytic             | 2000   | -40°C to 105°C |
| 97F8061           |    | Genteq  | Standard | 15    |     | 370 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB200E000A440EAS  | S  | PROLINE | Stock    | 20    |     | 440 | 1.25  | Oval  | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F9022           |    | Genteq  | Special  | 35    | 7.5 | 370 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23M731F400CD1H1   |    | Genteq  | Special  | 730   |     | 400 | 1.75  | Round | 3.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23F172F150DC1H1   |    | Genteq  | Special  | 1700  |     | 150 | 2     | Round | 2.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F6784BX         | BX | Genteq  | Standard | 36    |     | 330 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 27L862RR          | RR | Genteq  | Standard | 35    | 24  | 400 | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| PB400Y075C440EA   |    | PROLINE | Standard | 40    | 7.5 | 440 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23J142F300DE1H1   |    | Genteq  | Special  | 1400  |     | 300 | 2     | Round | 3.625 | Electrolytic             | 2000   | -40°C to 105°C |
| 23B103F080DC1H1   |    | Genteq  | Special  | 10000 |     | 80  | 2     | Round | 2.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23H441F450BG1H1   |    | Genteq  | Special  | 440   |     | 450 | 1.375 | Round | 4.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F6935           |    | Genteq  | Special  | 10.5  |     | 540 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23J431F300BC1H1   |    | Genteq  | Special  | 430   |     | 300 | 1.375 | Round | 2.625 | Electrolytic             | 2000   | -40°C to 105°C |
| 40L6101           |    | Genteq  | Stock    | 1     |     | 600 | 0.67  | Oval  | 1.25  | Dry-Axial Leaded         | 100000 | -55°C to 105°C |
| 97F6884BR         | BR | Genteq  | Standard | 33    | 15  | 280 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23M123F300FL1H1   |    | Genteq  | Special  | 12000 |     | 300 | 3     | Round | 8.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23M601F400BF1H1   |    | Genteq  | Special  | 600   |     | 400 | 1.375 | Round | 4.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23A842F080BD1H1   |    | Genteq  | Special  | 8400  |     | 80  | 1.375 | Round | 3.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 97F9042           |    | Genteq  | Standard | 55    |     | 440 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23B113F100DG1H1   |    | Genteq  | Special  | 11000 |     | 100 | 2     | Round | 4.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23H112F400CH1H1   |    | Genteq  | Special  | 1100  |     | 400 | 1.75  | Round | 5.125 | Electrolytic             | 2000   | -40°C to 85°C  |

|                   |    |         |          |       |     |     |       |       |       |                          |       |                |
|-------------------|----|---------|----------|-------|-----|-----|-------|-------|-------|--------------------------|-------|----------------|
| PB150Z100S440DABX | BX | PROLINE | Standard | 15    | 10  | 440 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23B123F060CC1H1   |    | Genteq  | Special  | 12000 |     | 60  | 1.75  | Round | 2.625 | Electrolytic             | 3000  | -40°C to 85°C  |
| 23H522F300E1H1    |    | Genteq  | Special  | 5200  |     | 300 | 2.5   | Round | 5.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23J472F250EH1H1   |    | Genteq  | Special  | 4700  |     | 250 | 2.5   | Round | 5.125 | Electrolytic             | 2000  | -40°C to 105°C |
| 23M102F300BE1H1   |    | Genteq  | Special  | 1000  |     | 300 | 1.375 | Round | 3.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23J811F350CE1H1   |    | Genteq  | Special  | 810   |     | 350 | 1.75  | Round | 3.625 | Electrolytic             | 2000  | -40°C to 105°C |
| 23J421F400DC1H1   |    | Genteq  | Special  | 420   |     | 400 | 2     | Round | 2.625 | Electrolytic             | 2000  | -40°C to 105°C |
| 23C903F075FJ1H1   |    | Genteq  | Special  | 90000 |     | 75  | 3     | Round | 5.875 | Electrolytic             | 1000  | -45°C to 95°C  |
| 27L7005           |    | Genteq  | Special  | 36    | 12  | 280 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 100°C |
| 97F6882BX         | BX | Genteq  | Standard | 24    | 8   | 280 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F6601BX         | BX | Genteq  | Standard | 10    |     | 400 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| PB075E000P440CABX | BX | PROLINE | Standard | 7.5   |     | 440 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23A123F075CC1H1   |    | Genteq  | Special  | 12000 |     | 75  | 1.75  | Round | 2.625 | Electrolytic             | 1000  | -40°C to 85°C  |
| 97F6603           |    | Genteq  | Special  | 24    |     | 400 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23M122F250DB1H1   |    | Genteq  | Special  | 1200  |     | 250 | 2     | Round | 2.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23M342F200CF1H1   |    | Genteq  | Special  | 3400  |     | 200 | 1.75  | Round | 4.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23B453F080FF1H1   |    | Genteq  | Special  | 45000 |     | 80  | 3     | Round | 4.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| PB200Z075S440DA   |    | PROLINE | Standard | 20    | 7.5 | 440 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23A223F080CF1H1   |    | Genteq  | Special  | 22000 |     | 80  | 1.75  | Round | 4.125 | Electrolytic             | 1000  | -40°C to 85°C  |
| 23B122F200BG1H1   |    | Genteq  | Special  | 1200  |     | 200 | 1.375 | Round | 4.625 | Electrolytic             | 3000  | -40°C to 85°C  |
| 27L428BX          | BX | Genteq  | Standard | 24    | 15  | 400 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23A222F150DB1H1   |    | Genteq  | Special  | 2200  |     | 150 | 2     | Round | 2.125 | Electrolytic             | 1000  | -40°C to 85°C  |
| 23C541F250BC1H1   |    | Genteq  | Special  | 540   |     | 250 | 1.375 | Round | 2.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| 23M232F400FD1H1   |    | Genteq  | Special  | 2300  |     | 400 | 3     | Round | 3.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23C132F250DC1H1   |    | Genteq  | Special  | 1300  |     | 250 | 2     | Round | 2.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| 27L551            |    | Genteq  | Standard | 20    |     | 440 | 1.25  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F9606BX         | BX | Genteq  | Standard | 25    |     | 370 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23F114F050FH1H1   |    | Genteq  | Special  | 11000 |     | 50  | 3     | Round | 5.125 | Electrolytic             | 1000  | -55°C to 105°C |
| PB300E000C440DAS  | S  | PROLINE | Stock    | 30    |     | 440 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F5450BX         | BX | Genteq  | Special  | 30    | 7.5 | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F9897           |    | Genteq  | Standard | 60    | 5   | 440 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F8037S          | S  | Genteq  | Stock    | 25    |     | 240 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| PB550Z050T370DA   |    | PROLINE | Standard | 55    | 5   | 370 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F6812BX         | BX | Genteq  | Standard | 17.5  |     | 280 | 1.5   | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23F812F100DF1H1   |    | Genteq  | Special  | 8100  |     | 100 | 2     | Round | 4.125 | Electrolytic             | 1000  | -55°C to 105°C |
| 23B542F200EH1H1   |    | Genteq  | Special  | 5400  |     | 200 | 2.5   | Round | 5.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| 97F9047           |    | Genteq  | Standard | 20    | 5   | 440 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23C123F150FE1H1   |    | Genteq  | Special  | 12000 |     | 150 | 3     | Round | 3.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| 97F6907BX         | BX | Genteq  | Special  | 10    |     | 480 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F9437           |    | Genteq  | Standard | 15    | 5   | 370 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 25L752            |    | Genteq  | Special  | 25    | 4   | 440 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23H501F250BB1H1   |    | Genteq  | Special  | 500   |     | 250 | 1.375 | Round | 2.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| PB175E000A370DA   |    | PROLINE | Standard | 17.5  |     | 370 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F6770BX         | BX | Genteq  | Standard | 17.5  |     | 330 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23A213F050BF1H1   |    | Genteq  | Special  | 21000 |     | 50  | 1.375 | Round | 4.125 | Electrolytic             | 1000  | -40°C to 85°C  |
| 97F5388           |    | Genteq  | Standard | 12.5  |     | 440 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23A532F150CG1H1   |    | Genteq  | Special  | 5300  |     | 150 | 1.75  | Round | 4.625 | Electrolytic             | 1000  | -40°C to 85°C  |
| 97F5159           |    | Genteq  | Standard | 40    |     | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| PB350Z075S440EABX | BX | PROLINE | Standard | 35    | 7.5 | 440 | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23B552F080BD1H1   |    | Genteq  | Special  | 5500  |     | 80  | 1.375 | Round | 3.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| 97F9045           |    | Genteq  | Special  | 15    | 7.5 | 440 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23C203F150F1H1    |    | Genteq  | Special  | 20000 |     | 150 | 3     | Round | 5.625 | Electrolytic             | 1000  | -45°C to 95°C  |

|                   |    |         |          |       |     |     |       |       |       |                          |        |                |
|-------------------|----|---------|----------|-------|-----|-----|-------|-------|-------|--------------------------|--------|----------------|
| 97F6930BR         | BR | Genteq  | Standard | 10    |     | 580 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F5330BX         | BX | Genteq  | Special  | 25    | 4   | 440 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB450Z075S370DABX | BX | PROLINE | Standard | 45    | 7.5 | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F9635S          | S  | Genteq  | Stock    | 30    |     | 440 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23B493F060EF1H1   |    | Genteq  | Special  | 49000 |     | 60  | 2.5   | Round | 4.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23H362F200CH1H1   |    | Genteq  | Special  | 3600  |     | 200 | 1.75  | Round | 5.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23A323F050BI1H1   |    | Genteq  | Special  | 32000 |     | 50  | 1.375 | Round | 5.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 23M162F400DG1H1   |    | Genteq  | Special  | 1600  |     | 400 | 2     | Round | 4.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23J202F300CI1H1   |    | Genteq  | Special  | 2000  |     | 300 | 1.75  | Round | 5.625 | Electrolytic             | 2000   | -40°C to 105°C |
| 23B723F060FF1H1   |    | Genteq  | Special  | 72000 |     | 60  | 3     | Round | 4.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23M672F350FI1H1   |    | Genteq  | Special  | 6700  |     | 350 | 3     | Round | 5.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F9642BX         | BX | Genteq  | Standard | 40    |     | 440 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23A913F080FH1H1   |    | Genteq  | Special  | 91000 |     | 80  | 3     | Round | 5.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 97F8048BX         | BX | Genteq  | Standard | 80    |     | 240 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L1050           |    | Genteq  | Standard | 25    | 10  | 370 | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23B563F075EI1H1   |    | Genteq  | Special  | 56000 |     | 75  | 2.5   | Round | 5.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23F661F250CC1H1   |    | Genteq  | Special  | 660   |     | 250 | 1.75  | Round | 2.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 27L7001           |    | Genteq  | Standard | 10    |     | 400 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 100°C |
| 23C143F150FF1H1   |    | Genteq  | Special  | 14000 |     | 150 | 3     | Round | 4.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F8240           |    | Genteq  | Special  | 1.5   |     | 600 | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 40L3331           |    | Genteq  | Stock    | 3.3   |     | 400 | 0.69  | Oval  | 1.25  | Dry-Axial Leaded         | 100000 | -55°C to 105°C |
| 97F9951           |    | Genteq  | Standard | 40    | 7.5 | 440 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6858           |    | Genteq  | Standard | 10    |     | 280 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23H182F450FF1H1   |    | Genteq  | Special  | 1800  |     | 450 | 3     | Round | 4.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 27L7005BX         | BX | Genteq  | Special  | 36    | 12  | 280 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 100°C |
| 97F9024           |    | Genteq  | Special  | 40    | 5   | 370 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB150E000P440CA   |    | PROLINE | Standard | 15    |     | 440 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23F723F080FL1H1   |    | Genteq  | Special  | 72000 |     | 80  | 3     | Round | 8.625 | Electrolytic             | 1000   | -55°C to 105°C |
| PB650E000T370DA   |    | PROLINE | Standard | 65    |     | 370 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23B162F200CE1H1   |    | Genteq  | Special  | 1600  |     | 200 | 1.75  | Round | 3.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| PB800Z100T440EA   |    | PROLINE | Standard | 80    | 10  | 440 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F9741BX         | BX | Genteq  | Standard | 45    | 5   | 440 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23M312F200DD1H1   |    | Genteq  | Special  | 3100  |     | 200 | 2     | Round | 3.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23M701F350BE1H1   |    | Genteq  | Special  | 700   |     | 350 | 1.375 | Round | 3.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| PB450Z075T440DA   |    | PROLINE | Standard | 45    | 7.5 | 440 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23J632F200EI1H1   |    | Genteq  | Special  | 6300  |     | 200 | 2.5   | Round | 5.625 | Electrolytic             | 2000   | -40°C to 105°C |
| 97F9043           |    | Genteq  | Standard | 60    |     | 440 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23B113F060BE1H1   |    | Genteq  | Special  | 11000 |     | 60  | 1.375 | Round | 3.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23C463F060DG1H1   |    | Genteq  | Special  | 46000 |     | 60  | 2     | Round | 4.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F6757BX         | BX | Genteq  | Standard | 34    |     | 330 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23D612F028BB1H1   |    | Genteq  | Special  | 6100  |     | 28  | 1.375 | Round | 2.125 | Electrolytic             | 1000   | -55°C to 85°C  |
| 23M401F400CB1H1   |    | Genteq  | Special  | 400   |     | 400 | 1.75  | Round | 2.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23C882F100BH1H1   |    | Genteq  | Special  | 8800  |     | 100 | 1.375 | Round | 5.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23J252F400FH1H1   |    | Genteq  | Special  | 2500  |     | 400 | 3     | Round | 5.125 | Electrolytic             | 2000   | -40°C to 105°C |
| 97F9972BX         | BX | Genteq  | Standard | 50    | 10  | 370 | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F5362BX         | BX | Genteq  | Special  | 25    | 7.5 | 440 | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23H132F350CG1H1   |    | Genteq  | Special  | 1300  |     | 350 | 1.75  | Round | 4.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| PB500Y075D440GABX | BX | PROLINE | Standard | 50    | 7.5 | 440 | 2     | Oval  | 5.25  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23C603F050DH1H1   |    | Genteq  | Special  | 60000 |     | 50  | 2     | Round | 5.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F6759           |    | Genteq  | Standard | 24    |     | 330 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| PB350E000S370CABX | BX | PROLINE | Standard | 35    |     | 370 | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 41L4221           |    | Genteq  | Stock    | 2.2   |     | 400 | 0.69  | Round | 1.22  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |

|                   |    |         |          |        |     |      |       |       |       |                          |        |                |
|-------------------|----|---------|----------|--------|-----|------|-------|-------|-------|--------------------------|--------|----------------|
| 27L570BX          | BX | Genteq  | Standard | 5      |     | 370  | 1.25  | Oval  | 1.56  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6921           |    | Genteq  | Standard | 26     |     | 580  | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F6522           |    | Genteq  | Standard | 24     |     | 280  | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23D173F016BD1H1   |    | Genteq  | Special  | 17000  |     | 16   | 1.375 | Round | 3.125 | Electrolytic             | 1000   | -55°C to 85°C  |
| 97F6869BX         | BX | Genteq  | Standard | 42     |     | 280  | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F5054           |    | Genteq  | Standard | 30     |     | 370  | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6708           |    | Genteq  | Standard | 13     |     | 330  | 1.5   | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 27L727RR          | RR | Genteq  | Standard | 45     | 19  | 300  | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23D663F007CE1H1   |    | Genteq  | Special  | 66000  |     | 7.5  | 1.75  | Round | 3.625 | Electrolytic             | 1000   | -55°C to 85°C  |
| 97F6509           |    | Genteq  | Standard | 38     |     | 280  | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23D292F055BB1H1   |    | Genteq  | Special  | 2900   |     | 55   | 1.375 | Round | 2.125 | Electrolytic             | 1000   | -55°C to 85°C  |
| 97F6680BR         | BR | Genteq  | Special  | 24     |     | 480  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F6606BX         | BX | Genteq  | Standard | 10     |     | 400  | 1.5   | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23A592F150DF1H1   |    | Genteq  | Special  | 5900   |     | 150  | 2     | Round | 4.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 97F9319BX         | BX | Genteq  | Special  | 55     | 7.5 | 440  | 2     | Oval  | 5.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6684BX         | BX | Genteq  | Special  | 12.5   |     | 440  | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 42L2152           |    | Genteq  | Stock    | 0.15   |     | 1200 | 0.67  | Round | 1.22  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 97F5205BX         | BX | Genteq  | Special  | 35     |     | 440  | 2.5   | Round | 3.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 40L6682           |    | Genteq  | Stock    | 0.68   |     | 600  | 0.55  | Oval  | 1.25  | Dry-Axial Leaded         | 100000 | -55°C to 105°C |
| 23A104F050FE1H1   |    | Genteq  | Special  | 100000 |     | 50   | 3     | Round | 3.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| PB400E000C440DABX | BX | PROLINE | Standard | 40     |     | 440  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 27L1003BX         | BX | Genteq  | Standard | 20     |     | 440  | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F5670           |    | Genteq  | Special  | 40     | 7.5 | 240  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9038BX         | BX | Genteq  | Standard | 17.5   |     | 440  | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23D532F055CB1H1   |    | Genteq  | Special  | 5300   |     | 55   | 1.75  | Round | 2.125 | Electrolytic             | 1000   | -55°C to 85°C  |
| 23F813F050FF1H1   |    | Genteq  | Special  | 81000  |     | 50   | 3     | Round | 4.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 27L1045           |    | Genteq  | Standard | 60     |     | 370  | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23C263F100EF1H1   |    | Genteq  | Special  | 26000  |     | 100  | 2.5   | Round | 4.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23H132F450EF1H1   |    | Genteq  | Special  | 1300   |     | 450  | 2.5   | Round | 4.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 41L4100           |    | Genteq  | Stock    | 10     |     | 400  | 1.18  | Round | 1.65  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 97F8044S          | S  | Genteq  | Stock    | 60     |     | 240  | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23M701F400DC1H1   |    | Genteq  | Special  | 700    |     | 400  | 2     | Round | 2.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 27L967            |    | Genteq  | Standard | 45     | 7.5 | 440  | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23B762F150FD1H1   |    | Genteq  | Special  | 7600   |     | 150  | 3     | Round | 3.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| PB550Z050T440EA   |    | PROLINE | Standard | 55     | 5   | 440  | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| PB250E000P440DABX | BX | PROLINE | Standard | 25     |     | 440  | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23C672F200FE1H1   |    | Genteq  | Special  | 6700   |     | 200  | 3     | Round | 3.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23B183F050BH1H1   |    | Genteq  | Special  | 18000  |     | 50   | 1.375 | Round | 5.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 27L470BX          | BX | Genteq  | Standard | 25     | 10  | 300  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23C213F080CG1H1   |    | Genteq  | Special  | 21000  |     | 80   | 1.75  | Round | 4.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23F232F150DD1H1   |    | Genteq  | Special  | 2300   |     | 150  | 2     | Round | 3.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 23F452F080CB1H1   |    | Genteq  | Special  | 4500   |     | 80   | 1.75  | Round | 2.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F6534BX         | BX | Genteq  | Special  | 28     |     | 170  | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23A911F150BB1H1   |    | Genteq  | Special  | 910    |     | 150  | 1.375 | Round | 2.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 27L514BX          | BX | Genteq  | Standard | 60     |     | 370  | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9614BX         | BX | Genteq  | Standard | 40     |     | 370  | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6907           |    | Genteq  | Special  | 10     |     | 480  | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F9630           |    | Genteq  | Standard | 20     |     | 440  | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB800Z075T370EA   |    | PROLINE | Standard | 80     | 7.5 | 370  | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |

|                   |    |         |          |       |     |      |       |       |       |                          |        |                |
|-------------------|----|---------|----------|-------|-----|------|-------|-------|-------|--------------------------|--------|----------------|
| PB500Z100S370EABX | BX | PROLINE | Standard | 50    | 10  | 370  | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23C173F060BF1H1   |    | Genteq  | Special  | 17000 |     | 60   | 1.375 | Round | 4.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F6683           |    | Genteq  | Special  | 21    |     | 480  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| PB040E000A370AA   |    | PROLINE | Standard | 4     |     | 370  | 1.25  | Oval  | 1.56  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F6926BX         | BX | Genteq  | Standard | 26    |     | 400  | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23D593F016CH1H1   |    | Genteq  | Special  | 59000 |     | 16   | 1.75  | Round | 5.125 | Electrolytic             | 1000   | -55°C to 85°C  |
| 23F742F100CG1H1   |    | Genteq  | Special  | 7400  |     | 100  | 1.75  | Round | 4.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 23J401F250BB1H1   |    | Genteq  | Special  | 400   |     | 250  | 1.375 | Round | 2.125 | Electrolytic             | 2000   | -40°C to 105°C |
| 27L907BX          | BX | Genteq  | Special  | 55    |     | 240  | 1.75  | Oval  | 3.5   | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23B113F100C11H1   |    | Genteq  | Special  | 11000 |     | 100  | 1.75  | Round | 5.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23B123F080B11H1   |    | Genteq  | Special  | 12000 |     | 80   | 1.375 | Round | 5.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23F753F050EH1H1   |    | Genteq  | Special  | 75000 |     | 50   | 2.5   | Round | 5.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 23F403F075FE1H1   |    | Genteq  | Special  | 40000 |     | 75   | 3     | Round | 3.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 23M112F300BF1H1   |    | Genteq  | Special  | 1100  |     | 300  | 1.375 | Round | 4.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 27L576            |    | Genteq  | Special  | 20    | 8   | 400  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| PB200E000S440CA   |    | PROLINE | Standard | 20    |     | 440  | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23D513F020CH1H1   |    | Genteq  | Special  | 51000 |     | 20   | 1.75  | Round | 5.125 | Electrolytic             | 1000   | -55°C to 85°C  |
| 97F6695           |    | Genteq  | Special  | 6.5   |     | 480  | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F6777RC         | RC | Genteq  | Special  | 35    |     | 330  | 1.5   | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| PB300E000A370EABX | BX | PROLINE | Standard | 30    |     | 370  | 1.25  | Oval  | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F6925RC         | RC | Genteq  | Special  | 48    |     | 300  | 2     | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| PB450E000S370DA   |    | PROLINE | Standard | 45    |     | 370  | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23F522F200E11H1   |    | Genteq  | Special  | 5200  |     | 200  | 2.5   | Round | 5.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 23A153F050BD1H1   |    | Genteq  | Special  | 15000 |     | 50   | 1.375 | Round | 3.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 97F8056BX         | BX | Genteq  | Standard | 5     |     | 370  | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6902           |    | Genteq  | Special  | 55    |     | 240  | 2     | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23M301F450BD1H1   |    | Genteq  | Special  | 300   |     | 450  | 1.375 | Round | 3.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F6727BR         | BR | Genteq  | Standard | 32    |     | 330  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F6919           |    | Genteq  | Standard | 16    |     | 540  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23A682F150C11H1   |    | Genteq  | Special  | 6800  |     | 150  | 1.75  | Round | 5.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 27L5200           |    | Genteq  | Standard | 50    | 5   | 440  | 2     | Oval  | 5.25  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23H172F450EH1H1   |    | Genteq  | Special  | 1700  |     | 450  | 2.5   | Round | 5.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| PB200Z075S440DABX | BX | PROLINE | Standard | 20    | 7.5 | 440  | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23B712F250FJ1H1   |    | Genteq  | Special  | 7100  |     | 250  | 3     | Round | 5.875 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F6773           |    | Genteq  | Standard | 22.5  |     | 330  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F9845BX         | BX | Genteq  | Standard | 40    | 7.5 | 370  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23C681F250CB1H1   |    | Genteq  | Special  | 680   |     | 250  | 1.75  | Round | 2.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F6778RC         | RC | Genteq  | Standard | 45    |     | 330  | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23B263F060DE1H1   |    | Genteq  | Special  | 26000 |     | 60   | 2     | Round | 3.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23F502F200FF1H1   |    | Genteq  | Special  | 5000  |     | 200  | 3     | Round | 4.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 42L3152           |    | Genteq  | Stock    | 0.15  |     | 2000 | 0.77  | Round | 1.65  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 23B123F075CD1H1   |    | Genteq  | Special  | 12000 |     | 75   | 1.75  | Round | 3.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F9817           |    | Genteq  | Standard | 60    | 7.5 | 370  | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F8036           |    | Genteq  | Standard | 15    |     | 240  | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23F302F100DB1H1   |    | Genteq  | Special  | 3000  |     | 100  | 2     | Round | 2.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 23B533F050EF1H1   |    | Genteq  | Special  | 53000 |     | 50   | 2.5   | Round | 4.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23M122F400DE1H1   |    | Genteq  | Special  | 1200  |     | 400  | 2     | Round | 3.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23C144F060F11H1   |    | Genteq  | Special  | 14000 | 0   | 60   | 3     | Round | 5.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| PB550Z100T440EA   |    | PROLINE | Standard | 55    | 10  | 440  | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23A114F050EH1H1   |    | Genteq  | Special  | 11000 | 0   | 50   | 2.5   | Round | 5.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 23M172F250BG1H1   |    | Genteq  | Special  | 1700  |     | 250  | 1.375 | Round | 4.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23H292F200CF1H1   |    | Genteq  | Special  | 2900  |     | 200  | 1.75  | Round | 4.125 | Electrolytic             | 2000   | -40°C to 85°C  |



|                   |    |         |          |       |     |     |       |       |       |                          |       |                |
|-------------------|----|---------|----------|-------|-----|-----|-------|-------|-------|--------------------------|-------|----------------|
| 25L6755BR         | BR | Genteq  | Standard | 20    | 8   | 280 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| PB350Y050C370DA   |    | PROLINE | Standard | 35    | 5   | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F9054BX         | BX | Genteq  | Special  | 30    | 10  | 440 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23F802F150EI1H1   |    | Genteq  | Special  | 8000  |     | 150 | 2.5   | Round | 5.625 | Electrolytic             | 1000  | -55°C to 105°C |
| 97F6801           |    | Genteq  | Standard | 6     |     | 280 | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23B682F150DI1H1   |    | Genteq  | Special  | 6800  |     | 150 | 2     | Round | 5.625 | Electrolytic             | 3000  | -40°C to 85°C  |
| 97F9758BX         | BX | Genteq  | Standard | 45    | 10  | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F5814           |    | Genteq  | Special  | 25    | 5   | 370 | 2     | Round | 4.25  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F9071BX         | BX | Genteq  | Special  | 35    |     | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23J771F300BF1H1   |    | Genteq  | Special  | 770   |     | 300 | 1.375 | Round | 4.125 | Electrolytic             | 2000  | -40°C to 105°C |
| PB800Z050T370EABX | BX | PROLINE | Standard | 80    | 5   | 370 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F8076           |    | Genteq  | Special  | 50    |     | 480 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23B782F200FH1H1   |    | Genteq  | Special  | 7800  |     | 200 | 3     | Round | 5.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| 23J112F300BI1H1   |    | Genteq  | Special  | 1100  |     | 300 | 1.375 | Round | 5.625 | Electrolytic             | 2000  | -40°C to 105°C |
| 97F8245BX         | BX | Genteq  | Standard | 5     |     | 600 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 27L947BX          | BX | Genteq  | Standard | 45    | 7.5 | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F5115           |    | Genteq  | Special  | 35    |     | 440 | 2     | Round | 4.25  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F8056           |    | Genteq  | Standard | 5     |     | 370 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23B453F060DI1H1   |    | Genteq  | Special  | 45000 |     | 60  | 2     | Round | 5.625 | Electrolytic             | 3000  | -40°C to 85°C  |
| 97F5481BX         | BX | Genteq  | Special  | 25    | 10  | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| PB450E000C440EABX | BX | PROLINE | Standard | 45    |     | 440 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| PB200E000A370DABX | BX | PROLINE | Standard | 20    |     | 370 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F9451BX         | BX | Genteq  | Standard | 20    | 10  | 440 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23F222F250DH1H1   |    | Genteq  | Special  | 2200  |     | 250 | 2     | Round | 5.125 | Electrolytic             | 1000  | -55°C to 105°C |
| 23J162F350DI1H1   |    | Genteq  | Special  | 1600  |     | 350 | 2     | Round | 5.625 | Electrolytic             | 2000  | -40°C to 105°C |
| 97F6771           |    | Genteq  | Standard | 18    |     | 330 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23J981F300CD1H1   |    | Genteq  | Special  | 980   |     | 300 | 1.75  | Round | 3.125 | Electrolytic             | 2000  | -40°C to 105°C |
| 97F6696BX         | BX | Genteq  | Special  | 38    |     | 300 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F8049           |    | Genteq  | Standard | 85    |     | 240 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23B203F060CE1H1   |    | Genteq  | Special  | 20000 |     | 60  | 1.75  | Round | 3.625 | Electrolytic             | 3000  | -40°C to 85°C  |
| 97F6762           |    | Genteq  | Standard | 11    |     | 330 | 1.5   | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F9998BX         | BX | Genteq  | Standard | 15    | 7.5 | 440 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 27L1054S          | S  | Genteq  | Stock    | 20    |     | 440 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23F603F080FJ1H1   |    | Genteq  | Special  | 60000 |     | 80  | 3     | Round | 5.875 | Electrolytic             | 1000  | -55°C to 105°C |
| 23F672F200FH1H1   |    | Genteq  | Special  | 6700  |     | 200 | 3     | Round | 5.125 | Electrolytic             | 1000  | -55°C to 105°C |
| 97F8043           |    | Genteq  | Standard | 55    |     | 240 | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F5501           |    | Genteq  | Special  | 25    | 5   | 440 | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23F203F075CH1H1   |    | Genteq  | Special  | 20000 |     | 75  | 1.75  | Round | 5.125 | Electrolytic             | 1000  | -55°C to 105°C |
| 23J212F350EG1H1   |    | Genteq  | Special  | 2100  |     | 350 | 2.5   | Round | 4.625 | Electrolytic             | 2000  | -40°C to 105°C |
| 97F6516BX         | BX | Genteq  | Standard | 22.5  |     | 280 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| PB050E000A370AA   |    | PROLINE | Standard | 5     |     | 370 | 1.25  | Oval  | 1.56  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F5670BX         | BX | Genteq  | Special  | 40    | 7.5 | 240 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F6812RC         | RC | Genteq  | Standard | 17.5  |     | 280 | 1.5   | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| PB450E000C370DA   |    | PROLINE | Standard | 45    |     | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23A473F080FD1H1   |    | Genteq  | Special  | 47000 |     | 80  | 3     | Round | 3.125 | Electrolytic             | 1000  | -40°C to 85°C  |
| PB300E000C370CA   |    | PROLINE | Standard | 30    |     | 370 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23M401F450CC1H1   |    | Genteq  | Special  | 400   |     | 450 | 1.75  | Round | 2.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 97F6606           |    | Genteq  | Standard | 10    |     | 400 | 1.5   | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |

|                   |    |         |          |            |     |      |       |       |       |                          |        |                |
|-------------------|----|---------|----------|------------|-----|------|-------|-------|-------|--------------------------|--------|----------------|
| 97F6836RC         | RC | Genteq  | Standard | 48         |     | 280  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23C173F080CF1H1   |    | Genteq  | Special  | 17000      |     | 80   | 1.75  | Round | 4.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 27L176            |    | Genteq  | Special  | 7.5        |     | 540  | 1.5   | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 27L865BR          | BR | Genteq  | Standard | 15         | 6   | 400  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23F772F200FJ1H1   |    | Genteq  | Special  | 7700       |     | 200  | 3     | Round | 5.875 | Electrolytic             | 1000   | -55°C to 105°C |
| PB550Z075T440EAS  | S  | PROLINE | Stock    | 55         | 7.5 | 440  | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 25L2754           |    | Genteq  | Standard | 35         | 10  | 440  | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23B843F080FL1H1   |    | Genteq  | Special  | 84000      |     | 80   | 3     | Round | 8.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F9996           |    | Genteq  | Standard | 40         | 7.5 | 440  | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23H482F400FL1H1   |    | Genteq  | Special  | 4800       |     | 400  | 3     | Round | 8.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23D223F035CF1H1   |    | Genteq  | Special  | 22000      |     | 35   | 1.75  | Round | 4.125 | Electrolytic             | 1000   | -55°C to 85°C  |
| PB600E000D440HA   |    | PROLINE | Standard | 60         |     | 440  | 2     | Oval  | 4.25  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23M232F400EF1H1   |    | Genteq  | Special  | 2300       |     | 400  | 2.5   | Round | 4.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F5337           |    | Genteq  | Standard | 4          |     | 440  | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB800Z100T440EABX | BX | PROLINE | Standard | 80         | 10  | 440  | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23H481F450CD1H1   |    | Genteq  | Special  | 480        |     | 450  | 1.75  | Round | 3.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 40L3221           |    | Genteq  | Stock    | 2.2        |     | 400  | 0.56  | Oval  | 1.25  | Dry-Axial Leaded         | 100000 | -55°C to 105°C |
| 27L591BX          | BX | Genteq  | Standard | 35         | 15  | 300  | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F9152           |    | Genteq  | Standard | 40         |     | 440  | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23M143F200FH1H1   |    | Genteq  | Special  | 14000      |     | 200  | 3     | Round | 5.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23F632F100CF1H1   |    | Genteq  | Special  | 6300       |     | 100  | 1.75  | Round | 4.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 23C303F060CF1H1   |    | Genteq  | Special  | 30000      |     | 60   | 1.75  | Round | 4.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23C183F100C11H1   |    | Genteq  | Special  | 18000      |     | 100  | 1.75  | Round | 5.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F6765BX         | BX | Genteq  | Standard | 6          |     | 330  | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23H122F300BH1H1   |    | Genteq  | Special  | 1200       |     | 300  | 1.375 | Round | 5.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23H102F350CE1H1   |    | Genteq  | Special  | 1000       |     | 350  | 1.75  | Round | 3.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23A164F050FH1H1   |    | Genteq  | Special  | 16000<br>0 |     | 50   | 3     | Round | 5.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 23A842F150EE1H1   |    | Genteq  | Special  | 8400       |     | 150  | 2.5   | Round | 3.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 23J861F300BG1H1   |    | Genteq  | Special  | 860        |     | 300  | 1.375 | Round | 4.625 | Electrolytic             | 2000   | -40°C to 105°C |
| 23F173F080CH1H1   |    | Genteq  | Special  | 17000      |     | 80   | 1.75  | Round | 5.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 23M182F250CD1H1   |    | Genteq  | Special  | 1800       |     | 250  | 1.75  | Round | 3.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 42L1201           |    | Genteq  | Stock    | 2          |     | 850  | 1.12  | Round | 1.65  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 23B102F250DC1H1   |    | Genteq  | Special  | 1000       |     | 250  | 2     | Round | 2.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 27L402BR          | BR | Genteq  | Standard | 24         | 8   | 300  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23B143F080CF1H1   |    | Genteq  | Special  | 14000      |     | 80   | 1.75  | Round | 4.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23J492F350FL1H1   |    | Genteq  | Special  | 4900       |     | 350  | 3     | Round | 8.625 | Electrolytic             | 2000   | -40°C to 105°C |
| 23F223F075ED1H1   |    | Genteq  | Special  | 22000      |     | 75   | 2.5   | Round | 3.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F6745BX         | BX | Genteq  | Standard | 21         |     | 330  | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23J522F300FH1H1   |    | Genteq  | Special  | 5200       |     | 300  | 3     | Round | 5.125 | Electrolytic             | 2000   | -40°C to 105°C |
| 23M212F450FE1H1   |    | Genteq  | Special  | 2100       |     | 450  | 3     | Round | 3.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23A352F100BC1H1   |    | Genteq  | Special  | 3500       |     | 100  | 1.375 | Round | 2.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 97F6865BX         | BX | Genteq  | Standard | 35         |     | 280  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 42L3473           |    | Genteq  | Stock    | 0.047      |     | 2000 | 0.57  | Round | 1.22  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 23C123F200FJ1H1   |    | Genteq  | Special  | 12000      |     | 200  | 3     | Round | 5.875 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F6518BX         | BX | Genteq  | Standard | 8          |     | 330  | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F8044           |    | Genteq  | Standard | 60         |     | 240  | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F5583           |    | Genteq  | Standard | 2          |     | 440  | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB300Z050S370CA   |    | PROLINE | Standard | 30         | 5   | 370  | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23B113F200FL1H1   |    | Genteq  | Special  | 11000      |     | 200  | 3     | Round | 8.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23A472F100BD1H1   |    | Genteq  | Special  | 4700       |     | 100  | 1.375 | Round | 3.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 23M902F250FG1H1   |    | Genteq  | Special  | 9000       |     | 250  | 3     | Round | 4.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| PB400Z075S370DABX | BX | PROLINE | Standard | 40         | 7.5 | 370  | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| PB200E000S440CABX | BX | PROLINE | Standard | 20         |     | 440  | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F9965           |    | Genteq  | Standard | 15         | 10  | 370  | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |

|                    |    |         |          |       |     |     |       |       |       |                          |       |                |
|--------------------|----|---------|----------|-------|-----|-----|-------|-------|-------|--------------------------|-------|----------------|
| 23C323F080EE1H1    |    | Genteq  | Special  | 32000 |     | 80  | 2.5   | Round | 3.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| 97F8036S           | S  | Genteq  | Stock    | 15    |     | 240 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F9365            |    | Genteq  | Special  | 25    |     | 480 | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23B373F050ED1H1    |    | Genteq  | Special  | 37000 |     | 50  | 2.5   | Round | 3.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| PB300E000C240CA    |    | PROLINE | Standard | 30    |     | 240 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23M302F300ED1H1    |    | Genteq  | Special  | 3000  |     | 300 | 2.5   | Round | 3.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23M802F250FF1H1    |    | Genteq  | Special  | 8000  |     | 250 | 3     | Round | 4.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| PB350Y100C370DAB X | BX | PROLINE | Standard | 35    | 10  | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F9005            |    | Genteq  | Standard | 20    |     | 370 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23F573F080F11H1    |    | Genteq  | Special  | 57000 |     | 80  | 3     | Round | 5.625 | Electrolytic             | 1000  | -55°C to 105°C |
| 23C203F080DE1H1    |    | Genteq  | Special  | 20000 |     | 80  | 2     | Round | 3.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| 23C593F060DI1H1    |    | Genteq  | Special  | 59000 |     | 60  | 2     | Round | 5.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| 97F6934BX          | BX | Genteq  | Standard | 26    |     | 540 | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23D333F020CE1H1    |    | Genteq  | Special  | 33000 |     | 20  | 1.75  | Round | 3.625 | Electrolytic             | 1000  | -55°C to 85°C  |
| PB150Y075C440CAB X | BX | PROLINE | Standard | 15    | 7.5 | 440 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F9041BX          | BX | Genteq  | Standard | 35    |     | 440 | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23B343F075DI1H1    |    | Genteq  | Special  | 34000 |     | 75  | 2     | Round | 5.625 | Electrolytic             | 3000  | -40°C to 85°C  |
| 97F9678BX          | BX | Genteq  | Standard | 25    | 10  | 370 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23C222F200DD1H1    |    | Genteq  | Special  | 2200  |     | 200 | 2     | Round | 3.125 | Electrolytic             | 1000  | -45°C to 95°C  |
| 27L590BR           | BR | Genteq  | Standard | 24    | 11  | 300 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23B803F050FF1H1    |    | Genteq  | Special  | 80000 |     | 50  | 3     | Round | 4.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| 23F592F080DB1H1    |    | Genteq  | Special  | 5900  |     | 80  | 2     | Round | 2.125 | Electrolytic             | 1000  | -55°C to 105°C |
| 23F352F080BC1H1    |    | Genteq  | Special  | 3500  |     | 80  | 1.375 | Round | 2.625 | Electrolytic             | 1000  | -55°C to 105°C |
| 23M701F450DD1H1    |    | Genteq  | Special  | 700   |     | 450 | 2     | Round | 3.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| PB175E000P370CA    |    | PROLINE | Standard | 17.5  |     | 370 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F9608S           | S  | Genteq  | Stock    | 30    |     | 370 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F9966            |    | Genteq  | Standard | 20    | 7.5 | 370 | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23H762F300F11H1    |    | Genteq  | Special  | 7600  |     | 300 | 3     | Round | 5.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23D323F016BH1H1    |    | Genteq  | Special  | 32000 |     | 16  | 1.375 | Round | 5.125 | Electrolytic             | 1000  | -55°C to 85°C  |
| 23B103F100CH1H1    |    | Genteq  | Special  | 10000 |     | 100 | 1.75  | Round | 5.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| 97F9451BR          | BR | Genteq  | Standard | 20    | 10  | 440 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23H192F350EE1H1    |    | Genteq  | Special  | 1900  |     | 350 | 2.5   | Round | 3.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 97F6537BR          | BR | Genteq  | Standard | 24    |     | 330 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F6945            |    | Genteq  | Standard | 24    |     | 580 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23F703F050FE1H1    |    | Genteq  | Special  | 70000 |     | 50  | 3     | Round | 3.625 | Electrolytic             | 1000  | -55°C to 105°C |
| 23B313F100FH1H1    |    | Genteq  | Special  | 31000 |     | 100 | 3     | Round | 5.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| PB200Y050C440CA    |    | PROLINE | Standard | 20    | 5   | 440 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23J732F300FL1H1    |    | Genteq  | Special  | 7300  |     | 300 | 3     | Round | 8.625 | Electrolytic             | 2000  | -40°C to 105°C |
| 27L695BX           | BX | Genteq  | Standard | 7.5   |     | 440 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23B403F060DH1H1    |    | Genteq  | Special  | 40000 |     | 60  | 2     | Round | 5.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| 23C212F150BE1H1    |    | Genteq  | Special  | 2100  |     | 150 | 1.375 | Round | 3.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| 97F9637BX          | BX | Genteq  | Standard | 30    |     | 440 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F5067BX          | BX | Genteq  | Standard | 12.5  |     | 370 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F9201            |    | Genteq  | Standard | 4     |     | 370 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23C153F080CE1H1    |    | Genteq  | Special  | 15000 |     | 80  | 1.75  | Round | 3.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| 23F542F150FD1H1    |    | Genteq  | Special  | 5400  |     | 150 | 3     | Round | 3.125 | Electrolytic             | 1000  | -55°C to 105°C |
| PB750E000T370EABX  | BX | PROLINE | Standard | 75    |     | 370 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23F383F080FF1H1    |    | Genteq  | Special  | 38000 |     | 80  | 3     | Round | 4.125 | Electrolytic             | 1000  | -55°C to 105°C |
| 97F6538BR          | BR | Genteq  | Standard | 35    |     | 280 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23A673F060FD1H1    |    | Genteq  | Special  | 67000 |     | 60  | 3     | Round | 3.125 | Electrolytic             | 1000  | -40°C to 85°C  |
| 97F9142BX          | BX | Genteq  | Standard | 17.5  | 7.5 | 440 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23H212F300DF1H1    |    | Genteq  | Special  | 2100  |     | 300 | 2     | Round | 4.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23C162F250CE1H1    |    | Genteq  | Special  | 1600  |     | 250 | 1.75  | Round | 3.625 | Electrolytic             | 1000  | -45°C to 95°C  |

|                   |    |         |          |       |    |     |       |       |       |                          |       |                |
|-------------------|----|---------|----------|-------|----|-----|-------|-------|-------|--------------------------|-------|----------------|
| 23A104F060FF1H1   |    | Genteq  | Special  | 10000 |    | 60  | 3     | Round | 4.125 | Electrolytic             | 1000  | -40°C to 85°C  |
| 97F6602           |    | Genteq  | Standard | 15    |    | 400 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 27L600BX          | BX | Genteq  | Standard | 39    | 13 | 330 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F6930           |    | Genteq  | Standard | 10    |    | 580 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F9828BX         | BX | Genteq  | Standard | 30    | 10 | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 27L757BX          | BX | Genteq  | Special  | 55    |    | 440 | 2     | Round | 5.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23B223F050DD1H1   |    | Genteq  | Special  | 22000 |    | 50  | 2     | Round | 3.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| 23M272F350EE1H1   |    | Genteq  | Special  | 2700  |    | 350 | 2.5   | Round | 3.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 27L987            |    | Genteq  | Standard | 3     |    | 370 | 1.25  | Oval  | 1.56  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F9834           |    | Genteq  | Standard | 35    | 5  | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 27L428            |    | Genteq  | Standard | 24    | 15 | 400 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 27L705            |    | Genteq  | Standard | 42    | 22 | 280 | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23H132F250DC1H1   |    | Genteq  | Special  | 1300  |    | 250 | 2     | Round | 2.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23C292F200CG1H1   |    | Genteq  | Special  | 2900  |    | 200 | 1.75  | Round | 4.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| 23H172F250B11H1   |    | Genteq  | Special  | 1700  |    | 250 | 1.375 | Round | 5.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23M322F450FH1H1   |    | Genteq  | Special  | 3200  |    | 450 | 3     | Round | 5.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 97F9044BX         | BX | Genteq  | Special  | 15    | 5  | 440 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23F213F060DF1H1   |    | Genteq  | Special  | 21000 |    | 60  | 2     | Round | 4.125 | Electrolytic             | 1000  | -55°C to 105°C |
| PB500E000C370DAS  | S  | PROLINE | Stock    | 50    |    | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23C572F100DB1H1   |    | Genteq  | Special  | 5700  |    | 100 | 2     | Round | 2.125 | Electrolytic             | 1000  | -45°C to 95°C  |
| 23C282F200DE1H1   |    | Genteq  | Special  | 2800  |    | 200 | 2     | Round | 3.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| 23C504F075FE1H1   |    | Genteq  | Special  | 50000 |    | 75  | 3     | Round | 3.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| 97F5914BX         | BX | Genteq  | Standard | 32.5  |    | 370 | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23J242F200CG1H1   |    | Genteq  | Special  | 2400  |    | 200 | 1.75  | Round | 4.625 | Electrolytic             | 2000  | -40°C to 105°C |
| 23M401F300BB1H1   |    | Genteq  | Special  | 400   |    | 300 | 1.375 | Round | 2.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23B132F150BD1H1   |    | Genteq  | Special  | 1300  |    | 150 | 1.375 | Round | 3.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| 23J671F200BC1H1   |    | Genteq  | Special  | 670   |    | 200 | 1.375 | Round | 2.625 | Electrolytic             | 2000  | -40°C to 105°C |
| 23M692F350FJ1H1   |    | Genteq  | Special  | 6900  |    | 350 | 3     | Round | 5.875 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23C143F150E11H1   |    | Genteq  | Special  | 14000 |    | 150 | 2.5   | Round | 5.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| 23M153F250FL1H1   |    | Genteq  | Special  | 15000 |    | 250 | 3     | Round | 8.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 97F9827BX         | BX | Genteq  | Standard | 25    | 10 | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| PB450Z100S370EABX | BX | PROLINE | Standard | 45    | 10 | 370 | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F5705           |    | Genteq  | Standard | 5     |    | 370 | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23D133F055CF1H1   |    | Genteq  | Special  | 13000 |    | 55  | 1.75  | Round | 4.125 | Electrolytic             | 1000  | -55°C to 85°C  |
| 97F9805BX         | BX | Genteq  | Standard | 45    |    | 440 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 27L1022           |    | Genteq  | Standard | 3     |    | 440 | 1.25  | Oval  | 1.56  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23M771F300BD1H1   |    | Genteq  | Special  | 770   |    | 300 | 1.375 | Round | 3.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 97F9814           |    | Genteq  | Standard | 20    | 5  | 370 | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23F442F100CD1H1   |    | Genteq  | Special  | 4400  |    | 100 | 1.75  | Round | 3.125 | Electrolytic             | 1000  | -55°C to 105°C |
| 23M202F400EE1H1   |    | Genteq  | Special  | 2000  |    | 400 | 2.5   | Round | 3.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23A723F100FL1H1   |    | Genteq  | Special  | 72000 |    | 100 | 3     | Round | 8.625 | Electrolytic             | 1000  | -40°C to 85°C  |
| 97F9735BX         | BX | Genteq  | Standard | 35    | 5  | 440 | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23M172F250DC1H1   |    | Genteq  | Special  | 1700  |    | 250 | 2     | Round | 2.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23F172F150CD1H1   |    | Genteq  | Special  | 1700  |    | 150 | 1.75  | Round | 3.125 | Electrolytic             | 1000  | -55°C to 105°C |
| 97F6764BR         | BR | Genteq  | Standard | 5     |    | 330 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23C473F080FE1H1   |    | Genteq  | Special  | 47000 |    | 80  | 3     | Round | 3.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| PB250Z050S370CABX | BX | PROLINE | Standard | 25    | 5  | 370 | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23D183F028BG1H1   |    | Genteq  | Special  | 18000 |    | 28  | 1.375 | Round | 4.625 | Electrolytic             | 1000  | -55°C to 85°C  |
| 23B163F100EF1H1   |    | Genteq  | Special  | 16000 |    | 100 | 2.5   | Round | 4.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| PB450Y050C440EABX | BX | PROLINE | Standard | 45    | 5  | 440 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23H742F200EH1H1   |    | Genteq  | Special  | 7400  |    | 200 | 2.5   | Round | 5.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23F481F250BD1H1   |    | Genteq  | Special  | 480   |    | 250 | 1.375 | Round | 3.125 | Electrolytic             | 1000  | -55°C to 105°C |
| 23H321F450BE1H1   |    | Genteq  | Special  | 320   |    | 450 | 1.375 | Round | 3.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| PB350E000A370EAS  | S  | PROLINE | Stock    | 35    |    | 370 | 1.25  | Oval  | 4.75  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |

|                   |    |         |          |        |     |     |       |       |       |                          |       |                |
|-------------------|----|---------|----------|--------|-----|-----|-------|-------|-------|--------------------------|-------|----------------|
| 23B383F075FD1H1   |    | Genteq  | Special  | 38000  |     | 75  | 3     | Round | 3.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| 23F242F250D1H1    |    | Genteq  | Special  | 2400   |     | 250 | 2     | Round | 5.625 | Electrolytic             | 1000  | -55°C to 105°C |
| 23C381F250BB1H1   |    | Genteq  | Special  | 380    |     | 250 | 1.375 | Round | 2.125 | Electrolytic             | 1000  | -45°C to 95°C  |
| 23A103F100B1H1    |    | Genteq  | Special  | 10000  |     | 100 | 1.375 | Round | 5.625 | Electrolytic             | 1000  | -40°C to 85°C  |
| 23F771F200DB1H1   |    | Genteq  | Special  | 770    |     | 200 | 2     | Round | 2.125 | Electrolytic             | 1000  | -55°C to 105°C |
| PB700Z075T440GA   |    | PROLINE | Standard | 70     | 7.5 | 440 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 27L589BR          | BR | Genteq  | Standard | 10     | 5   | 400 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23B353F060C1H1    |    | Genteq  | Special  | 35000  |     | 60  | 1.75  | Round | 5.625 | Electrolytic             | 3000  | -40°C to 85°C  |
| 27L6094BX         | BX | Genteq  | Special  | 3      |     | 660 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23J242F300D1H1    |    | Genteq  | Special  | 2400   |     | 300 | 2     | Round | 5.625 | Electrolytic             | 2000  | -40°C to 105°C |
| 97F8218BX         | BX | Genteq  | Standard | 30     |     | 240 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23C223F060BH1H1   |    | Genteq  | Special  | 22000  |     | 60  | 1.375 | Round | 5.125 | Electrolytic             | 1000  | -45°C to 95°C  |
| 97F8090           |    | Genteq  | Standard | 20     |     | 240 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 27L566S           | S  | Genteq  | Stock    | 7.5    |     | 370 | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| PB700Z100T440EA   |    | PROLINE | Standard | 70     | 10  | 440 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F6952RC         | RC | Genteq  | Standard | 36     |     | 540 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23F343F050DF1H1   |    | Genteq  | Special  | 34000  |     | 50  | 2     | Round | 4.125 | Electrolytic             | 1000  | -55°C to 105°C |
| 97F9318BX         | BX | Genteq  | Special  | 55     | 5   | 440 | 2     | Oval  | 5.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| PB350E000P240DA   |    | PROLINE | Standard | 35     |     | 240 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| PB100E000A440CA   |    | PROLINE | Standard | 10     |     | 440 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F9059BX         | BX | Genteq  | Special  | 55     | 5   | 440 | 2     | Oval  | 6.25  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23J302F250EE1H1   |    | Genteq  | Special  | 3000   |     | 250 | 2.5   | Round | 3.625 | Electrolytic             | 2000  | -40°C to 105°C |
| 23J991F400C1H1    |    | Genteq  | Special  | 990    |     | 400 | 1.75  | Round | 5.625 | Electrolytic             | 2000  | -40°C to 105°C |
| 23M202F350CH1H1   |    | Genteq  | Special  | 2000   |     | 350 | 1.75  | Round | 5.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 97F6857RC         | RC | Genteq  | Standard | 8      |     | 280 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23B123F050DB1H1   |    | Genteq  | Special  | 12000  |     | 50  | 2     | Round | 2.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| 97F6871RC         | RC | Genteq  | Standard | 12     |     | 280 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| PB040E000A440AABX | BX | PROLINE | Standard | 4      |     | 440 | 1.25  | Oval  | 1.56  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23F123F075B1H1    |    | Genteq  | Special  | 12000  |     | 75  | 1.375 | Round | 5.625 | Electrolytic             | 1000  | -55°C to 105°C |
| 23M342F400E1H1    |    | Genteq  | Special  | 3400   |     | 400 | 2.5   | Round | 5.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23C373F080EF1H1   |    | Genteq  | Special  | 37000  |     | 80  | 2.5   | Round | 4.125 | Electrolytic             | 1000  | -45°C to 95°C  |
| 97F6674BX         | BX | Genteq  | Special  | 12     |     | 480 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| PB150E000P440CAS  | S  | PROLINE | Stock    | 15     |     | 440 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F6683BR         | BR | Genteq  | Special  | 21     |     | 480 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23C502F080BC1H1   |    | Genteq  | Special  | 5000   |     | 80  | 1.375 | Round | 2.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| 97F6777BX         | BX | Genteq  | Special  | 35     |     | 330 | 1.5   | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23B433F050DH1H1   |    | Genteq  | Special  | 43000  |     | 50  | 2     | Round | 5.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| 23F922F150FG1H1   |    | Genteq  | Special  | 9200   |     | 150 | 3     | Round | 4.625 | Electrolytic             | 1000  | -55°C to 105°C |
| 97F5276BX         | BX | Genteq  | Standard | 60     |     | 370 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F6940           |    | Genteq  | Standard | 35     |     | 580 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23F154F050FL1H1   |    | Genteq  | Special  | 150000 |     | 50  | 3     | Round | 8.625 | Electrolytic             | 1000  | -55°C to 105°C |
| 23H461F350BD1H1   |    | Genteq  | Special  | 460    |     | 350 | 1.375 | Round | 3.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23J521F350BF1H1   |    | Genteq  | Special  | 520    |     | 350 | 1.375 | Round | 4.125 | Electrolytic             | 2000  | -40°C to 105°C |
| 23D233F007BC1H1   |    | Genteq  | Special  | 23000  |     | 7.5 | 1.375 | Round | 2.625 | Electrolytic             | 1000  | -55°C to 85°C  |
| 97F9698BX         | BX | Genteq  | Special  | 25     | 4   | 440 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23A144F050FG1H1   |    | Genteq  | Special  | 140000 |     | 50  | 3     | Round | 4.625 | Electrolytic             | 1000  | -40°C to 85°C  |
| 23C143F060DB1H1   |    | Genteq  | Special  | 14000  |     | 60  | 2     | Round | 2.125 | Electrolytic             | 1000  | -45°C to 95°C  |
| 23J581F350DC1H1   |    | Genteq  | Special  | 580    |     | 350 | 2     | Round | 2.625 | Electrolytic             | 2000  | -40°C to 105°C |
| 25L6753           |    | Genteq  | Standard | 35     | 13  | 280 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23B483F050D1H1    |    | Genteq  | Special  | 48000  |     | 50  | 2     | Round | 5.625 | Electrolytic             | 3000  | -40°C to 85°C  |
| PB400Y050C440EA   |    | PROLINE | Standard | 40     | 5   | 440 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23B603F080FH1H1   |    | Genteq  | Special  | 60000  |     | 80  | 3     | Round | 5.125 | Electrolytic             | 3000  | -40°C to 85°C  |

|                    |    |         |          |       |     |     |       |       |       |                          |        |                |
|--------------------|----|---------|----------|-------|-----|-----|-------|-------|-------|--------------------------|--------|----------------|
| 23D253F016CC1H1    |    | Genteq  | Special  | 25000 |     | 16  | 1.75  | Round | 2.625 | Electrolytic             | 1000   | -55°C to 85°C  |
| 27L6014            |    | Genteq  | Special  | 6     |     | 660 | 1.25  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23A833F050FD1H1    |    | Genteq  | Special  | 83000 |     | 50  | 3     | Round | 3.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 23F283F075EE1H1    |    | Genteq  | Special  | 28000 |     | 75  | 2.5   | Round | 3.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 27L213BX           | BX | Genteq  | Standard | 7.5   |     | 400 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23J951F400DG1H1    |    | Genteq  | Special  | 950   |     | 400 | 2     | Round | 4.625 | Electrolytic             | 2000   | -40°C to 105°C |
| 41L4301            |    | Genteq  | Stock    | 3     |     | 400 | 0.79  | Round | 1.22  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 27L1020            |    | Genteq  | Standard | 2     |     | 370 | 1.25  | Oval  | 1.56  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23H392F250D11H1    |    | Genteq  | Special  | 3900  |     | 250 | 2     | Round | 5.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 27L430BX           | BX | Genteq  | Standard | 18    | 6   | 280 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23C503F080EH1H1    |    | Genteq  | Special  | 50000 |     | 80  | 2.5   | Round | 5.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23J401F350DB1H1    |    | Genteq  | Special  | 400   |     | 350 | 2     | Round | 2.125 | Electrolytic             | 2000   | -40°C to 105°C |
| 23B853F075FJ1H1    |    | Genteq  | Special  | 85000 |     | 75  | 3     | Round | 5.875 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23F133F060B11H1    |    | Genteq  | Special  | 13000 |     | 60  | 1.375 | Round | 5.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F5927            |    | Genteq  | Standard | 70    | 7.5 | 440 | 2.5   | Round | 5.25  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23F282F150DE1H1    |    | Genteq  | Special  | 2800  |     | 150 | 2     | Round | 3.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 23B752F150EF1H1    |    | Genteq  | Special  | 7500  |     | 150 | 2.5   | Round | 4.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 27L566             |    | Genteq  | Standard | 7.5   |     | 370 | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9477BX          | BX | Genteq  | Standard | 45    | 10  | 440 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB200Y050C440CAB X | BX | PROLINE | Standard | 20    | 5   | 440 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23B662F100DD1H1    |    | Genteq  | Special  | 6600  |     | 100 | 2     | Round | 3.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 27L366             |    | Genteq  | Standard | 40    |     | 600 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6886            |    | Genteq  | Standard | 27    | 8   | 280 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F9060BX          | BX | Genteq  | Special  | 55    | 7.5 | 440 | 2     | Oval  | 6.25  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23C383F100E11H1    |    | Genteq  | Special  | 38000 |     | 100 | 2.5   | Round | 5.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| PB150E000A370CAS   | S  | PROLINE | Stock    | 15    |     | 370 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F6727RC          | RC | Genteq  | Standard | 32    |     | 330 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23A353F100EH1H1    |    | Genteq  | Special  | 35000 |     | 100 | 2.5   | Round | 5.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 23C382F200DG1H1    |    | Genteq  | Special  | 3800  |     | 200 | 2     | Round | 4.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23B283F050DE1H1    |    | Genteq  | Special  | 28000 |     | 50  | 2     | Round | 3.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23C662F150C11H1    |    | Genteq  | Special  | 6600  |     | 150 | 1.75  | Round | 5.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23M242F450FF1H1    |    | Genteq  | Special  | 2400  |     | 450 | 3     | Round | 4.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23J441F350BE1H1    |    | Genteq  | Special  | 440   |     | 350 | 1.375 | Round | 3.625 | Electrolytic             | 2000   | -40°C to 105°C |
| 23A193F150FH1H1    |    | Genteq  | Special  | 19000 |     | 150 | 3     | Round | 5.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 23B242F200DF1H1    |    | Genteq  | Special  | 2400  |     | 200 | 2     | Round | 4.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F6960            |    | Genteq  | Standard | 8     | 2   | 400 | 1.75  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 27L562BX           | BX | Genteq  | Special  | 45    | 19  | 330 | 1.75  | Oval  | 5.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 27L1001BX          | BX | Genteq  | Standard | 45    |     | 440 | 2.5   | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6675            |    | Genteq  | Special  | 16    |     | 480 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 27L1002BX          | BX | Genteq  | Standard | 20    |     | 370 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 40L3101            |    | Genteq  | Stock    | 1     |     | 400 | 0.39  | Oval  | 1.25  | Dry-Axial Leaded         | 100000 | -55°C to 105°C |
| 23B643F075FG1H1    |    | Genteq  | Special  | 64000 |     | 75  | 3     | Round | 4.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23A132F150BC1H1    |    | Genteq  | Special  | 1300  |     | 150 | 1.375 | Round | 2.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 23F193F100FF1H1    |    | Genteq  | Special  | 19000 |     | 100 | 3     | Round | 4.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F5320            |    | Genteq  | Standard | 50    |     | 440 | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23F272F250EF1H1    |    | Genteq  | Special  | 2700  |     | 250 | 2.5   | Round | 4.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F9062            |    | Genteq  | Standard | 60    | 5   | 440 | 2     | Oval  | 6.25  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB300Z050S440DABX  | BX | PROLINE | Standard | 30    | 5   | 440 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23C653F060FD1H1    |    | Genteq  | Special  | 65000 |     | 60  | 3     | Round | 3.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F9850            |    | Genteq  | Standard | 50    | 5   | 440 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23B173F150FJ1H1    |    | Genteq  | Special  | 17000 |     | 150 | 3     | Round | 5.875 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23B203F050BI1H1    |    | Genteq  | Special  | 20000 |     | 50  | 1.375 | Round | 5.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F8053BX          | BX | Genteq  | Standard | 120   |     | 240 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23H921F400CF1H1    |    | Genteq  | Special  | 920   |     | 400 | 1.75  | Round | 4.125 | Electrolytic             | 2000   | -40°C to 85°C  |

|                   |    |         |          |       |     |      |       |       |       |                          |        |                |
|-------------------|----|---------|----------|-------|-----|------|-------|-------|-------|--------------------------|--------|----------------|
| 23B282F200ED1H1   |    | Genteq  | Special  | 2800  |     | 200  | 2.5   | Round | 3.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| PB060E000A440BABX | BX | PROLINE | Standard | 6     |     | 440  | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23A113F100DD1H1   |    | Genteq  | Special  | 11000 |     | 100  | 2     | Round | 3.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 97F6601           |    | Genteq  | Standard | 10    |     | 400  | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23F483F075E1H1    |    | Genteq  | Special  | 48000 |     | 75   | 2.5   | Round | 5.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 23C363F050CG1H1   |    | Genteq  | Special  | 36000 |     | 50   | 1.75  | Round | 4.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 27L1053BX         | BX | Genteq  | Standard | 7.5   |     | 440  | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 42L3562           |    | Genteq  | Stock    | 0.56  |     | 2000 | 1.14  | Round | 2.17  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 23C143F080B1H1    |    | Genteq  | Special  | 14000 |     | 80   | 1.375 | Round | 5.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23F252F080BB1H1   |    | Genteq  | Special  | 2500  |     | 80   | 1.375 | Round | 2.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F6921BX         | BX | Genteq  | Standard | 26    |     | 580  | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23B852F250FL1H1   |    | Genteq  | Special  | 8500  |     | 250  | 3     | Round | 8.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| PB200Z050S370CABX | BX | PROLINE | Standard | 20    | 5   | 370  | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| PB600E000C370EA   |    | PROLINE | Standard | 60    |     | 370  | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23B193F080CH1H1   |    | Genteq  | Special  | 19000 |     | 80   | 1.75  | Round | 5.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| PB550E000P370EABX | BX | PROLINE | Standard | 55    |     | 370  | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23M272F300CH1H1   |    | Genteq  | Special  | 2700  |     | 300  | 1.75  | Round | 5.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F6918BR         | BR | Genteq  | Special  | 28    |     | 480  | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23J701F400DE1H1   |    | Genteq  | Special  | 700   |     | 400  | 2     | Round | 3.625 | Electrolytic             | 2000   | -40°C to 105°C |
| 27L7000BX         | BX | Genteq  | Standard | 48    |     | 280  | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 100°C |
| 23B242F150CD1H1   |    | Genteq  | Special  | 2400  |     | 150  | 1.75  | Round | 3.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F8050           |    | Genteq  | Standard | 90    |     | 240  | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23H222F450FG1H1   |    | Genteq  | Special  | 2200  |     | 450  | 3     | Round | 4.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F6716BX         | BX | Genteq  | Standard | 20    |     | 330  | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| PB050E000A370AAS  | S  | PROLINE | Stock    | 5     |     | 370  | 1.25  | Oval  | 1.56  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F8058S          | S  | Genteq  | Stock    | 7.5   |     | 370  | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23B163F050BG1H1   |    | Genteq  | Special  | 16000 |     | 50   | 1.375 | Round | 4.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F9881BX         | BX | Genteq  | Standard | 35    | 7.5 | 440  | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6601BR         | BR | Genteq  | Standard | 10    |     | 400  | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F9997           |    | Genteq  | Standard | 15    | 5   | 440  | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F5056           |    | Genteq  | Standard | 40    |     | 370  | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L880S           | S  | Genteq  | Stock    | 45    | 5   | 370  | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9121BX         | BX | Genteq  | Standard | 15    |     | 370  | 1.75  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L729BX          | BX | Genteq  | Special  | 20    | 4   | 400  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F9627BX         | BX | Genteq  | Special  | 15    |     | 440  | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F8293           |    | Genteq  | Standard | 48    |     | 330  | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L20             |    | Genteq  | Standard | 30    | 5   | 440  | 2.5   | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F5436           |    | Genteq  | Standard | 6     |     | 440  | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6881           |    | Genteq  | Standard | 42    | 14  | 280  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 42L2332           |    | Genteq  | Stock    | 0.33  |     | 1200 | 0.77  | Round | 1.65  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 23M452F450FL1H1   |    | Genteq  | Special  | 4500  |     | 450  | 3     | Round | 8.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23F132F150CC1H1   |    | Genteq  | Special  | 1300  |     | 150  | 1.75  | Round | 2.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F9022BX         | BX | Genteq  | Special  | 35    | 7.5 | 370  | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6761RC         | RC | Genteq  | Standard | 17.5  |     | 330  | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23B502F100DC1H1   |    | Genteq  | Special  | 5000  |     | 100  | 2     | Round | 2.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23F962F050CB1H1   |    | Genteq  | Special  | 9600  |     | 50   | 1.75  | Round | 2.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 23J392F300FF1H1   |    | Genteq  | Special  | 3900  |     | 300  | 3     | Round | 4.125 | Electrolytic             | 2000   | -40°C to 105°C |
| PB250Z100S440DA   |    | PROLINE | Standard | 25    | 10  | 440  | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F6884BX         | BX | Genteq  | Standard | 33    | 15  | 280  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F5475           |    | Genteq  | Special  | 20    | 4   | 370  | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |

|                    |    |         |          |       |    |     |       |       |       |                            |        |                |
|--------------------|----|---------|----------|-------|----|-----|-------|-------|-------|----------------------------|--------|----------------|
| 23C163F080DD1H1    |    | Genteq  | Special  | 16000 |    | 80  | 2     | Round | 3.125 | Electrolytic               | 1000   | -45°C to 95°C  |
| 27L401             |    | Genteq  | Standard | 20    | 8  | 300 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 97F6603RC          | RC | Genteq  | Special  | 24    |    | 400 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 97F6779BX          | BX | Genteq  | Standard | 18    |    | 330 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| PB020E000P370CAB X | BX | PROLINE | Standard | 2     |    | 370 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved)   | 10000  | -40°C to 70°C  |
| 97F6661BX          | BX | Genteq  | Standard | 14    |    | 400 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 97F9381            |    | Genteq  | Standard | 35    |    | 440 | 2     | Oval  | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 97F6934BR          | BR | Genteq  | Standard | 26    |    | 540 | 2     | Oval  | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 23J781F400CG1H1    |    | Genteq  | Special  | 780   |    | 400 | 1.75  | Round | 4.625 | Electrolytic               | 2000   | -40°C to 105°C |
| 97F9365BX          | BX | Genteq  | Special  | 25    |    | 480 | 1.75  | Round | 4.75  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 97F9005BX          | BX | Genteq  | Standard | 20    |    | 370 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 24DB250B330PA      |    | Genteq  | Standard | 25    |    | 330 | 1.75  | Round | 3.189 | Dry (UL Construction Only) | 60000  | -40°C to 70°C  |
| 23A223F100DH1H1    |    | Genteq  | Special  | 22000 |    | 100 | 2     | Round | 5.125 | Electrolytic               | 1000   | -40°C to 85°C  |
| 97F6864BX          | BX | Genteq  | Standard | 24    |    | 280 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 23B313F060CH1H1    |    | Genteq  | Special  | 31000 |    | 60  | 1.75  | Round | 5.125 | Electrolytic               | 3000   | -40°C to 85°C  |
| 23B623F050EG1H1    |    | Genteq  | Special  | 62000 |    | 50  | 2.5   | Round | 4.625 | Electrolytic               | 3000   | -40°C to 85°C  |
| 27L6082BX          | BX | Genteq  | Special  | 20    |    | 660 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 25L756             |    | Genteq  | Standard | 60    | 10 | 440 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 97F5567BX          | BX | Genteq  | Special  | 35    | 10 | 370 | 1.75  | Oval  | 4.25  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 23F473F075FF1H1    |    | Genteq  | Special  | 47000 |    | 75  | 3     | Round | 4.125 | Electrolytic               | 1000   | -55°C to 105°C |
| 27L571             |    | Genteq  | Standard | 4     |    | 370 | 1.25  | Oval  | 1.56  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 97F6698BR          | BR | Genteq  | Standard | 13    |    | 400 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 23C472F250EG1H1    |    | Genteq  | Special  | 4700  |    | 250 | 2.5   | Round | 4.625 | Electrolytic               | 1000   | -45°C to 95°C  |
| 23J492F200EG1H1    |    | Genteq  | Special  | 4900  |    | 200 | 2.5   | Round | 4.625 | Electrolytic               | 2000   | -40°C to 105°C |
| 97F5283            |    | Genteq  | Special  | 30    |    | 370 | 2.5   | Round | 2.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 41L4501            |    | Genteq  | Stock    | 5     |    | 400 | 0.85  | Round | 1.65  | Dry-Axial Leaded           | 100000 | -40°C to 85°C  |
| 97F6680            |    | Genteq  | Special  | 24    |    | 480 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 23J771F350DD1H1    |    | Genteq  | Special  | 770   |    | 350 | 2     | Round | 3.125 | Electrolytic               | 2000   | -40°C to 105°C |
| PB125E000A440DAS   | S  | PROLINE | Stock    | 12.5  |    | 440 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved)   | 10000  | -40°C to 70°C  |
| 23D283F028CF1H1    |    | Genteq  | Special  | 28000 |    | 28  | 1.75  | Round | 4.125 | Electrolytic               | 1000   | -55°C to 85°C  |
| 97F9859BX          | BX | Genteq  | Standard | 45    | 5  | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 27L68              |    | Genteq  | Standard | 30    | 18 | 400 | 2     | Oval  | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| PB400Y100D440EA    |    | PROLINE | Standard | 40    | 10 | 440 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved)   | 10000  | -40°C to 70°C  |
| 23B163F150F1H1     |    | Genteq  | Special  | 16000 |    | 150 | 3     | Round | 5.625 | Electrolytic               | 3000   | -40°C to 85°C  |
| 97F6929BX          | BX | Genteq  | Standard | 12    |    | 400 | 1.5   | Oval  | 2.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 23A193F080CE1H1    |    | Genteq  | Special  | 19000 |    | 80  | 1.75  | Round | 3.625 | Electrolytic               | 1000   | -40°C to 85°C  |
| 23C113F080BG1H1    |    | Genteq  | Special  | 11000 |    | 80  | 1.375 | Round | 4.625 | Electrolytic               | 1000   | -45°C to 95°C  |
| PB350Z100T440DA    |    | PROLINE | Standard | 35    | 10 | 440 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved)   | 10000  | -40°C to 70°C  |
| 97F5705BX          | BX | Genteq  | Standard | 5     |    | 370 | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 23F113F075BH1H1    |    | Genteq  | Special  | 11000 |    | 75  | 1.375 | Round | 5.125 | Electrolytic               | 1000   | -55°C to 105°C |
| 27L757             |    | Genteq  | Special  | 55    |    | 440 | 2     | Round | 5.75  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 27L1022BX          | BX | Genteq  | Standard | 3     |    | 440 | 1.25  | Oval  | 1.56  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 97F6602BR          | BR | Genteq  | Standard | 15    |    | 400 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 23J291F350BC1H1    |    | Genteq  | Special  | 290   |    | 350 | 1.375 | Round | 2.625 | Electrolytic               | 2000   | -40°C to 105°C |
| 23J691F400CF1H1    |    | Genteq  | Special  | 690   |    | 400 | 1.75  | Round | 4.125 | Electrolytic               | 2000   | -40°C to 105°C |
| 23F213F080DH1H1    |    | Genteq  | Special  | 21000 |    | 80  | 2     | Round | 5.125 | Electrolytic               | 1000   | -55°C to 105°C |
| 23C303F080DH1H1    |    | Genteq  | Special  | 30000 |    | 80  | 2     | Round | 5.125 | Electrolytic               | 1000   | -45°C to 95°C  |
| 23B213F075CG1H1    |    | Genteq  | Special  | 21000 |    | 75  | 1.75  | Round | 4.625 | Electrolytic               | 3000   | -40°C to 85°C  |
| PB030E000A370AA    |    | PROLINE | Standard | 3     |    | 370 | 1.25  | Oval  | 1.56  | Oil-Filled (UL Approved)   | 10000  | -40°C to 70°C  |



|                   |    |         |          |        |     |     |       |       |       |                            |        |                |
|-------------------|----|---------|----------|--------|-----|-----|-------|-------|-------|----------------------------|--------|----------------|
| PB800Z050T370EA   |    | PROLINE | Standard | 80     | 5   | 370 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved)   | 10000  | -40°C to 70°C  |
| 23M901F450CG1H1   |    | Genteq  | Special  | 900    |     | 450 | 1.75  | Round | 4.625 | Electrolytic               | 2000   | -40°C to 85°C  |
| PB500Y100D440GABX | BX | PROLINE | Standard | 50     | 10  | 440 | 2     | Oval  | 5.25  | Oil-Filled (UL Approved)   | 10000  | -40°C to 70°C  |
| 41L6101           |    | Genteq  | Stock    | 1      |     | 600 | 0.61  | Round | 1.22  | Dry-Axial Leaded           | 100000 | -40°C to 85°C  |
| 23A652F100CC1H1   |    | Genteq  | Special  | 6500   |     | 100 | 1.75  | Round | 2.625 | Electrolytic               | 1000   | -40°C to 85°C  |
| 97F9366BX         | BX | Genteq  | Standard | 35     |     | 240 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 23F811F250BG1H1   |    | Genteq  | Special  | 810    |     | 250 | 1.375 | Round | 4.625 | Electrolytic               | 1000   | -55°C to 105°C |
| 97F9642           |    | Genteq  | Standard | 40     |     | 440 | 2     | Round | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 23B153F075BI1H1   |    | Genteq  | Special  | 15000  |     | 75  | 1.375 | Round | 5.625 | Electrolytic               | 3000   | -40°C to 85°C  |
| 23B532F080CB1H1   |    | Genteq  | Special  | 5300   |     | 80  | 1.75  | Round | 2.125 | Electrolytic               | 3000   | -40°C to 85°C  |
| 97F9082           |    | Genteq  | Standard | 20     |     | 440 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 27L724BX          | BX | Genteq  | Standard | 24     | 11  | 280 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 24DB350B370PA     |    | Genteq  | Standard | 35     |     | 370 | 1.75  | Round | 3.189 | Dry (UL Construction Only) | 60000  | -40°C to 70°C  |
| PB650E000T370DABX | BX | PROLINE | Standard | 65     |     | 370 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved)   | 10000  | -40°C to 70°C  |
| 23A423F060CH1H1   |    | Genteq  | Special  | 42000  |     | 60  | 1.75  | Round | 5.125 | Electrolytic               | 1000   | -40°C to 85°C  |
| 97F8071BX         | BX | Genteq  | Standard | 60     |     | 370 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 97F9848           |    | Genteq  | Standard | 35     | 5   | 440 | 2     | Round | 4.75  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 23J322F250DI1H1   |    | Genteq  | Special  | 3200   |     | 250 | 2     | Round | 5.625 | Electrolytic               | 2000   | -40°C to 105°C |
| 27L444RR          | RR | Genteq  | Special  | 37     | 11  | 300 | 1.75  | Oval  | 4.25  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 97F5251           |    | Genteq  | Standard | 70     |     | 440 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 97F6946           |    | Genteq  | Standard | 21     |     | 580 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 23C443F100FG1H1   |    | Genteq  | Special  | 44000  |     | 100 | 3     | Round | 4.625 | Electrolytic               | 1000   | -45°C to 95°C  |
| PB550Z050T370DABX | BX | PROLINE | Standard | 55     | 5   | 370 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved)   | 10000  | -40°C to 70°C  |
| 23D852F028BC1H1   |    | Genteq  | Special  | 8500   |     | 28  | 1.375 | Round | 2.625 | Electrolytic               | 1000   | -55°C to 85°C  |
| 23C114F050FG1H1   |    | Genteq  | Special  | 110000 |     | 50  | 3     | Round | 4.625 | Electrolytic               | 1000   | -45°C to 95°C  |
| 23J132F350CI1H1   |    | Genteq  | Special  | 1300   |     | 350 | 1.75  | Round | 5.625 | Electrolytic               | 2000   | -40°C to 105°C |
| 23D153F020CB1H1   |    | Genteq  | Special  | 15000  |     | 20  | 1.75  | Round | 2.125 | Electrolytic               | 1000   | -55°C to 85°C  |
| 23H272F350EG1H1   |    | Genteq  | Special  | 2700   |     | 350 | 2.5   | Round | 4.625 | Electrolytic               | 2000   | -40°C to 85°C  |
| PB500E000P240EABX | BX | PROLINE | Standard | 50     |     | 240 | 1.75  | Round | 4.75  | Oil-Filled (UL Approved)   | 10000  | -40°C to 70°C  |
| 27L542            |    | Genteq  | Standard | 10.5   | 8   | 330 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| PB500Z075S370EA   |    | PROLINE | Standard | 50     | 7.5 | 370 | 2     | Round | 4.75  | Oil-Filled (UL Approved)   | 10000  | -40°C to 70°C  |
| PB150Z050S440CABX | BX | PROLINE | Standard | 15     | 5   | 440 | 2     | Round | 2.88  | Oil-Filled (UL Approved)   | 10000  | -40°C to 70°C  |
| 25L6755BX         | BX | Genteq  | Standard | 20     | 8   | 280 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 23M332F250DF1H1   |    | Genteq  | Special  | 3300   |     | 250 | 2     | Round | 4.125 | Electrolytic               | 2000   | -40°C to 85°C  |
| 97F8064S          | S  | Genteq  | Stock    | 25     |     | 370 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 27L1024S          | S  | Genteq  | Stock    | 5      |     | 440 | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 97F5567           |    | Genteq  | Special  | 35     | 10  | 370 | 1.75  | Oval  | 4.25  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 97F6670BX         | BX | Genteq  | Special  | 38.5   |     | 370 | 2     | Oval  | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 23H142F400DH1H1   |    | Genteq  | Special  | 1400   |     | 400 | 2     | Round | 5.125 | Electrolytic               | 2000   | -40°C to 85°C  |
| PB060E000A440BAS  | S  | PROLINE | Stock    | 6      |     | 440 | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved)   | 10000  | -40°C to 70°C  |
| 41L4682           |    | Genteq  | Stock    | 0.68   |     | 400 | 0.39  | Round | 1.22  | Dry-Axial Leaded           | 100000 | -40°C to 85°C  |
| 97F6539BX         | BX | Genteq  | Standard | 14     |     | 400 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 23J102F350CG1H1   |    | Genteq  | Special  | 1000   |     | 350 | 1.75  | Round | 4.625 | Electrolytic               | 2000   | -40°C to 105°C |
| 23F233F075DG1H1   |    | Genteq  | Special  | 23000  |     | 75  | 2     | Round | 4.625 | Electrolytic               | 1000   | -55°C to 105°C |
| 97F6924           |    | Genteq  | Standard | 13     |     | 540 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 23M701F300CB1H1   |    | Genteq  | Special  | 700    |     | 300 | 1.75  | Round | 2.125 | Electrolytic               | 2000   | -40°C to 85°C  |
| 23D153F035CD1H1   |    | Genteq  | Special  | 15000  |     | 35  | 1.75  | Round | 3.125 | Electrolytic               | 1000   | -55°C to 85°C  |
| 23D732F055BF1H1   |    | Genteq  | Special  | 7300   |     | 55  | 1.375 | Round | 4.125 | Electrolytic               | 1000   | -55°C to 85°C  |
| 23F142F150BF1H1   |    | Genteq  | Special  | 1400   |     | 150 | 1.375 | Round | 4.125 | Electrolytic               | 1000   | -55°C to 105°C |
| PB250E000P440DAS  | S  | PROLINE | Stock    | 25     |     | 440 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved)   | 10000  | -40°C to 70°C  |

|                   |    |         |          |       |     |     |       |       |       |                          |        |                |
|-------------------|----|---------|----------|-------|-----|-----|-------|-------|-------|--------------------------|--------|----------------|
| PB400Y100D440EABX | BX | PROLINE | Standard | 40    | 10  | 440 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| PB100Y100C440CABX | BX | PROLINE | Standard | 10    | 10  | 440 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F6200           |    | Genteq  | Special  | 9.4   |     | 290 | 1.5   | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| PB200Z100S440DA   |    | PROLINE | Standard | 20    | 10  | 440 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23H432F250FD1H1   |    | Genteq  | Special  | 4300  |     | 250 | 3     | Round | 3.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23C832F100CD1H1   |    | Genteq  | Special  | 8300  |     | 100 | 1.75  | Round | 3.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23C543F080FF1H1   |    | Genteq  | Special  | 54000 |     | 80  | 3     | Round | 4.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| PB040E000A440AAS  | S  | PROLINE | Stock    | 4     |     | 440 | 1.25  | Oval  | 1.56  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F6526RC         | RC | Genteq  | Standard | 10    |     | 400 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23B533F080FG1H1   |    | Genteq  | Special  | 53000 |     | 80  | 3     | Round | 4.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23H142F300DD1H1   |    | Genteq  | Special  | 1400  |     | 300 | 2     | Round | 3.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23F321F200BB1H1   |    | Genteq  | Special  | 320   |     | 200 | 1.375 | Round | 2.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 23H201F400BB1H1   |    | Genteq  | Special  | 200   |     | 400 | 1.375 | Round | 2.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 42L1101           |    | Genteq  | Stock    | 1     |     | 850 | 0.81  | Round | 1.65  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| PB500E000T440DABX | BX | PROLINE | Standard | 50    |     | 440 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F9885           |    | Genteq  | Standard | 50    | 5   | 370 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23B213F080ED1H1   |    | Genteq  | Special  | 21000 |     | 80  | 2.5   | Round | 3.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23M372F450FJ1H1   |    | Genteq  | Special  | 3700  |     | 450 | 3     | Round | 5.875 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F9737           |    | Genteq  | Standard | 35    | 7.5 | 440 | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6535           |    | Genteq  | Standard | 24    |     | 400 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 27L7003RC         | RC | Genteq  | Standard | 26    |     | 330 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 100°C |
| PB400Z100S440EABX | BX | PROLINE | Standard | 40    | 10  | 440 | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 27L989            |    | Genteq  | Special  | 30    |     | 240 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB030E000A440AABX | BX | PROLINE | Standard | 3     |     | 440 | 1.25  | Oval  | 1.56  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23C503F100FH1H1   |    | Genteq  | Special  | 50000 |     | 100 | 3     | Round | 5.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| PB350Z050T440CA   |    | PROLINE | Standard | 35    | 5   | 440 | 2.5   | Round | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23F492F150DI1H1   |    | Genteq  | Special  | 4900  |     | 150 | 2     | Round | 5.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F9021BX         | BX | Genteq  | Special  | 35    | 5   | 370 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23C403F075EF1H1   |    | Genteq  | Special  | 40000 |     | 75  | 2.5   | Round | 4.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F8048           |    | Genteq  | Standard | 80    |     | 240 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F8240BX         | BX | Genteq  | Special  | 1.5   |     | 600 | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB350Y075C440EABX | BX | PROLINE | Standard | 35    | 7.5 | 440 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| PB500Y050C370EA   |    | PROLINE | Standard | 50    | 5   | 370 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 27L444            |    | Genteq  | Special  | 37    | 11  | 300 | 1.75  | Oval  | 4.25  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23C891F250DB1H1   |    | Genteq  | Special  | 890   |     | 250 | 2     | Round | 2.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23F152F250CG1H1   |    | Genteq  | Special  | 1500  |     | 250 | 1.75  | Round | 4.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 23M162F450EF1H1   |    | Genteq  | Special  | 1600  |     | 450 | 2.5   | Round | 4.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 41L6201           |    | Genteq  | Stock    | 2     |     | 600 | 0.73  | Round | 1.65  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| PB075E000A370BA   |    | PROLINE | Standard | 7.5   |     | 370 | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 27L322BX          | BX | Genteq  | Special  | 80    |     | 440 | 2.5   | Round | 5.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L868            |    | Genteq  | Special  | 80    | 10  | 440 | 2     | Oval  | 5.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23J612F200FF1H1   |    | Genteq  | Special  | 6100  |     | 200 | 3     | Round | 4.125 | Electrolytic             | 2000   | -40°C to 105°C |
| 97F5483           |    | Genteq  | Special  | 35    | 4   | 370 | 1.75  | Oval  | 4.25  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB450E000C370DABX | BX | PROLINE | Standard | 45    |     | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23C122F250BG1H1   |    | Genteq  | Special  | 1200  |     | 250 | 1.375 | Round | 4.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23J122F300CE1H1   |    | Genteq  | Special  | 1200  |     | 300 | 1.75  | Round | 3.625 | Electrolytic             | 2000   | -40°C to 105°C |
| PB020E000A440AA   |    | PROLINE | Standard | 2     |     | 440 | 1.25  | Oval  | 1.56  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23C123F060BD1H1   |    | Genteq  | Special  | 12000 |     | 60  | 1.375 | Round | 3.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F9987           |    | Genteq  | Standard | 50    | 7.5 | 440 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23M312F250CG1H1   |    | Genteq  | Special  | 3100  |     | 250 | 1.75  | Round | 4.625 | Electrolytic             | 2000   | -40°C to 85°C  |

|                   |    |         |          |       |     |     |       |       |       |                          |       |                |
|-------------------|----|---------|----------|-------|-----|-----|-------|-------|-------|--------------------------|-------|----------------|
| PB350Y100C370DA   |    | PROLINE | Standard | 35    | 10  | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| PB350Y075C370DA   |    | PROLINE | Standard | 35    | 7.5 | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23C233F100DI1H1   |    | Genteq  | Special  | 23000 |     | 100 | 2     | Round | 5.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| 23F592F080BE1H1   |    | Genteq  | Special  | 5900  |     | 80  | 1.375 | Round | 3.625 | Electrolytic             | 1000  | -55°C to 105°C |
| 23F843F050EI1H1   |    | Genteq  | Special  | 84000 |     | 50  | 2.5   | Round | 5.625 | Electrolytic             | 1000  | -55°C to 105°C |
| 97F6505           |    | Genteq  | Standard | 17.5  |     | 330 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F5482           |    | Genteq  | Special  | 30    | 5   | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23M252F350DH1H1   |    | Genteq  | Special  | 2500  |     | 350 | 2     | Round | 5.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| PB300Z075S440DA   |    | PROLINE | Standard | 30    | 7.5 | 440 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 27L6016BX         | BX | Genteq  | Special  | 8     |     | 660 | 1.25  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 27L758BX          | BX | Genteq  | Special  | 50    |     | 440 | 2     | Round | 5.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23A833F050EF1H1   |    | Genteq  | Special  | 83000 |     | 50  | 2.5   | Round | 4.125 | Electrolytic             | 1000  | -40°C to 85°C  |
| 27L569BX          | BX | Genteq  | Special  | 50    | 5   | 440 | 2.5   | Round | 4.25  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F6926RC         | RC | Genteq  | Standard | 26    |     | 400 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23H292F200DE1H1   |    | Genteq  | Special  | 2900  |     | 200 | 2     | Round | 3.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 97F8243           |    | Genteq  | Special  | 3     |     | 600 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23M102F300DB1H1   |    | Genteq  | Special  | 1000  |     | 300 | 2     | Round | 2.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 97F9751BX         | BX | Genteq  | Special  | 20    | 4   | 370 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23F602F060CB1H1   |    | Genteq  | Special  | 6000  |     | 60  | 1.75  | Round | 2.125 | Electrolytic             | 1000  | -55°C to 105°C |
| PB500E000C370DABX | BX | PROLINE | Standard | 50    |     | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F9030BX         | BX | Genteq  | Special  | 50    | 10  | 370 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23C592F150CH1H1   |    | Genteq  | Special  | 5900  |     | 150 | 1.75  | Round | 5.125 | Electrolytic             | 1000  | -45°C to 95°C  |
| 23B902F075CC1H1   |    | Genteq  | Special  | 9000  |     | 75  | 1.75  | Round | 2.625 | Electrolytic             | 3000  | -40°C to 85°C  |
| 23C253F075CH1H1   |    | Genteq  | Special  | 25000 |     | 75  | 1.75  | Round | 5.125 | Electrolytic             | 1000  | -45°C to 95°C  |
| 23H172F200BG1H1   |    | Genteq  | Special  | 1700  |     | 200 | 1.375 | Round | 4.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23C303F100EG1H1   |    | Genteq  | Special  | 30000 |     | 100 | 2.5   | Round | 4.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| 27L5201           |    | Genteq  | Standard | 50    | 10  | 440 | 2     | Oval  | 5.25  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23M352F250CH1H1   |    | Genteq  | Special  | 3500  |     | 250 | 1.75  | Round | 5.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23M562F250FD1H1   |    | Genteq  | Special  | 5600  |     | 250 | 3     | Round | 3.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| PB600Z100T440EA   |    | PROLINE | Standard | 60    | 10  | 440 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23C772F100BG1H1   |    | Genteq  | Special  | 7700  |     | 100 | 1.375 | Round | 4.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| 23C432F200DH1H1   |    | Genteq  | Special  | 4300  |     | 200 | 2     | Round | 5.125 | Electrolytic             | 1000  | -45°C to 95°C  |
| PB450Y050C370DA   |    | PROLINE | Standard | 45    | 5   | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F8248           |    | Genteq  | Standard | 8     |     | 600 | 1.25  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23C643F080FG1H1   |    | Genteq  | Special  | 64000 |     | 80  | 3     | Round | 4.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| 23A263F080CG1H1   |    | Genteq  | Special  | 26000 |     | 80  | 1.75  | Round | 4.625 | Electrolytic             | 1000  | -40°C to 85°C  |
| 97F9898BX         | BX | Genteq  | Standard | 60    | 7.5 | 440 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| PB400Y075C370DA   |    | PROLINE | Standard | 40    | 7.5 | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23B393F080FE1H1   |    | Genteq  | Special  | 39000 |     | 80  | 3     | Round | 3.625 | Electrolytic             | 3000  | -40°C to 85°C  |
| 97F6885BR         | BR | Genteq  | Standard | 36    | 12  | 280 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23F932F200FL1H1   |    | Genteq  | Special  | 9300  |     | 200 | 3     | Round | 8.625 | Electrolytic             | 1000  | -55°C to 105°C |
| 23B272F250EE1H1   |    | Genteq  | Special  | 2700  |     | 250 | 2.5   | Round | 3.625 | Electrolytic             | 3000  | -40°C to 85°C  |
| PB350E000S440DA   |    | PROLINE | Standard | 35    |     | 440 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F9007BX         | BX | Genteq  | Standard | 35    |     | 370 | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23A242F150CC1H1   |    | Genteq  | Special  | 2400  |     | 150 | 1.75  | Round | 2.625 | Electrolytic             | 1000  | -40°C to 85°C  |
| 23B143F100DI1H1   |    | Genteq  | Special  | 14000 |     | 100 | 2     | Round | 5.625 | Electrolytic             | 3000  | -40°C to 85°C  |
| 23H841F350CD1H1   |    | Genteq  | Special  | 840   |     | 350 | 1.75  | Round | 3.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23H122F350DE1H1   |    | Genteq  | Special  | 1200  |     | 350 | 2     | Round | 3.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 97F6676           |    | Genteq  | Special  | 3     |     | 480 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F6774BR         | BR | Genteq  | Standard | 24    |     | 330 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23M901F400BI1H1   |    | Genteq  | Special  | 900   |     | 400 | 1.375 | Round | 5.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 97F8255BX         | BX | Genteq  | Standard | 30    |     | 600 | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23H123F200FI1H1   |    | Genteq  | Special  | 12000 |     | 200 | 3     | Round | 5.625 | Electrolytic             | 2000  | -40°C to 85°C  |

|                    |    |         |          |       |     |     |       |       |       |                          |        |                |
|--------------------|----|---------|----------|-------|-----|-----|-------|-------|-------|--------------------------|--------|----------------|
| 23F143F075DD1H1    |    | Genteq  | Special  | 14000 |     | 75  | 2     | Round | 3.125 | Electrolytic             | 1000   | -55°C to 105°C |
| PB350Y075C370DAB X | BX | PROLINE | Standard | 35    | 7.5 | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F5050BX          | BX | Genteq  | Standard | 15    |     | 370 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23C392F150DD1H1    |    | Genteq  | Special  | 3900  |     | 150 | 2     | Round | 3.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| PB350Z050S440EABX  | BX | PROLINE | Standard | 35    | 5   | 440 | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23A363F075DG1H1    |    | Genteq  | Special  | 36000 |     | 75  | 2     | Round | 4.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| PB250Y100C370CAB X | BX | PROLINE | Standard | 25    | 10  | 370 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23D153F028CC1H1    |    | Genteq  | Special  | 15000 |     | 28  | 1.75  | Round | 2.625 | Electrolytic             | 1000   | -55°C to 85°C  |
| PB500Y050D440GAB X | BX | PROLINE | Standard | 50    | 5   | 440 | 2     | Oval  | 5.25  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F5239BX          | BX | Genteq  | Standard | 55    |     | 480 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23H182F300DE1H1    |    | Genteq  | Special  | 1800  |     | 300 | 2     | Round | 3.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23F632F150EG1H1    |    | Genteq  | Special  | 6300  |     | 150 | 2.5   | Round | 4.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 23M113F200E11H1    |    | Genteq  | Special  | 11000 |     | 200 | 2.5   | Round | 5.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23F461F250CB1H1    |    | Genteq  | Special  | 460   |     | 250 | 1.75  | Round | 2.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F9090            |    | Genteq  | Standard | 40    |     | 440 | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 40L3682            |    | Genteq  | Stock    | 0.68  |     | 400 | 0.3   | Oval  | 1.25  | Dry-Axial Leaded         | 100000 | -55°C to 105°C |
| 97F6760BX          | BX | Genteq  | Standard | 12    |     | 330 | 1.5   | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 27L92BX            | BX | Genteq  | Special  | 80    | 7.5 | 440 | 2     | Oval  | 5.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23J971F300BH1H1    |    | Genteq  | Special  | 970   |     | 300 | 1.375 | Round | 5.125 | Electrolytic             | 2000   | -40°C to 105°C |
| 23J422F200EF1H1    |    | Genteq  | Special  | 4200  |     | 200 | 2.5   | Round | 4.125 | Electrolytic             | 2000   | -40°C to 105°C |
| 97F6535BR          | BR | Genteq  | Standard | 24    |     | 400 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23C373F100FF1H1    |    | Genteq  | Special  | 37000 |     | 100 | 3     | Round | 4.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23H202F300CG1H1    |    | Genteq  | Special  | 2000  |     | 300 | 1.75  | Round | 4.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23F342F100BF1H1    |    | Genteq  | Special  | 3400  |     | 100 | 1.375 | Round | 4.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F8052            |    | Genteq  | Standard | 100   |     | 240 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23B193F080DF1H1    |    | Genteq  | Special  | 19000 |     | 80  | 2     | Round | 4.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F9630BX          | BX | Genteq  | Standard | 20    |     | 440 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23C213F150FJ1H1    |    | Genteq  | Special  | 21000 |     | 150 | 3     | Round | 5.875 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23M492F400F11H1    |    | Genteq  | Special  | 4900  |     | 400 | 3     | Round | 5.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F6774BX          | BX | Genteq  | Standard | 24    |     | 330 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F5116BX          | BX | Genteq  | Standard | 40    |     | 440 | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F8312BX          | BX | Genteq  | Standard | 90    |     | 370 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9856            |    | Genteq  | Standard | 40    | 5   | 440 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6783BX          | BX | Genteq  | Special  | 25    |     | 330 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 27L430             |    | Genteq  | Standard | 18    | 6   | 280 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23B132F250CE1H1    |    | Genteq  | Special  | 1300  |     | 250 | 1.75  | Round | 3.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F6766BR          | BR | Genteq  | Standard | 7     |     | 330 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23M652F300E11H1    |    | Genteq  | Special  | 6500  |     | 300 | 2.5   | Round | 5.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F6951BR          | BR | Genteq  | Standard | 22.5  |     | 540 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23A163F075CD1H1    |    | Genteq  | Special  | 16000 |     | 75  | 1.75  | Round | 3.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 97F9730BX          | BX | Genteq  | Standard | 25    | 5   | 440 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB300E000P440DAB X | BX | PROLINE | Standard | 30    |     | 440 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23B373F050C11H1    |    | Genteq  | Special  | 37000 |     | 50  | 1.75  | Round | 5.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F9641            |    | Genteq  | Standard | 40    |     | 440 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23F293F100F11H1    |    | Genteq  | Special  | 29000 |     | 100 | 3     | Round | 5.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F6744BX          | BX | Genteq  | Special  | 12.5  |     | 330 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F6767BX          | BX | Genteq  | Standard | 10    |     | 330 | 1.5   | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F8218            |    | Genteq  | Standard | 30    |     | 240 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23M751F250BC1H1    |    | Genteq  | Special  | 750   |     | 250 | 1.375 | Round | 2.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F9063BX          | BX | Genteq  | Standard | 60    | 7.5 | 440 | 2     | Oval  | 6.25  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB700E000T370EA    |    | PROLINE | Standard | 70    |     | 370 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |

|                   |    |         |          |       |     |     |       |       |       |                          |       |                |
|-------------------|----|---------|----------|-------|-----|-----|-------|-------|-------|--------------------------|-------|----------------|
| PB300Z100S440DABX | BX | PROLINE | Standard | 30    | 10  | 440 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23J202F250CG1H1   |    | Genteq  | Special  | 2000  |     | 250 | 1.75  | Round | 4.625 | Electrolytic             | 2000  | -40°C to 105°C |
| 97F6945BR         | BR | Genteq  | Standard | 24    |     | 580 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| PB300Y075C370DA   |    | PROLINE | Standard | 30    | 7.5 | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23A592F100DB1H1   |    | Genteq  | Special  | 5900  |     | 100 | 2     | Round | 2.125 | Electrolytic             | 1000  | -40°C to 85°C  |
| 23F293F075DI1H1   |    | Genteq  | Special  | 29000 |     | 75  | 2     | Round | 5.625 | Electrolytic             | 1000  | -55°C to 105°C |
| 23H391F400DB1H1   |    | Genteq  | Special  | 390   |     | 400 | 2     | Round | 2.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 97F9979BX         | BX | Genteq  | Standard | 25    | 7.5 | 440 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23C123F080CD1H1   |    | Genteq  | Special  | 12000 |     | 80  | 1.75  | Round | 3.125 | Electrolytic             | 1000  | -45°C to 95°C  |
| 23B472F060BB1H1   |    | Genteq  | Special  | 4700  |     | 60  | 1.375 | Round | 2.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| 23J151F400BB1H1   |    | Genteq  | Special  | 150   |     | 400 | 1.375 | Round | 2.125 | Electrolytic             | 2000  | -40°C to 105°C |
| 97F9859           |    | Genteq  | Standard | 45    | 5   | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F6696           |    | Genteq  | Special  | 38    |     | 300 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F6804           |    | Genteq  | Special  | 10    |     | 280 | 1.25  | Oval  | 2.62  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F6931           |    | Genteq  | Standard | 20    |     | 580 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23C143F100CG1H1   |    | Genteq  | Special  | 14000 |     | 100 | 1.75  | Round | 4.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| PB500Z100T440EA   |    | PROLINE | Standard | 50    | 10  | 440 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23C652F150ED1H1   |    | Genteq  | Special  | 6500  |     | 150 | 2.5   | Round | 3.125 | Electrolytic             | 1000  | -45°C to 95°C  |
| 23J152F200CD1H1   |    | Genteq  | Special  | 1500  |     | 200 | 1.75  | Round | 3.125 | Electrolytic             | 2000  | -40°C to 105°C |
| 23B262F150BH1H1   |    | Genteq  | Special  | 2600  |     | 150 | 1.375 | Round | 5.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| PB550Z100T370DABX | BX | PROLINE | Standard | 55    | 10  | 370 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23F353F080EH1H1   |    | Genteq  | Special  | 35000 |     | 80  | 2.5   | Round | 5.125 | Electrolytic             | 1000  | -55°C to 105°C |
| 97F9615           |    | Genteq  | Standard | 40    |     | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F6530           |    | Genteq  | Standard | 40    |     | 280 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23F323F060DI1H1   |    | Genteq  | Special  | 32000 |     | 60  | 2     | Round | 5.625 | Electrolytic             | 1000  | -55°C to 105°C |
| 23H582F250EH1H1   |    | Genteq  | Special  | 5800  |     | 250 | 2.5   | Round | 5.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| PB600E000D440HABX | BX | PROLINE | Standard | 60    |     | 440 | 2     | Oval  | 4.25  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23B203F075DE1H1   |    | Genteq  | Special  | 20000 |     | 75  | 2     | Round | 3.625 | Electrolytic             | 3000  | -40°C to 85°C  |
| 97F6865RC         | RC | Genteq  | Standard | 35    |     | 280 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F9673BX         | BX | Genteq  | Standard | 20    | 5   | 370 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F8049BX         | BX | Genteq  | Standard | 85    |     | 240 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 27L7009BX         | BX | Genteq  | Special  | 24    |     | 400 | 1.25  | Oval  | 3.12  | Oil-Filled (UL Approved) | 60000 | -40°C to 100°C |
| 97F6882BR         | BR | Genteq  | Standard | 24    | 8   | 280 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23C832F080DB1H1   |    | Genteq  | Special  | 8300  |     | 80  | 2     | Round | 2.125 | Electrolytic             | 1000  | -45°C to 95°C  |
| PB300Y075C440DA   |    | PROLINE | Standard | 30    | 7.5 | 440 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| PB600Z100T370EA   |    | PROLINE | Standard | 60    | 10  | 370 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23B163F060DC1H1   |    | Genteq  | Special  | 16000 |     | 60  | 2     | Round | 2.625 | Electrolytic             | 3000  | -40°C to 85°C  |
| 97F6857BR         | BR | Genteq  | Standard | 8     |     | 280 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F6886BX         | BX | Genteq  | Standard | 27    | 8   | 280 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F9007           |    | Genteq  | Standard | 35    |     | 370 | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23B662F060BC1H1   |    | Genteq  | Special  | 6600  |     | 60  | 1.375 | Round | 2.625 | Electrolytic             | 3000  | -40°C to 85°C  |
| 97F6765           |    | Genteq  | Standard | 6     |     | 330 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23H182F350DH1H1   |    | Genteq  | Special  | 1800  |     | 350 | 2     | Round | 5.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23F124F050FI1H1   |    | Genteq  | Special  | 12000 |     | 50  | 3     | Round | 5.625 | Electrolytic             | 1000  | -55°C to 105°C |
| 27L6093           |    | Genteq  | Special  | 2.5   |     | 660 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23H242F200CE1H1   |    | Genteq  | Special  | 2400  |     | 200 | 1.75  | Round | 3.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 97F8254           |    | Genteq  | Standard | 25    |     | 600 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F6762BX         | BX | Genteq  | Standard | 11    |     | 330 | 1.5   | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 27L865BX          | BX | Genteq  | Standard | 15    | 6   | 400 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F5781BX         | BX | Genteq  | Standard | 50    | 7.5 | 440 | 2     | Oval  | 5.25  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |

|                   |    |         |          |       |     |     |       |       |       |                            |        |                |
|-------------------|----|---------|----------|-------|-----|-----|-------|-------|-------|----------------------------|--------|----------------|
| 24DB400B370PA     |    | Genteq  | Standard | 40    |     | 370 | 1.75  | Round | 3.189 | Dry (UL Construction Only) | 60000  | -40°C to 70°C  |
| 23M292F350DI1H1   |    | Genteq  | Special  | 2900  |     | 350 | 2     | Round | 5.625 | Electrolytic               | 2000   | -40°C to 85°C  |
| 23F353F060FD1H1   |    | Genteq  | Special  | 35000 |     | 60  | 3     | Round | 3.125 | Electrolytic               | 1000   | -55°C to 105°C |
| 97F6947BX         | BX | Genteq  | Special  | 52    |     | 330 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 23B163F060CD1H1   |    | Genteq  | Special  | 16000 |     | 60  | 1.75  | Round | 3.125 | Electrolytic               | 3000   | -40°C to 85°C  |
| PB550E000T440EABX | BX | PROLINE | Standard | 55    |     | 440 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved)   | 10000  | -40°C to 70°C  |
| 97F9608           |    | Genteq  | Standard | 30    |     | 370 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 23J172F200DD1H1   |    | Genteq  | Special  | 1700  |     | 200 | 2     | Round | 3.125 | Electrolytic               | 2000   | -40°C to 105°C |
| 23M472F350EI1H1   |    | Genteq  | Special  | 4700  |     | 350 | 2.5   | Round | 5.625 | Electrolytic               | 2000   | -40°C to 85°C  |
| 97F6804BX         | BX | Genteq  | Special  | 10    |     | 280 | 1.25  | Oval  | 2.62  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 97F6602BX         | BX | Genteq  | Standard | 15    |     | 400 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 97F5368BX         | BX | Genteq  | Special  | 35    | 5   | 440 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| PB350Y100C440EABX | BX | PROLINE | Standard | 35    | 10  | 440 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved)   | 10000  | -40°C to 70°C  |
| 23D283F016BG1H1   |    | Genteq  | Special  | 28000 |     | 16  | 1.375 | Round | 4.625 | Electrolytic               | 1000   | -55°C to 85°C  |
| PB700Z100T440EABX | BX | PROLINE | Standard | 70    | 10  | 440 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved)   | 10000  | -40°C to 70°C  |
| 23H112F450EE1H1   |    | Genteq  | Special  | 1100  |     | 450 | 2.5   | Round | 3.625 | Electrolytic               | 2000   | -40°C to 85°C  |
| 97F9053           |    | Genteq  | Special  | 30    | 7.5 | 440 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 23B172F250CG1H1   |    | Genteq  | Special  | 1700  |     | 250 | 1.75  | Round | 4.625 | Electrolytic               | 3000   | -40°C to 85°C  |
| 23B233F100EI1H1   |    | Genteq  | Special  | 23000 |     | 100 | 2.5   | Round | 5.625 | Electrolytic               | 3000   | -40°C to 85°C  |
| 27L947            |    | Genteq  | Standard | 45    | 7.5 | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 97F9264           |    | Genteq  | Standard | 20    |     | 410 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 23H981F450CI1H1   |    | Genteq  | Special  | 980   |     | 450 | 1.75  | Round | 5.625 | Electrolytic               | 2000   | -40°C to 85°C  |
| 23C253F050BI1H1   |    | Genteq  | Special  | 25000 |     | 50  | 1.375 | Round | 5.625 | Electrolytic               | 1000   | -45°C to 95°C  |
| 23C333F075DH1H1   |    | Genteq  | Special  | 33000 |     | 75  | 2     | Round | 5.125 | Electrolytic               | 1000   | -45°C to 95°C  |
| PB150Z075S370CABX | BX | PROLINE | Standard | 15    | 7.5 | 370 | 2     | Round | 2.88  | Oil-Filled (UL Approved)   | 10000  | -40°C to 70°C  |
| 97F9628           |    | Genteq  | Standard | 17.5  |     | 440 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 97F6768BX         | BX | Genteq  | Standard | 14    |     | 330 | 1.5   | Oval  | 2.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 23J841F200BD1H1   |    | Genteq  | Special  | 840   |     | 200 | 1.375 | Round | 3.125 | Electrolytic               | 2000   | -40°C to 105°C |
| 23H262F300CI1H1   |    | Genteq  | Special  | 2600  |     | 300 | 1.75  | Round | 5.625 | Electrolytic               | 2000   | -40°C to 85°C  |
| 23M162F400CI1H1   |    | Genteq  | Special  | 1600  |     | 400 | 1.75  | Round | 5.625 | Electrolytic               | 2000   | -40°C to 85°C  |
| 41L2150           |    | Genteq  | Stock    | 15    |     | 250 | 0.96  | Round | 1.65  | Dry-Axial Leaded           | 100000 | -40°C to 85°C  |
| PB650E000T440EABX | BX | PROLINE | Standard | 65    |     | 440 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved)   | 10000  | -40°C to 70°C  |
| 97F9001BX         | BX | Genteq  | Standard | 7.5   |     | 370 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 23F133F100FD1H1   |    | Genteq  | Special  | 13000 |     | 100 | 3     | Round | 3.125 | Electrolytic               | 1000   | -55°C to 105°C |
| 23D413F028CI1H1   |    | Genteq  | Special  | 41000 |     | 28  | 3     | Round | 8.625 | Electrolytic               | 1000   | -55°C to 85°C  |
| 23A183F050BE1H1   |    | Genteq  | Special  | 18000 |     | 50  | 1.375 | Round | 3.625 | Electrolytic               | 1000   | -40°C to 85°C  |
| 23A692F150DG1H1   |    | Genteq  | Special  | 6900  |     | 150 | 2     | Round | 4.625 | Electrolytic               | 1000   | -40°C to 85°C  |
| 97F6950BX         | BX | Genteq  | Standard | 12    | 12  | 400 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 23H112F200BD1H1   |    | Genteq  | Special  | 1100  |     | 200 | 1.375 | Round | 3.125 | Electrolytic               | 2000   | -40°C to 85°C  |
| 97F9251BX         | BX | Genteq  | Standard | 25    | 3.2 | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 97F8049S          | S  | Genteq  | Stock    | 85    |     | 240 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| PB500E000S370DABX | BX | PROLINE | Standard | 50    |     | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved)   | 10000  | -40°C to 70°C  |
| 97F8254BX         | BX | Genteq  | Standard | 25    |     | 600 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 97F5362           |    | Genteq  | Special  | 25    | 7.5 | 440 | 2     | Oval  | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 23B402F100BF1H1   |    | Genteq  | Special  | 4000  |     | 100 | 1.375 | Round | 4.125 | Electrolytic               | 3000   | -40°C to 85°C  |
| PB450Y100C440EABX | BX | PROLINE | Standard | 45    | 10  | 440 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved)   | 10000  | -40°C to 70°C  |
| 97F8294           |    | Genteq  | Standard | 60    |     | 330 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 23F792F075CC1H1   |    | Genteq  | Special  | 7900  |     | 75  | 1.75  | Round | 2.625 | Electrolytic               | 1000   | -55°C to 105°C |
| 97F6702BX         | BX | Genteq  | Special  | 7     |     | 330 | 1.25  | Oval  | 2.62  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 23H381F450CC1H1   |    | Genteq  | Special  | 380   |     | 450 | 1.75  | Round | 2.625 | Electrolytic               | 2000   | -40°C to 85°C  |
| 23A483F060DG1H1   |    | Genteq  | Special  | 48000 |     | 60  | 2     | Round | 4.625 | Electrolytic               | 1000   | -40°C to 85°C  |

|                   |    |         |          |       |     |     |       |       |       |                          |        |                |
|-------------------|----|---------|----------|-------|-----|-----|-------|-------|-------|--------------------------|--------|----------------|
| PB450Z075T440DABX | BX | PROLINE | Standard | 45    | 7.5 | 440 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 27L322            |    | Genteq  | Special  | 80    |     | 440 | 2.5   | Round | 5.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23A163F075DC1H1   |    | Genteq  | Special  | 16000 |     | 75  | 2     | Round | 2.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 97F9053BX         | BX | Genteq  | Special  | 30    | 7.5 | 440 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23B433F060EE1H1   |    | Genteq  | Special  | 43000 |     | 60  | 2.5   | Round | 3.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F6925           |    | Genteq  | Special  | 48    |     | 300 | 2     | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23J132F400EF1H1   |    | Genteq  | Special  | 1300  |     | 400 | 2.5   | Round | 4.125 | Electrolytic             | 2000   | -40°C to 105°C |
| 23J362F400FL1H1   |    | Genteq  | Special  | 3600  |     | 400 | 3     | Round | 8.625 | Electrolytic             | 2000   | -40°C to 105°C |
| 23J271F400CB1H1   |    | Genteq  | Special  | 270   |     | 400 | 1.75  | Round | 2.125 | Electrolytic             | 2000   | -40°C to 105°C |
| PB300Y075C440DABX | BX | PROLINE | Standard | 30    | 7.5 | 440 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23J602F250FG1H1   |    | Genteq  | Special  | 6000  |     | 250 | 3     | Round | 4.625 | Electrolytic             | 2000   | -40°C to 105°C |
| 27L1001           |    | Genteq  | Standard | 45    |     | 440 | 2.5   | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F5437BX         | BX | Genteq  | Standard | 3     |     | 440 | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23C692F075CB1H1   |    | Genteq  | Special  | 6900  |     | 75  | 1.75  | Round | 2.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23H502F200DI1H1   |    | Genteq  | Special  | 5000  |     | 200 | 2     | Round | 5.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23M222F250BI1H1   |    | Genteq  | Special  | 2200  |     | 250 | 1.375 | Round | 5.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23C891F250BE1H1   |    | Genteq  | Special  | 890   |     | 250 | 1.375 | Round | 3.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 40L3501           |    | Genteq  | Stock    | 5     |     | 400 | 0.69  | Oval  | 1.75  | Dry-Axial Leaded         | 100000 | -55°C to 105°C |
| 23C123F200FI1H1   |    | Genteq  | Special  | 12000 |     | 200 | 3     | Round | 5.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F6522BX         | BX | Genteq  | Standard | 24    |     | 280 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| PB150Y050C440CA   |    | PROLINE | Standard | 15    | 5   | 440 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F9836BX         | BX | Genteq  | Special  | 30    | 4   | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23C283F075ED1H1   |    | Genteq  | Special  | 28000 |     | 75  | 2.5   | Round | 3.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| PB450E000P370EABX | BX | PROLINE | Standard | 45    |     | 370 | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F6770           |    | Genteq  | Standard | 17.5  |     | 330 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F9636BX         | BX | Genteq  | Standard | 30    |     | 440 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F8050S          | S  | Genteq  | Stock    | 90    |     | 240 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB300E000C240CABX | BX | PROLINE | Standard | 30    |     | 240 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F6537           |    | Genteq  | Standard | 24    |     | 330 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F6694           |    | Genteq  | Special  | 20    |     | 480 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| PB300E000P370DABX | BX | PROLINE | Standard | 30    |     | 370 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23C133F075DC1H1   |    | Genteq  | Special  | 13000 |     | 75  | 2     | Round | 2.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23A802F100BG1H1   |    | Genteq  | Special  | 8000  |     | 100 | 1.375 | Round | 4.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 23M272F400EG1H1   |    | Genteq  | Special  | 2700  |     | 400 | 2.5   | Round | 4.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23A463F050CG1H1   |    | Genteq  | Special  | 46000 |     | 50  | 1.75  | Round | 4.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 23B133F150FG1H1   |    | Genteq  | Special  | 13000 |     | 150 | 3     | Round | 4.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F6727           |    | Genteq  | Standard | 32    |     | 330 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 27L176BR          | BR | Genteq  | Special  | 7.5   |     | 540 | 1.5   | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23C203F060DC1H1   |    | Genteq  | Special  | 20000 |     | 60  | 2     | Round | 2.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23A313F100EG1H1   |    | Genteq  | Special  | 31000 |     | 100 | 2.5   | Round | 4.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| PB550E000T370DA   |    | PROLINE | Standard | 55    |     | 370 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23B412F150CG1H1   |    | Genteq  | Special  | 4100  |     | 150 | 1.75  | Round | 4.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F8005BX         | BX | Genteq  | Special  | 30    |     | 440 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23M102F450DF1H1   |    | Genteq  | Special  | 1000  |     | 450 | 2     | Round | 4.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F6519           |    | Genteq  | Standard | 16    |     | 330 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 27L543BX          | BX | Genteq  | Standard | 9.5   | 6.5 | 330 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 27L7008           |    | Genteq  | Special  | 11    | 6   | 330 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 100°C |
| 97F6683BX         | BX | Genteq  | Special  | 21    |     | 480 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23B262F250DH1H1   |    | Genteq  | Special  | 2600  |     | 250 | 2     | Round | 5.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F9973BX         | BX | Genteq  | Standard | 55    | 7.5 | 370 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23F854F250DC1H1   |    | Genteq  | Special  | 850   |     | 250 | 2     | Round | 2.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 23B421F250BC1H1   |    | Genteq  | Special  | 420   |     | 250 | 1.375 | Round | 2.625 | Electrolytic             | 3000   | -40°C to 85°C  |

|                    |    |         |          |            |     |     |       |       |       |                          |        |                |
|--------------------|----|---------|----------|------------|-----|-----|-------|-------|-------|--------------------------|--------|----------------|
| 97F6885BX          | BX | Genteq  | Standard | 36         | 12  | 280 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F6758            |    | Genteq  | Standard | 15         |     | 330 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| PB250E000P440DA    |    | PROLINE | Standard | 25         |     | 440 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23F542F150EF1H1    |    | Genteq  | Special  | 5400       |     | 150 | 2.5   | Round | 4.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 23H791F450DF1H1    |    | Genteq  | Special  | 790        |     | 450 | 2     | Round | 4.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23C542F075BC1H1    |    | Genteq  | Special  | 5400       |     | 75  | 1.375 | Round | 2.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23C213F050DB1H1    |    | Genteq  | Special  | 21000      |     | 50  | 2     | Round | 2.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23H132F200BE1H1    |    | Genteq  | Special  | 1300       |     | 200 | 1.375 | Round | 3.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23H122F300CD1H1    |    | Genteq  | Special  | 1200       |     | 300 | 1.75  | Round | 3.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 41L4101            |    | Genteq  | Stock    | 1          |     | 400 | 0.47  | Round | 1.22  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 97F8071            |    | Genteq  | Standard | 60         |     | 370 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L862             |    | Genteq  | Standard | 35         | 24  | 400 | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F6766S           | S  | Genteq  | Stock    | 7          |     | 330 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23A283F080DF1H1    |    | Genteq  | Special  | 28000      |     | 80  | 2     | Round | 4.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| PB400E000S370DAB X | BX | PROLINE | Standard | 40         |     | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23H701F250BC1H1    |    | Genteq  | Special  | 700        |     | 250 | 1.375 | Round | 2.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23J102F250BF1H1    |    | Genteq  | Special  | 1000       |     | 250 | 1.375 | Round | 4.125 | Electrolytic             | 2000   | -40°C to 105°C |
| 97F6878            |    | Genteq  | Standard | 20         | 15  | 280 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23B652F075CB1H1    |    | Genteq  | Special  | 6500       |     | 75  | 1.75  | Round | 2.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F6779            |    | Genteq  | Standard | 18         |     | 330 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23M252F200BH1H1    |    | Genteq  | Special  | 2500       |     | 200 | 1.375 | Round | 5.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23H681F450CF1H1    |    | Genteq  | Special  | 680        |     | 450 | 1.75  | Round | 4.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23A133F075BF1H1    |    | Genteq  | Special  | 13000      |     | 75  | 1.375 | Round | 4.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 97F9993            |    | Genteq  | Standard | 25         | 7.5 | 440 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23C163F075CE1H1    |    | Genteq  | Special  | 16000      |     | 75  | 1.75  | Round | 3.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F8251            |    | Genteq  | Standard | 15         |     | 600 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23C184F060FL1H1    |    | Genteq  | Special  | 18000<br>0 |     | 60  | 3     | Round | 8.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23D203F028CD1H1    |    | Genteq  | Special  | 20000      |     | 28  | 1.75  | Round | 3.125 | Electrolytic             | 1000   | -55°C to 85°C  |
| 23F372F150ED1H1    |    | Genteq  | Special  | 3700       |     | 150 | 2.5   | Round | 3.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 23F461F200BC1H1    |    | Genteq  | Special  | 460        |     | 200 | 1.375 | Round | 2.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F6643BX          | BX | Genteq  | Special  | 30         |     | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F6673BX          | BX | Genteq  | Special  | 14         |     | 480 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F6884            |    | Genteq  | Standard | 33         | 15  | 280 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F8008BX          | BX | Genteq  | Special  | 50         |     | 440 | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB150E000P370CA    |    | PROLINE | Standard | 15         |     | 370 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23C233F080CH1H1    |    | Genteq  | Special  | 23000      |     | 80  | 1.75  | Round | 5.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 27L442RR           | RR | Genteq  | Standard | 28         | 7   | 280 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 27L1044            |    | Genteq  | Standard | 55         |     | 370 | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23C223F100EE1H1    |    | Genteq  | Special  | 22000      |     | 100 | 2.5   | Round | 3.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23J781F250DB1H1    |    | Genteq  | Special  | 780        |     | 250 | 2     | Round | 2.125 | Electrolytic             | 2000   | -40°C to 105°C |
| PB300Y050C440DAB X | BX | PROLINE | Standard | 30         | 5   | 440 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F5114            |    | Genteq  | Special  | 35         |     | 370 | 2     | Round | 4.25  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9025            |    | Genteq  | Special  | 40         | 7.5 | 370 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L7003            |    | Genteq  | Standard | 26         |     | 330 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 100°C |
| 23J242F350EH1H1    |    | Genteq  | Special  | 2400       |     | 350 | 2.5   | Round | 5.125 | Electrolytic             | 2000   | -40°C to 105°C |
| 23C162F200BG1H1    |    | Genteq  | Special  | 1600       |     | 200 | 1.375 | Round | 4.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23F552F075CB1H1    |    | Genteq  | Special  | 5500       |     | 75  | 1.75  | Round | 2.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F6684            |    | Genteq  | Special  | 12.5       |     | 440 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F9039            |    | Genteq  | Standard | 20         |     | 440 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L401BX           | BX | Genteq  | Standard | 20         | 8   | 300 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| PB125E000P440CAB X | BX | PROLINE | Standard | 12.5       |     | 440 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23J362F200EE1H1    |    | Genteq  | Special  | 3600       |     | 200 | 2.5   | Round | 3.625 | Electrolytic             | 2000   | -40°C to 105°C |



|                  |    |         |          |       |    |      |       |       |       |                          |        |                |
|------------------|----|---------|----------|-------|----|------|-------|-------|-------|--------------------------|--------|----------------|
| 23B352F200EE1H1  |    | Genteq  | Special  | 3500  |    | 200  | 2.5   | Round | 3.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23F263F050CF1H1  |    | Genteq  | Special  | 26000 |    | 50   | 1.75  | Round | 4.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F8069BX        | BX | Genteq  | Standard | 50    |    | 370  | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23J481F200BB1H1  |    | Genteq  | Special  | 480   |    | 200  | 1.375 | Round | 2.125 | Electrolytic             | 2000   | -40°C to 105°C |
| 23C663F050FD1H1  |    | Genteq  | Special  | 66000 |    | 50   | 3     | Round | 3.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 27L432           |    | Genteq  | Standard | 22    | 7  | 280  | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23C343F100BC1H1  |    | Genteq  | Special  | 3400  |    | 100  | 1.375 | Round | 2.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23A172F150BD1H1  |    | Genteq  | Special  | 1700  |    | 150  | 1.375 | Round | 3.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 97F5401          |    | Genteq  | Special  | 45    | 5  | 440  | 2     | Oval  | 5.25  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 41L6681          |    | Genteq  | Stock    | 6.8   |    | 600  | 1.12  | Round | 2.17  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| PB250Z100S370CA  |    | PROLINE | Standard | 25    | 10 | 370  | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23F123F150FJ1H1  |    | Genteq  | Special  | 12000 |    | 150  | 3     | Round | 5.875 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F8039          |    | Genteq  | Standard | 35    |    | 240  | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L647BX         | BX | Genteq  | Standard | 50    | 10 | 440  | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6768          |    | Genteq  | Standard | 14    |    | 330  | 1.5   | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 25L2005BX        | BX | Genteq  | Special  | 35    |    | 370  | 1.25  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23C104F050FF1H1  |    | Genteq  | Special  | 10000 | 0  | 50   | 3     | Round | 4.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F9002BX        | BX | Genteq  | Standard | 10    |    | 370  | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB125E000A370CAS | S  | PROLINE | Stock    | 12.5  |    | 370  | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F9627          |    | Genteq  | Special  | 15    |    | 440  | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F8242          |    | Genteq  | Special  | 2.5   |    | 600  | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB020E000P370CA  |    | PROLINE | Standard | 2     |    | 370  | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23D173F055CH1H1  |    | Genteq  | Special  | 17000 |    | 55   | 1.75  | Round | 5.125 | Electrolytic             | 1000   | -55°C to 85°C  |
| 23A133F150EH1H1  |    | Genteq  | Special  | 13000 |    | 150  | 2.5   | Round | 5.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 23H512F300FF1H1  |    | Genteq  | Special  | 5100  |    | 300  | 3     | Round | 4.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F6881BX        | BX | Genteq  | Standard | 42    | 14 | 280  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| PB450Z050T440DA  |    | PROLINE | Standard | 45    | 5  | 440  | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F6866          |    | Genteq  | Standard | 40    |    | 280  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F8246BX        | BX | Genteq  | Standard | 6     |    | 600  | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23C642F080CB1H1  |    | Genteq  | Special  | 6400  |    | 80   | 1.75  | Round | 2.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 42L4473          |    | Genteq  | Stock    | 0.047 |    | 3000 | 0.73  | Round | 1.65  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 23A673F060EF1H1  |    | Genteq  | Special  | 67000 |    | 60   | 2.5   | Round | 4.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 27L667BX         | BX | Genteq  | Standard | 42    | 22 | 400  | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 27L590RR         | RR | Genteq  | Standard | 24    | 11 | 300  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23H302F350EH1H1  |    | Genteq  | Special  | 3000  |    | 350  | 2.5   | Round | 5.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23C242F100BB1H1  |    | Genteq  | Special  | 2400  |    | 100  | 1.375 | Round | 2.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| PB050E000P440CA  |    | PROLINE | Standard | 5     |    | 440  | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 27L791           |    | Genteq  | Standard | 8     |    | 580  | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23A413F075DH1H1  |    | Genteq  | Special  | 41000 |    | 75   | 2     | Round | 5.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 97F9084BX        | BX | Genteq  | Standard | 55    |    | 440  | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F8041BX        | BX | Genteq  | Standard | 45    |    | 240  | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23A263F150FL1H1  |    | Genteq  | Special  | 26000 |    | 150  | 3     | Round | 8.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 97F5457BX        | BX | Genteq  | Special  | 7.5   |    | 370  | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23F353F060EF1H1  |    | Genteq  | Special  | 35000 |    | 60   | 2.5   | Round | 4.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F8253BX        | BX | Genteq  | Standard | 20    |    | 600  | 1.5   | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23H192F450E1H1   |    | Genteq  | Special  | 1900  |    | 450  | 2.5   | Round | 5.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| PB300Y100C440EA  |    | PROLINE | Standard | 30    | 10 | 440  | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F9844          |    | Genteq  | Standard | 45    | 5  | 440  | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23C663F050EF1H1  |    | Genteq  | Special  | 66000 |    | 50   | 2.5   | Round | 4.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F8040BX        | BX | Genteq  | Standard | 40    |    | 240  | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |

|                  |    |         |          |       |     |      |       |       |       |                          |        |                |
|------------------|----|---------|----------|-------|-----|------|-------|-------|-------|--------------------------|--------|----------------|
| 23H261F350BB1H1  |    | Genteq  | Special  | 260   |     | 350  | 1.375 | Round | 2.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F6755RC        | RC | Genteq  | Standard | 26    |     | 330  | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| PB020E000A370AA  |    | PROLINE | Standard | 2     |     | 370  | 1.25  | Oval  | 1.56  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F6883          |    | Genteq  | Standard | 36    | 20  | 280  | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23F532F050BB1H1  |    | Genteq  | Special  | 5300  |     | 50   | 1.375 | Round | 2.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 23B902F050BD1H1  |    | Genteq  | Special  | 9000  |     | 50   | 1.375 | Round | 3.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| PB400E000P440EA  |    | PROLINE | Standard | 40    |     | 440  | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 27L443RR         | RR | Genteq  | Standard | 17    | 7   | 400  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23H861F450CH1H1  |    | Genteq  | Special  | 860   |     | 450  | 1.75  | Round | 5.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F6947          |    | Genteq  | Special  | 52    |     | 330  | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F9626S         | S  | Genteq  | Stock    | 15    |     | 440  | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L633BX         | BX | Genteq  | Standard | 70    | 5   | 370  | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23H122F250BF1H1  |    | Genteq  | Special  | 1200  |     | 250  | 1.375 | Round | 4.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23B222F250CI1H1  |    | Genteq  | Special  | 2200  |     | 250  | 1.75  | Round | 5.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F6753BX        | BX | Genteq  | Special  | 7     |     | 330  | 1.5   | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23J312F200CI1H1  |    | Genteq  | Special  | 3100  |     | 200  | 1.75  | Round | 5.625 | Electrolytic             | 2000   | -40°C to 105°C |
| 27L6012BX        | BX | Genteq  | Special  | 4     |     | 660  | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L7001BR        | BR | Genteq  | Standard | 10    |     | 400  | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 100°C |
| 23M112F350BH1H1  |    | Genteq  | Special  | 1100  |     | 350  | 1.375 | Round | 5.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23H211F450BC1H1  |    | Genteq  | Special  | 210   |     | 450  | 1.375 | Round | 2.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F5103          |    | Genteq  | Special  | 30    |     | 440  | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23D433F007BF1H1  |    | Genteq  | Special  | 43000 |     | 7.5  | 1.375 | Round | 4.125 | Electrolytic             | 1000   | -55°C to 85°C  |
| 97F9816BX        | BX | Genteq  | Standard | 60    | 5   | 370  | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F8053          |    | Genteq  | Standard | 120   |     | 240  | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9837BX        | BX | Genteq  | Special  | 35    | 4   | 370  | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23A113F075BE1H1  |    | Genteq  | Special  | 11000 |     | 75   | 1.375 | Round | 3.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 97F6868RC        | RC | Genteq  | Standard | 26    |     | 280  | 1.5   | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 42L3222          |    | Genteq  | Stock    | 0.22  |     | 2000 | 0.93  | Round | 1.65  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 97F9012S         | S  | Genteq  | Stock    | 70    |     | 370  | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L576BX         | BX | Genteq  | Special  | 20    | 8   | 400  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F6746BX        | BX | Genteq  | Standard | 12    |     | 330  | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F6950          |    | Genteq  | Standard | 12    | 12  | 400  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23B433F100FL1H1  |    | Genteq  | Special  | 43000 |     | 100  | 3     | Round | 8.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F9987BX        | BX | Genteq  | Standard | 50    | 7.5 | 440  | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6855BR        | BR | Genteq  | Standard | 22.5  |     | 280  | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23D213F016BE1H1  |    | Genteq  | Special  | 21000 |     | 16   | 1.375 | Round | 3.625 | Electrolytic             | 1000   | -55°C to 85°C  |
| 23H552F200EF1H1  |    | Genteq  | Special  | 5500  |     | 200  | 2.5   | Round | 4.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F8064          |    | Genteq  | Standard | 25    |     | 370  | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23C103F075CC1H1  |    | Genteq  | Special  | 10000 |     | 75   | 1.75  | Round | 2.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| PB400E000S370DA  |    | PROLINE | Standard | 40    |     | 370  | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23A203F050CC1H1  |    | Genteq  | Special  | 20000 |     | 50   | 1.75  | Round | 2.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 23A643F075FE1H1  |    | Genteq  | Special  | 64000 |     | 75   | 3     | Round | 3.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 23H472F300EH1H1  |    | Genteq  | Special  | 4700  |     | 300  | 2.5   | Round | 5.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| PB450E000C370DAS | S  | PROLINE | Stock    | 45    |     | 370  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23C283F050DC1H1  |    | Genteq  | Special  | 28000 |     | 50   | 2     | Round | 2.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23H232F350FD1H1  |    | Genteq  | Special  | 2300  |     | 350  | 3     | Round | 3.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F6902BX        | BX | Genteq  | Special  | 55    |     | 240  | 2     | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23C882F050BC1H1  |    | Genteq  | Special  | 8800  |     | 50   | 1.375 | Round | 2.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F9319          |    | Genteq  | Special  | 55    | 7.5 | 440  | 2     | Oval  | 5.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6952BR        | BR | Genteq  | Standard | 36    |     | 540  | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23C632F100CC1H1  |    | Genteq  | Special  | 6300  |     | 100  | 1.75  | Round | 2.625 | Electrolytic             | 1000   | -45°C to 95°C  |

|                   |    |         |          |       |      |     |       |       |       |                          |       |                |
|-------------------|----|---------|----------|-------|------|-----|-------|-------|-------|--------------------------|-------|----------------|
| 23D203F028BH1H1   |    | Genteq  | Special  | 20000 |      | 28  | 1.375 | Round | 5.125 | Electrolytic             | 1000  | -55°C to 85°C  |
| 23C712F075BD1H1   |    | Genteq  | Special  | 7100  |      | 75  | 1.375 | Round | 3.125 | Electrolytic             | 1000  | -45°C to 95°C  |
| 97F6755BX         | BX | Genteq  | Standard | 26    |      | 330 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23B532F250FG1H1   |    | Genteq  | Special  | 5300  |      | 250 | 3     | Round | 4.625 | Electrolytic             | 3000  | -40°C to 85°C  |
| PB150Z050S370CABX | BX | PROLINE | Standard | 15    | 5    | 370 | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 27L402            |    | Genteq  | Standard | 24    | 8    | 300 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23A153F100CG1H1   |    | Genteq  | Special  | 15000 |      | 100 | 1.75  | Round | 4.625 | Electrolytic             | 1000  | -40°C to 85°C  |
| 97F5266BX         | BX | Genteq  | Special  | 45    |      | 370 | 2.5   | Round | 3.12  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23F462F060BC1H1   |    | Genteq  | Special  | 4600  |      | 60  | 1.375 | Round | 2.625 | Electrolytic             | 1000  | -55°C to 105°C |
| PB550Z075T370DABX | BX | PROLINE | Standard | 55    | 7.5  | 370 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| PB100E000P440CA   |    | PROLINE | Standard | 10    |      | 440 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23H322F200CG1H1   |    | Genteq  | Special  | 3200  |      | 200 | 1.75  | Round | 4.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23J302F200DG1H1   |    | Genteq  | Special  | 3000  |      | 200 | 2     | Round | 4.625 | Electrolytic             | 2000  | -40°C to 105°C |
| 97F8313           |    | Genteq  | Special  | 46    |      | 600 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 27L540BX          | BX | Genteq  | Standard | 16.5  | 11.5 | 330 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F6931BR         | BR | Genteq  | Standard | 20    |      | 580 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 27L388            |    | Genteq  | Special  | 60    |      | 440 | 2     | Oval  | 4.25  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23B233F075DF1H1   |    | Genteq  | Special  | 23000 |      | 75  | 2     | Round | 4.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| 97F9638S          | S  | Genteq  | Stock    | 35    |      | 440 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| PB050E000A440BA   |    | PROLINE | Standard | 5     |      | 440 | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23C233F080DF1H1   |    | Genteq  | Special  | 23000 |      | 80  | 2     | Round | 4.125 | Electrolytic             | 1000  | -45°C to 95°C  |
| 23F953F050FG1H1   |    | Genteq  | Special  | 95000 |      | 50  | 3     | Round | 4.625 | Electrolytic             | 1000  | -55°C to 105°C |
| 23H312F300D11H1   |    | Genteq  | Special  | 3100  |      | 300 | 2     | Round | 5.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 97F9844BX         | BX | Genteq  | Standard | 45    | 5    | 440 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23H122F350CF1H1   |    | Genteq  | Special  | 1200  |      | 350 | 1.75  | Round | 4.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 97F8044BX         | BX | Genteq  | Standard | 60    |      | 240 | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| PB300Y050C370DABX | BX | PROLINE | Standard | 30    | 5    | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F9992BX         | BX | Genteq  | Standard | 15    | 7.5  | 440 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23M742F200EF1H1   |    | Genteq  | Special  | 7400  |      | 200 | 2.5   | Round | 4.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 27L414BX          | BX | Genteq  | Standard | 70    | 10   | 370 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23F212F150B11H1   |    | Genteq  | Special  | 2100  |      | 150 | 1.375 | Round | 5.625 | Electrolytic             | 1000  | -55°C to 105°C |
| PB020E000A370AABX | BX | PROLINE | Standard | 2     |      | 370 | 1.25  | Oval  | 1.56  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F9491           |    | Genteq  | Standard | 30    |      | 370 | 1.25  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| PB600E000T440EA   |    | PROLINE | Standard | 60    |      | 440 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 27L1008           |    | Genteq  | Standard | 60    | 10   | 370 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 27L635            |    | Genteq  | Special  | 90    |      | 440 | 2.5   | Round | 5.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 27L727            |    | Genteq  | Standard | 45    | 19   | 300 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23M552F300FE1H1   |    | Genteq  | Special  | 5500  |      | 300 | 3     | Round | 3.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 97F6839BX         | BX | Genteq  | Special  | 43.5  |      | 280 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23H152F250BH1H1   |    | Genteq  | Special  | 1500  |      | 250 | 1.375 | Round | 5.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23H222F250DE1H1   |    | Genteq  | Special  | 2200  |      | 250 | 2     | Round | 3.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23B502F050BB1H1   |    | Genteq  | Special  | 5000  |      | 50  | 1.375 | Round | 2.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| 23C173F050BF1H1   |    | Genteq  | Special  | 17000 |      | 50  | 1.375 | Round | 4.125 | Electrolytic             | 1000  | -45°C to 95°C  |
| 97F9051BX         | BX | Genteq  | Special  | 25    | 10   | 440 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F9837           |    | Genteq  | Special  | 35    | 4    | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 27L635BX          | BX | Genteq  | Special  | 90    |      | 440 | 2.5   | Round | 5.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 27L907            |    | Genteq  | Special  | 55    |      | 240 | 1.75  | Oval  | 3.5   | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23A252F100BB1H1   |    | Genteq  | Special  | 2500  |      | 100 | 1.375 | Round | 2.125 | Electrolytic             | 1000  | -40°C to 85°C  |
| 23C282F150BG1H1   |    | Genteq  | Special  | 2800  |      | 150 | 1.375 | Round | 4.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| 23F313F080EG1H1   |    | Genteq  | Special  | 31000 |      | 80  | 2.5   | Round | 4.625 | Electrolytic             | 1000  | -55°C to 105°C |

|                   |    |         |          |            |     |     |       |       |       |                          |        |                |
|-------------------|----|---------|----------|------------|-----|-----|-------|-------|-------|--------------------------|--------|----------------|
| 97F6771BX         | BX | Genteq  | Standard | 18         |     | 330 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23F263F075DH1H1   |    | Genteq  | Special  | 26000      |     | 75  | 2     | Round | 5.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 23M551F350BD1H1   |    | Genteq  | Special  | 550        |     | 350 | 1.375 | Round | 3.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 27L6015           |    | Genteq  | Special  | 7          |     | 660 | 1.25  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6956BX         | BX | Genteq  | Standard | 22.5       |     | 540 | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23H262F400E1H1    |    | Genteq  | Special  | 2600       |     | 400 | 2.5   | Round | 5.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23B173F050DC1H1   |    | Genteq  | Special  | 17000      |     | 50  | 2     | Round | 2.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23B172F150BE1H1   |    | Genteq  | Special  | 1700       |     | 150 | 1.375 | Round | 3.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23F832F075BF1H1   |    | Genteq  | Special  | 8300       |     | 75  | 1.375 | Round | 4.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 23A104F060E1H1    |    | Genteq  | Special  | 10000<br>0 |     | 60  | 2.5   | Round | 5.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 27L872            |    | Genteq  | Standard | 60         | 5   | 370 | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9834S          | S  | Genteq  | Stock    | 35         | 5   | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6751BX         | BX | Genteq  | Special  | 9.25       |     | 330 | 1.25  | Oval  | 3.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F9981           |    | Genteq  | Standard | 30         | 5   | 440 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23F663F050EG1H1   |    | Genteq  | Special  | 66000      |     | 50  | 2.5   | Round | 4.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 23B152F250CF1H1   |    | Genteq  | Special  | 1500       |     | 250 | 1.75  | Round | 4.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23C123F075BG1H1   |    | Genteq  | Special  | 12000      |     | 75  | 1.375 | Round | 4.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23C413F050CH1H1   |    | Genteq  | Special  | 41000      |     | 50  | 1.75  | Round | 5.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F5729BX         | BX | Genteq  | Standard | 50         | 5   | 440 | 2     | Oval  | 5.25  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23A233F060BH1H1   |    | Genteq  | Special  | 23000      |     | 60  | 1.375 | Round | 5.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 23B143F100EE1H1   |    | Genteq  | Special  | 14000      |     | 100 | 2.5   | Round | 3.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23F183F060DE1H1   |    | Genteq  | Special  | 18000      |     | 60  | 2     | Round | 3.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 23F132F100BB1H1   |    | Genteq  | Special  | 1300       |     | 100 | 1.375 | Round | 2.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F5481           |    | Genteq  | Special  | 25         | 10  | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23B561F250BD1H1   |    | Genteq  | Special  | 460        |     | 250 | 1.375 | Round | 3.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F9858           |    | Genteq  | Standard | 50         | 7.5 | 370 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 41L2301           |    | Genteq  | Stock    | 3          |     | 250 | 0.53  | Round | 1.22  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 97F6526BR         | BR | Genteq  | Standard | 10         |     | 400 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23F134F050FJ1H1   |    | Genteq  | Special  | 13000<br>0 |     | 50  | 3     | Round | 5.875 | Electrolytic             | 1000   | -55°C to 105°C |
| 23C373F080FD1H1   |    | Genteq  | Special  | 37000      |     | 80  | 3     | Round | 3.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23H952F300FL1H1   |    | Genteq  | Special  | 9500       |     | 300 | 3     | Round | 8.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 27L1044BX         | BX | Genteq  | Standard | 55         |     | 370 | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23A353F075ED1H1   |    | Genteq  | Special  | 35000      |     | 75  | 2.5   | Round | 3.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| PB2502075S440DABX | BX | PROLINE | Standard | 25         | 7.5 | 440 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 27L1051           |    | Genteq  | Special  | 50         | 5   | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9991           |    | Genteq  | Standard | 20         | 7.5 | 370 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9626BX         | BX | Genteq  | Standard | 15         |     | 440 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F5339           |    | Genteq  | Standard | 5          |     | 440 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L590            |    | Genteq  | Standard | 24         | 11  | 300 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23F192F250DG1H1   |    | Genteq  | Special  | 1900       |     | 250 | 2     | Round | 4.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 23A172F150CB1H1   |    | Genteq  | Special  | 1700       |     | 150 | 1.75  | Round | 2.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 97F6505BX         | BX | Genteq  | Standard | 17.5       |     | 330 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23H112F200CB1H1   |    | Genteq  | Special  | 1100       |     | 200 | 1.75  | Round | 2.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F5161           |    | Genteq  | Standard | 15         |     | 370 | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F8056S          | S  | Genteq  | Stock    | 5          |     | 370 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23B843F060FG1H1   |    | Genteq  | Special  | 84000      |     | 60  | 3     | Round | 4.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23A124F050E1H1    |    | Genteq  | Special  | 12000<br>0 |     | 50  | 2.5   | Round | 5.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 27L432BX          | BX | Genteq  | Standard | 22         | 7   | 280 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F6678BX         | BX | Genteq  | Special  | 4.5        |     | 480 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F6940BR         | BR | Genteq  | Standard | 35         |     | 580 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F6644BX         | BX | Genteq  | Special  | 45         |     | 300 | 1.75  | Oval  | 4.25  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |

|                    |    |         |          |       |      |      |       |       |       |                          |        |                |
|--------------------|----|---------|----------|-------|------|------|-------|-------|-------|--------------------------|--------|----------------|
| 23B682F250F1H1     |    | Genteq  | Special  | 6800  |      | 250  | 3     | Round | 5.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23C812F150EE1H1    |    | Genteq  | Special  | 8100  |      | 150  | 2.5   | Round | 3.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 42L3332            |    | Genteq  | Stock    | 0.33  |      | 2000 | 1.12  | Round | 1.65  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 27L590BX           | BX | Genteq  | Standard | 24    | 11   | 300  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F6690            |    | Genteq  | Special  | 36    | 12   | 260  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23M113F200FF1H1    |    | Genteq  | Special  | 11000 |      | 200  | 3     | Round | 4.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23A203F080DD1H1    |    | Genteq  | Special  | 20000 |      | 80   | 2     | Round | 3.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 97F9678            |    | Genteq  | Standard | 25    | 10   | 370  | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23F113F060DC1H1    |    | Genteq  | Special  | 11000 |      | 60   | 2     | Round | 2.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 23B312F150DD1H1    |    | Genteq  | Special  | 3100  |      | 150  | 2     | Round | 3.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| PB400Y050C440EAB X | BX | PROLINE | Standard | 40    | 5    | 440  | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| PB500E000C370DA    |    | PROLINE | Standard | 50    |      | 370  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| PB450Z100T440DA    |    | PROLINE | Standard | 45    | 10   | 440  | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23H182F300CF1H1    |    | Genteq  | Special  | 1800  |      | 300  | 1.75  | Round | 4.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F9203            |    | Genteq  | Standard | 6     |      | 370  | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F5707BX          | BX | Genteq  | Special  | 7.5   |      | 370  | 1.25  | Oval  | 2.62  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23B902F150FE1H1    |    | Genteq  | Special  | 9000  |      | 150  | 3     | Round | 3.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23M192F250BH1H1    |    | Genteq  | Special  | 1900  |      | 250  | 1.375 | Round | 5.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F9012BX          | BX | Genteq  | Standard | 70    |      | 370  | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23C113F100DD1H1    |    | Genteq  | Special  | 11000 |      | 100  | 2     | Round | 3.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23B413F080EH1H1    |    | Genteq  | Special  | 41000 |      | 80   | 2.5   | Round | 5.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F9640            |    | Genteq  | Standard | 35    |      | 440  | 2.5   | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23C183F100ED1H1    |    | Genteq  | Special  | 18000 |      | 100  | 2.5   | Round | 3.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23F113F060CD1H1    |    | Genteq  | Special  | 11000 |      | 60   | 1.75  | Round | 3.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 27L556             |    | Genteq  | Standard | 70    | 7.5  | 370  | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6746            |    | Genteq  | Standard | 12    |      | 330  | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23B452F150DF1H1    |    | Genteq  | Special  | 4500  |      | 150  | 2     | Round | 4.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23M681F450CE1H1    |    | Genteq  | Special  | 680   |      | 450  | 1.75  | Round | 3.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 27L7001RC          | RC | Genteq  | Standard | 10    |      | 400  | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 100°C |
| 27L540             |    | Genteq  | Standard | 16.5  | 11.5 | 330  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23F243F060ED1H1    |    | Genteq  | Special  | 24000 |      | 60   | 2.5   | Round | 3.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 23M142F350DD1H1    |    | Genteq  | Special  | 1400  |      | 350  | 2     | Round | 3.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F5116            |    | Genteq  | Standard | 40    |      | 440  | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23B852F060CB1H1    |    | Genteq  | Special  | 8500  |      | 60   | 1.75  | Round | 2.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23H152F350ED1H1    |    | Genteq  | Special  | 1500  |      | 350  | 2.5   | Round | 3.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F9815S           | S  | Genteq  | Stock    | 55    | 5    | 370  | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F5011            |    | Genteq  | Standard | 10    |      | 440  | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L378             |    | Genteq  | Standard | 45    | 10   | 440  | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F5608BX          | BX | Genteq  | Special  | 35    | 7.5  | 370  | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23C403F050DE1H1    |    | Genteq  | Special  | 40000 |      | 50   | 2     | Round | 3.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| PB350Y050C440EA    |    | PROLINE | Standard | 35    | 5    | 440  | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23A803F080FG1H1    |    | Genteq  | Special  | 80000 |      | 80   | 3     | Round | 4.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 27L1024BX          | BX | Genteq  | Standard | 5     |      | 440  | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6854            |    | Genteq  | Standard | 34    |      | 280  | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23M992F200EH1H1    |    | Genteq  | Special  | 9900  |      | 200  | 2.5   | Round | 5.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F9979            |    | Genteq  | Standard | 25    | 7.5  | 440  | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 40L6472            |    | Genteq  | Stock    | 0.47  |      | 600  | 0.46  | Oval  | 1.25  | Dry-Axial Leaded         | 100000 | -55°C to 105°C |
| 23F961F150BD1H1    |    | Genteq  | Special  | 960   |      | 150  | 1.375 | Round | 3.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 23M221F400BB1H1    |    | Genteq  | Special  | 220   |      | 400  | 1.375 | Round | 2.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23A203F060BG1H1    |    | Genteq  | Special  | 20000 |      | 60   | 1.375 | Round | 4.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 97F8040            |    | Genteq  | Standard | 40    |      | 240  | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB200Z075S370CABX  | BX | PROLINE | Standard | 20    | 7.5  | 370  | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |

|                   |    |         |          |       |     |     |       |       |       |                            |       |                |
|-------------------|----|---------|----------|-------|-----|-----|-------|-------|-------|----------------------------|-------|----------------|
| 97F8243BX         | BX | Genteq  | Special  | 3     |     | 600 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved)   | 60000 | -40°C to 70°C  |
| 97F6749BX         | BX | Genteq  | Standard | 13.5  |     | 330 | 1.5   | Oval  | 2.88  | Oil-Filled (UL Approved)   | 60000 | -40°C to 90°C  |
| PB350Z050S440EA   |    | PROLINE | Standard | 35    | 5   | 440 | 2     | Round | 4.75  | Oil-Filled (UL Approved)   | 10000 | -40°C to 70°C  |
| 97F9632S          | S  | Genteq  | Stock    | 25    |     | 440 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved)   | 60000 | -40°C to 70°C  |
| PB600E000D440HAS  | S  | PROLINE | Stock    | 60    |     | 440 | 2     | Oval  | 4.25  | Oil-Filled (UL Approved)   | 10000 | -40°C to 70°C  |
| 24DB450B370PA     |    | Genteq  | Standard | 45    |     | 370 | 1.75  | Round | 3.189 | Dry (UL Construction Only) | 60000 | -40°C to 70°C  |
| 23F122F200BH1H1   |    | Genteq  | Special  | 1200  |     | 200 | 1.375 | Round | 5.125 | Electrolytic               | 1000  | -55°C to 105°C |
| 97F6622           |    | Genteq  | Standard | 24    |     | 400 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved)   | 60000 | -40°C to 90°C  |
| 97F8045BX         | BX | Genteq  | Standard | 65    |     | 240 | 2     | Round | 4.75  | Oil-Filled (UL Approved)   | 60000 | -40°C to 70°C  |
| 23A153F075BG1H1   |    | Genteq  | Special  | 15000 |     | 75  | 1.375 | Round | 4.625 | Electrolytic               | 1000  | -40°C to 85°C  |
| 23A114F080FJ1H1   |    | Genteq  | Special  | 11000 | 0   | 80  | 3     | Round | 5.875 | Electrolytic               | 1000  | -40°C to 85°C  |
| 23C163F150FG1H1   |    | Genteq  | Special  | 16000 |     | 150 | 3     | Round | 4.625 | Electrolytic               | 1000  | -45°C to 95°C  |
| 97F8250BX         | BX | Genteq  | Standard | 12    |     | 600 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved)   | 60000 | -40°C to 70°C  |
| 23F112F200DC1H1   |    | Genteq  | Special  | 1100  |     | 200 | 2     | Round | 2.625 | Electrolytic               | 1000  | -55°C to 105°C |
| 97F5520           |    | Genteq  | Special  | 45    | 5   | 370 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved)   | 60000 | -40°C to 70°C  |
| 97F8020           |    | Genteq  | Special  | 54    |     | 440 | 2.5   | Round | 4.25  | Oil-Filled (UL Approved)   | 60000 | -40°C to 70°C  |
| 23D293F035CH1H1   |    | Genteq  | Special  | 29000 |     | 35  | 1.75  | Round | 5.125 | Electrolytic               | 1000  | -55°C to 85°C  |
| 97F5337BX         | BX | Genteq  | Standard | 4     |     | 440 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved)   | 60000 | -40°C to 70°C  |
| 97F8070S          | S  | Genteq  | Stock    | 55    |     | 370 | 2     | Round | 4.75  | Oil-Filled (UL Approved)   | 60000 | -40°C to 70°C  |
| 97F9609           |    | Genteq  | Standard | 30    |     | 370 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved)   | 60000 | -40°C to 70°C  |
| 97F5121BX         | BX | Genteq  | Special  | 15    |     | 440 | 2     | Round | 2.88  | Oil-Filled (UL Approved)   | 60000 | -40°C to 70°C  |
| 97F6872BX         | BX | Genteq  | Standard | 48    |     | 280 | 2     | Oval  | 2.88  | Oil-Filled (UL Approved)   | 60000 | -40°C to 90°C  |
| 23J112F400EE1H1   |    | Genteq  | Special  | 1100  |     | 400 | 2.5   | Round | 3.625 | Electrolytic               | 2000  | -40°C to 105°C |
| 25L2754BX         | BX | Genteq  | Standard | 35    | 10  | 440 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved)   | 60000 | -40°C to 70°C  |
| 23M512F300EG1H1   |    | Genteq  | Special  | 5100  |     | 300 | 2.5   | Round | 4.625 | Electrolytic               | 2000  | -40°C to 85°C  |
| PB300E000C240CAS  | S  | PROLINE | Stock    | 30    |     | 240 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved)   | 10000 | -40°C to 70°C  |
| PB550E000S370DABX | BX | PROLINE | Standard | 55    |     | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved)   | 10000 | -40°C to 70°C  |
| 97F9621           |    | Genteq  | Standard | 50    |     | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved)   | 60000 | -40°C to 70°C  |
| 97F6860           |    | Genteq  | Standard | 15    |     | 280 | 1.5   | Oval  | 2.88  | Oil-Filled (UL Approved)   | 60000 | -40°C to 90°C  |
| 27L647            |    | Genteq  | Standard | 50    | 10  | 440 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved)   | 60000 | -40°C to 70°C  |
| 23D563F020CI1H1   |    | Genteq  | Special  | 56000 |     | 20  | 3     | Round | 8.625 | Electrolytic               | 1000  | -55°C to 85°C  |
| 23C712F200EH1H1   |    | Genteq  | Special  | 7100  |     | 200 | 2.5   | Round | 5.125 | Electrolytic               | 1000  | -45°C to 95°C  |
| 23J282F400FI1H1   |    | Genteq  | Special  | 2800  |     | 400 | 3     | Round | 5.625 | Electrolytic               | 2000  | -40°C to 105°C |
| PB350Y100C440EA   |    | PROLINE | Standard | 35    | 10  | 440 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved)   | 10000 | -40°C to 70°C  |
| PB700E000T440EA   |    | PROLINE | Standard | 70    |     | 440 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved)   | 10000 | -40°C to 70°C  |
| PB250E000A440EAS  | S  | PROLINE | Stock    | 25    |     | 440 | 1.25  | Oval  | 4.75  | Oil-Filled (UL Approved)   | 10000 | -40°C to 70°C  |
| 23J512F250FF1H1   |    | Genteq  | Special  | 5100  |     | 250 | 3     | Round | 4.125 | Electrolytic               | 2000  | -40°C to 105°C |
| 97F9845           |    | Genteq  | Standard | 40    | 7.5 | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved)   | 60000 | -40°C to 70°C  |
| 97F9045BX         | BX | Genteq  | Special  | 15    | 7.5 | 440 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved)   | 60000 | -40°C to 70°C  |
| 23B212F200DE1H1   |    | Genteq  | Special  | 2100  |     | 200 | 2     | Round | 3.625 | Electrolytic               | 3000  | -40°C to 85°C  |
| PB500Z075T440EA   |    | PROLINE | Standard | 50    | 7.5 | 440 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved)   | 10000 | -40°C to 70°C  |
| 23F722F075BE1H1   |    | Genteq  | Special  | 7200  |     | 75  | 1.375 | Round | 3.625 | Electrolytic               | 1000  | -55°C to 105°C |
| 23C332F200CH1H1   |    | Genteq  | Special  | 3300  |     | 200 | 1.75  | Round | 5.125 | Electrolytic               | 1000  | -45°C to 95°C  |
| 23H122F250CC1H1   |    | Genteq  | Special  | 1200  |     | 250 | 1.75  | Round | 2.625 | Electrolytic               | 2000  | -40°C to 85°C  |
| 23F263F100FH1H1   |    | Genteq  | Special  | 26000 |     | 100 | 3     | Round | 5.125 | Electrolytic               | 1000  | -55°C to 105°C |
| 23H102F250BE1H1   |    | Genteq  | Special  | 1000  |     | 250 | 1.375 | Round | 3.625 | Electrolytic               | 2000  | -40°C to 85°C  |
| 23A682F075BC1H1   |    | Genteq  | Special  | 6800  |     | 75  | 1.375 | Round | 2.625 | Electrolytic               | 1000  | -40°C to 85°C  |
| 23F771F200BE1H1   |    | Genteq  | Special  | 770   |     | 200 | 1.375 | Round | 3.625 | Electrolytic               | 1000  | -55°C to 105°C |
| 23A482F075BB1H1   |    | Genteq  | Special  | 4800  |     | 75  | 1.375 | Round | 2.125 | Electrolytic               | 1000  | -40°C to 85°C  |

|                   |    |         |          |       |     |      |       |       |       |                          |        |                |
|-------------------|----|---------|----------|-------|-----|------|-------|-------|-------|--------------------------|--------|----------------|
| 23A154F060FJ1H1   |    | Genteq  | Special  | 15000 |     | 60   | 3     | Round | 5.875 | Electrolytic             | 1000   | -40°C to 85°C  |
| 23J531F350CC1H1   |    | Genteq  | Special  | 530   |     | 350  | 1.75  | Round | 2.625 | Electrolytic             | 2000   | -40°C to 105°C |
| 23C453F060CI1H1   |    | Genteq  | Special  | 45000 |     | 60   | 1.75  | Round | 5.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F6946BR         | BR | Genteq  | Standard | 21    |     | 580  | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F9644BX         | BX | Genteq  | Standard | 45    |     | 440  | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23C263F150FL1H1   |    | Genteq  | Special  | 26000 |     | 150  | 3     | Round | 8.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23C603F075EI1H1   |    | Genteq  | Special  | 60000 |     | 75   | 2.5   | Round | 5.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| PB700E000T370EABX | BX | PROLINE | Standard | 70    |     | 370  | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| PB100E000A370CABX | BX | PROLINE | Standard | 10    |     | 370  | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23F232F250EE1H1   |    | Genteq  | Special  | 2300  |     | 250  | 2.5   | Round | 3.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 23M371F450BE1H1   |    | Genteq  | Special  | 370   |     | 450  | 1.375 | Round | 3.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 27L5201BX         | BX | Genteq  | Standard | 50    | 10  | 440  | 2     | Oval  | 5.25  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9204BX         | BX | Genteq  | Standard | 7.5   |     | 370  | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L889BX          | BX | Genteq  | Standard | 45    | 5   | 440  | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB125E000A370CA   |    | PROLINE | Standard | 12.5  |     | 370  | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| PB400Z050T440CABX | BX | PROLINE | Standard | 40    | 5   | 440  | 2.5   | Round | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F5461BX         | BX | Genteq  | Special  | 15    |     | 370  | 1.75  | Oval  | 2.62  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB300Z075S370DA   |    | PROLINE | Standard | 30    | 7.5 | 370  | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F6805           |    | Genteq  | Standard | 10    |     | 280  | 1.5   | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 27L1030BX         | BX | Genteq  | Standard | 2.5   |     | 370  | 1.25  | Oval  | 1.56  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23M852F300FH1H1   |    | Genteq  | Special  | 8500  |     | 300  | 3     | Round | 5.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23D373F028CH1H1   |    | Genteq  | Special  | 37000 |     | 28   | 1.75  | Round | 5.125 | Electrolytic             | 1000   | -55°C to 85°C  |
| PB300E000C440DA   |    | PROLINE | Standard | 30    |     | 440  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23J112F250DC1H1   |    | Genteq  | Special  | 1100  |     | 250  | 2     | Round | 2.625 | Electrolytic             | 2000   | -40°C to 105°C |
| 97F5170BX         | BX | Genteq  | Special  | 20    |     | 370  | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 42L2102           |    | Genteq  | Stock    | 0.1   |     | 1200 | 0.55  | Round | 1.22  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 23F472F080BD1H1   |    | Genteq  | Special  | 4700  |     | 80   | 1.375 | Round | 3.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F9616           |    | Genteq  | Standard | 40    |     | 370  | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23J912F200FI1H1   |    | Genteq  | Special  | 9100  |     | 200  | 3     | Round | 5.625 | Electrolytic             | 2000   | -40°C to 105°C |
| 97F6606RC         | RC | Genteq  | Standard | 10    |     | 400  | 1.5   | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 27L989BX          | BX | Genteq  | Special  | 30    |     | 240  | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB550E000D440EABX | BX | PROLINE | Standard | 55    |     | 440  | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F9951BX         | BX | Genteq  | Standard | 40    | 7.5 | 440  | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6745           |    | Genteq  | Standard | 21    |     | 330  | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F9366           |    | Genteq  | Standard | 35    |     | 240  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L566BX          | BX | Genteq  | Standard | 7.5   |     | 370  | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23B313F075DH1H1   |    | Genteq  | Special  | 31000 |     | 75   | 2     | Round | 5.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 41L7301           |    | Genteq  | Stock    | 3     |     | 700  | 1.12  | Round | 1.65  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 23C104F080FL1H1   |    | Genteq  | Special  | 10000 |     | 80   | 3     | Round | 8.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23B792F080BF1H1   |    | Genteq  | Special  | 7900  |     | 80   | 1.375 | Round | 4.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23H941F450DG1H1   |    | Genteq  | Special  | 940   |     | 450  | 2     | Round | 4.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23D193F055CI1H1   |    | Genteq  | Special  | 19000 |     | 55   | 3     | Round | 8.625 | Electrolytic             | 1000   | -55°C to 85°C  |
| PB350E000S440DABX | BX | PROLINE | Standard | 35    |     | 440  | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F9884S          | S  | Genteq  | Stock    | 45    |     | 370  | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6839           |    | Genteq  | Special  | 43.5  |     | 280  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23J481F400BH1H1   |    | Genteq  | Special  | 480   |     | 400  | 1.375 | Round | 5.125 | Electrolytic             | 2000   | -40°C to 105°C |
| 97F6711BX         | BX | Genteq  | Special  | 16    |     | 330  | 1.5   | Oval  | 3.5   | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23F433F075EH1H1   |    | Genteq  | Special  | 43000 |     | 75   | 2.5   | Round | 5.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 23F193F080CI1H1   |    | Genteq  | Special  | 19000 |     | 80   | 1.75  | Round | 5.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 23B472F100BG1H1   |    | Genteq  | Special  | 4700  |     | 100  | 1.375 | Round | 4.625 | Electrolytic             | 3000   | -40°C to 85°C  |

|                   |    |         |          |        |     |     |       |       |       |                          |       |                |
|-------------------|----|---------|----------|--------|-----|-----|-------|-------|-------|--------------------------|-------|----------------|
| 23A123F100CF1H1   |    | Genteq  | Special  | 12000  |     | 100 | 1.75  | Round | 4.125 | Electrolytic             | 1000  | -40°C to 85°C  |
| 97F9874BX         | BX | Genteq  | Standard | 55     | 7.5 | 440 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F9732           |    | Genteq  | Standard | 25     | 7.5 | 440 | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F6709BX         | BX | Genteq  | Special  | 14     |     | 330 | 1.5   | Oval  | 3.12  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23C403F075FD1H1   |    | Genteq  | Special  | 40000  |     | 75  | 3     | Round | 3.125 | Electrolytic             | 1000  | -45°C to 95°C  |
| 27L946BX          | BX | Genteq  | Standard | 40     | 5   | 440 | 2.5   | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 27L961BX          | BX | Genteq  | Standard | 25     |     | 440 | 1.25  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23B104F050FH1H1   |    | Genteq  | Special  | 100000 |     | 50  | 3     | Round | 5.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| 23B132F200CD1H1   |    | Genteq  | Special  | 1300   |     | 200 | 1.75  | Round | 3.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| 97F6823BX         | BX | Genteq  | Standard | 28     |     | 280 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23C322F250DH1H1   |    | Genteq  | Special  | 3200   |     | 250 | 2     | Round | 5.125 | Electrolytic             | 1000  | -45°C to 95°C  |
| 97F6727BX         | BX | Genteq  | Standard | 32     |     | 330 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 27L705BX          | BX | Genteq  | Standard | 42     | 22  | 280 | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| PB150Y100C370CA   |    | PROLINE | Standard | 15     | 10  | 370 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| PB300Y050C370DA   |    | PROLINE | Standard | 30     | 5   | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F6935BX         | BX | Genteq  | Special  | 10.5   |     | 540 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| PB450E000S440DA   |    | PROLINE | Standard | 45     |     | 440 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| PB450E000S440DABX | BX | PROLINE | Standard | 45     |     | 440 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| PB300E000A370EA   |    | PROLINE | Standard | 30     |     | 370 | 1.25  | Oval  | 4.75  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 27L480            |    | Genteq  | Special  | 20     | 6   | 400 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23D842F035BD1H1   |    | Genteq  | Special  | 8400   |     | 35  | 1.375 | Round | 3.125 | Electrolytic             | 1000  | -55°C to 85°C  |
| 23B372F250EG1H1   |    | Genteq  | Special  | 3700   |     | 250 | 2.5   | Round | 4.625 | Electrolytic             | 3000  | -40°C to 85°C  |
| 23A143F100DE1H1   |    | Genteq  | Special  | 14000  |     | 100 | 2     | Round | 3.625 | Electrolytic             | 1000  | -40°C to 85°C  |
| 97F9170           |    | Genteq  | Special  | 35     |     | 440 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 27L591            |    | Genteq  | Standard | 35     | 15  | 300 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F8313BX         | BX | Genteq  | Special  | 46     |     | 600 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23H602F300FG1H1   |    | Genteq  | Special  | 6000   |     | 300 | 3     | Round | 4.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 97F9391BX         | BX | Genteq  | Special  | 80     |     | 370 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F9696BX         | BX | Genteq  | Standard | 20     | 7.5 | 440 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F5704           |    | Genteq  | Standard | 4      |     | 370 | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23B182F150CC1H1   |    | Genteq  | Special  | 1800   |     | 150 | 1.75  | Round | 2.625 | Electrolytic             | 3000  | -40°C to 85°C  |
| 23A153F150E11H1   |    | Genteq  | Special  | 15000  |     | 150 | 2.5   | Round | 5.625 | Electrolytic             | 1000  | -40°C to 85°C  |
| 97F6846           |    | Genteq  | Standard | 29     |     | 280 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23C572F100BE1H1   |    | Genteq  | Special  | 5700   |     | 100 | 1.375 | Round | 3.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| 97F6890           |    | Genteq  | Standard | 18     | 10  | 280 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23J252F250DG1H1   |    | Genteq  | Special  | 2500   |     | 250 | 2     | Round | 4.625 | Electrolytic             | 2000  | -40°C to 105°C |
| 23J172F200BI1H1   |    | Genteq  | Special  | 1700   |     | 200 | 1.375 | Round | 5.625 | Electrolytic             | 2000  | -40°C to 105°C |
| 23A134F080FL1H1   |    | Genteq  | Special  | 130000 |     | 80  | 3     | Round | 8.625 | Electrolytic             | 1000  | -40°C to 85°C  |
| PB450Y075C370DABX | BX | PROLINE | Standard | 45     | 7.5 | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F9625BX         | BX | Genteq  | Standard | 15     |     | 440 | 1.25  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 27L797RC          | RC | Genteq  | Standard | 15     | 7.5 | 400 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| PB200Y100C370DA   |    | PROLINE | Standard | 20     | 10  | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F6517RC         | RC | Genteq  | Standard | 15     |     | 400 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23B352F150CF1H1   |    | Genteq  | Special  | 3500   |     | 150 | 1.75  | Round | 4.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| 97F6871BR         | BR | Genteq  | Standard | 12     |     | 280 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F9017BX         | BX | Genteq  | Special  | 20     | 7.5 | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23C114F060FG1H1   |    | Genteq  | Special  | 110000 |     | 60  | 3     | Round | 4.625 | Electrolytic             | 1000  | -45°C to 95°C  |



|                    |    |         |          |       |     |     |       |       |       |                          |        |                |
|--------------------|----|---------|----------|-------|-----|-----|-------|-------|-------|--------------------------|--------|----------------|
| 97F8005            |    | Genteq  | Special  | 30    |     | 440 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F5475BX          | BX | Genteq  | Special  | 20    | 4   | 370 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9632            |    | Genteq  | Standard | 25    |     | 440 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F5491            |    | Genteq  | Special  | 30    | 4   | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23J112F350DF1H1    |    | Genteq  | Special  | 1100  |     | 350 | 2     | Round | 4.125 | Electrolytic             | 2000   | -40°C to 105°C |
| 97F9069BX          | BX | Genteq  | Special  | 25    |     | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23F233F050CE1H1    |    | Genteq  | Special  | 23000 |     | 50  | 1.75  | Round | 3.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F9613            |    | Genteq  | Standard | 35    |     | 370 | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23B252F200CH1H1    |    | Genteq  | Special  | 2500  |     | 200 | 1.75  | Round | 5.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F6698RC          | RC | Genteq  | Standard | 13    |     | 400 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F5066BX          | BX | Genteq  | Standard | 10    |     | 370 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9669BX          | BX | Genteq  | Standard | 40    |     | 440 | 2     | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 41L6301            |    | Genteq  | Stock    | 3     |     | 600 | 0.89  | Round | 1.65  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 27L542BX           | BX | Genteq  | Standard | 10.5  | 8   | 330 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F9203BX          | BX | Genteq  | Standard | 6     |     | 370 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23J232F250CH1H1    |    | Genteq  | Special  | 2300  |     | 250 | 1.75  | Round | 5.125 | Electrolytic             | 2000   | -40°C to 105°C |
| 23A333F080DG1H1    |    | Genteq  | Special  | 33000 |     | 80  | 2     | Round | 4.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 23F962F100DG1H1    |    | Genteq  | Special  | 9600  |     | 100 | 2     | Round | 4.625 | Electrolytic             | 1000   | -55°C to 105°C |
| PB450Z050T440DAS   | S  | PROLINE | Stock    | 45    | 5   | 440 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23H561F400DC1H1    |    | Genteq  | Special  | 560   |     | 400 | 2     | Round | 2.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F9840BX          | BX | Genteq  | Standard | 40    | 5   | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9779BX          | BX | Genteq  | Standard | 40    | 7.5 | 440 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23B402F200FD1H1    |    | Genteq  | Special  | 4000  |     | 200 | 3     | Round | 3.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23M112F400CF1H1    |    | Genteq  | Special  | 1100  |     | 400 | 1.75  | Round | 4.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F9038            |    | Genteq  | Standard | 17.5  |     | 440 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23A333F100FE1H1    |    | Genteq  | Special  | 33000 |     | 100 | 3     | Round | 3.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 27L366BX           | BX | Genteq  | Standard | 40    |     | 600 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L1027            |    | Genteq  | Standard | 10    |     | 440 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 41L7682            |    | Genteq  | Stock    | 0.68  |     | 700 | 0.67  | Round | 1.22  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 23H351F400BD1H1    |    | Genteq  | Special  | 350   |     | 400 | 1.375 | Round | 3.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23C711F200BC1H1    |    | Genteq  | Special  | 710   |     | 200 | 1.375 | Round | 2.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F6510BX          | BX | Genteq  | Special  | 50    |     | 260 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23H132F350DF1H1    |    | Genteq  | Special  | 1300  |     | 350 | 2     | Round | 4.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F8073S           | S  | Genteq  | Stock    | 70    |     | 370 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9242BX          | BX | Genteq  | Special  | 20    |     | 440 | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6698BX          | BX | Genteq  | Standard | 13    |     | 400 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F6505RC          | RC | Genteq  | Standard | 17.5  |     | 330 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23C532F200EF1H1    |    | Genteq  | Special  | 5300  |     | 200 | 2.5   | Round | 4.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23A453F100FG1H1    |    | Genteq  | Special  | 45000 |     | 100 | 3     | Round | 4.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| PB200Y075C370CAB X | BX | PROLINE | Standard | 20    | 7.5 | 370 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23A632F060BB1H1    |    | Genteq  | Special  | 6300  |     | 60  | 1.375 | Round | 2.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 23J311F300BB1H1    |    | Genteq  | Special  | 310   |     | 300 | 1.375 | Round | 2.125 | Electrolytic             | 2000   | -40°C to 105°C |
| 23B303F060DF1H1    |    | Genteq  | Special  | 30000 |     | 60  | 2     | Round | 4.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F6940BX          | BX | Genteq  | Standard | 35    |     | 580 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23A403F060DF1H1    |    | Genteq  | Special  | 40000 |     | 60  | 2     | Round | 4.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| PB550E000D440EAS   | S  | PROLINE | Stock    | 55    |     | 440 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| PB450Z100T440DABX  | BX | PROLINE | Standard | 45    | 10  | 440 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23J421F400BG1H1    |    | Genteq  | Special  | 420   |     | 400 | 1.375 | Round | 4.625 | Electrolytic             | 2000   | -40°C to 105°C |
| 23F753F060FI1H1    |    | Genteq  | Special  | 75000 |     | 60  | 3     | Round | 5.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 27L862BR           | BR | Genteq  | Standard | 35    | 24  | 400 | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F6537RC          | RC | Genteq  | Standard | 24    |     | 330 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |

|                   |    |         |          |        |    |      |       |       |       |                          |        |                |
|-------------------|----|---------|----------|--------|----|------|-------|-------|-------|--------------------------|--------|----------------|
| 97F6872RC         | RC | Genteq  | Standard | 48     |    | 280  | 2     | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23A114F075FJ1H1   |    | Genteq  | Special  | 110000 |    | 75   | 3     | Round | 5.875 | Electrolytic             | 1000   | -40°C to 85°C  |
| 23F252F150CF1H1   |    | Genteq  | Special  | 2500   |    | 150  | 1.75  | Round | 4.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 27L637            |    | Genteq  | Special  | 80     | 5  | 440  | 2     | Oval  | 6.25  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23F212F200DF1H1   |    | Genteq  | Special  | 2100   |    | 200  | 2     | Round | 4.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 23D982F016BB1H1   |    | Genteq  | Special  | 9800   |    | 16   | 1.375 | Round | 2.125 | Electrolytic             | 1000   | -55°C to 85°C  |
| 97F6921RC         | RC | Genteq  | Standard | 26     |    | 580  | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 27L827RC          | RC | Genteq  | Standard | 18     | 10 | 330  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23H721F350DC1H1   |    | Genteq  | Special  | 720    |    | 350  | 2     | Round | 2.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F6768BR         | BR | Genteq  | Standard | 14     |    | 330  | 1.5   | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23A842F100DC1H1   |    | Genteq  | Special  | 8400   |    | 100  | 2     | Round | 2.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| PB075E000A440CA   |    | PROLINE | Standard | 7.5    |    | 440  | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23B102F200CC1H1   |    | Genteq  | Special  | 1000   |    | 200  | 1.75  | Round | 2.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F9115           |    | Genteq  | Special  | 45     |    | 370  | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6812           |    | Genteq  | Standard | 17.5   |    | 280  | 1.5   | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23H322F250CI1H1   |    | Genteq  | Special  | 3200   |    | 250  | 1.75  | Round | 5.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23B272F100CB1H1   |    | Genteq  | Special  | 2700   |    | 100  | 1.75  | Round | 2.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F9689BX         | BX | Genteq  | Standard | 40     | 5  | 370  | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23C382F150CE1H1   |    | Genteq  | Special  | 3800   |    | 150  | 1.75  | Round | 3.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F6863           |    | Genteq  | Special  | 22.5   |    | 280  | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23M312F300DG1H1   |    | Genteq  | Special  | 3100   |    | 300  | 2     | Round | 4.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F8063BX         | BX | Genteq  | Standard | 20     |    | 370  | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9004BX         | BX | Genteq  | Standard | 15     |    | 370  | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23M182F200CC1H1   |    | Genteq  | Special  | 1800   |    | 200  | 1.75  | Round | 2.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23H721F400BI1H1   |    | Genteq  | Special  | 720    |    | 400  | 1.375 | Round | 5.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 41L2101           |    | Genteq  | Stock    | 1      |    | 250  | 0.43  | Round | 0.75  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 23B222F250ED1H1   |    | Genteq  | Special  | 2200   |    | 250  | 2.5   | Round | 3.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23B133F100DH1H1   |    | Genteq  | Special  | 13000  |    | 100  | 2     | Round | 5.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23F162F200CF1H1   |    | Genteq  | Special  | 1600   |    | 200  | 1.75  | Round | 4.125 | Electrolytic             | 1000   | -55°C to 105°C |
| PB600E000C370EABX | BX | PROLINE | Standard | 60     |    | 370  | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F8038BX         | BX | Genteq  | Standard | 30     |    | 240  | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9884           |    | Genteq  | Standard | 45     |    | 370  | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23H442F300FE1H1   |    | Genteq  | Special  | 4400   |    | 300  | 3     | Round | 3.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F9978           |    | Genteq  | Standard | 25     | 5  | 440  | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23J962F250FL1H1   |    | Genteq  | Special  | 9600   |    | 250  | 3     | Round | 8.625 | Electrolytic             | 2000   | -40°C to 105°C |
| 97F6887BX         | BX | Genteq  | Standard | 38     | 17 | 280  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| PB600E000T370DA   |    | PROLINE | Standard | 60     |    | 370  | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 27L7007           |    | Genteq  | Special  | 18     | 8  | 330  | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 100°C |
| 97F8039S          | S  | Genteq  | Stock    | 35     |    | 240  | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23M132F200CB1H1   |    | Genteq  | Special  | 1300   |    | 200  | 1.75  | Round | 2.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23D143F035BG1H1   |    | Genteq  | Special  | 14000  |    | 35   | 1.375 | Round | 4.625 | Electrolytic             | 1000   | -55°C to 85°C  |
| 97F9451RR         | RR | Genteq  | Standard | 20     | 10 | 440  | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F5564           |    | Genteq  | Standard | 8      |    | 370  | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6801BX         | BX | Genteq  | Standard | 6      |    | 280  | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| PB600E000P370EABX | BX | PROLINE | Standard | 60     |    | 370  | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23F442F150DH1H1   |    | Genteq  | Special  | 4400   |    | 150  | 2     | Round | 5.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 23J192F400FF1H1   |    | Genteq  | Special  | 1900   |    | 400  | 3     | Round | 4.125 | Electrolytic             | 2000   | -40°C to 105°C |
| 42L3223           |    | Genteq  | Stock    | 0.022  |    | 2000 | 0.41  | Round | 1.22  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 23C153F075BI1H1   |    | Genteq  | Special  | 15000  |    | 75   | 1.375 | Round | 5.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23H661F350BF1H1   |    | Genteq  | Special  | 660    |    | 350  | 1.375 | Round | 4.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F8054           |    | Genteq  | Standard | 3      |    | 370  | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L414            |    | Genteq  | Standard | 70     | 10 | 370  | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |

|                  |    |         |          |       |    |     |       |       |       |                          |       |                |
|------------------|----|---------|----------|-------|----|-----|-------|-------|-------|--------------------------|-------|----------------|
| 23H282F250CH1H1  |    | Genteq  | Special  | 2800  |    | 250 | 1.75  | Round | 5.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 97F9871BX        | BX | Genteq  | Standard | 20    |    | 440 | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F9810          |    | Genteq  | Standard | 15    | 5  | 370 | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23F302F200EE1H1  |    | Genteq  | Special  | 3000  |    | 200 | 2.5   | Round | 3.625 | Electrolytic             | 1000  | -55°C to 105°C |
| PB100E000A370CAS | S  | PROLINE | Stock    | 10    |    | 370 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23M282F400FE1H1  |    | Genteq  | Special  | 2800  |    | 400 | 3     | Round | 3.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23M401F400BD1H1  |    | Genteq  | Special  | 400   |    | 400 | 1.375 | Round | 3.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 97F9978BX        | BX | Genteq  | Standard | 25    | 5  | 440 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23D123F020BC1H1  |    | Genteq  | Special  | 12000 |    | 20  | 1.375 | Round | 2.625 | Electrolytic             | 1000  | -55°C to 85°C  |
| 97F6855          |    | Genteq  | Standard | 22.5  |    | 280 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 27L791BX         | BX | Genteq  | Standard | 8     |    | 580 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23C463F050C11H1  |    | Genteq  | Special  | 46000 |    | 50  | 1.75  | Round | 5.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| 23M262F300DF1H1  |    | Genteq  | Special  | 2600  |    | 300 | 2     | Round | 4.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| PB300E000P440DAS | S  | PROLINE | Stock    | 30    |    | 440 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23C362F250D11H1  |    | Genteq  | Special  | 3600  |    | 250 | 2     | Round | 5.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| 23C184F050FL1H1  |    | Genteq  | Special  | 18000 | 0  | 50  | 3     | Round | 8.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| 23M232F250DD1H1  |    | Genteq  | Special  | 2300  |    | 250 | 2     | Round | 3.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23A113F050BC1H1  |    | Genteq  | Special  | 11000 |    | 50  | 1.375 | Round | 2.625 | Electrolytic             | 1000  | -40°C to 85°C  |
| PB500Z050T370DA  |    | PROLINE | Standard | 50    | 5  | 370 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23C102F250CC1H1  |    | Genteq  | Special  | 1000  |    | 250 | 1.75  | Round | 2.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| 23H271F450CB1H1  |    | Genteq  | Special  | 270   |    | 450 | 1.75  | Round | 2.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23B253F050CF1H1  |    | Genteq  | Special  | 25000 |    | 50  | 1.75  | Round | 4.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| 23B292F080BB1H1  |    | Genteq  | Special  | 2900  |    | 80  | 1.375 | Round | 2.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| 23F273F080FD1H1  |    | Genteq  | Special  | 27000 |    | 80  | 3     | Round | 3.125 | Electrolytic             | 1000  | -55°C to 105°C |
| 97F9010S         | S  | Genteq  | Stock    | 55    |    | 370 | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23D523F016CG1H1  |    | Genteq  | Special  | 52000 |    | 16  | 1.75  | Round | 4.625 | Electrolytic             | 1000  | -55°C to 85°C  |
| 97F6676BX        | BX | Genteq  | Special  | 3     |    | 480 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F9897BX        | BX | Genteq  | Standard | 60    | 5  | 440 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23J162F400FE1H1  |    | Genteq  | Special  | 1600  |    | 400 | 3     | Round | 3.625 | Electrolytic             | 2000  | -40°C to 105°C |
| 23C402F250FD1H1  |    | Genteq  | Special  | 4000  |    | 250 | 3     | Round | 3.125 | Electrolytic             | 1000  | -45°C to 95°C  |
| 97F6643BR        | BR | Genteq  | Special  | 30    |    | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23A273F050CD1H1  |    | Genteq  | Special  | 27000 |    | 50  | 1.75  | Round | 3.125 | Electrolytic             | 1000  | -40°C to 85°C  |
| 23J261F400BD1H1  |    | Genteq  | Special  | 260   |    | 400 | 1.375 | Round | 3.125 | Electrolytic             | 2000  | -40°C to 105°C |
| 23F113F080CE1H1  |    | Genteq  | Special  | 11000 |    | 80  | 1.75  | Round | 3.625 | Electrolytic             | 1000  | -55°C to 105°C |
| 23B733F075FH1H1  |    | Genteq  | Special  | 73000 |    | 75  | 3     | Round | 5.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| PB500E000P240EA  |    | PROLINE | Standard | 50    |    | 240 | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23B872F200F11H1  |    | Genteq  | Special  | 8700  |    | 200 | 3     | Round | 5.625 | Electrolytic             | 3000  | -40°C to 85°C  |
| 97F5063BX        | BX | Genteq  | Special  | 17.5  |    | 370 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F8256          |    | Genteq  | Standard | 35    |    | 600 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F9040BX        | BX | Genteq  | Standard | 25    |    | 440 | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23A782F050BB1H1  |    | Genteq  | Special  | 7800  |    | 50  | 1.375 | Round | 2.125 | Electrolytic             | 1000  | -40°C to 85°C  |
| 97F5710          |    | Genteq  | Special  | 10    |    | 370 | 1.25  | Oval  | 2.62  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23D114F007C11H1  |    | Genteq  | Special  | 11000 | 0  | 7.5 | 3     | Round | 8.625 | Electrolytic             | 1000  | -55°C to 85°C  |
| 23H682F300FH1H1  |    | Genteq  | Special  | 6800  |    | 300 | 3     | Round | 5.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 97F6836BR        | BR | Genteq  | Standard | 48    |    | 280 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 27L204BX         | BX | Genteq  | Standard | 35    | 10 | 440 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F9042BX        | BX | Genteq  | Standard | 55    |    | 440 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| PB300E000P440DA  |    | PROLINE | Standard | 30    |    | 440 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23A583F060EE1H1  |    | Genteq  | Special  | 58000 |    | 60  | 2.5   | Round | 3.625 | Electrolytic             | 1000  | -40°C to 85°C  |
| 97F5913          |    | Genteq  | Standard | 30    |    | 370 | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23J391F400CC1H1  |    | Genteq  | Special  | 390   |    | 400 | 1.75  | Round | 2.625 | Electrolytic             | 2000  | -40°C to 105°C |
| 23F103F150FH1H1  |    | Genteq  | Special  | 10000 |    | 150 | 3     | Round | 5.125 | Electrolytic             | 1000  | -55°C to 105°C |
| 27L476           |    | Genteq  | Standard | 33    | 15 | 330 | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |

|                 |    |         |          |       |     |     |       |       |       |                            |        |                |
|-----------------|----|---------|----------|-------|-----|-----|-------|-------|-------|----------------------------|--------|----------------|
| 97F9614S        | S  | Genteq  | Stock    | 40    |     | 370 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 23B233F060CF1H1 |    | Genteq  | Special  | 23000 |     | 60  | 1.75  | Round | 4.125 | Electrolytic               | 3000   | -40°C to 85°C  |
| 23F103F060BG1H1 |    | Genteq  | Special  | 10000 |     | 60  | 1.375 | Round | 4.625 | Electrolytic               | 1000   | -55°C to 105°C |
| 23D173F035B1H1  |    | Genteq  | Special  | 17000 |     | 35  | 1.375 | Round | 5.625 | Electrolytic               | 1000   | -55°C to 85°C  |
| 24DB450B250PA   |    | Genteq  | Standard | 45    |     | 250 | 1.75  | Round | 3.189 | Dry (UL Construction Only) | 60000  | -40°C to 70°C  |
| 23A683F075EH1H1 |    | Genteq  | Special  | 68000 |     | 75  | 2.5   | Round | 5.125 | Electrolytic               | 1000   | -40°C to 85°C  |
| 97F9832BX       | BX | Genteq  | Standard | 45    | 10  | 370 | 2     | Round | 4.75  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 97F9683         |    | Genteq  | Standard | 30    | 7.5 | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 23C532F250EH1H1 |    | Genteq  | Special  | 5300  |     | 250 | 2.5   | Round | 5.125 | Electrolytic               | 1000   | -45°C to 95°C  |
| 23F611F200BD1H1 |    | Genteq  | Special  | 610   |     | 200 | 1.375 | Round | 3.125 | Electrolytic               | 1000   | -55°C to 105°C |
| 23F402F200EG1H1 |    | Genteq  | Special  | 4000  |     | 200 | 2.5   | Round | 4.625 | Electrolytic               | 1000   | -55°C to 105°C |
| 97F9830         |    | Genteq  | Standard | 35    | 10  | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 23F722F150EH1H1 |    | Genteq  | Special  | 7200  |     | 150 | 2.5   | Round | 5.125 | Electrolytic               | 1000   | -55°C to 105°C |
| 23C843F080FJ1H1 |    | Genteq  | Special  | 84000 |     | 80  | 3     | Round | 5.875 | Electrolytic               | 1000   | -45°C to 95°C  |
| 97F6857BX       | BX | Genteq  | Standard | 8     |     | 280 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 97F5056BX       | BX | Genteq  | Standard | 40    |     | 370 | 1.75  | Round | 4.75  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 97F9885BX       | BX | Genteq  | Standard | 50    | 5   | 370 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 23A872F075CB1H1 |    | Genteq  | Special  | 8700  |     | 75  | 1.75  | Round | 2.125 | Electrolytic               | 1000   | -40°C to 85°C  |
| 97F9752         |    | Genteq  | Standard | 25    | 4   | 370 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 23J211F350BB1H1 |    | Genteq  | Special  | 210   |     | 350 | 1.375 | Round | 2.125 | Electrolytic               | 2000   | -40°C to 105°C |
| 23F752F050BC1H1 |    | Genteq  | Special  | 7500  |     | 50  | 1.375 | Round | 2.625 | Electrolytic               | 1000   | -55°C to 105°C |
| 97F9004         |    | Genteq  | Standard | 15    |     | 370 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 41L7471         |    | Genteq  | Stock    | 4.7   |     | 700 | 1.18  | Round | 2.17  | Dry-Axial Leaded           | 100000 | -40°C to 85°C  |
| 23C103F200FH1H1 |    | Genteq  | Special  | 10000 |     | 200 | 3     | Round | 5.125 | Electrolytic               | 1000   | -45°C to 95°C  |
| 23M232F300DE1H1 |    | Genteq  | Special  | 2300  |     | 300 | 2     | Round | 3.625 | Electrolytic               | 2000   | -40°C to 85°C  |
| 97F6535RC       | RC | Genteq  | Standard | 24    |     | 400 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 97F9043BX       | BX | Genteq  | Standard | 60    |     | 440 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 97F9968BX       | BX | Genteq  | Standard | 30    | 7.5 | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 97F6921BR       | BR | Genteq  | Standard | 26    |     | 580 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 97F9046         |    | Genteq  | Special  | 15    | 10  | 440 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 97F6703BX       | BX | Genteq  | Standard | 8     |     | 330 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| PB150E000A440EA |    | PROLINE | Standard | 15    |     | 440 | 1.25  | Oval  | 4.75  | Oil-Filled (UL Approved)   | 10000  | -40°C to 70°C  |
| 27L68BX         | BX | Genteq  | Standard | 30    | 18  | 400 | 2     | Oval  | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 97F5573BX       | BX | Genteq  | Special  | 10    |     | 370 | 1.75  | Oval  | 2.12  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 97F6778BX       | BX | Genteq  | Standard | 45    |     | 330 | 2     | Oval  | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 97F9848S        | S  | Genteq  | Stock    | 35    | 5   | 440 | 2     | Round | 4.75  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 23C343F080D11H1 |    | Genteq  | Special  | 34000 |     | 80  | 2     | Round | 5.625 | Electrolytic               | 1000   | -45°C to 95°C  |
| 23A753F050D11H1 |    | Genteq  | Special  | 75000 |     | 50  | 2     | Round | 5.625 | Electrolytic               | 1000   | -40°C to 85°C  |
| 97F9028BX       | BX | Genteq  | Special  | 50    | 5   | 370 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| PB200E000S370CA |    | PROLINE | Standard | 20    |     | 370 | 2     | Round | 2.88  | Oil-Filled (UL Approved)   | 10000  | -40°C to 70°C  |
| 23H202F400EG1H1 |    | Genteq  | Special  | 2000  |     | 400 | 2.5   | Round | 4.625 | Electrolytic               | 2000   | -40°C to 85°C  |
| 23J422F200FD1H1 |    | Genteq  | Special  | 4200  |     | 200 | 3     | Round | 3.125 | Electrolytic               | 2000   | -40°C to 105°C |
| 97F6656BX       | BX | Genteq  | Standard | 7.5   |     | 400 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 23B352F100DB1H1 |    | Genteq  | Special  | 3500  |     | 100 | 2     | Round | 2.125 | Electrolytic               | 3000   | -40°C to 85°C  |
| 97F9027         |    | Genteq  | Special  | 45    | 5   | 370 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 97F9996BX       | BX | Genteq  | Standard | 40    | 7.5 | 440 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 41L2681         |    | Genteq  | Stock    | 6.8   |     | 250 | 0.79  | Round | 1.22  | Dry-Axial Leaded           | 100000 | -40°C to 85°C  |
| 23J321F400BE1H1 |    | Genteq  | Special  | 320   |     | 400 | 1.375 | Round | 3.625 | Electrolytic               | 2000   | -40°C to 105°C |
| 23J591F400CE1H1 |    | Genteq  | Special  | 590   |     | 400 | 1.75  | Round | 3.625 | Electrolytic               | 2000   | -40°C to 105°C |
| 27L176RC        | RC | Genteq  | Special  | 7.5   |     | 540 | 1.5   | Oval  | 2.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 23C773F050EG1H1 |    | Genteq  | Special  | 77000 |     | 50  | 2.5   | Round | 4.625 | Electrolytic               | 1000   | -45°C to 95°C  |

|                    |    |         |          |       |     |      |       |       |       |                          |        |                |
|--------------------|----|---------|----------|-------|-----|------|-------|-------|-------|--------------------------|--------|----------------|
| 23B842F075DB1H1    |    | Genteq  | Special  | 8400  |     | 75   | 2     | Round | 2.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F8055            |    | Genteq  | Standard | 4     |     | 370  | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6923BX          | BX | Genteq  | Special  | 32    |     | 540  | 2     | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| PB550Z075T440EA    |    | PROLINE | Standard | 55    | 7.5 | 440  | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 27L572BX           | BX | Genteq  | Standard | 12.5  |     | 370  | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23A593F080FE1H1    |    | Genteq  | Special  | 59000 |     | 80   | 3     | Round | 3.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 97F9008            |    | Genteq  | Standard | 45    |     | 370  | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L573RR           | RR | Genteq  | Standard | 40    | 15  | 280  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23M172F300B1H1     |    | Genteq  | Special  | 1700  |     | 300  | 1.375 | Round | 5.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F9202BX          | BX | Genteq  | Standard | 5     |     | 370  | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB030E000A440AA    |    | PROLINE | Standard | 3     |     | 440  | 1.25  | Oval  | 1.56  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23J352F350FH1H1    |    | Genteq  | Special  | 3500  |     | 350  | 3     | Round | 5.125 | Electrolytic             | 2000   | -40°C to 105°C |
| 23C143F075BH1H1    |    | Genteq  | Special  | 14000 |     | 75   | 1.375 | Round | 5.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| PB250Y075C370CAB X | BX | PROLINE | Standard | 25    | 7.5 | 370  | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23M801F450CF1H1    |    | Genteq  | Special  | 800   |     | 450  | 1.75  | Round | 4.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F8059            |    | Genteq  | Standard | 10    |     | 370  | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6715BX          | BX | Genteq  | Standard | 19    |     | 330  | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F9086BX          | BX | Genteq  | Special  | 30    |     | 440  | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9028            |    | Genteq  | Special  | 50    | 5   | 370  | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23M102F400DD1H1    |    | Genteq  | Special  | 1000  |     | 400  | 2     | Round | 3.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| PB060E000A440BA    |    | PROLINE | Standard | 6     |     | 440  | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23B553F075FF1H1    |    | Genteq  | Special  | 55000 |     | 75   | 3     | Round | 4.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23A203F075CE1H1    |    | Genteq  | Special  | 20000 |     | 75   | 1.75  | Round | 3.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 97F6530RC          | RC | Genteq  | Standard | 40    |     | 280  | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F6695BX          | BX | Genteq  | Special  | 6.5   |     | 480  | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23C104F050E11H1    |    | Genteq  | Special  | 10000 | 0   | 50   | 2.5   | Round | 5.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F6515            |    | Genteq  | Standard | 10    |     | 330  | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23J222F300DH1H1    |    | Genteq  | Special  | 2200  |     | 300  | 2     | Round | 5.125 | Electrolytic             | 2000   | -40°C to 105°C |
| 97F5463BX          | BX | Genteq  | Standard | 20    |     | 370  | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9603BX          | BX | Genteq  | Standard | 20    |     | 370  | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9802BX          | BX | Genteq  | Standard | 50    |     | 370  | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23J532F200FE1H1    |    | Genteq  | Special  | 5300  |     | 200  | 3     | Round | 3.625 | Electrolytic             | 2000   | -40°C to 105°C |
| 23B133F080CE1H1    |    | Genteq  | Special  | 13000 |     | 80   | 1.75  | Round | 3.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23B323F050DF1H1    |    | Genteq  | Special  | 32000 |     | 50   | 2     | Round | 4.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F5239            |    | Genteq  | Standard | 55    |     | 480  | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23H371F450BF1H1    |    | Genteq  | Special  | 370   |     | 450  | 1.375 | Round | 4.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23C572F150DF1H1    |    | Genteq  | Special  | 5700  |     | 150  | 2     | Round | 4.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F5816            |    | Genteq  | Special  | 25    | 7.5 | 370  | 2     | Round | 4.25  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23C711F250BD1H1    |    | Genteq  | Special  | 710   |     | 250  | 1.375 | Round | 3.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F6758BX          | BX | Genteq  | Standard | 15    |     | 330  | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23F153F060DD1H1    |    | Genteq  | Special  | 15000 |     | 60   | 2     | Round | 3.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 23M701F200BB1H1    |    | Genteq  | Special  | 700   |     | 200  | 1.375 | Round | 2.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23H202F200CD1H1    |    | Genteq  | Special  | 2000  |     | 200  | 1.75  | Round | 3.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 27L470             |    | Genteq  | Standard | 25    | 10  | 300  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F5161BX          | BX | Genteq  | Standard | 15    |     | 370  | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB150E000A440EABX  | BX | PROLINE | Standard | 15    |     | 440  | 1.25  | Oval  | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F6641            |    | Genteq  | Special  | 52    |     | 170  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 42L4333            |    | Genteq  | Stock    | 0.033 |     | 3000 | 0.79  | Round | 1.22  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 23F113F100DH1H1    |    | Genteq  | Special  | 11000 |     | 100  | 2     | Round | 5.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 23F163F060CF1H1    |    | Genteq  | Special  | 16000 |     | 60   | 1.75  | Round | 4.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 40L3151            |    | Genteq  | Stock    | 1.5   |     | 400  | 0.48  | Oval  | 1.25  | Dry-Axial Leaded         | 100000 | -55°C to 105°C |

|                   |    |         |          |       |     |     |       |       |       |                          |        |                |
|-------------------|----|---------|----------|-------|-----|-----|-------|-------|-------|--------------------------|--------|----------------|
| 97F6746BR         | BR | Genteq  | Standard | 12    |     | 330 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23H162F350DG1H1   |    | Genteq  | Special  | 1600  |     | 350 | 2     | Round | 4.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23F721F150BC1H1   |    | Genteq  | Special  | 720   |     | 150 | 1.375 | Round | 2.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 23J142F250BI1H1   |    | Genteq  | Special  | 1400  |     | 250 | 1.375 | Round | 5.625 | Electrolytic             | 2000   | -40°C to 105°C |
| 25L501BX          | BX | Genteq  | Standard | 40    |     | 440 | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23M132F350CE1H1   |    | Genteq  | Special  | 1300  |     | 350 | 1.75  | Round | 3.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23C573F050EE1H1   |    | Genteq  | Special  | 57000 |     | 50  | 2.5   | Round | 3.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 41L2300           |    | Genteq  | Stock    | 30    |     | 250 | 1.16  | Round | 2.17  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| PB800Z075T440EABX | BX | PROLINE | Standard | 80    | 7.5 | 440 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23C263F080CI1H1   |    | Genteq  | Special  | 26000 |     | 80  | 1.75  | Round | 5.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F8058           |    | Genteq  | Standard | 7.5   |     | 370 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23F841F200CC1H1   |    | Genteq  | Special  | 840   |     | 200 | 1.75  | Round | 2.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 23C132F200CC1H1   |    | Genteq  | Special  | 1300  |     | 200 | 1.75  | Round | 2.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23H431F400BE1H1   |    | Genteq  | Special  | 430   |     | 400 | 1.375 | Round | 3.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F8078           |    | Genteq  | Special  | 8     |     | 440 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23A233F100EE1H1   |    | Genteq  | Special  | 23000 |     | 100 | 2.5   | Round | 3.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| PB750E000T370EA   |    | PROLINE | Standard | 75    |     | 370 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23B682F200FG1H1   |    | Genteq  | Special  | 6800  |     | 200 | 3     | Round | 4.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23F453F050DH1H1   |    | Genteq  | Special  | 45000 |     | 50  | 2     | Round | 5.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F8070BX         | BX | Genteq  | Standard | 55    |     | 370 | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9631           |    | Genteq  | Standard | 20    |     | 440 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23F112F250DD1H1   |    | Genteq  | Special  | 1100  |     | 250 | 2     | Round | 3.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 41L2251           |    | Genteq  | Stock    | 2.5   |     | 250 | 0.47  | Round | 1.22  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| PB700Z075T370EA   |    | PROLINE | Standard | 70    | 7.5 | 370 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23F143F080DE1H1   |    | Genteq  | Special  | 14000 |     | 80  | 2     | Round | 3.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 27L727BR          | BR | Genteq  | Standard | 45    | 19  | 300 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23A862F100CD1H1   |    | Genteq  | Special  | 8600  |     | 100 | 1.75  | Round | 3.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 27L480BX          | BX | Genteq  | Special  | 20    | 6   | 400 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F9200           |    | Genteq  | Special  | 3     |     | 370 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23B793F050EI1H1   |    | Genteq  | Special  | 79000 |     | 50  | 2.5   | Round | 5.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23B541F250CB1H1   |    | Genteq  | Special  | 540   |     | 250 | 1.75  | Round | 2.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23J192F400EI1H1   |    | Genteq  | Special  | 1900  |     | 400 | 2.5   | Round | 5.625 | Electrolytic             | 2000   | -40°C to 105°C |
| PB400E000C370DAS  | S  | PROLINE | Stock    | 40    |     | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| PB600E000S370DA   |    | PROLINE | Standard | 60    |     | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23C322F200DF1H1   |    | Genteq  | Special  | 3200  |     | 200 | 2     | Round | 4.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F9200BX         | BX | Genteq  | Special  | 3     |     | 370 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6659           |    | Genteq  | Standard | 12    |     | 400 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F8071S          | S  | Genteq  | Stock    | 60    |     | 370 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6854BX         | BX | Genteq  | Standard | 34    |     | 280 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F8036BX         | BX | Genteq  | Standard | 15    |     | 240 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23B152F100BB1H1   |    | Genteq  | Special  | 1500  |     | 100 | 1.375 | Round | 2.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 23C612F060BB1H1   |    | Genteq  | Special  | 6100  |     | 60  | 1.375 | Round | 2.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23M901F400CE1H1   |    | Genteq  | Special  | 900   |     | 400 | 1.75  | Round | 3.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F6855BX         | BX | Genteq  | Standard | 22.5  |     | 280 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| PB150Z100S370CA   |    | PROLINE | Standard | 15    | 10  | 370 | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F6682BX         | BX | Genteq  | Special  | 31.5  |     | 420 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F6533BR         | BR | Genteq  | Standard | 30    |     | 280 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F5043           |    | Genteq  | Special  | 10    |     | 370 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9026           |    | Genteq  | Special  | 40    | 10  | 370 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB600E000T440EABX | BX | PROLINE | Standard | 60    |     | 440 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 27L443BX          | BX | Genteq  | Standard | 17    | 7   | 400 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23F342F200FD1H1   |    | Genteq  | Special  | 3400  |     | 200 | 3     | Round | 3.125 | Electrolytic             | 1000   | -55°C to 105°C |

|                 |    |         |          |       |     |     |       |       |       |                          |       |                |
|-----------------|----|---------|----------|-------|-----|-----|-------|-------|-------|--------------------------|-------|----------------|
| 97F6733BX       | BX | Genteq  | Special  | 40    |     | 330 | 2     | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23A173F100CH1H1 |    | Genteq  | Special  | 17000 |     | 100 | 1.75  | Round | 5.125 | Electrolytic             | 1000  | -40°C to 85°C  |
| 97F9071         |    | Genteq  | Special  | 35    |     | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F9849S        | S  | Genteq  | Stock    | 40    | 5   | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 25L261          |    | Genteq  | Standard | 80    | 10  | 370 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F6767         |    | Genteq  | Standard | 10    |     | 330 | 1.5   | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23M552F250EF1H1 |    | Genteq  | Special  | 5500  |     | 250 | 2.5   | Round | 4.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23H222F350EF1H1 |    | Genteq  | Special  | 2200  |     | 350 | 2.5   | Round | 4.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 27L522          |    | Genteq  | Standard | 80    | 7.5 | 370 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23C242F250DF1H1 |    | Genteq  | Special  | 2400  |     | 250 | 2     | Round | 4.125 | Electrolytic             | 1000  | -45°C to 95°C  |
| 97F9855         |    | Genteq  | Standard | 40    | 7.5 | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F6952         |    | Genteq  | Standard | 36    |     | 540 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F6692BX       | BX | Genteq  | Special  | 8.5   |     | 480 | 1.5   | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F6539         |    | Genteq  | Standard | 14    |     | 400 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23M232F200BG1H1 |    | Genteq  | Special  | 2300  |     | 200 | 1.375 | Round | 4.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| PB250Z075S370CA |    | PROLINE | Standard | 25    | 7.5 | 370 | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F9011         |    | Genteq  | Standard | 65    |     | 370 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F9811BX       | BX | Genteq  | Standard | 15    | 7.5 | 370 | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F6761         |    | Genteq  | Standard | 17.5  |     | 330 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F5388S        | S  | Genteq  | Stock    | 12.5  |     | 440 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23F313F050CG1H1 |    | Genteq  | Special  | 31000 |     | 50  | 1.75  | Round | 4.625 | Electrolytic             | 1000  | -55°C to 105°C |
| 97F8039BX       | BX | Genteq  | Standard | 35    |     | 240 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F9843BX       | BX | Genteq  | Standard | 40    | 5   | 440 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23J591F350BG1H1 |    | Genteq  | Special  | 590   |     | 350 | 1.375 | Round | 4.625 | Electrolytic             | 2000  | -40°C to 105°C |
| 97F9039BX       | BX | Genteq  | Standard | 20    |     | 440 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23D783F007CF1H1 |    | Genteq  | Special  | 78000 |     | 7.5 | 1.75  | Round | 4.125 | Electrolytic             | 1000  | -55°C to 85°C  |
| 27L1050BX       | BX | Genteq  | Standard | 25    | 10  | 370 | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23M301F350BB1H1 |    | Genteq  | Special  | 300   |     | 350 | 1.375 | Round | 2.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23C563F060EE1H1 |    | Genteq  | Special  | 56000 |     | 60  | 2.5   | Round | 3.625 | Electrolytic             | 1000  | -45°C to 95°C  |
| PB350E000A370EA |    | PROLINE | Standard | 35    |     | 370 | 1.25  | Oval  | 4.75  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23A213F150F11H1 |    | Genteq  | Special  | 21000 |     | 150 | 3     | Round | 5.625 | Electrolytic             | 1000  | -40°C to 85°C  |
| 97F6755BR       | BR | Genteq  | Standard | 26    |     | 330 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23H203F200BH1H1 |    | Genteq  | Special  | 2000  |     | 200 | 1.375 | Round | 5.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23H342F350E11H1 |    | Genteq  | Special  | 3400  |     | 350 | 2.5   | Round | 5.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| PB500Z050T440HA |    | PROLINE | Standard | 50    | 5   | 440 | 2.5   | Round | 4.25  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F5781         |    | Genteq  | Standard | 50    | 7.5 | 440 | 2     | Oval  | 5.25  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23B312F250FD1H1 |    | Genteq  | Special  | 3100  |     | 250 | 3     | Round | 3.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| 23M142F300BG1H1 |    | Genteq  | Special  | 1400  |     | 300 | 1.375 | Round | 4.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 97F6871BX       | BX | Genteq  | Standard | 12    |     | 280 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F9037         |    | Genteq  | Standard | 15    |     | 440 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 27L729RR        | RR | Genteq  | Special  | 20    | 4   | 400 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23J462F300FG1H1 |    | Genteq  | Special  | 4600  |     | 300 | 3     | Round | 4.625 | Electrolytic             | 2000  | -40°C to 105°C |
| 23M142F400CH1H1 |    | Genteq  | Special  | 1400  |     | 400 | 1.75  | Round | 5.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 97F9683BX       | BX | Genteq  | Standard | 30    | 7.5 | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23D113F055BI1H1 |    | Genteq  | Special  | 11000 |     | 55  | 1.375 | Round | 5.625 | Electrolytic             | 1000  | -55°C to 85°C  |
| 23F383F075EG1H1 |    | Genteq  | Special  | 38000 |     | 75  | 2.5   | Round | 4.625 | Electrolytic             | 1000  | -55°C to 105°C |
| 23M801F400BH1H1 |    | Genteq  | Special  | 800   |     | 400 | 1.375 | Round | 5.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| PB300E000S370CA |    | PROLINE | Standard | 30    |     | 370 | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 97F9826BX       | BX | Genteq  | Standard | 25    | 7.5 | 370 | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23H152F350CH1H1 |    | Genteq  | Special  | 1500  |     | 350 | 1.75  | Round | 5.125 | Electrolytic             | 2000  | -40°C to 85°C  |

|                   |    |         |          |       |     |      |       |       |       |                          |        |                |
|-------------------|----|---------|----------|-------|-----|------|-------|-------|-------|--------------------------|--------|----------------|
| 97F5114BX         | BX | Genteq  | Special  | 35    |     | 370  | 2     | Round | 4.25  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9462           |    | Genteq  | Standard | 40    | 10  | 370  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23C143F060BE1H1   |    | Genteq  | Special  | 14000 |     | 60   | 1.375 | Round | 3.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23B213F100EH1H1   |    | Genteq  | Special  | 21000 |     | 100  | 2.5   | Round | 5.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F6927           |    | Genteq  | Special  | 11.5  | 3   | 400  | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| PB200Z050S440CA   |    | PROLINE | Standard | 20    | 5   | 440  | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| PB300Y100C440EABX | BX | PROLINE | Standard | 30    | 10  | 440  | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23F673F060FH1H1   |    | Genteq  | Special  | 67000 |     | 60   | 3     | Round | 5.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 97F8078BX         | BX | Genteq  | Special  | 8     |     | 440  | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L6093BX         | BX | Genteq  | Special  | 2.5   |     | 660  | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23A154F060F1H1    |    | Genteq  | Special  | 15000 | 0   | 60   | 3     | Round | 5.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 27L63BX           | BX | Genteq  | Standard | 80    |     | 370  | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23C892F075BE1H1   |    | Genteq  | Special  | 8900  |     | 75   | 1.375 | Round | 3.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23F232F100CB1H1   |    | Genteq  | Special  | 2300  |     | 100  | 1.75  | Round | 2.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 23D842F055BG1H1   |    | Genteq  | Special  | 8400  |     | 55   | 1.375 | Round | 4.625 | Electrolytic             | 1000   | -55°C to 85°C  |
| 27L589RR          | RR | Genteq  | Standard | 10    | 5   | 400  | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F9121           |    | Genteq  | Standard | 15    |     | 370  | 1.75  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F5459BX         | BX | Genteq  | Standard | 12.5  |     | 370  | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23B663F060EH1H1   |    | Genteq  | Special  | 66000 |     | 60   | 2.5   | Round | 5.125 | Electrolytic             | 3000   | -40°C to 85°C  |
| PB300E000S440DABX | BX | PROLINE | Standard | 30    |     | 440  | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23A263F050DC1H1   |    | Genteq  | Special  | 26000 |     | 50   | 2     | Round | 2.625 | Electrolytic             | 1000   | -40°C to 85°C  |
| 23F143F050BF1H1   |    | Genteq  | Special  | 14000 |     | 50   | 1.375 | Round | 4.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 23B292F150B1H1    |    | Genteq  | Special  | 2900  |     | 150  | 1.375 | Round | 5.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F9739BX         | BX | Genteq  | Standard | 40    | 5   | 440  | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB250Y075C370CA   |    | PROLINE | Standard | 25    | 7.5 | 370  | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F6686           |    | Genteq  | Special  | 11.5  |     | 480  | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F6703RC         | RC | Genteq  | Standard | 8     |     | 330  | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F6933           |    | Genteq  | Standard | 18    |     | 540  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F6712BX         | BX | Genteq  | Special  | 17.5  |     | 330  | 1.5   | Oval  | 3.5   | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 42L4103           |    | Genteq  | Stock    | 0.01  |     | 3000 | 0.47  | Round | 1.22  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 97F9978S          | S  | Genteq  | Stock    | 25    | 5   | 440  | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB600E000T370DABX | BX | PROLINE | Standard | 60    |     | 370  | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23F802F080BG1H1   |    | Genteq  | Special  | 8000  |     | 80   | 1.375 | Round | 4.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 23J112F300DD1H1   |    | Genteq  | Special  | 1100  |     | 300  | 2     | Round | 3.125 | Electrolytic             | 2000   | -40°C to 105°C |
| 97F9123BX         | BX | Genteq  | Special  | 17.5  |     | 370  | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9494BX         | BX | Genteq  | Standard | 35    | 7.5 | 440  | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6933BX         | BX | Genteq  | Standard | 18    |     | 540  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23C302F150DC1H1   |    | Genteq  | Special  | 3000  |     | 150  | 2     | Round | 2.625 | Electrolytic             | 1000   | -45°C to 95°C  |
| 97F6850           |    | Genteq  | Standard | 45    |     | 280  | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23F193F075DF1H1   |    | Genteq  | Special  | 19000 |     | 75   | 2     | Round | 4.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 23F553F075FG1H1   |    | Genteq  | Special  | 55000 |     | 75   | 3     | Round | 4.625 | Electrolytic             | 1000   | -55°C to 105°C |
| 27L1003RR         | RR | Genteq  | Standard | 20    |     | 440  | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6788BR         | BR | Genteq  | Standard | 2.5   |     | 330  | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F9871           |    | Genteq  | Standard | 20    |     | 440  | 2     | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB040E000A440AA   |    | PROLINE | Standard | 4     |     | 440  | 1.25  | Oval  | 1.56  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 41L4681           |    | Genteq  | Stock    | 6.8   |     | 400  | 0.98  | Round | 1.65  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 97F6922BX         | BX | Genteq  | Special  | 8     |     | 525  | 1.5   | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| PB300Z050S440DA   |    | PROLINE | Standard | 30    | 5   | 440  | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23F921F150CB1H1   |    | Genteq  | Special  | 920   |     | 150  | 1.75  | Round | 2.125 | Electrolytic             | 1000   | -55°C to 105°C |



|                    |    |         |          |       |     |     |       |       |       |                          |        |                |
|--------------------|----|---------|----------|-------|-----|-----|-------|-------|-------|--------------------------|--------|----------------|
| 23H112F300DC1H1    |    | Genteq  | Special  | 1100  |     | 300 | 2     | Round | 2.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| PB400Z075S370DA    |    | PROLINE | Standard | 40    | 7.5 | 370 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23A183F100ED1H1    |    | Genteq  | Special  | 18000 |     | 100 | 2.5   | Round | 3.125 | Electrolytic             | 1000   | -40°C to 85°C  |
| 97F6945BX          | BX | Genteq  | Standard | 24    |     | 580 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23C582F250FF1H1    |    | Genteq  | Special  | 5800  |     | 250 | 3     | Round | 4.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 25L502BX           | BX | Genteq  | Standard | 35    |     | 440 | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23J152F200BH1H1    |    | Genteq  | Special  | 1500  |     | 200 | 1.375 | Round | 5.125 | Electrolytic             | 2000   | -40°C to 105°C |
| 97F6622RC          | RC | Genteq  | Standard | 24    |     | 400 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23D113F028BD1H1    |    | Genteq  | Special  | 11000 |     | 28  | 1.375 | Round | 3.125 | Electrolytic             | 1000   | -55°C to 85°C  |
| PB550Z075T440EABX  | BX | PROLINE | Standard | 55    | 7.5 | 440 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23J561F300CB1H1    |    | Genteq  | Special  | 560   |     | 300 | 1.75  | Round | 2.125 | Electrolytic             | 2000   | -40°C to 105°C |
| PB400E000P440EABX  | BX | PROLINE | Standard | 40    |     | 440 | 1.75  | Round | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23F522F250FH1H1    |    | Genteq  | Special  | 5200  |     | 250 | 3     | Round | 5.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 23M402F250DG1H1    |    | Genteq  | Special  | 4000  |     | 250 | 2     | Round | 4.625 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F6622BR          | BR | Genteq  | Standard | 24    |     | 400 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F9006BX          | BX | Genteq  | Standard | 25    |     | 370 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9600BX          | BX | Genteq  | Standard | 17.5  |     | 370 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6930RC          | RC | Genteq  | Standard | 10    |     | 580 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| PB700Z100T370EA    |    | PROLINE | Standard | 70    | 10  | 370 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 23H401F300BB1H1    |    | Genteq  | Special  | 400   |     | 300 | 1.375 | Round | 2.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 97F9207BX          | BX | Genteq  | Standard | 25    |     | 240 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6680RC          | RC | Genteq  | Special  | 24    |     | 480 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| PB150Y050C370CAB X | BX | PROLINE | Standard | 15    | 5   | 370 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 27L444BR           | BR | Genteq  | Special  | 37    | 11  | 300 | 1.75  | Oval  | 4.25  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| PB200E000P370CA    |    | PROLINE | Standard | 20    |     | 370 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F6506            |    | Genteq  | Standard | 14    |     | 330 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F9052BX          | BX | Genteq  | Special  | 30    | 5   | 440 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L6073            |    | Genteq  | Special  | 15    |     | 660 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| PB100E000A370CA    |    | PROLINE | Standard | 10    |     | 370 | 1.25  | Oval  | 2.88  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F5483BX          | BX | Genteq  | Special  | 35    | 4   | 370 | 1.75  | Oval  | 4.25  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 27L729BR           | BR | Genteq  | Special  | 20    | 4   | 400 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 23C263F100FD1H1    |    | Genteq  | Special  | 26000 |     | 100 | 3     | Round | 3.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| PB800Z075T440EA    |    | PROLINE | Standard | 80    | 7.5 | 440 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved) | 10000  | -40°C to 70°C  |
| 97F8065            |    | Genteq  | Standard | 30    |     | 370 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23H352F250DH1H1    |    | Genteq  | Special  | 3500  |     | 250 | 2     | Round | 5.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 23M352F300DH1H1    |    | Genteq  | Special  | 3500  |     | 300 | 2     | Round | 5.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 27L709             |    | Genteq  | Standard | 26    |     | 400 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F9444BX          | BX | Genteq  | Standard | 15    |     | 370 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9061BX          | BX | Genteq  | Standard | 55    | 10  | 440 | 2     | Oval  | 6.25  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 23F513F080FH1H1    |    | Genteq  | Special  | 51000 |     | 80  | 3     | Round | 5.125 | Electrolytic             | 1000   | -55°C to 105°C |
| 23C133F080BH1H1    |    | Genteq  | Special  | 13000 |     | 80  | 1.375 | Round | 5.125 | Electrolytic             | 1000   | -45°C to 95°C  |
| 23B532F150DG1H1    |    | Genteq  | Special  | 5300  |     | 150 | 2     | Round | 4.625 | Electrolytic             | 3000   | -40°C to 85°C  |
| 97F8084            |    | Genteq  | Standard | 60    |     | 440 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F9832            |    | Genteq  | Standard | 45    | 10  | 370 | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 97F6774RC          | RC | Genteq  | Standard | 24    |     | 330 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 90°C  |
| 97F8065S           | S  | Genteq  | Stock    | 30    |     | 370 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000  | -40°C to 70°C  |
| 41L2200            |    | Genteq  | Stock    | 20    |     | 250 | 1.1   | Round | 1.65  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |
| 23H242F300ED1H1    |    | Genteq  | Special  | 2400  |     | 300 | 2.5   | Round | 3.125 | Electrolytic             | 2000   | -40°C to 85°C  |
| 42L1472            |    | Genteq  | Stock    | 0.47  |     | 850 | 0.67  | Round | 1.22  | Dry-Axial Leaded         | 100000 | -40°C to 85°C  |

|                   |    |         |          |            |     |     |       |       |       |                            |        |                |
|-------------------|----|---------|----------|------------|-----|-----|-------|-------|-------|----------------------------|--------|----------------|
| 23B542F100BH1H1   |    | Genteq  | Special  | 5400       |     | 100 | 1.375 | Round | 5.125 | Electrolytic               | 3000   | -40°C to 85°C  |
| 23H411F450DC1H1   |    | Genteq  | Special  | 410        |     | 450 | 2     | Round | 2.625 | Electrolytic               | 2000   | -40°C to 85°C  |
| 40L3471           |    | Genteq  | Stock    | 4.7        |     | 400 | 0.64  | Oval  | 1.75  | Dry-Axial Leaded           | 100000 | -55°C to 105°C |
| 23M452F350FF1H1   |    | Genteq  | Special  | 4500       |     | 350 | 3     | Round | 4.125 | Electrolytic               | 2000   | -40°C to 85°C  |
| 25L6755RR         | RR | Genteq  | Standard | 20         | 8   | 280 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 23F622F060BD1H1   |    | Genteq  | Special  | 6200       |     | 60  | 1.375 | Round | 3.125 | Electrolytic               | 1000   | -55°C to 105°C |
| 23M372F350EG1H1   |    | Genteq  | Special  | 3700       |     | 350 | 2.5   | Round | 4.625 | Electrolytic               | 2000   | -40°C to 85°C  |
| PB500Y075D440GA   |    | PROLINE | Standard | 50         | 7.5 | 440 | 2     | Oval  | 5.25  | Oil-Filled (UL Approved)   | 10000  | -40°C to 70°C  |
| 23M172F350CG1H1   |    | Genteq  | Special  | 1700       |     | 350 | 1.75  | Round | 4.625 | Electrolytic               | 2000   | -40°C to 85°C  |
| 97F8246           |    | Genteq  | Standard | 6          |     | 600 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 97F7050           |    | Genteq  | Special  | 120        |     | 240 | 2     | Oval  | 4.75  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 23D563F007BH1H1   |    | Genteq  | Special  | 56000      |     | 7.5 | 1.375 | Round | 5.125 | Electrolytic               | 1000   | -55°C to 85°C  |
| PB4002075S440EA   |    | PROLINE | Standard | 40         | 7.5 | 440 | 2     | Round | 4.75  | Oil-Filled (UL Approved)   | 10000  | -40°C to 70°C  |
| 97F6533RC         | RC | Genteq  | Standard | 30         |     | 280 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 97F5501BX         | BX | Genteq  | Special  | 25         | 5   | 440 | 2     | Oval  | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 23C182F200BH1H1   |    | Genteq  | Special  | 1800       |     | 200 | 1.375 | Round | 5.125 | Electrolytic               | 1000   | -45°C to 95°C  |
| 23F242F200ED1H1   |    | Genteq  | Special  | 2400       |     | 200 | 2.5   | Round | 3.125 | Electrolytic               | 1000   | -55°C to 105°C |
| 23F652F080CC1H1   |    | Genteq  | Special  | 6500       |     | 80  | 1.75  | Round | 2.625 | Electrolytic               | 1000   | -55°C to 105°C |
| PB150Z075S370CA   |    | PROLINE | Standard | 15         | 7.5 | 370 | 2     | Round | 2.88  | Oil-Filled (UL Approved)   | 10000  | -40°C to 70°C  |
| 27L382BX          | BX | Genteq  | Standard | 8.5        | 3.5 | 280 | 1.75  | Oval  | 2.12  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 24DB250B370PA     |    | Genteq  | Standard | 25         |     | 370 | 1.75  | Round | 3.189 | Dry (UL Construction Only) | 60000  | -40°C to 70°C  |
| 27L1021           |    | Genteq  | Standard | 2          |     | 440 | 1.25  | Oval  | 1.56  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 23D313F020BI1H1   |    | Genteq  | Special  | 31000      |     | 20  | 1.375 | Round | 5.625 | Electrolytic               | 1000   | -55°C to 85°C  |
| 23J381F400BF1H1   |    | Genteq  | Special  | 380        |     | 400 | 1.375 | Round | 4.125 | Electrolytic               | 2000   | -40°C to 105°C |
| 97F6761BX         | BX | Genteq  | Standard | 17.5       |     | 330 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 23F591F200CB1H1   |    | Genteq  | Special  | 590        |     | 200 | 1.75  | Round | 2.125 | Electrolytic               | 1000   | -55°C to 105°C |
| 23B512F100CD1H1   |    | Genteq  | Special  | 5100       |     | 100 | 1.75  | Round | 3.125 | Electrolytic               | 3000   | -40°C to 85°C  |
| 97F6603BR         | BR | Genteq  | Special  | 24         |     | 400 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| PB700Z050T370EABX | BX | PROLINE | Standard | 70         | 5   | 370 | 2.5   | Round | 4.75  | Oil-Filled (UL Approved)   | 10000  | -40°C to 70°C  |
| 23M102F350CD1H1   |    | Genteq  | Special  | 1000       |     | 350 | 1.75  | Round | 3.125 | Electrolytic               | 2000   | -40°C to 85°C  |
| 27L724RR          | RR | Genteq  | Standard | 24         | 11  | 280 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 97F9743BX         | BX | Genteq  | Standard | 17.5       |     | 370 | 1.25  | Oval  | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 23M142F200BD1H1   |    | Genteq  | Special  | 1400       |     | 200 | 1.375 | Round | 3.125 | Electrolytic               | 2000   | -40°C to 85°C  |
| 97F6755           |    | Genteq  | Standard | 26         |     | 330 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 97F6867           |    | Genteq  | Standard | 52         |     | 280 | 2     | Oval  | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 23C134F060FH1H1   |    | Genteq  | Special  | 13000<br>0 |     | 60  | 3     | Round | 5.125 | Electrolytic               | 1000   | -45°C to 95°C  |
| 97F6931BX         | BX | Genteq  | Standard | 20         |     | 580 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 23B383F075EF1H1   |    | Genteq  | Special  | 38000      |     | 75  | 2.5   | Round | 4.125 | Electrolytic               | 3000   | -40°C to 85°C  |
| 23C463F050ED1H1   |    | Genteq  | Special  | 46000      |     | 50  | 2.5   | Round | 3.125 | Electrolytic               | 1000   | -45°C to 95°C  |
| 97F5121           |    | Genteq  | Special  | 15         |     | 440 | 2     | Round | 2.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 25L752BX          | BX | Genteq  | Special  | 25         | 4   | 440 | 2     | Round | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 97F6931RC         | RC | Genteq  | Standard | 20         |     | 580 | 1.75  | Oval  | 4.75  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 23M322F400FF1H1   |    | Genteq  | Special  | 3200       |     | 400 | 3     | Round | 4.125 | Electrolytic               | 2000   | -40°C to 85°C  |
| 23H641F400BH1H1   |    | Genteq  | Special  | 640        |     | 400 | 1.375 | Round | 5.125 | Electrolytic               | 2000   | -40°C to 85°C  |
| 97F6925BX         | BX | Genteq  | Special  | 48         |     | 300 | 2     | Oval  | 2.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 97F6869           |    | Genteq  | Standard | 42         |     | 280 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 97F9826           |    | Genteq  | Standard | 25         | 7.5 | 370 | 2     | Round | 2.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |
| 97F6623           |    | Genteq  | Standard | 24         |     | 400 | 2     | Oval  | 2.88  | Oil-Filled (UL Approved)   | 60000  | -40°C to 90°C  |
| 23H382F200ED1H1   |    | Genteq  | Special  | 3800       |     | 200 | 2.5   | Round | 3.125 | Electrolytic               | 2000   | -40°C to 85°C  |
| 97F8054S          | S  | Genteq  | Stock    | 3          |     | 370 | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved)   | 60000  | -40°C to 70°C  |

|                 |    |         |          |       |    |     |       |       |       |                          |       |                |
|-----------------|----|---------|----------|-------|----|-----|-------|-------|-------|--------------------------|-------|----------------|
| 27L20BX         | BX | Genteq  | Standard | 30    | 5  | 440 | 2.5   | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 23H432F250EF1H1 |    | Genteq  | Special  | 4300  |    | 250 | 2.5   | Round | 4.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 97F9009BX       | BX | Genteq  | Standard | 50    |    | 370 | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| PB400E000C370DA |    | PROLINE | Standard | 40    |    | 370 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23B701F250DB1H1 |    | Genteq  | Special  | 700   |    | 250 | 2     | Round | 2.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| 23A473F080EF1H1 |    | Genteq  | Special  | 47000 |    | 80  | 2.5   | Round | 4.125 | Electrolytic             | 1000  | -40°C to 85°C  |
| 27L990BX        | BX | Genteq  | Special  | 35    |    | 240 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 27L6017BX       | BX | Genteq  | Special  | 10    |    | 660 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F6920         |    | Genteq  | Standard | 16    |    | 540 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F9895BX       | BX | Genteq  | Standard | 45    | 5  | 370 | 2     | Round | 4.75  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F6855RC       | RC | Genteq  | Standard | 22.5  |    | 280 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F5304         |    | Genteq  | Special  | 15    |    | 440 | 1.75  | Oval  | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F8072BX       | BX | Genteq  | Standard | 65    |    | 370 | 2.5   | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F6543         |    | Genteq  | Special  | 28    |    | 280 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F6537BX       | BX | Genteq  | Standard | 24    |    | 330 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23F192F250ED1H1 |    | Genteq  | Special  | 1900  |    | 250 | 2.5   | Round | 3.125 | Electrolytic             | 1000  | -55°C to 105°C |
| 23B192F250DF1H1 |    | Genteq  | Special  | 1900  |    | 250 | 2     | Round | 4.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| 97F8055S        | S  | Genteq  | Stock    | 4     |    | 370 | 1.25  | Oval  | 2.12  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F9983         |    | Genteq  | Standard | 30    | 10 | 440 | 2     | Round | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 97F9606S        | S  | Genteq  | Stock    | 25    |    | 370 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| 27L1003         |    | Genteq  | Standard | 20    |    | 440 | 1.75  | Round | 2.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 70°C  |
| PB350E000P370DA |    | PROLINE | Standard | 35    |    | 370 | 1.75  | Round | 3.88  | Oil-Filled (UL Approved) | 10000 | -40°C to 70°C  |
| 23M262F250CF1H1 |    | Genteq  | Special  | 2600  |    | 250 | 1.75  | Round | 4.125 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23D213F020BF1H1 |    | Genteq  | Special  | 21000 |    | 20  | 1.375 | Round | 4.125 | Electrolytic             | 1000  | -55°C to 85°C  |
| 23B623F060FE1H1 |    | Genteq  | Special  | 62000 |    | 60  | 3     | Round | 3.625 | Electrolytic             | 3000  | -40°C to 85°C  |
| 97F6694BX       | BX | Genteq  | Special  | 20    |    | 480 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23H561F350BE1H1 |    | Genteq  | Special  | 560   |    | 350 | 1.375 | Round | 3.625 | Electrolytic             | 2000  | -40°C to 85°C  |
| 23J132F200DC1H1 |    | Genteq  | Special  | 1300  |    | 200 | 2     | Round | 2.625 | Electrolytic             | 2000  | -40°C to 105°C |
| 97F6782         |    | Genteq  | Special  | 18.5  |    | 330 | 1.5   | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 97F6757         |    | Genteq  | Standard | 34    |    | 330 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |
| 23B183F075CF1H1 |    | Genteq  | Special  | 18000 |    | 75  | 1.75  | Round | 4.125 | Electrolytic             | 3000  | -40°C to 85°C  |
| 23J122F250CD1H1 |    | Genteq  | Special  | 1200  |    | 250 | 1.75  | Round | 3.125 | Electrolytic             | 2000  | -40°C to 105°C |
| 97F6655BX       | BX | Genteq  | Standard | 50    |    | 260 | 1.75  | Oval  | 3.88  | Oil-Filled (UL Approved) | 60000 | -40°C to 90°C  |

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Film Capacitors](#) category:*

*Click to view products by [Genteq](#) manufacturer:*

Other Similar products are found below :

[F339X134748MIP2T0](#) [F450KG153J250ALH0J](#) [750-1018](#) [FKP1-1500160010P15](#) [FKP1R031007D00JYSD](#) [FKP1R031507E00JYSD](#)  
[FKP1U024707E00KYSD](#) [82DC4100CK60J](#) [82EC1100DQ50K](#) [PFR5101J100J11L16.5TA18](#) [PME261JB5220KR19T0](#) [A451GK223M040A](#)  
[A561ED221M450A](#) [QXJ2E474KTPT](#) [QXL2B333KTPT](#) [R49AN347000A1K](#) [EEC2G505HQA406](#) [B25668A6676A375](#) [B25673A4282E140](#)  
[BFC233868148](#) [BFC2370GC222](#) [C3B2AD44400B20K](#) [C4ASWBU3220A3EK](#) [CB027C0473J--](#) [CB177I0184J--](#) [CB182K0184J--](#) [23PW210](#)  
[950CQW5H-F](#) [SBDC3470AA10J](#) [SCD105K122A3-22](#) [2N3155](#) [A571EH331M450A](#) [FKP1-2202KV5P15](#) [FKS3-680040010P10](#)  
[QXL2E473KTPT](#) [445450-1](#) [B25669A3996J375](#) [46KI322000M1M](#) [46KR415050M1K](#) [4BSNBX4100ZBFJ](#) [MKP383510063JKP2T0](#)  
[MKPY2-.02230020P15](#) [MKT 1813-368-015](#) [4055292001](#) [46KN410000N1K](#) [EEC2E106HQA405](#) [EEC2G205HQA402](#) [EEC2G805HQA415](#)  
[P409CP224M250AH470](#) [82EC2150DQ50K](#)