


## Silicone Free Thin Film

### SFT Series

This material is suitable where there are concerns about the use of Silicones. Our Silicone free materials use a ceramic filled Polyurethane. They have a high thermal conductivity with good electrical insulation properties. Available with one side adhesive coating. Can be supplied die-cut to customer specification.



#### PRODUCT APPLICATION

- Medical Applications
- Laser Equipment
- LED's
- Aerospace
- HDD
- Automotive

Specification	SFT80-XX(-T1)	SFT90-XX(-T1)
Thermal Conductivity (W/m.k)	1.8	6.0
Thickness (mm)	0.15/0.30	0.10/0.12/0.30
Thermal Resistance (K/W)	0.20	0.09
Thermal Impedance ( $^{\circ}\text{C} \cdot \text{cm}^2/\text{W}$ )	73	33
Density ( $\text{g}/\text{cm}^3$ )	2.26	1.46
Break down voltage (kV)	4	4 (0.12 ~ 0.3mm)
Dielectric Break down voltage (kV/mm)	25	25
Tensile Strength ( $\text{N}/\text{mm}^2$ )	3.0	2.5
Elongation (%)	130	150
Temperature range ( $^{\circ}\text{C}$ )	-40~+125	-40~+125
Standard sheet size (mm)	250 x 225	250 x 225
Available with adhesive	1 Side (-T1)	1 Side (-T1)
Colour	Blue	Light Blue

#### AMEC Thermasol

1-2 Steam Mill Lane, Great Yarmouth, Norfolk, NR31 0HP

Telephone: +44(0) 1493 668622 Fax: +44(0) 1493 668623

Email: [sales@amecthermasol.co.uk](mailto:sales@amecthermasol.co.uk) Website: [www.amecthermasol.co.uk](http://www.amecthermasol.co.uk)

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [amec thermasol](#) manufacturer:*

Other Similar products are found below :

[SFT80-0.15](#) [FCTL73-15](#) [MPC303025T](#) [FCTS73-10N](#) [W8TR500G-0.5GF](#) [MPC101020T](#) [MHP-2550A-250A](#) [MPC202025T](#) [FCH30305T](#)  
[MPC151525T](#)