

Brands

Products

Markets

Solutions

Resources

Support

Company

Catalog

Home

HOME







Catamount

PRINT

Grommeting

T&B Catalog Number: GRNY-062-0-C UPC Number: 72849407940 Status: Active

Description:

Extruded Grommeting Black Nylon 6/6 For Max. Panel Thickness .062, 100 Feet P

ROHS SUBMITTAL PACKAGE

Features

- Used to line panel edges and knockouts where the chafing of wires is a concer
- Available in 8 stock sizes in 100-ft. lengths for panels from .040 .250 inches the stocked materials to cover a wide range of applications.

General

G. G. F. F. G. F. G. F. F. G. F. F. G. F. F. G. F. F. F. G. F.	
Style	Extruded
Material	Nylon 6/6
Color	Black

Dimension Information

For Panel Thickness Max (inches)	0.062
C (inches)	0.045
D (inches)	0.200
E (inches)	0.170

Specifications

Flammability Rating UL 94 V-2

Tooling

Application Tools SR-100

Packaging

Order Multiple 1 Inner Package 1 Outer Package 15 Feet per Roll 100 Package Height 12 Package Length 18 Package Width 12.5 T&B Sold in UOM Fach

T&B Weight Per UOM 0.82 lbs. Each

Notes

Grommet is used to protect panel edges and knock-outs where the chafing of p

Certifications

RoHS Compliance Yes Generate Compliance

Global Site T&B Access (Dist o Contact Us About Us

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Wire Identification category:

Click to view products by ABB manufacturer:

Other Similar products are found below:

CU6337-000 CU6342-000 FCA-410-12 11631010 1-1768037-1 1-1768037-2 1-1768050-0 PXLK-VI Q62184-1 A64304-000 QMT221 HK032WE1NF038B 1330-0519-10 1395199-1 1395200-1 1395202-1 DMVF050WE-300S6 D-SCE-1K-2.4-50-4-CS7834 1538738-1 E90935-000 EC1238-000 EC1465-000 EC1855-000 EC1859-000 EC1863-000 EC5415-000 EC7277-000 EC7352-000 EC7603-000 EC7707-000 EC7735-000 EC7768-000 EC7828-000 EC7854-000 EC7952-000 EC8128-000 1768037-8 1768041-7 NC-127191-10-9 HS048WE2NF038B C03232-000 HTCM-SCE-14-4H-9 HTMS-3/16-9 HT-SCE-1/4-2.0-4 HT-SCE-3/16-2.0-4 HTTMS-1/2-1.50-9 HTTMS-CM-1/2-4H-9 HX-SCE-19.0-50-9 HX-SCE-6.4-50-4 C25254-000