

REVISIONS
SEE SHEET 1

TABLE I


DASH NO	CONNECTOR SHELL SIZE REF	A		B		C		D		E		F		G		H		K		L		M		N	
		+ .031/-.016 DIM	MIN CLEARANCE	MAX DIM	MIN CABLE	MAX DIM	MAX CLOSED DIM	+ .020/-.000 DIA	+ .000/-.020 DIA	MAX DIM	+ .000/-.020 DIA	+ .016 DIM	+ .020/-.000 DIA	+ .016 DIM	+ .000/-.020 DIA	+ .016 DIM	+ .000/-.020 DIA	MAX DIM	MIN DIM	MAX DIM	+ .031 DIM	+ .016 DIM	MAX DIM	+ .031 DIM	+ .016 DIM
3C	8S, 10S	.188 (4.8)	.239 (6.1)	.812 (20.6)	.812 (20.6)	.389 (9.9)	.231 (5.9)	.217 (5.5)	.315 (8.0)	.125 (3.2)	.441 (11.2)	1.375 (34.9)	.156 (4.0)	.473 (12.0)	.254 (6.5)										
4C	10SL, 12, 12S	.188 (4.8)	.317 (8.1)	.937 (23.8)	.937 (23.8)	.510 (13.0)	.315 (8.0)	.296 (7.5)	.440 (11.2)	.125 (3.2)	.560 (14.2)	1.375 (34.9)	.156 (4.0)	.473 (12.0)	.254 (6.5)										
6C	14, 14S	.188 (4.8)	.443 (11.3)	1.062 (27.0)	.827 (21.0)	.627 (15.9)	.440 (11.2)	.390 (9.9)	.515 (13.1)	.125 (3.2)	.676 (17.2)	1.375 (34.9)	.156 (4.0)	.473 (12.0)	.254 (6.5)										
8C	16, 16S	.188 (4.8)	.551 (14.0)	1.188 (30.2)	.744 (18.9)	.744 (18.9)	.434 (11.0)	.434 (11.0)	.515 (13.1)	.125 (3.2)	.800 (20.3)	1.375 (34.9)	.156 (4.0)	.473 (12.0)	.254 (6.5)										
10C	18	.188 (4.8)	.630 (16.0)	1.312 (33.3)	.870 (22.1)	.870 (22.1)	.614 (15.6)	.434 (11.0)	.614 (15.6)	.125 (3.2)	.926 (23.5)	1.437 (36.5)	.156 (4.0)	.537 (13.6)	.281 (7.1)										
12C	20, 22	.250 (6.4)	.771 (19.6)	1.562 (39.7)	1.037 (26.3)	1.037 (26.3)	.738 (18.7)	.596 (15.1)	.738 (18.7)	.156 (4.0)	1.107 (28.1)	1.437 (36.5)	.156 (4.0)	.625 (15.9)	.320 (8.1)										
16C	24, 28	.250 (6.4)	.959 (24.4)	1.750 (44.5)	1.286 (32.7)	1.286 (32.7)	.926 (23.5)	.596 (15.1)	.926 (23.5)	.156 (4.0)	1.357 (34.5)	1.562 (39.7)	.156 (4.0)	.662 (16.8)	.344 (8.7)										
20C	32	.312 (7.9)	1.271 (32.3)	2.250 (57.2)	1.890 (40.4)	1.890 (40.4)	1.200 (30.5)	.596 (15.1)	1.200 (30.5)	.156 (4.0)	1.670 (42.4)	1.812 (46.0)	.156 (4.0)	.940 (23.9)	.406 (10.3)										
24C	36	.312 (7.9)	1.396 (35.5)	2.375 (60.3)	1.844 (46.8)	1.844 (46.8)	1.363 (34.6)	.888 (22.8)	1.363 (34.6)	.188 (4.8)	1.920 (48.8)	2.062 (52.4)	.156 (4.0)	.940 (23.9)	.406 (10.3)										
28C	40	.312 (7.9)	1.646 (41.8)	2.625 (66.7)	2.083 (52.9)	2.083 (52.9)	1.611 (40.9)	1.107 (28.1)	1.611 (40.9)	.188 (4.8)	2.162 (54.9)	2.262 (57.9)	.156 (4.0)	.940 (23.9)	.406 (10.3)										
32C	44	.375 (9.5)	1.896 (48.2)	2.812 (71.4)	2.332 (59.2)	2.332 (59.2)	1.865 (47.4)	1.421 (36.1)	1.865 (47.4)	.188 (4.8)	2.412 (61.3)	2.188 (55.6)	.188 (4.8)	1.047 (26.6)	.500 (12.7)										

TABLE I, CONTINUED

DASH NO	P MIN DEG	R MIN DIM	T +.016 DIM	U THREAD CLASS 2A	V AN5000 DASH NO	W MS35338 DASH NO	X THREAD CLASS 2B	Y MIN DIM	Z DIA APPROXIMATE (GLAND)	BUSHING REF GS3420 DASH NO	MAX CABLE ENTRY
3C	20°	.531 (13.5)	.641 (16.3)	.138-32 UNC	6-8	6-32	500-28 UNEF	469 (11.9)	.219 (5.6)	3* 219 (5.6)	
4C	20°	.531 (13.5)	.641 (16.3)	.138-32 UNC	6-10	6-32	.625-24 UNEF	594 (15.1)	.312 (7.9)	4* 312 (7.9)	
6C	30°	.531 (13.5)	.641 (16.3)	.138-32 UNC	6-10	6-32	.750-20 UNEF	594 (15.1)	.438 (11.1)	6* 438 (11.1)	
8C	30°	.531 (13.5)	.641 (16.3)	.138-32 UNC	6-12	6-32	.875-20 UNEF	719 (18.3)	.531 (13.5)	8* 531 (13.5)	
10C	30°	.531 (13.5)	.672 (17.1)	.138-32 UNC	6-12	6-32	1.000-20 UNEF	719 (18.3)	.625 (15.9)	10* 625 (15.9)	
12C	30°	.531 (13.5)	.719 (18.3)	.164-32 UNC	8-14	248	1.188-18 UNEF	844 (21.4)	.750 (19.1)	12* 750 (19.1)	
16C	30°	.531 (13.5)	.719 (18.3)	.164-32 UNC	8-18	N/A	1.438-18 UNEF	1.062 (27.0)	.938 (23.8)	16* 938 (23.8)	
20C	35°	.562 (14.3)	.797 (20.2)	.250-20 UNC	416-22	284	1.750-18 UNS	1.187 (30.1)	1.250 (31.8)	20* 1.250 (31.8)	
24C	35°	.781 (19.8)	1.016 (25.8)	.250-20 UNC	416-22	N/A	2.000-18 UNS	1.312 (33.3)	1.375 (34.9)	24* 1.375 (34.9)	
28C	35°	.781 (19.8)	1.016 (25.8)	.250-20 UNC	416-22	N/A	2.250-16 UN	1.312 (33.3)	1.625 (41.3)	28* 1.625 (41.3)	
32C	35°	.781 (19.8)	1.172 (29.8)	.250-20 UNC	416-22	N/A	2.500-16 UN	1.312 (33.3)	1.875 (47.6)	32* 1.875 (47.6)	

NOTES:

- ASSEMBLY IDENTIFIED WITH MANUFACTURERS NAME & P/N, SPACE PERMITTING.
- GLENRAIR 600 SERIES BACKSHELL ASSEMBLY TOOLS ARE RECOMMENDED FOR ASSEMBLY AND INSTALLATION.
- WHEN THE RETAINING RING IS NOT USED, THE DIMENSIONS LISTED IN COLUMN "H" SHALL BE THE MINIMUM OUTER DIAMETER OF THE GLAND FOR THE ASSOCIATED DASH NUMBER.
- OPTIONAL RETAINING RING SHALL BE BONDED TO GLAND.
- LUBRICANT, VV-P-236, MAY BE APPLIED TO THREADS AND SURFACES OF SLEEVE IF REQUIRED.
- FOR SIZES -3 THRU -10, SERRATIONS SHALL BE COVERED WITH RUBBER. LARGER SIZES MAY BE COVERED WITH RUBBER. DEPTH OF RUBBER SHALL NOT EXCEED .013.
- FOR ADDITIONAL CLOSEDOWN OF Ø Z, BUSHINGS GS3420-3* THRU GS3420-32* MAY BE USED. Ø Z SHALL BE FREE OF OBSTRUCTIONS. BUSHINGS ARE NOT SUPPLIED AND MUST BE ORDERED SEPARATELY.
- MATERIAL/FINISH:
CLAMP BODY & SADDLES - AL ALLOY/CADMIIUM PLATE, OLIVE DRAB OVER ELECTROLESS NICKEL (FINISH NOT FOR USE IN SPACE APPLICATION)
SLEEVE - AL ALLOY/GOLD IRIDIITE
SCREWS & WASHERS - CRES/PASSIVATE
GLAND - SILICONE/NA
RETAINING RING - BRASS SAE 70, HARD TEMPER ONLY/NA



THIS COPYRIGHTED DOCUMENT IS THE PROPERTY OF GLENRAIR, INC. AND IS FURNISHED ON THE CONDITION THAT IT IS NOT TO BE DISCLOSED, REPRODUCED, IN WHOLE OR IN PART, OR USED TO SOLICIT QUOTATIONS FROM COMPETITIVE SOURCES, OR USED FOR THE DESIGN OR CONSTRUCTION OF ANY EQUIPMENT, WITHOUT THE WRITTEN PERMISSION OF GLENRAIR, INC. THIS DOCUMENT IS VALID FOR THE ENTIRE TERM OF THE PATENT RIGHTS HEREIN HAS BEEN DEVELOPED AT GLENRAIR'S EXPENSE AND MAY BE USED FOR ENGINEERING EVALUATION AND INCORPORATION INTO TECHNICAL SPECIFICATIONS AND OTHER DOCUMENTS WHICH SPECIFY REQUIREMENTS OF PRODUCTS FROM GLENRAIR, INC.

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES. DIMENSIONS IN PARENTHESES ARE FOR REFERENCE ONLY.

FRACCTIONS ± 1/16
DECIMALS .XX ±.03 (0.8)
ANGLES .XX ±.015 (0.4)
TOLERANCES:
FRACTIONS ± 1/16
DECIMALS .XX ±.03 (0.8)
ANGLES .XX ±.015 (0.4)

DO NOT SCALE THIS DRAWING
SHEET NO.

DATE: 05/21/08

SCALE: N/A

WEIGHT: N/A

REV. 1

REV. 2

REV. 3

REV. 4

REV. 5

REV. 6

REV. 7

REV. 8

REV. 9

REV. 10

REV. 11

REV. 12

REV. 13

REV. 14

REV. 15

REV. 16

REV. 17

REV. 18

REV. 19

REV. 20

REV. 21

REV. 22

REV. 23

REV. 24

REV. 25

REV. 26

REV. 27

REV. 28

REV. 29

REV. 30

REV. 31

REV. 32

REV. 33

REV. 34

REV. 35

REV. 36

REV. 37

REV. 38

REV. 39

REV. 40

REV. 41

REV. 42

REV. 43

REV. 44

REV. 45

REV. 46

REV. 47

REV. 48

REV. 49

REV. 50

REV. 51

REV. 52

REV. 53

REV. 54

REV. 55

REV. 56

REV. 57

REV. 58

REV. 59

REV. 60

REV. 61

REV. 62

REV. 63

REV. 64

REV. 65

REV. 66

REV. 67

REV. 68

REV. 69

REV. 70

REV. 71

REV. 72

REV. 73

REV. 74

REV. 75

REV. 76

REV. 77

REV. 78

REV. 79

REV. 80

REV. 81

REV. 82

REV. 83

REV. 84

REV. 85

REV. 86

REV. 87

REV. 88

REV. 89

REV. 90

REV. 91

REV. 92

REV. 93

REV. 94

REV. 95

REV. 96

REV. 97

REV. 98

REV. 99

REV. 100

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Heat Shrink Cable Boots & End Caps](#) category:

Click to view products by [Glenair](#) manufacturer:

Other Similar products are found below :

[577159N001](#) [007758-000](#) [610368N003](#) [645494-000](#) [M85049/141-02HU](#) [M85049/141-03HU](#) [M85049/141-04HU](#) [687025-000](#) [705331-000](#)
[718446-000](#) [725666N001](#) [729257-000](#) [F21914-000](#) [F27131-000](#) [F85868-000](#) [770-006A103R](#) [770-006A304W1](#) [770-006A305W1](#) [770-](#)
[006A308W1](#) [770-011T303W1](#) [770-011T304W1](#) [770-020S702W1](#) [770-020S704W1](#) [806138-000](#) [806542N001](#) [807507-000](#) [808059-000](#)
[808296-000](#) [808362-000](#) [808828-000](#) [809125-000](#) [809130-000](#) [809218-000](#) [811218-000](#) [811288-000](#) [812014-000](#) [812047-000](#) [813166-000](#)
[813767N002](#) [814417-000](#) [819115N001](#) [819117N001](#) [823026-000](#) [823070-000](#) [825002-000](#) [841189N001](#) [861471-000](#) [866647-000](#) [937577-](#)
[000](#) [950764-000](#)