

Helaglass

Features & Benefits:

G6SE is a glass fibre braid lightly impregnated with silicone.

Electrical:

- Dielectric strength : 0.8kV

Physical-chemical:

- Good resistance to chemical atmospheres
- Good flexibility
- Fireproof

Application:

GSS is used for the insulation of wires in heating elements and other domestic appliances subject to high temperatures.

This flexible glass-fibre braided sleeving is impregnated with silicone and is especially suited for thermal protection in lighting applications.

Material Data:

Material: Glass fibre with silicone

Colour: White (WE)

Operating Temp: -60°C to +250°C Continuous, (peaks of +450°C)

Flammability: Self-extinguishing

Mftrs List No.	Dia (mm)	Length (L) Metres	Colour
GSS1	1.0	25	White
GSS1.5	1.5	25	White
GSS2	2.0	25	White
GSS2.5	2.5	25	White
GSS3	3.0	25	White
GSS4	4.0	25	White
GSS5	5.0	25	White
GSS6	6.0	25	White
GSS7	7.0	25	White
GSS8	8.0	25	White
GSS10	10.0	25	White

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Wire Identification](#) category:

Click to view products by [Hellermann](#) manufacturer:

Other Similar products are found below :

[CU6337-000](#) [CU6342-000](#) [FCA-410-12](#) [11631010](#) [1-1768037-1](#) [1-1768037-2](#) [1-1768050-0](#) [PXLK-VI](#) [Q62184-1](#) [A64304-000](#) [QMT221](#)
[HK032WE1NF038B](#) [1330-0519-10](#) [1395199-1](#) [1395200-1](#) [1395202-1](#) [DMVF050WE-300S6](#) [D-SCE-1K-2.4-50-4-CS7834](#) [1538738-1](#)
[E90935-000](#) [EC1238-000](#) [EC1465-000](#) [EC1855-000](#) [EC1859-000](#) [EC1863-000](#) [EC5415-000](#) [EC7277-000](#) [EC7352-000](#) [EC7603-000](#)
[EC7707-000](#) [EC7735-000](#) [EC7768-000](#) [EC7828-000](#) [EC7854-000](#) [EC7952-000](#) [EC8128-000](#) [1768037-8](#) [1768041-7](#) [NC-127191-10-9](#)
[HS048WE2NF038B](#) [C03232-000](#) [HTCM-SCE-14-4H-9](#) [HTMS-3/16-9](#) [HT-SCE-1/4-2.0-4](#) [HT-SCE-3/16-2.0-4](#) [HTTMS-1/2-1.50-9](#) [HTTMS-](#)
[CM-1/2-4H-9](#) [HX-SCE-19.0-50-9](#) [HX-SCE-6.4-50-4](#) [C25254-000](#)