

Housing screw connection - SACC-BP-M-M12/M15-7-THR SCO - 1413998

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Housing screw connection, PlugLink:M12-SPEEDCON, Rear mounting, M15 x 1

Why buy this product

- Easy device integration, thanks to mechanical port screw connections with threaded fastening
- Flexible PCB assembly: two-piece connectors for wave and THR soldering
- ☑ SPEEDCON fast locking system reduces cabling times



Key Commercial Data

Packing unit	20 STK
Minimum order quantity	20 STK
GTIN	4 055626 022680
GTIN	4055626022680
Weight per Piece (excluding packing)	10.740 g
Custom tariff number	79070000
Country of origin	Germany
Note	Made to Order (non-returnable)

Technical data

Ambient conditions

Ambient temperature (operation)	-25 °C 85 °C (Plug / socket)
	-40 °C 85 °C (without mechanical actuation)
Degree of protection	IP67 (correctly plugged in and locked)
General	
Note	The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using

12/22/2016 Page 1 / 3



Housing screw connection - SACC-BP-M-M12/M15-7-THR SCO - 1413998

Technical data

General

	a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.
Standards/regulations	M12 connector IEC 61076-2-101 In line with
Insertion/withdrawal cycles	> 100
Torque	1.5 Nm 2 Nm (Installation-side)
Mounting type	Rear mounting M15 x 1 Spacing between the top edge of the PCB and the back of the front plate: 7 mm

Material

Material, knurls	Zinc die-cast, nickel-plated
Material	Zinc die-cast (nickel-plated)
Sealing material	FKM (O-ring on housing)
Additional material specifications	Brass, nickel-plated (Locking nut)

Cable

Standards/specifications	M12 connector IEC 61076-2-101 In line with
--------------------------	--


Standards and Regulations


Standard designation	M12 connector
Standards/regulations	IEC 61076-2-101

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Drawings





Classifications

eCl@ss

eCl@ss 5.1	27143423
eCl@ss 6.0	27143423
eCl@ss 8.0	23100602

12/22/2016 Page 2 / 3



Housing screw connection - SACC-BP-M-M12/M15-7-THR SCO - 1413998

Classifications

eCl@ss

eCl@ss	
eCl@ss 9.0	23100602
ETIM	
ETIM 4.0	EC001855
ETIM 5.0	EC002350
ETIM 6.0	EC002350
UNSPSC	
UNSPSC 13.2	31171603
Approvals	
Approvals	
Approvals	
EAC	
Ex Approvals	
Approval details	
EAC	B.01742

Phoenix Contact 2016 © - all rights reserved http://www.phoenixcontact.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular Metric Connectors category:

Click to view products by Phoenix Contact manufacturer:

Other Similar products are found below :

 1424048
 1021212
 600X518037X
 6STD09SAM99B70X
 6STD15PCR99B70A
 8R4000A16M020
 1200910002
 1201150041
 1203580030

 1200700064
 1200700263
 1200700416
 1200730102
 1200770002
 1-2823588-2
 130203-0054
 1300140026
 1300150099
 1-3637-600-5205

 1545399
 1594331
 1600413
 1612606
 1612618
 1614660
 1A4000-348
 CA06EW24-10P-B-03
 21036836414
 2823064-1
 1610759
 A1642LK

 I1-T
 1R3006A20M005
 41-01016
 41-40017
 42-00006
 42-01015
 4-22281-1
 4-22284-9
 43-00002
 43-00113
 43-00130

 43-01028
 43-01034
 43-01090
 43-01203
 43-01209
 43-01335