

**T&B Catalog Number:** C10-8A 78621080344

**Description:** Non-Insulated Flag Terminal For Wire Range 12-10 Stud Size #8, Metallic

Status: Active




Table Product Line   029	WEB_USE	
-US Cutsheet PDF Catalog Link http://www-public.tnb.com/contractor/docs/stakon.pdf  Features - Flag terminals allow a 90 degree connection to the terminal block without bending the wire.  General -Insulation Type Non-Insulated -Terminal Series C Copper -Finish Electro -Tin Plated -Color Metallic -Vire Range 12-10 -Stud Size #8  Dimension Information -Stuck Thickness .04 -A (inches) .66 -B (inches) .31 -C (inches) .25 -M (inches) .48  Specifications -Temperature Rating 150°C -Flammability Rating UL 94 V-0  Tooling -Tool Charts Available on Website -Application Tools ERG4004 -Recommended Tool ERG4004 -Recommended Tool ERG4004 -Rackaging -T&B Order Multiple 50 -T&B Order Multiple 50 -Package in Units .250 -Package in Units .250 -Package Type Standard -T&B Sold in UOM Each -Atlemate Package Qty C52 -Application Support -Overview Available on Website -Wire Guide Tables Available on Website -Vertifications -Certifications -Certifications		020
Features		
Features - Flag terminals allow a 90 degree connection to the terminal block without bending the wire.  General -Insulation Type Non-Insulated -Terminal Series C -Material Copper -Finish Electro -Tin Plated -Color Metallic -Wire Range 12-10 -Stud Size #8  Dimension Information -Stock Thickness .04 -A (inches) .66 -B (inches) .31 -C (inches) .25 -M (inches) .48  Specifications -Temperature Rating 150°C -Flammability Rating UL 94 V-0  Tooling -Tool Charts Available on Website -Application Tools ERG4004 -Recommended Tool ERG4004 -Packaging -T&B Order Multiple 50 -T&B Inner Pack 50 -Package in Units 250 -Package in Units 250 -Package in Units 250 -Package Type Standard -T&B Weight Per UOM 0.4 lbs. per 100 -Alternate Package Qty C52 -Application Support -Overview Available on Website -Wire Guide Tables Available on Website -Verview Available on Website -Verview Available on Website -Verview Available on Website -Wire Guide Tables Available on Website	CC Cutoffoct P. Cutalog Link	
terminal block without bending the wire.  General  -Insulation Type Non-Insulated -Terminal Series C -Material Copper -Finish Electro -Tin Plated -Color Metallic -Wire Range 12-10 -Stud Size #8  Dimension Information -Stock Thickness .0.4 -A (inches) .66 -B (inches) .31 -C (inches) .25 -M (inches) .48  Specifications -Temperature Rating 150°C -Flammability Rating UL 94 V-0  Tooling -Tool Charts Available on Website -Application Tools ERG4004  Packaging -T&B Order Multiple 50 -T&B Order Multiple 50 -T&B Order Multiple 50 -Package in Units 250 -Package in Units 250 -Package Type Standard -T&B Sold in UOM Each -T&B Weight Per UOM 0.4 lbs. per 100 -Alternate Package Qty C52  Application Support -Vereview Available on Website -Wire Guide Tables Notavailable on Mylar Tape.  Certifications	Features	·
Insulation Type	-	Flag terminals allow a 90 degree connection to the
-Insulation Type		terminal block without bending the wire.
-Terminal Series         C           -Material         Copper           -Finish         Electro -Tin Plated           -Color         Metallic           -Wire Range         12-10           -Stud Size         #8           Dimension Information           -Stock Thickness         .04           -A (inches)         .66           -B (inches)         .31           -C (inches)         .25           -M (inches)         .48           Specifications           -Temperature Rating         150°C           -Flammability Rating         UL 94 V-0           Tooling         UL 94 V-0           Tool Charts         Available on Website           -Application Tools         ERG4004           -Recommended Tool         ERG4004           Packaging         -T&B Order Multiple         50           -Table Units         250           -Package in Units         250           -Package Type         Standard           -T&B Sold in UOM         Each           -T&B Weight Per UOM         0.4 lbs. per 100           -Alternate Package Qty         C52           Application Support         Available on Website	General	
-Material Copper -Finish Electro -Tin Plated -Color Metallic -Wire Range 12-10 -Stud Size #8  Dimension Information -Stock Thickness .04 -A (inches) .66 -B (inches) .31 -C (inches) .25 -M (inches) .48  Specifications -Temperature Rating 150°C -Flammability Rating UL 94 V-0  Tooling -Tool Charts Available on Website -Application Tools ERG4004  Packaging -T&B Order Multiple 50 -T&B Inner Pack 50 -Package in Units 250 -Package Type Standard -T&B Sold in UOM Each -T&B Weight Per UOM 0.4 lbs. per 100 -Alternate Package Qty C52  Application Support -Overview Available on Website -Wire Guide Tables - Not available on Website - Not available on Website	-Insulation Type	Non-Insulated
-Finish Electro -Tin Plated  -Color Metallic  -Wire Range 12-10  -Stud Size #8  Dimension Information  -Stock Thickness .04  -A (inches) .66  -B (inches) .31  -C (inches) .48  Specifications  -Temperature Rating 150°C  -Flammability Rating UL 94 V-0  Tooling  -Tool Charts Available on Website  -Application Tools ERG4004  -Recommended Tool ERG4004  -Packaging  -T&B Order Multiple 50  -Rab Inner Pack 50  -Package in Units 250  -Package Type Standard  -T&B Weight Per UOM 0.4 lbs. per 100  -Alternate Package Qty C52  Application Support  -Overview Available on Website  -Wire Guide Tables Available on Website  -Verriew Available on Website  -Vire Guide Tables Available on Website  -Votersiew -Vire Guide Tables Available on Mylar Tape.  Certifications	-Terminal Series	С
-Color Metallic  -Wire Range 12-10  -Stud Size #8  Dimension Information  -Stock Thickness .04  -A (inches) .66  -B (inches) .31  -C (inches) .25  -M (inches) .48  Specifications  -Temperature Rating 150°C  -Flammability Rating UL 94 V-0  Tooling  -Tool Charts Available on Website  -Application Tools ERG4004  Packaging  -T&B Order Multiple 50  -T&B Units 250  -Package in Units 250  -Package Type Standard  -T&B Sold in UOM Each  -T&B Weight Per UOM 0.4 lbs. per 100  -Alternate Package Qty C52  -Application Support  -Overview Available on Website  -Wire Guide Tables Available on Website  -Wire Guide Tables Available on Website  -Viere Guide Tables Available on Mylar Tape.  Certifications	-Material	Copper
-Wire Range 12-10 -Stud Size #8  Dimension Information -Stock Thickness .04 -A (inches) .66 -B (inches) .31 -C (inches) .25 -M (inches) .48  Specifications -Temperature Rating 150°C -Flammability Rating UL 94 V-0  Tooling -Tool Charts Available on Website -Application Tools ERG4004 -Recommended Tool ERG4004  Packaging -T&B Order Multiple 50 -T&B Inner Pack 50 -Package in Units 250 -Package in Units 250 -Package in UnoM Each -T&B Sold in UOM Each -T&B Weight Per UOM 0.4 lbs. per 100 -Alternate Package Qty C52 -Application Support -Overview Available on Website -Wire Guide Tables Available on Website -Wire Guide Tables Available on Mylar Tape.  Certifications	-Finish	Electro -Tin Plated
-Stud Size #8  Dimension Information -Stock Thickness .04 -A (inches) .66 -B (inches) .31 -C (inches) .25 -M (inches) .48  Specifications -Temperature Rating .150°C -Flammability Rating UL 94 V-0  Tooling -Tool Charts Available on Website -Application Tools ERG4004  Packaging -T&B Order Multiple .50 -T&B Inner Pack .50 -Package in Units .250 -Package Type .Standard -T&B Weight Per UOM .4 lbs. per 100 -Alternate Package Qty .52  Application Support -Overview Available on Website -Wire Guide Tables Available on Website -Vier Guide Tables Available on Mylar Tape.  Certifications	-Color	Metallic
Dimension Information           -Stock Thickness         .04           -A (inches)         .66           -B (inches)         .31           -C (inches)         .25           -M (inches)         .48           Specifications         .48           -Temperature Rating         150°C           -Flammability Rating         UL 94 V-0           Tooling         .700 Charts           -Application Tools         ERG4004           -Recommended Tool         ERG4004           Packaging         .78 B Order Multiple           -TaB Inner Pack         50           -Package in Units         250           -Package Type         Standard           -TaB Sold in UOM         Each           -TaB Weight Per UOM         0.4 lbs. per 100           -Alternate Package Qty         C52           Application Support         Overview           -Wire Guide Tables         Available on Website           Notes         Not available on Mylar Tape.           Certifications	-Wire Range	12-10
-Stock Thickness .04 -A (inches) .66 -B (inches) .31 -C (inches) .25 -M (inches) .48  Specifications -Temperature Rating .50°C -Flammability Rating .0L 94 V-0  Tooling -Tool Charts .4vailable on Website -Application Tools .ERG4004 -Recommended Tool .ERG4004  Packaging -T&B Order Multiple .50 -T&B Inner Pack .50 -Package in Units .250 -Package Type .Standard -T&B Sold in UOM .Each -T&B Weight Per UOM .0.4 lbs. per 100 -Alternate Package Qty .C52  Application Support -Overview .Available on Website  Notes - Not available on Mylar Tape.  Certifications	-Stud Size	#8
-A (inches) .66 -B (inches) .31 -C (inches) .25 -M (inches) .48  Specifications -Temperature Rating .150°C -Flammability Rating .UL 94 V-0  Tooling -Tool Charts .Available on Website -Application Tools .ERG4004 -Recommended Tool .ERG4004  Packaging -T&B Order Multiple .50 -T&B Inner Pack .50 -Package in Units .250 -Package Type .Standard -T&B Sold in UOM .Each -T&B Weight Per UOM .4 lbs. per 100 -Alternate Package Qty .C52  Application Support -Overview .Available on Website  Notes - Not available on Mylar Tape.  Certifications	Dimension Information	
-B (inches) .31 -C (inches) .25 -M (inches) .48  Specifications -Temperature Rating 150°C -Flammability Rating UL 94 V-0  Tooling -Tool Charts Available on Website -Application Tools ERG4004 -Recommended Tool ERG4004  Packaging -T&B Order Multiple 50 -T&B Inner Pack 50 -Package in Units 250 -Package Type Standard -T&B Sold in UOM Each -T&B Weight Per UOM 0.4 lbs. per 100 -Alternate Package Qty C52  Application Support -Overview Available on Website  Not available on Mylar Tape.  Certifications	-Stock Thickness	.04
-C (inches) .25 -M (inches) .48  Specifications -Temperature Rating 150°C -Flammability Rating UL 94 V-0  Tooling -Tool Charts Available on Website -Application Tools ERG4004 -Recommended Tool ERG4004  Packaging -T&B Order Multiple 50 -T&B Inner Pack 50 -Package in Units 250 -Package Type Standard -T&B Sold in UOM Each -T&B Weight Per UOM 0.4 lbs. per 100 -Alternate Package Qty C52  Application Support -Overview Available on Website -Wire Guide Tables Available on Mylar Tape.  Certifications	-A (inches)	.66
-M (inches) .48  Specifications -Temperature Rating 150°C -Flammability Rating UL 94 V-0  Tooling -Tool Charts Available on Website -Application Tools ERG4004 -Recommended Tool ERG4004  Packaging -T&B Order Multiple 50 -T&B Inner Pack 50 -Package in Units 250 -Package Type Standard -T&B Sold in UOM Each -T&B Weight Per UOM 0.4 lbs. per 100 -Alternate Package Qty C52  Application Support -Overview Available on Website  Notes - Not available on Mylar Tape.  Certifications	-B (inches)	.31
Specifications -Temperature Rating 150°C -Flammability Rating UL 94 V-0  Tooling -Tool Charts Available on Website -Application Tools ERG4004 -Recommended Tool ERG4004  Packaging -T&B Order Multiple 50 -T&B Inner Pack 50 -Package in Units 250 -Package Type Standard -T&B Sold in UOM Each -T&B Weight Per UOM 0.4 lbs. per 100 -Alternate Package Qty C52  Application Support -Overview Available on Website  Notes - Not available on Mylar Tape.  Certifications	-C (inches)	.25
-Temperature Rating 150°C -Flammability Rating UL 94 V-0  Tooling -Tool Charts Available on Website -Application Tools ERG4004 -Recommended Tool ERG4004  Packaging -T&B Order Multiple 50 -T&B Inner Pack 50 -Package in Units 250 -Package Type Standard -T&B Sold in UOM Each -T&B Weight Per UOM 0.4 lbs. per 100 -Alternate Package Qty C52  Application Support -Overview Available on Website -Wire Guide Tables Available on Mylar Tape.  Certifications	-M (inches)	.48
-Flammability Rating UL 94 V-0  Tooling -Tool Charts Available on Website -Application Tools ERG4004 -Recommended Tool ERG4004  Packaging -T&B Order Multiple 50 -T&B Inner Pack 50 -Package in Units 250 -Package Type Standard -T&B Sold in UOM Each -T&B Weight Per UOM 0.4 lbs. per 100 -Alternate Package Qty C52  Application Support -Overview Available on Website -Wire Guide Tables Available on Mylar Tape.  Certifications	Specifications	
Tool Charts Available on Website  -Application Tools ERG4004 -Recommended Tool ERG4004  Packaging -T&B Order Multiple 50 -T&B Inner Pack 50 -Package in Units 250 -Package Type Standard -T&B Sold in UOM Each -T&B Weight Per UOM 0.4 lbs. per 100 -Alternate Package Qty C52  Application Support -Overview Available on Website -Wire Guide Tables Available on Mylar Tape.  Certifications	-Temperature Rating	150°C
-Tool Charts Available on Website  -Application Tools ERG4004  -Recommended Tool ERG4004  Packaging  -T&B Order Multiple 50  -T&B Inner Pack 50  -Package in Units 250  -Package Type Standard  -T&B Sold in UOM Each  -T&B Weight Per UOM 0.4 lbs. per 100  -Alternate Package Qty C52  Application Support  -Overview Available on Website  -Wire Guide Tables Available on Mylar Tape.  Certifications	-Flammability Rating	UL 94 V-0
-Application Tools ERG4004 -Recommended Tool ERG4004  Packaging -T&B Order Multiple 50 -T&B Inner Pack 50 -Package in Units 250 -Package Type Standard -T&B Sold in UOM Each -T&B Weight Per UOM 0.4 lbs. per 100 -Alternate Package Qty C52  Application Support -Overview Available on Website -Wire Guide Tables Available on Mylar Tape.  Certifications	Tooling	
-Recommended Tool ERG4004  Packaging  -T&B Order Multiple 50  -T&B Inner Pack 50  -Package in Units 250  -Package Type Standard  -T&B Sold in UOM Each  -T&B Weight Per UOM 0.4 lbs. per 100  -Alternate Package Qty C52  Application Support  -Overview Available on Website  -Wire Guide Tables Available on Mylar Tape.  Certifications	-Tool Charts	Available on Website
Packaging -T&B Order Multiple 50 -T&B Inner Pack 50 -Package in Units 250 -Package Type Standard -T&B Sold in UOM Each -T&B Weight Per UOM 0.4 lbs. per 100 -Alternate Package Qty C52 Application Support -Overview Available on Website -Wire Guide Tables Available on Mylar Tape.  Certifications	-Application Tools	ERG4004
-T&B Order Multiple 50  -T&B Inner Pack 50  -Package in Units 250  -Package Type Standard  -T&B Sold in UOM Each  -T&B Weight Per UOM 0.4 lbs. per 100  -Alternate Package Qty C52  Application Support  -Overview Available on Website  -Wire Guide Tables Available on Website  Notes  Not available on Mylar Tape.  Certifications	-Recommended Tool	ERG4004
-T&B Inner Pack 50 -Package in Units 250 -Package Type Standard -T&B Sold in UOM Each -T&B Weight Per UOM 0.4 lbs. per 100 -Alternate Package Qty C52  Application Support -Overview Available on Website -Wire Guide Tables Available on Website  Notes - Not available on Mylar Tape.  Certifications	Packaging	
-Package in Units 250 -Package Type Standard -T&B Sold in UOM Each -T&B Weight Per UOM 0.4 lbs. per 100 -Alternate Package Qty C52  Application Support -Overview Available on Website -Wire Guide Tables Available on Website  Notes - Not available on Mylar Tape.  Certifications	-T&B Order Multiple	50
-Package Type Standard  -T&B Sold in UOM Each  -T&B Weight Per UOM 0.4 lbs. per 100  -Alternate Package Qty C52  Application Support  -Overview Available on Website  -Wire Guide Tables Available on Website  Notes  Not available on Mylar Tape.  Certifications	-T&B Inner Pack	50
-T&B Sold in UOM Each -T&B Weight Per UOM 0.4 lbs. per 100 -Alternate Package Qty C52 Application Support -Overview Available on Website -Wire Guide Tables Available on Website  Notes - Not available on Mylar Tape. Certifications	-Package in Units	250
-T&B Weight Per UOM 0.4 lbs. per 100 -Alternate Package Qty C52  Application Support -Overview Available on Website -Wire Guide Tables Available on Website  Notes - Not available on Mylar Tape.  Certifications	-Package Type	Standard
-Alternate Package Qty  Application Support  -Overview Available on Website  -Wire Guide Tables Available on Website  Notes  Not available on Mylar Tape.  Certifications	-T&B Sold in UOM	Each
Application Support  -Overview Available on Website  -Wire Guide Tables Available on Website  Notes  Not available on Mylar Tape.  Certifications	-T&B Weight Per UOM	0.4 lbs. per 100
-Overview Available on Website -Wire Guide Tables Available on Website  Notes - Not available on Mylar Tape.  Certifications	• ,	C52
-Wire Guide Tables Available on Website  Notes - Not available on Mylar Tape.  Certifications	Application Support	
Notes - Not available on Mylar Tape.  Certifications		
- Not available on Mylar Tape.  Certifications		Available on Website
Certifications	Notes	
	-	Not available on Mylar Tape.
-RoHS Compliance Yes		
	-RoHS Compliance	Yes



## U.S. Electrical On-line Catalog

## Certifications





File Nbr: E9809

For further technical assistance, please contact us...

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125

Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321

Email:techsupport@tnb.com

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for abb manufacturer:

Other Similar products are found below:

TV10-516R 017667013 RF727 2CMA100178R1000 5SDD 92Z0401 ESV14-BS EZS-21-250 F204AC-40/0.03 F362-25/0.03

GJL1211001R0011 GJL1211201R8000 GJL1211501R8000 GJL1213001R0017 GJL1213001R0101 GJL1311001R0101 GJL1311001R8010

GJL1311201R0001 GJL1313001R0011 GJL1313001R0101 GJL1317201R0001 A40-30-10-84 AF09-30-01-11 AF460-30-11-68 1455 B14
250 EF45-30 ERG297 HSC2-20 ISAM201904R1001 ISAM350000R1003 ISAZ721201R1009 ISAZ721201R1014 ISAZ721201R1025

ISDA057197R1 ISFA611101R1002 ISFA611130R1103 ISFA611131R1101 ISFA611143R1101 ISFA611202R1108 ISFA611203R1108

ISFA611215R1001 ISFA611216R1108 ISFA611285R1002 ISFA611702R6006 ISFA616162R1025 ISFA619100R3015

ISVR730020R0200 IPC4111 OS30FACC12 OS60GJ03