

▶ **PVC-coated series****PVC model****149.Y**

- Length 155 mm.
- $\Delta\Delta$  : 25 g.

**Gripping model****146.1Y**

- $\varnothing$  2.5 to 4 mm in-line grip.
- Length 140 mm.
- $\Delta\Delta$  : 25 g.

**PVC model****152.Y**


- Length 150 mm.
- $\Delta\Delta$  : 25 g.

**Gripping model****146.2Y**

- $\varnothing$  2.5 to 4 mm right-angle grip.
- Length 140 mm.
- $\Delta\Delta$  : 25 g.

▶ **High-precision series****141 Straight models**

- Non-serrated easy-flex snipe tips.

	Length mm	$\Delta\Delta$ g
<b>141.11</b>	110	13
<b>141.12</b>	120	14

**Straight shouldered model****142.1**

- Non-serrated easy-flex snipe tips.
- Length 112 mm.
- $\Delta\Delta$  : 13 g.

**Offset model at 15****142.2**

- Non-serrated easy-flex snipe tips.
- Length 117 mm.
- $\Delta\Delta$  : 15 g.

**Curved model****143**

- Non-serrated easy-flex snipe tips.
- Length 114 mm.
- $\Delta\Delta$  : 14 g.

**Ultra-flat straight model****144**

- Finely contoured, non-serrated tips.
- Length 120 mm.
- $\Delta\Delta$  : 17 g.

**Splayed straight model****145**

- Non-serrated tips.
- Tip width 7 mm.
- Length 123 mm.
- $\Delta\Delta$  : 14 g.



## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [facom](#) manufacturer:*

Other Similar products are found below :

[92A.5,5](#) [ARB.5.5X40](#) [AMR](#) [ANXR10X75](#) [AEF.J6](#) [AEF.J1](#) [EH.107](#) [EH.103](#) [256.2.5](#) [MT.J3](#) [986058](#) [75.10](#) [PB.MTJ5](#) [84E.J1](#) [455B](#) [440.19](#)  
[44.6X7](#) [440.6](#) [440.21](#) [R.306-25D](#) [R.217](#) [R.5](#) [J.13LA](#) [431.LE](#) [405.10](#) [425.E](#) [405.12E](#) [R.216](#) [601](#) [AEF.1,5X35](#) [AEFP.00X35](#) [AEX.J2](#)  
[AEX.9X75](#) [AEX.7X35](#) [251A.2.5](#) [HB.2B](#) [440.20](#) [435.E](#) [432.LMT](#) [44.12X13](#) [440.5H](#) [440.22](#) [R.304DA](#) [427.MT](#) [416.PMT](#) [113A.6C](#)  
[113A.10C](#) [251A.3](#) [89S.JP8](#) [AEF.1,8X35](#)