3M Low Tack - Paper Masking Tape 1104

Product Data Sheet

Date: January 2012 Supersedes: Dec 1995

Product Description	3M Paper Masking Tape 1104 is a chamois coloured crepe paper coated with a low tack rubber resin adhesive.
Key Features	 Ideal for use on sensitive materials such as anodized metals e.g aluminium, titanium, treated woods or other critical surfaces. Crepe paper backing for conformability that will maintain integrity when formed around corners. Backing saturated for easy tear – resists slivering yet hand tearable. Rubber adhesive with instant adhesion. Good holding power that resists lifting or curling and helps reduce rework. Special backsize treatment controls unwind and helps reduce waste. Designed for indoor use only. Tape should not be subjected to outdoor exposure or prolonged periods of sunlight as product may become very difficult to remove.

Physical Properties

Adhesive Type	Rubber
Backing Type	Crepe Paper
Tape Colour	Chamois
Thickness AFERA 5006	0.147 mm

Performance Characteristics	Adhesion to Stainless Steel AFERA 5001	6.0 N/25mm
	Tensile Strength AFERA 5004	80 N/25mm
	Elongation at break	10%
	Temperature Range	135°C for 1 hour

	Date: 08.2004	
Storage	Store under normal conditions of 70`F (21`C) and 50% R.H. in the original carton.	
Shelf Life	3M 1104 has a shelf life of 12 months from date of manufacture when stored in the original carton at 21°C (70°F) & 50 % Relative Humidity	
Precautionary Information	Refer to product label and Material Safety Data Sheet for health an safety information before using the product. For information please contact your local 3M Office. www.3M.com	
Important Notice	All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method or application. All questions of liability relating to this product are governed by the terms of the sale subject, where applicable, to the prevailing law	

specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications. This is because 3M cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations

3M is a trademark the 3M Company.

3M United Kingdom PLC 3M House, 28 Great Jackson Street, Manchester, M15 4PA	Product Information : Tel 0870 60 800 50 Fax 0870 60 700 99	3M Ireland Limited The Iveagh Building The Park, Carrickmines Dublin 18, Ireland	Customer Service : Tel (01) 280 3555 Fax (01) 280 3509
--	---	--	--

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for 3m manufacturer:

Other Similar products are found below :

SC401U 98-0003-3071-6 80-0012-6467-2 00-054007-70220-7 00-054007-34717-0 5952-3/4"x15yds 021200-40230 6840-2X50-GRAY 6A11-A0121-007.0-0 701-W 7993MP-2CIRCLE-100 FDV14-187C FE-5100-5126-4 FE-5100-5273-4 FE-5100-5492-0 8124/14 812510-100 8125/17 813216 8204-3LFM 8425-8 MNG14BCX FP301-1-6"-Clear FV14-6C 920102-01-25-R 927739-40 929835-01-28-RK 929974-01-40-R 951240-2520-AR-PR 960X/980X 98-0003-3075-7 HF365/16SF HF36564-100 HF625/26-30 1/2-5-4492W 1/2-5-5430 1/2-5-850S 1/2-5-3431 12X12-6-4056B 12X12-6-433 12X12-6-4930 1311 13-500-NB 14526-EZ5B-300-02C 1-4-4658F 14520-EZAB-300-0EC DSTK9013-3420 DSTK9015-3402 14T26-SZLB-200-0LC 14T50-SZWB-100-0NC