



*a Leiterplattenlayout
 printed circuit board layout
 modèle de la carte imprimée

Bestellbezeichnung Designation Désignation	Farbe Color Couleur	Polzahl Poles Pôles	Verpackungseinheit Package unit Unité d'emballage
BTOR 1 GELB	gelb yellow jaune	2	200
BTOR 1 ROT	rot red rouge	2	200
BTOR 1 SCHWARZ	schwarz black noir	2	200
BTOR 1 WEISS	weiß white blanc	2	200

Verpackung: lose im Karton oder Kunststoffbeutel
 Packaging: in bulk in a cardboard box or a plastic bag
 Emballage: en vrac dans un carton ou sachet en plastique

BTOR 1

RCA-Einbaukupplung nach JEITA RC-5231, stehende Ausführung, für Leiterplatten

1. Temperaturbereich	-20 °C/+70 °C
2. Werkstoffe	
Kontaktträger	PBT GF, V0 nach UL 94
Innerer Kontakt	CuZn, unterkupfert und verzinkt
Äußerer Kontakt	CuZn, unterkupfert und vernickelt
3. Mechanische Daten	
Steckkraft	≤ 30 N
Ziehkraft	1–15 N
Steckzyklen	≥ 5000
Kontaktierung mit	RCA-Steckern STO, XSTO
4. Elektrische Daten	
Durchgangswiderstand	≤ 30 mΩ
Bemessungsstrom	2 A
Bemessungsspannung	34 V AC/DC
Prüfspannung	500 V/60 s
Isolationswiderstand	≥ 10 ⁸ Ω

BTOR 1

RCA chassis socket acc. to JEITA RC-5231, upright version, for printed circuit boards

1. Temperature range	-20 °C/+70 °C
2. Materials	
Body	PBT GF, V0 according to UL 94
Inner contact	CuZn, pre-coppered and tinned
Outer contact	CuZn, pre-coppered and nickeled
3. Mechanical data	
Insertion force	≤ 30 N
Withdrawal force	1–15 N
Mating cycles	≥ 5000
Mating with	RCA plugs STO, XSTO
4. Electrical data	
Contact resistance	≤ 30 mΩ
Rated current	2 A
Rated voltage	34 V AC/DC
Test voltage	500 V/60 s
Insulation resistance	≥ 10 ⁸ Ω

BTOR 1

Embase femelle RCA suivant JEITA RC-5231, version droite, pour cartes imprimées

1. Température d'utilisation	-20 °C/+70 °C
2. Matériaux	
Corps isolant	PBT GF, V0 suivant UL 94
Contact intérieur	CuZn, sous-cuivré et étamé
Contact extérieur	CuZn, sous-cuivré et nickelé
3. Caractéristiques mécaniques	
Force d'insertion	≤ 30 N
Force de séparation	1–15 N
Nombre de manœuvres	≥ 5000
Raccordement avec	connecteurs mâles RCA STO, XSTO
4. Caractéristiques électriques	
Résistance de contact	≤ 30 mΩ
Courant assigné	2 A
Tension assignée	34 V AC/DC
Tension d'essai	500 V/60 s
Résistance d'isolement	≥ 10 ⁸ Ω

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [lumberg](#) manufacturer:

Other Similar products are found below :

[RK20-603/5M](#) [ASBSM 10/LED 3](#) [ASBS-R 8/LED 5-4](#) [ASBSV 8 5](#) [BTO 1 V ROT](#) [BTOR 1 SCHWARZ](#) [18315 0976 PMC 151](#) [KRE8](#) [SBS](#)
[4/LED 3](#) [SFV 80](#) [RK30/2M](#) [RKWT 4-07/5M](#) [ASBS-R 4 5-4](#) [ASBS-R 4/LED 5-4](#) [BTO 1 ROT](#) [BTO 1 SCHWARZ](#) [BTO 1 V SCHWARZ](#)
[BTOR 1 GELB](#) [BTOR 1 WEISS](#) [KB3](#) [KRES10](#) [KRESS8](#) [KS8](#) [KRM 07](#) [2480 01](#) [0103 03](#) [WKV 81](#) [RK 30-738/20F](#) [RKMV 4-225/10 M](#)
[RKT 5-644/2M](#) [RKT 4-679/5M](#) [HZ30](#) [ASBS 2 M12-S2326](#) [1614 16](#) [0985 706 100/10M](#) [RST 4-RKWT 4-602/1M](#) [WKV50](#) [RST 4-633/2M](#)
[RST 4-RKWT 4-602/3M](#) [RS-TU](#) [WSV 30](#) [0986 EMC 102](#) [0250 03](#) [RKWT 5-612/5M](#) [0980 ESL 393-121](#) [RST 5L-RKT 5L-949/5 M](#) [ASBM](#)
[6/LED 3-344/5 M](#) [RKT 4-646/2M](#) [RKHL 8/S 5,5](#) [0985 YM57530 100/20M](#)