

Digital Multimeter



Features:

- 3 ¾ digit LCD (63 mm × 31 mm), 5999 count
- Auto / manual ranging selector
- Display back light
- Over moulded cases
- Diode, continuity buzzer and data hold
- Capacitance measurement
- Temperature measurement
- Frequency measurement
- RS-232 PC interface
- 1-year warranty
- Meets IEC 1010, 1,000 V CAT II, 600 V CAT III
- CE compliant
- Fused 10 A range
- RS-232C
- Relative Mode
- Full Icon display
- Sleep mode
- Low battery display
- Input impedance for DCV : approximately 10 MΩ
- Power : 9 V battery (6F22) included
- Weight : Approximately 312 g
- Size : 177 mm × 73.5 mm × 35 mm
- Includes : Test leads, manual, point contact temperature probe, test clip, RS-232C cable and software

Function	Range	Accuracy
DC Voltage	600 mV, 6 V, 60 V, 600 V, 1,000 V	± (0.5% +3)
AC Voltage	600 mV, 6 V, 60 V, 600 V, 1,000 V	± (1% +2)
DC Current	60 mA, 600 mA, 10 A	± (1.2% +3)
AC Current	60 mA, 600 mA, 10 A	± (2% +5)
Resistance	600 Ω, 6 kΩ, 600 kΩ, 6 MΩ, 60 MΩ	± (1% +2)
Capacitance	6 nF, 60 nF, 600 nF, 6 μF, 60 μF, 600 μF, 6 mF	± (4% +3)
Frequency	6 KHz, 60 KHz, 600 KHz, 6 MHz, 60 MHz	± (0.05% +3)
Temperature °C	-40°C to 1,000°C	± (1% +3)

Part Number Table

Description	Part Number
Multimeter, Digital	72-7750

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. TENMA™ is the registered trademark of the Group. © Premier Farnell plc 2012.



Bags

DMT-1CC

Number 07.0540

Soft carrying bags,

of soft artificial leather with wrist strap and inner lining, for digital and analog multimeters.

- DMT-1CC inside dim.: 100x150x35mm
- DMT-2CC inside dim.: 100x170x35mm
- DMT-4CC inside dim.: 110x190x50mm



Technical Facts Bags

Inside dimensions

100x150x35mm

X-ON Electronics

Authorized Distributor

Click to view similar products for [Tenma manufacturer](#).

Other Similar products are found below :

[BEBKQRT](#) [7210160727770A](#) [722630](#) [76090](#) [76097](#) [76300](#) [76350](#) [761444](#) [76020](#) [21685](#)
[7213300](#) [7213768](#) [7214058](#) [7214316](#) [7214320](#) [7214322](#) [ST5C](#) [76270](#) [BECKKRT](#)
[BECKMRT](#) [7210179727770A](#) [727635](#) [76082](#) [761662](#) [76021](#)