



DRAWING

- 1.CABLE:UL2919,28AWG 3C MINI COAX AND 8C(28AWG)
SHIELD:AL/MY COVERAGE+DRAIN WIRE+BRAID
JACKET:PVC WITH EMBOSHING,COMPLIANCE ROHS,COLOR:BLACK,Ø.D:8.0mm±0.2mm
- 2.CONNECTOR:1 PCS HDD15 PIN MALE SOLDER TYPE CONNECTOR
INSULATOR:P.B.T.+GLASS FIBER,COLOR:BLUE
SHELL:NICKEL PLATED
- 3.CONNECTOR:1 PCS HDD15 PIN FEMALE SOLDER TYPE CONNECTOR
INSULATOR:P.B.T.+GLASS FIBER,COLOR:BLUE
SHELL:NICKEL PLATED
- 4.HOOD:PVC MOLDED TYPE WITH COPPER FOIL SHIELDED ON INNER
MOLD AND SOLDERED 360° AROUND ON ALL SEAMS
INJECTION OUTER MOLD WITH THUMB SCREW#4-57UNC
COLOR:BLACK,COMPLIANCE ROHS
- 5.2 PCS FERRITE CORE COLOR:BLACK
- 6.Fulfill ROHS Guideline
- 7.ELECTRONIC TEST: 100% OPEN SHORT+MISS WIRE TEST

HDD15PIN PLUG(P1)	WIRE	HDD15PIN JACK(J1)
1	---	1
6	---	6
2	---	2
7	---	7
3	---	3
8	---	8
4	---	4
5	---	5
10	---	10
11	---	11
12	---	12
13	---	13
14	---	14
15	---	15
SHELL	BRAID+D.W	SHELL

RED COND.
RED SHIELD.
GREEN COND.
GREEN SHIELD
BLUE COND.
BLUE SHIELD.

PART NO	C-15WGF/1.8	SHEET NO	1	THIRD ANGLE PROJECTION				
TITLE	HDD15 PIN PLUG TO HDD15 PIN JACK BLACK COLOR,L:1.8M					SCALE	N.T.S	DRAWN BY & DATE
						SIZE	A4	CHECKED BY & DATE
						UNIT		APPROVED BY & DATE
DWN NO	D-C-15WGF/1.8			<input checked="" type="checkbox"/> mm	<input type="checkbox"/> INCH			