

## TISAGLASS GAU1 SBS

-30°C to +155°C

### CHARACTERISTICS

#### Electrical

- Dielectric strength : about 0.8kV.

#### Physical-chemical

- Continuous working temperatures : -30°C to +155°C
- Peaks at +200°C
- Good resistance to oils and usual chemical atmospheres
- Compatible with most class F impregnation varnishes
- Very high flexibility

### PRODUCTS

- Standard colour : light brown (natural)
- Other colours on request : red, green, black, blue, yellow, grey

### PACKAGING

- Diameter 0.5 to 4.5mm : 200m rolls
- Diameter 5 to 12mm :100m rolls
- Diameter 14 to 20mm : 50m rolls
- Diameter 25 and 30mm : 25m rolls

### OPTIONS

- Others colours including marking by spiral tracers : consult us
- Sleeving supplied in cut lengths : consult us

### HANDLING

Glass fibre material as dust or broken particles provides skin irritation. The use of barrier creams on exposed areas will minimise the risk of skin irritation

**Polyurethane-impregnated braided fibreglass sleeving**

### STANDARDS

- NFC 93-941
- IEC 684-1 EN 60684-1 and IEC 684-2
- IEC 684-3 part 609 (pending standard)
- DIN 40620

### APPLICATIONS

- Internal cabling for class B and F static and rotating machines (motors, alternators)

### INNER DIAMETER

Nominal value mm	Tolerance mm	Nominal wall thickness mm	Approx. Linear weight Kg/km
0.5	+/- 0.15	0.15	0.95
1	+/- 0.20	0.25	2.10
1.5	+/- 0.20	0.25	2.80
2	+/- 0.20	0.25	3.35
2.5	+/- 0.20	0.25	4.10
3	+/- 0.20	0.25	4.85
3.5	+/- 0.25	0.25	5.30
4	+/- 0.25	0.25	5.90
4.5	+/- 0.30	0.25	7.80
5	+/- 0.30	0.25	8.20
6	+/- 0.30	0.30	11.9
7	+/- 0.30	0.30	12.4
8	+/- 0.30	0.30	14.0
9	+/- 0.50	0.30	15.1
10	+/- 0.50	0.35	20.4
12	+/- 0.50	0.40	31.8
14	+/- 0.50	0.50	45.0
16	+/- 1.00	0.60	59.0
18	+/- 1.00	0.60	73.0
20	+/- 1.00	0.60	85.3
25	+/- 1.50	0.80	145
30	+/- 2.00	0.80	160

Standards : our products pass all or part of the requirements for the above-mentioned standards - consult-us

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Wire Identification category](#):*

*Click to view products by [Hellermann manufacturer](#):*

Other Similar products are found below :

[CU6337-000](#) [CU6342-000](#) [FCA-410-12](#) [11631010](#) [1-1768037-1](#) [1-1768037-2](#) [1-1768050-0](#) [PXLK-VI](#) [Q62184-1](#) [A64304-000](#) [QMT221](#)  
[HK032WE1NF038B](#) [1330-0519-10](#) [1395199-1](#) [1395200-1](#) [1395202-1](#) [DMVF050WE-300S6](#) [D-SCE-1K-2.4-50-4-CS7834](#) [1538738-1](#)  
[E90935-000](#) [EC1238-000](#) [EC1465-000](#) [EC1855-000](#) [EC1859-000](#) [EC1863-000](#) [EC5415-000](#) [EC7277-000](#) [EC7352-000](#) [EC7603-000](#)  
[EC7707-000](#) [EC7735-000](#) [EC7768-000](#) [EC7828-000](#) [EC7854-000](#) [EC7952-000](#) [EC8128-000](#) [1768037-8](#) [1768041-7](#) [NC-127191-10-9](#)  
[HS048WE2NF038B](#) [C03232-000](#) [HTCM-SCE-14-4H-9](#) [HTMS-3/16-9](#) [HT-SCE-1/4-2.0-4](#) [HT-SCE-3/16-2.0-4](#) [HTTMS-1/2-1.50-9](#) [HTTMS-](#)  
[CM-1/2-4H-9](#) [HX-SCE-19.0-50-9](#) [HX-SCE-6.4-50-4](#) [C25254-000](#)