



## ■ Features

- (1) High attenuation effect against high voltage pulse noise by amorphous core.
- (2) Block terminal with cover  
Simple wire connection  
High safety by cover.

## ■ Safety standard


UL1283, CSA Std. C22. 2 No. 8  
VDE0565 Teil. 3, Teil 3A2  
(VDE0565 will transfer to EN133200 )  
on and after July 23, 2003.

## ■ Specifications


Item	Model	MYB-1206-33	MYB-1210-33	MYB-1220-33	MYB-1230-33
1	Rated voltage (AC, DC)	250V			
2	Rated current (AC, DC) (Note)	6A	10A	20A	30A
3	Test voltage (terminal to case, AC 1 minute)	2500V (25°C, 70% RH)			
4	Isolation resistance (terminal to case, 500VDC)	100MΩ min. (25°C, 70% RH)			
5	Leakage current	125V, 60Hz	0.25mA max.		
		250V, 60Hz	0.5mA max.		
6	DC resistance	0.1Ω max.	0.05Ω max.	0.02Ω max.	0.01Ω max.
7	Temperature rise	30°C max.			
8	Operating temperature	-25 ~ +85°C			
9	Operating humidity	30% ~ 90% RH (No dewdrop)			
10	Storage temperature	-30 ~ +85°C			
11	Storage humidity	10% ~ 95% RH (No dewdrop)			
12	Vibration	Sweep: 10 ~ 55 ~ 10Hz (for 1 minute), Amplitude: 1.5mm X, Y and Z axes for 2 hours			
13	Safety standard	Approved by UL1283, CSA C22.2 No. 8 (C-UL) and VDE0565 Teil3, Teil3A2			
14	Weight (typ)	210g	260g	450g	510g

(Note) : Value at Ta ≤ 50°C. Refer to the derating curve shown below at Ta > 50°C.

## ■ Circuit



## ■ Derating




● Request customer specification for further details of specifications, outline, characteristics, etc.  
Read the instruction manual before usage.  
● Contact us about delivery before ordering.

# MYB-SERIES


■ MYB-1206-33

■ MYB-1210-33




Models	A	B	C	D
MYB-1206-33	108	75	90	26
MYB-1210-33	118	85	100	30

■ MYB-1220-33



■ MYB-1230-33



Case: Metal


(Unit: mm)

Noise Filter


## CHARACTERISTICS

### ■ Typical Insertion Loss


**MYB-1206-33**




**MYB-1210-33**




**MYB-1220-33**



**MYB-1230-33**



# MYB (50/70/90A)-SERIES



## ■ Features

- (1) High attenuation effect against high voltage pulse noise
- (2) Compact and low profile (H = 65mm)
- (3) Leakage current: 1mA max. (250V, 60Hz)

## ■ Safety standard


- (1) MYB-1250-33, MYB-1290-33  
Conforms to UL safety standard (UL1283)  
Conforms to CSA safety standard (CSA Std. C22. 2 No. 8)
- (2) MYB-1270-33  
UL1283, CSA Std. C22. 2 No. 8

## ■ Specifications


Item	Model	MYB-1250-33	MYB-1270-33	MYB-1290-33
1	Rated voltage (AC, DC)	250V		
2	Rated current (AC, DC) (Note)	50A	70A	90A
3	Test voltage (terminal to case, AC 1 minute)	2500V (25°C, 70% RH)		
4	Isolation resistance (terminal to case, 500VDC)	300MΩ min. (25°C, 70% RH)		
5	Leakage current	125V, 60Hz	0.5mA max.	
		250V, 60Hz	0.1mA max.	
6	DC resistance	2.5mΩ max.	1.9mΩ max.	1.3mΩ max.
7	Temperature rise	35°C max		
8	Operating temperature	-25 ~ +85°C		
9	Operating humidity	30% ~ 90% RH (No dewdrop)		
10	Storage temperature	-30 ~ +85°C		
11	Storage humidity	10% ~ 95% RH (No dewdrop)		
12	Vibration	Sweep: 10 ~ 55 ~ 10Hz (for 1 minute), Amplitude: 1.5mm X, Y and Z axes for 2 hours		
13	Safety standard	Only MYB-1270-33 is approved by UL 1283 and CSA std. C22. 2 No. 8		
14	Weight (typ)	2000g	2900g	3000g

(Note) : Value at Ta ≦50°C. Refer to the derating curve shown below at Ta > 50°C.

## ■ Circuit




## ■ Derating



- Request customer specification for further details of specifications, outline, characteristics, etc. Read the instruction manual before usage.
- Contact us about delivery before ordering.


# MYB (50/70/90A)-SERIES

## MYB-1250-33



## MYB-1270-33

## MYB-1290-33



Case: Metal


(Unit: mm)

# MYB (50/70/90A)-SERIES


## CHARACTERISTICS

■ Typical Insertion Loss


**MYB-1250-33**



**MYB-1270-33**



**MYB-1290-33**



Noise Filter

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Power Line Filters](#) category:*

*Click to view products by [TDK-Lambda](#) manufacturer:*

Other Similar products are found below :

[5B1](#) [6609019-3](#) [6609026-5](#) [6609030-6](#) [6609063-2](#) [6609973-2](#) [7-1609090-5](#) [F1500CA06](#) [F7382Z](#) [F7863Z](#) [FAHAV3100ZC000](#) [806276](#)  
[FN2020B-1-06](#) [FN2080B-10-06](#) [FN2090A-1-06](#) [FN2410H-32-33](#) [FN2410H-80-34](#) [FN2412H-16-44](#) [FN420-1-13](#) [FP144](#) [8-6609089-0](#) [12-](#)  
[MMB-030-11-D](#) [B84144A0050R120](#) [B84144A90R120](#) [20B1](#) [RSEL-2001A](#) [2B1](#) [LP183](#) [1-6609070-1](#) [F1500CA10](#) [1B1](#) [FN2020A-10-06](#)  
[FN2020B-3-06](#) [FN2060A-3-06](#) [FN2070A-16-06](#) [FN2070B-16-08](#) [FN2090A-20-06](#) [FN2090B-12-06](#) [FN2090Z-1-06](#) [FN2410H-25-33](#)  
[FN2410H-60-34](#) [FN2410H-8-44](#) [FN2412H-25-33](#) [FN2412H-8-44](#) [FN610R-3-06](#) [20EHZ7](#) [20K1](#) [30B6](#) [30BCF10R](#) [3K1](#)