
STATSHIELD® HIGH PUNCTURE MOISTURE BARRIER BAG



Specifications:

Standard Document

ANSI/ESD S541 (ANSI/ESD S20.20)

ANSI/ESD S11.4

Typical Values Electrical Properties

Surface Resistance (both exterior and interior) Discharge Shielding Static Shielding Charge Generation

Teflon

Quartz

Physical Properties

Film Thickness Puncture Strength Heat Seal Strength (Vetrod bar sealer) Seal Strength

MVTR Silicone Non-corrosive

Marking Adhesion

Chemical Properties

Corrosion

Meets Requirements of:

ESD Protective Packaging Level 2 Technical Requirements

Test Procedures/Method

ANSI/ESD STM11.11 ANSI/ESD STM11.31

20 volts EIA 541

-0.09 nC/sq. in. +0.10 nC/sq. in.

<10 nJ

>30 lbs

 1×10^4 to < 1×10^{11} ohms

Modified incline plane Modified incline plane

Nominal 0.0065" (.1651mm) ±10% MIL-STD-3010, 1003 MIL-STD-3010, 2065

>11 (lb/in width) ASTM D1876-93 >12 PSI ASTM D882 ≤0.014/q/100sq.in/24hours **ASTM F1249** Not detected ASTM E168

Pass MIL-STD-3010, M3005 **Pass** IPC-TM-650 2.4.1

No effect on aluminum, copper, silver, Sn-Pb coated foil,

stainless steel, low carbon steel

ANSI/ESD S541 Section 6.2 Outside an EPA

"Transportation of sensitive products outside of an EPA shall require packaging that provides:

- 1. Low charge generation
- 2. Dissipative or conductive materials for intimate contact
- 3. A structure that provides electrostatic discharge shielding."

RoHS 2, REACH and Conflict Minerals Statement

None of the RoHS 2 restricted materials, REACH substances of very high concern as of 2015/12/17, or Conflict Minerals are intentionally added in manufacturing this product. Ref: European Union Directive 2011/65/EU and Regulation (EC) No. 1907/2006/CE. See Desco Limited Warranty at Desco.com.

Statshield® and Statfree® are Registered Trademarks of Desco Industries Inc. See Bag Selection Chart Click HERE.



United States of America

Statshield® bags are packaged 100 per package in an oversized shielding bag. See Shielding Bag Storage at TB-7057.

NOTE: The complete dry package concept of packaging

for electronics requires three elements:

Dessicant - To Absorb Moisture

Statshield® Moisture Barrier Bags - To Protect

Moisture Barrier Bags Application Instructions.

Humidity Indicator Card - To Monitor Performance

For detailed instructions see Technical Bulletin TB-2031 -

Specifications and procedures subject to change without notice.

STATSHIELD® HIGH PUNCTURE, MOISTURE BARRIER BAG, 0.0065" (0.1651mm)



DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: Desco.com PHONE (909) 627-8178

DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021-1407 PHONE (781) 821-8370

DRAWING NUMBER 13760

DATE: June 2016

Heavy Duty Static

Polyester Layer

Layer

Dissipative Polyester Aluminum Shielding

Aluminum Shielding Layer High Performance Heavy Duty Static Dissipative Polyethylene

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Antistatic Control Products category:

Click to view products by Desco manufacturer:

Other Similar products are found below:

13505 13870 14404 20-053-0017 2229 2231 3039 37061 39792 42470 XON-ASB4X30 XON-ASB4X6 XON-ASB6X30 09813 09857

XON-ASB8X10 XON-ASB6X10 19695 09037 68101 68103 73741 13515 13869 13868 13485 13457 13245 13332 13205 13135 91070

8031 8523 13080 13215 157 ROLL BEIGE 1.0 VERAX1R-300R 17260 66051 12550 19863 09121 73831 13340 13338 04541 19696

16104 SPI-20686