



ELECTRONICS, INC.
 44 FARRAND STREET
 BLOOMFIELD, NJ 07003
 (973) 748-5089
<http://www.nteinc.com>

NTE5541 thru NTE5548 Silicon Controlled Rectifier (SCR) 35 Amp, TO48

Description:

The NTE5541 thru NTE5548 are silicon controlled rectifiers (SCR) packaged in a TO48 type case designed for industrial and consumer applications such as power supplies; battery chargers; temperature, motor, light and welder controls.


Absolute Maximum Ratings:

Repetitive Peak Off-State Voltage ($T_J = +100^\circ\text{C}$) V_{DRM}	
NTE5541	50V
NTE5543	200V
NTE5544	300V
NTE5545	400V
NTE5546	500V
NTE5547	600V
NTE5548	800V
Repetitive Peak Reverse Voltage ($T_J = +100^\circ\text{C}$) V_{RRM}	
NTE5541	50V
NTE5543	200V
NTE5544	300V
NTE5545	400V
NTE5546	500V
NTE5547	600V
NTE5548	800V
RMS On-State Current ($T_C = +75^\circ\text{C}$), $I_{(RMS)}$	
35A	
Peak Surge (Non-Repetitive) On-State Current (One Cycle at 50Hz or 60Hz), I_{TSM}	
300A	
Peak Gate-Trigger Current ($3\mu\text{s Max}$), I_{GTM}	
20A	
Peak Gate-Power Dissipation ($I_{GT} \leq I_{GTM}$ for $3\mu\text{s Max}$), P_{GM}	
20W	
Average Gate Power Dissipation, $P_{G(AV)}$	
500mW	
Operating Temperature Range, T_{oper}	
-40° to $+150^\circ\text{C}$	
Storage Temperature Range, T_{stg}	
-40° to $+150^\circ\text{C}$	
Typical Thermal Resistance, Junction-to-Case, R_{thJC}	
1.4°C/W	

Note 1. **NTE5541, NTE5542, NTE5544, and NTE5546** are a **discontinued** devices and **no longer available**.

Electrical Characteristics: (At “Maximum Ratings” and Specified Case Temperatures)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Peak Off-State Current	I_{DRM} , I_{RRM}	V_{DRM} & V_{RRM} = Max Rating, $T_J = +100^{\circ}C$, Gate Open	-	-	2.0	mA
Maximum On-State Voltage (Peak)	I_{HO}	$T_C = +25^{\circ}C$	-	-	50	mA
DC Gate Trigger Current	I_{GT}	Anode Voltage = 12V, $R_L = 30\Omega$, $T_C = +25^{\circ}C$	-	-	30	mA
DC Gate Trigger Voltage	V_{GT}	Anode Voltage = 12V, $R_L = 30\Omega$, $T_C = +25^{\circ}C$	-	-	2.0	V
Gate Controlled Turn-On Time	t_{gt}	$I_{GT} = 150mA$	-	2.5	-	μs
Critical Rate of Rise of Off-State Voltage	dv/dt (Critical)	Gate Open, $T_C = +100^{\circ}C$	-	100	-	V/ μs



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [SCRs category](#):

Click to view products by [NTE manufacturer](#):

Other Similar products are found below :

[NTE5428](#) [NTE5448](#) [NTE5457](#) [NTE5511](#) [T1500N16TOF VT](#) [T720N18TOF](#) [T880N14TOF](#) [T880N16TOF](#) [TS110-7UF](#) [TT104N12KOF-A](#)
[TT104N12KOF-K](#) [TT162N16KOF-A](#) [TT162N16KOF-K](#) [TT330N16AOF](#) [VS-16RIA100](#) [VS-22RIA20](#) [VS-2N5206](#) [VS-2N685](#) [VS-](#)
[40TPS08A-M3](#) [VS-ST230S12P1VPBF](#) [057219R](#) [CLB30I1200HB](#) [T1190N16TOF VT](#) [T1220N22TOF VT](#) [T201N70TOH](#) [T830N18TOF](#)
[TD92N16KOF-A](#) [TT250N12KOF-K](#) [VS-2N692](#) [VS-2N689](#) [VS-25RIA40](#) [VS-16RIA120](#) [VS-10RIA120](#) [VS-30TPS08PBF](#) [NTE5427](#)
[NTE5442](#) [VS-2N690](#) [VS-ST300S20P0PBF](#) [TT251N16KOF-K](#) [VS-22RIA100](#) [VS-16RIA40](#) [CR02AM-8#F00](#) [VS-ST110S12P0VPBF](#)
[TD250N16KOF-A](#) [VS-ST110S16P0](#) [VS-10RIA10](#) [VS-16TTS08-M3](#) [TS110-7A1-AP](#) [T930N36TOF VT](#) [T2160N24TOF VT](#)